

This is a digital copy of a book that was preserved for generations on library shelves before it was carefully scanned by Google as part of a project to make the world's books discoverable online.

It has survived long enough for the copyright to expire and the book to enter the public domain. A public domain book is one that was never subject to copyright or whose legal copyright term has expired. Whether a book is in the public domain may vary country to country. Public domain books are our gateways to the past, representing a wealth of history, culture and knowledge that's often difficult to discover.

Marks, notations and other marginalia present in the original volume will appear in this file - a reminder of this book's long journey from the publisher to a library and finally to you.

Usage guidelines


Google is proud to partner with libraries to digitize public domain materials and make them widely accessible. Public domain books belong to the public and we are merely their custodians. Nevertheless, this work is expensive, so in order to keep providing this resource, we have taken steps to prevent abuse by commercial parties, including placing technical restrictions on automated querying.

We also ask that you:

- + *Make non-commercial use of the files* We designed Google Book Search for use by individuals, and we request that you use these files for personal, non-commercial purposes.
- + Refrain from automated querying Do not send automated queries of any sort to Google's system: If you are conducting research on machine translation, optical character recognition or other areas where access to a large amount of text is helpful, please contact us. We encourage the use of public domain materials for these purposes and may be able to help.
- + *Maintain attribution* The Google "watermark" you see on each file is essential for informing people about this project and helping them find additional materials through Google Book Search. Please do not remove it.
- + *Keep it legal* Whatever your use, remember that you are responsible for ensuring that what you are doing is legal. Do not assume that just because we believe a book is in the public domain for users in the United States, that the work is also in the public domain for users in other countries. Whether a book is still in copyright varies from country to country, and we can't offer guidance on whether any specific use of any specific book is allowed. Please do not assume that a book's appearance in Google Book Search means it can be used in any manner anywhere in the world. Copyright infringement liability can be quite severe.

About Google Book Search

Google's mission is to organize the world's information and to make it universally accessible and useful. Google Book Search helps readers discover the world's books while helping authors and publishers reach new audiences. You can search through the full text of this book on the web at http://books.google.com/



WEALE'S SCIENTIFIC & TECHNICAL SERIES.

· · · · · · · · · · · · · · · · · · ·	
CIVIL ENGINEERING & SURVEYING.	
Civil Engineering. H. Law & D. K. CLARK	6/6
Pioneer Engineering. E. Dobson	4/6
Iron Bridges of Moderate Span. H. W. PENDRED.	2/-
Iron and Steel Bridges & Viaducts. F. CAMPIN .	3/6
Constructional Steel & Ironwork. F. CAMPIN	3/6
Tubular & Girder Bridges. G. D. DEMPSEY.	2/-
Tubular & Girder Bridges. G. D. DEMPSEY Materials and Construction. F. CAMPIN	3/-
Sanitary Work. C. Slagg	3/-
Roads & Streets. LAW, CLARK, & WALLIS-TAYLER.	6/-
Construction of Gasworks. S. Hughes & H.O'Connor	6/-
Water Works. S. Hughes	4/-
Well-Sinking. J. G. SWINDELL & G. R. BURNELL	2/-
T T T T T T T T T T T T T T T T T T T	16
'	
Library	
of the	
or the .	
Their angite of Their according	,
University of Wisconsin	- 1
	·
bollermakers neaty neckoner and Assistant	71-
Steam Boilers. R. Armstrong	1/6
Steam and Machinery Management. M. P. Balk.	2/6
Steam and the Steam Engine. D. K. CLARK.	3/6
Steam Engine, Theory of. T. BAKER	1/6
Steam Engine. Dr. LARDNER	1/6
Locomotive Engines. G. D. DEMPSEY & D. K. CLARK.	3/-
Locomotive Engine Driving. M. REYNOLDS	3/6
Stationary Engine Driving. M. REYNOLDS	3/6
Model Locomotive Engineer. M. REYNOLDS	3/6
Modern Workshop Practice. J. G. WINTON	3/6
Mechanical Engineering. F. CAMPIN	2/6
Details of Machinery. F. CAMPIN	31-
Details of Machinery. F. CAMPIN Elementary Marine Engineering. J. S. Breweb	1/6
ROSBY LOCKWOOD & SON	FC

WEALE'S SCIENTIFIC & TECHNICAL SERIE	S.
MECHANICAL ENGINEERING, &c.—contd.	-1
Sewing Machinery. J. W. URQUHART	2/-
Power of Water. J. GLYNN	2/- 2/-
Iron and West T ARMOUR	2/6
Iron and Heat. J. Armour	2/6
Mechanics. C. Tomlinson	1/6
Oranes and Machinery. J. GLYNN	1/6
Smithy and Force W. J. E. Chave	2/6
Smithy and Forge. W. J. E. Crane Sheet-Metal Worker's Guide. W. J. E. Crane	1/6
Elementary Electric Lighting. A. A. C. SWINTON .	1/6
	-,0
MINING & METALLURGY.	
Mining Calculations. T. A. O'DONAHUE	3/6
Mineralogy. A. RAMSAY	3/6
Coal Mining. Sir W. W. SMYTH & T. F. BROWN	3/6
Metallurgy of Iron. H. BAUERMAN	5/-
Mineral Surveyor's Guide. W. LINTERN	3/6
Slate and Slate Quarrying. D. O. DAVIES	3/-
Mining and Quarrying. J. H. COLLINS	1/6
Subterraneous Surveying. T. FENWICK & T. BAKER	2/6
Mining Tools. W. Morgans	
Plates to ditto. 4to	4/6
Physical Geology. PortLook & Tate	2/-
Physical Geology. PORTLOGE & TATE Historical Geology. R. TATE The above 2 vols., bound together	2/6
The above 2 vois., bound together	4/6
Electro-Metallurgy. A. WATT	3/6
NAVIGATION, SHIPBUILDING, &c.	
Navigation. J. Greenwood & W. H. Rosser	2/6
Practical Navigation. GREENWOOD, ROSSER & LAW .	7/-
Navigation and Nautical Astronomy. J. R. Young	2/6
Mathematical & Nautical Tables. LAW & Young .	4/-
Masting and Rigging. R. KIPPING	2/-
Sails and Sailmaking. R. KIPPING	2/6
Marine Engines. R. Murray & G. Carlisle	
Naval Architecture. J. PRAKE	•
Ships, Construction of. H. A. SOMMERFELDT.	1/6
Plates to ditto, 4to	
Shine and Roate W KI.AWN	1/6

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

AGRICULTURE & GARDENING.


Fertilisers & Feeding Stuffs. Dr. B. DYER	1/-
Draining and Embanking. PROF. J. SCOTT	1/6
Irrigation and Water Supply. PROF. J. SCOTT	1/6
Farm Roads, Fences, and Gates. PROF. J. SCOTT.	1/6
Farm Buildings. PROF. J. SCOTT	2/-
Farm Buildings. PROF. J. SCOTT	2/-
Field Implements and Machines. PROF. J. SCOTT.	2/-
Agricultural Surveying. PROF. J. SCOTT	1/6
The above 7 vols., bound together	12/-
Farm Management. R. S. BURN	2/6
Landed Estates Management. R. S. BURN	2/6
Farming—Soils. Manures. and Crops. R. S. Burn	
Farming -Outlines-Farming Economy. R.S. BURN	3/-
Farming—Cattle, Sheep, and Horses. R. S. BURN	2/6
Farming—Dairy, Pigs, and Poultry. R. S. BURN. Farming—Sewage & Irrigation. R. S. BURN.	2/-
Farming—Sewage & Irrigation. R. S. BURN.	2/6
The above 5 vols., bound together	12/-
Book-keeping for Farmers, J. M. WOODMAN .	2/6
Ready Reckoner for Land. A. Arman	2/-
Miller's & Farmer's Ready Reckoner	2/-
Hay and Straw Measurer. J. STEELE	2/-
Meat Production. J. EWART	2/6
The Sheep. W. C. SPOONER	3/6
Multum-in-Parvo Gardening. S. Wood	1/-
Forcing Garden. S. Wood	3/6
Forcing Garden. S. Wood	3/-
Kitchen Gardening. G. M. F. GLENNY	1/6
Cottage Gardening. E. Hobday	1/6
Garden Receipts. C. W. QUIN	1/6
Potatoes: How to Grow. J. Pink	2/-
Culture of Fruit Trees. M. Du Breuil	3/6
Tree Planter & Plant Propagator. S. Wood	2/-
Tree Pruner. S. Wood.	1/6
Tree Planter, Propagator, & Pruner. S. Wood.	3/6
Grafting and Budding. C. BALTET	2/6
Bees for Pleasure & Profit. G. G. Samson	1/-

CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court, E.C.



THE PHYSICS AND CHEMISTRY OF MINING





THE

PHYSICS AND CHEMISTRY OF MINING

AN ELEMENTARY CLASS-BOOK

FOR THE USE OF

STUDENTS PREPARING FOR THE BOARD OF EDUCATION
AND COUNTY COUNCIL EXAMINATIONS IN MINING
OR QUALIFYING FOR
COLLIERY MANAGERS' CERTIFICATES

BY

T. H. BYROM

PRINCIPAL ANALYTICAL CHEMIST TO THE WIGAN COAL AND IRON COMPANY LIMITED LECTURER ON CHEMISTRY, AND ON THE PHYSICS AND CHEMISTRY OF MINING, AT THE WIGAN TECHNICAL COLLEGE

With Mustrations



LONDON
CROSBY LOCKWOOD AND SON

1905

7 STATIONERS' HALL COURT, LUDGATE HILL

Printed at THE DARIEN PRESS, Edinburgh.

93537 FEB 23 1906

M L H B 9 9

PREFACE.

THE students of Mining are an ever-increasing multitude, who by present-day requirements are compelled to pay attention to at least the elements of many branches of modern science. The aim of the Author, in these notes relating to the Physics and Chemistry of Mining, is to place before the Mining Student a brief repertory of certain truths and phenomena, such as may be classed under that heading, which it is hoped may materially assist him in his studies.

As a general rule, text-books on Physics and Chemistry—though often excellent for the purposes for which they are written—deal largely with subjects which are neither interesting nor useful to the student of Mining, and either treat very slightly or omit altogether those points which are of special interest and importance to him. Further, there are very few books in which the principles of those sciences are dealt with in one volume.

The composition of the air; the importance of, and reason for, an abundant air-supply; the constitution and properties of the gases to be met with in the mine, some of them most deadly either as regards explosive properties or poisonous effects; the behaviour of gases under varying conditions of temperature and pressure; the indications of the barometer; the humidity of the air of the mine, and the dangers of coal dust: these (with many other) matters ought to have the most careful attention in a student's training and preparation for responsible work in the mine; and the Author trusts that the treatment of

such matters which is here given may be found of substantial practical utility as an elementary first course.

A series of questions, many of them taken from papers set at the Colliery Managers' Examinations and at the Board of Education's Examinations in Mining, has been appended to the volume.

The Author desires to acknowledge here, with many thanks, his indebtedness to Mr W. J. Orsman for information furnished in connection with the chapter dealing with Explosives; to Mr G. H. Winstanley for help and advice in several matters dealing more especially with practical mining; and to Messrs Philip Harris & Co., Birmingham, for the loan of many of the blocks used for the illustrations.

T. H. B.

WIGAN, *May* 1905.

CONTENTS.

CHAPTER I.

THE	ATMOSPHERE.

Nature of the atmosphere—The air possesses weight—Atmospheric pressure—The barometer—Importance of the barometer to the mine manager—The siphon	PAGE I
CHAPTER II.	
LAWS RELATING TO THE BEHAVIOUR OF GAS	ES.
Boyle's law—Effect of temperature on volume of gases—Charles's law—The effect of pressure on the boiling-point of water and liquids generally—Heat a form of energy—The effects of heat on solids—Conduction—Radiation—Heat promotes chemical action—Latent heat—Heat and its measurement—Maximum and minimum thermometers—Conversion of degrees Fahrenheit and Centigrade	8
CHAPTER III.	
THE DIFFUSION OF GASES.	
Diffusion of gases, how illustrated—Testing diffusion of gas— Ansell's firedamp indicator—The hygrometer and its use—Mr Henry Hall's experiments with coal dust—Apparatus for estimation of moisture — Mason's hygrometer — Daniell's hygrometer	25

CHAPTER IV.

COMPOSITION OF THE ATMOSPHERE.	PAGE					
Oxidation of metals—Oxygen and nitrogen—Apparatus for testing composition of the air—Preparation and properties of oxygen gas—Nitrogen and its properties						
CHAPTER V.						
SUNDRY CONSTITUENTS OF THE ATMOSPHE	RE.					
Aqueous vapour—Carbon di-oxide (carbonic acid gas)—Ammonia— Nitric acid—Ozone—Sulphur compounds	36					
CHAPTER VI.						
WATER.						
Composition of water—Apparatus for decomposing water—Pure water—Natural waters—Temporary and permanent hardness of water—Condensers—Water for boiler purposes—Hydrogen—Apparatus for preparation of hydrogen gas	41					
CHAPTER VII.						
CARBON.						
Carbon widely distributed — Lamp-black—Gas carbon — Coke—Animal charcoal or bone black—White damp—Black damp—Preparation of black damp	51					
CHAPTER VIII.						
FIRE-DAMP.—COMBUSTION.—COAL DUST AND ACTION.	ITS					
Methane, marsh gas, or fire-damp—Gases produced by an ex- plosion of fire-damp—Preparation of methane—Tests for the presence of fire-damp—Flame tests for fire-damp—Purpose of						

CONTENTS.	ix
gauze in safety-lamp—Ignition-point—Flash-point of oils—Naylor's and other safety-lamps—Lighting powers of lamps—Rumford's photometer—Bunsen's photometer—Stink damp—Ventilation—Combustion—Spontaneous combustion—Coaldust and its action	PAGE
CHAPTER IX.	
EXPLOSIVES.	
Nature of explosives—High explosives—Detonators—Firing of explosives—Gun-cotton—Nitro-glycerine—Gelignite—Tonite—Roburite—Ammonite—Bellite—Westphalite—Lime cartridges—Permitted explosives—Pneumatophores	86
CHAPTER X.	
COMPOSITION OF VARIOUS COALS AND FUEL	S.
Nature of coal—Anthracite—Cannel coal—Bituminous or flaming coals—Coke—Peat—Lignite—Wood—Liquid fuels—Undesirable elements in fuels—Ash—Sulphur and phosphorus—Nitrogen in coals—Briquettes	98
CHAPTER XI.	
METHODS OF ANALYSIS OF COAL.	
Specific gravity—Moisture in coal—Determination of ash—Chemical composition of the ash—Estimation of sulphur—Calorific value or heating power of coal	110

CHAPTER XII.

STRATA ADJOINING THE COAL-MEASURES.

Clays—Aluminous	shales—Iron	pyrites-	-Gan	ister–	-Iron	stone	5	
Analyses of the	ironstones—G	ranite						121

CHAPTER XIII.

MAGNETISM AND ELECTRICITY.

Ma	current—I Effects of batteries— construction	d its effect Dipping-need currents upon Induction- on—Secondathe electric	dles—l on each —Mag ary ba	Magnet other- neto-el tteries	ic el —Elec ectric or a	ffects ctro-r ma ccum	of nagno chine ulato:	a cu ets—l es — I rs—L	rrent- Prima Dynan ightir	ry no	PAG E
	welding		•	•	•	•	•	•	•	•	127
			AP	PENI	DIX.						
I.	USEFUL	TABLES,	Етс.	•							142
II.	MISCELL	ANEOUS	QUE	STION	IS	•	•	•			146
					-						
IN	DEX .										153

LIST OF ILLUSTRATIONS

FIG.			PAGE
1. Apparatus for weighing air	•	•	2
2. Diagram illustrating construction of barometer	•		3
3. Common form of pit barometer, with there	nome	ter	
attached			3
4. Aneroid barometer			5
5. Boyle's tube			8
6. Glass bulb and tube			IO
7. Tube for determining densities of gases .			II
8. Apparatus to show lowered boiling point .			12
9. Apparatus to test expansion of metal ball .			14
10. Apparatus to test linear expansion of metal roc	Ι.		15
11. Apparatus to show effect of contraction on heat	ed me	etal	
bar			16
12. Experiment to show conducting power of meta	ls .	•	17
13. Arrangement of mirrors, so as to focus heat.			18
14, 15. Common forms of thermometers			21
16. Apparatus for graduating thermometers at the	boili	ng-	
point of water			21
17. Leslie's air thermometer			22
18. Maximum and minimum thermometers .			23
19. Apparatus for diffusion experiment			26
20. Apparatus for moisture estimation		•	28
21 and 22. Mason's hygrometer			29
23. Daniell's hygrometer			30
24. Apparatus for testing the composition of the air	r.		32
25. Diagram illustrating the preparation of oyxgen	gas		33
26. Drawing the products of a gas flame through l	ime-w	ater	38
27. Apparatus for decomposing water		•	41
28. To illustrate decomposition of steam			42

LIST OF ILLUSTRATIONS.

xii

FIG.								PAG
	30. Condensers			•	•	•	•	44
_	Apparatus for the preparat	ion of	hydr	ogen	gas	•	•	49
_	Clowes's hydrogen lamp	•	•	•		•	•	60
33∙	Illustrating heights of flame	e " c a p	s"					6;
34.	Illustrating the action of ga	uze on	ı flan	ne .				79
35.	Naylor's safety-lamp .							72
36.	Electrical ignition of Naylo	r's lan	np					73
37·	Rumford's photometer .							74
38.	Bunsen's photometer .							75
-	Air burning in coal-gas .							80
	High-tension exploder .	•						89
41.	Estimation of volatile matte	er.						113
42.	Calorimeter (showing detail	s and	calor	imete	er in	actio	n)	116
43.	Dipping needle							129
	Solenoid							130
45,	46. Electro-magnet .							131
47.	Electric bell	•						132
	Leclanché cell	•						133
49.	Bichromate or Daniell batte	ery						134
	Bunsen or Grove's cell .							135
•	Illustrating induction .				_			135
-	Induction coil	•		-	-			136
-	Secondary battery accumula	ator	•	•	•	•	•	137
• • •	SCLUMIUM V DALLETY ALCUMIUM	awı						. 1/

CHAPTER I.

THE ATMOSPHERE.

WE are surrounded on all sides by an invisible gaseous mixture, commonly known as the atmosphere or air; and a study of the properties, physical and chemical, of this mixture, which obeys the laws relating to gases in general, will be interesting and instructive. Every so-called empty vessel is really full of air, and we are reminded of its presence by many things in our daily life; for instance, the resistance one experiences in walking against a breeze, or the disastrous effects of a wind storm, due to the air having been in a state of violent disturbance. From the very earliest periods, it must have been evident to man that the invisible "something" was necessary to life, as when deprived of it life became extinct, and the important and far-reaching effects of this atmosphere of ours are evident on every hand. The various changes of weather are due to it; soils are formed by the disintegration or crumbling of rocks by means of it; all the phenomena of sound would be impossible without its aid; by its behaviour the sun's rays, instead of scorching up the face of the earth, are modified in passing through the stratum or layer of air surrounding the globe.

The Air possesses Weight.—This may be proved by weighing a circular globe full of air (Fig. 1) and then attaching to it an air-pump, whereby the air may be removed, and afterwards re-weighing. There will be found a considerable decrease in weight.

A cubic foot of air, at a temperature of 0° Centigrade

and a pressure of 30 inches of the barometer, weighs $\cdot 0807$ lbs.; that is to say, about $12\frac{1}{2}$ cubic feet weigh one pound, and consequently the weight of air in a room 16 ft. by 14



FIG. 1.—Apparatus for weighing air.

ft. by 10 ft. will be, say, 180 lbs. In consequence of this weight, and the fact that the atmosphere extends to a height of several miles, it is to be expected that a considerable amount of pressure will be exerted by it upon all objects on the earth's surface.

Atmospheric Pressure.—This amounts to about

14.7 lbs. on every square inch of surface. Even on our bodies this pressure is always present, and totals up to several tons pressure, but being equal on all sides and from all directions, it does not cause inconvenience. If, however, the air from the *inside* of a vessel be removed by some means, such as an air-pump, unless the vessel is very strongly made and (preferably) circular in shape, the whole substance of it will be crushed in by the atmospheric pressure.

A striking experiment in proof of this may be made by taking a square tin canister, soldering a small tube in the lid, then soldering the lid securely on to the box. Introduce a little water into the canister and place it over a Bunsen gas burner, or the flame of a spirit lamp, until steam begins to issue from the tube. When this takes place remove the source of heat and quickly cork up the tube tightly. As the tin and its contents (steam) cool down, the steam will become condensed and a partial vacuum be formed inside; the resistance inside to the atmospheric pressure outside will get less and less, until finally the tin is crumpled up almost flat.

The Barometer.—That the atmosphere exerts pressure is also shown by means of the barometer, an instrument the construction and principle of which may be readily shown as follows: Take a glass tube 32 or 33




Fig. 2.—Diagram illustrating construction of barometer.



FIG. 3.—Common form of pit barometer, with thermometer attached.

inches long, and sealed at one end. By means of a small funnel, fill the tube with the fluid metal mercury, commonly called quicksilver, and placing the thumb on one end, turn the tube upside down, and bring the end under the surface of mercury contained in a small trough (Fig. 2).

Remove the thumb when the end of the tube is well under the surface of the mercury in the trough. The mercury, which before completely filled the tube, now falls until its level is about 2 or 3 inches from the sealed end, and there it remains stationary. This space above the mercury is a vacuum (except for a little vapour of mercury). On measuring the distance between the level of the mercury in the trough and that in the tube, it will be found to be about 30 inches (corresponding to the height of the barometer at the time of the experiment). The column of mercury is supported entirely by the atmospheric pressure on the surface of the metal in the trough (Fig. 3).

If the bore of the tube had an area in section equal to 1 square inch, there would be 30 cubic inches of mercury in a column 30 inches in height. Now 1 cubic inch of mercury weighs practically $\frac{1}{2}$ lb. (·491), therefore the whole column would weigh $30 \times \frac{1}{2} = 15$ lbs. But this column balances, or is balanced by, a column of air of the same area. Hence the weight or pressure of the air, on an area of 1 square inch, is equal to 15 lbs.

Mercury is the only metal which is liquid at ordinary temperatures, and on account of its weight it is eminently suitable for use in barometers. Water might be used for a rough kind of barometer, but there would be many objections, and a column of $30 \times 13\frac{1}{2}$ inches in height would be necessary ($13\frac{1}{2}$ being the density of mercury compared with water). Glycerine is the liquid used in some barometers. Its specific gravity is 1.26, and a column of about 27 feet in height is necessary. It possesses the great advantage that very slight variations in the atmospheric pressure are more readily indicated, being magnified practically ten times, as compared with an ordinary mercury barometer.

Another form of barometer is also in common use, named the aneroid (Fig. 4). In principle it consists of a flattened cylinder of corrugated metal, from which the air has been taken by means of an air pump. Fluctuations in

the pressure of the air cause the cylinder to be flattened slightly, or to expand slightly, and these movements are imparted to suitable mechanism and indicated by a pointer on the face of the instrument.

Importance of the Barometer to the Mine Manager.—The barometer is an instrument of the greatest importance to the mine manager. By its means

he is able to detect variations in the pressure of the air which will affect the ventilation of the mine. The greater the atmospheric pressure—that is, the higher the barometer column—the less danger of fire-damp in a coal mine, a lessened pressure denoting more likelihood of escaping gas from the fissures and cracks in the coal strata and from the coal itself.

The pressure of air on a mountain top is less than it is at the sea-level, and the higher one ascends, the less



Fig. 4.—Aneroid barometer.

the pressure becomes. It is found that a difference of 900 feet in height means a rise or fall of 1 inch of the mercury in the barometer. Consequently the pressure in the workings of the mine will be greater than at the surface, to an amount depending upon the depth of the mine.

The Siphon.—If a U-shaped tube, with one limb longer than the other, be taken and filled with water, no water will run out so long as the tube is sealed by the finger at one end, and the tube may be safely turned upside down without losing any of the liquid. The atmospheric pressure prevents it from coming out. Now if the open

and shorter limb be placed in water and the sealed end be placed at a lower level than the surface of the water, on removing the finger the liquid will flow out of the longer limb, and continue to do so until the vessel of water is either emptied, or its surface comes below the short end of the **U** tube. Such an arrangement is called a siphon, and it depends for its action on atmospheric pressure.

The column of liquid in the long limb weighs more than that in the short limb, and consequently runs out at the end of the long limb; the liquid in the shorter limb having to follow it, or else a vacuum would be formed. The effect is thus due to atmospheric pressure forcing up liquid in the short limb to compensate for that running out of the long limb.

The siphon is a very useful appliance in a laboratory for various purposes where such action of the atmosphere is to be utilised, as in separating a clear liquid from a sediment which has settled in it. Its practical application in the mine has limitations. It may be used for raising water over an elevation and delivering it at some lower level, or for draining water from a higher level to the pump, but it can never be used to transfer water from a lower to a higher level. Since its action depends upon atmospheric pressure, the vertical height over which water can be raised is about 34 feet, theoretically. In actual practice it is less than this, and rarely can much more than 20 feet be effectually dealt with, on account of leakage of the pipes and loss through friction.

The siphon on such a scale as this is constructed of a series of pipes joined together, and slight leakages at the joints is almost unavoidable. To start the siphon, the ends of the pipes are plugged and the pipes filled with water through an opening at the top of the bend. This is then sealed as tightly as possible, and the plugs or stoppers removed from the ends of the pipes, when a similar action goes on to that which takes place when using a glass tube

with unequal limbs. The end of the shorter limb is closed by a ball valve when the water gets below its level, thus keeping the pipes full of water.

The siphon is not often used in mining operations, but it may be useful sometimes where pumping machinery is not available.

The action of an ordinary suction pump depends also on atmospheric pressure. Before the pump is put in action the barrel and pipe contain air only, and the level of the water inside and out is the same. On moving the handle, a partial vacuum is caused under the piston, and the pressure of the atmosphere forces water up into the working barrel.

CHAPTER II.

LAWS RELATING TO THE BEHAVIOUR OF GASES.

WE have now to consider the laws relating to the behaviour of gases when subjected to certain conditions.



Fig. 5.—Boyle's tube.

Boyle's Law.—When any gas, or mixture of gases, is subjected to pressure, its bulk or volume is affected. If the pressure be increased, the volume is decreased; and vice versa, if the pressure be decreased then the volume is increased. Expressed more concisely, we should say that "the volume of gases varies inversely as the pressure to which they are subjected." This is known as Boyle's law, and it assumes the temperature to be constant.

It may be clearly proved by means of a bent glass tube sealed at one end, or two pieces of tube connected by rubber tubing, as shown in Fig. 5. The limb is closed by pouring a little mercury down the mouth of the open $\lim a$. The column of air in the short $\lim b$ is now at the same pressure as the outside air is. More mercury is now poured in the longer $\lim b$ until a height of 30 inches is attained, and the difference in volume of gas in the short $\lim b$ is noted. It will be found to have decreased to half its

original volume. That is to say, by adding another atmosphere's pressure (which we know to be equal to 30 inches of mercury approximately) the volume of air has become halved. We have therefore *doubled* the pressure and *halved* the volume.

Effect of Temperature on Volume of Gases.—Charles's Law.—The temperature is an important matter in dealing with the volume of gases, and the physicist Charles, who investigated the subject, found that gases have a definite and regular increase in volume for a definite increase in temperature, the pressure remaining the same. He proved that a gas increases in volume $\frac{1}{278}$ of its bulk for every 1° C. increase in temperature.

Plainly expressed, we should find, therefore, that 273 cubic feet of air, when raised in temperature 1° C., would become 274 cubic feet.

$$\left(\frac{1}{273} \text{ of } 273\right) + 273 = 274.$$

The opposite also applies, namely, for a decrease in temperature a corresponding decrease in volume occurs in the above proportion.

Suppose that a certain volume of air measures 50,000 cubic feet when the barometer indicates a pressure of 30 inches. What will be the volume if the pressure falls to 29 inches? If the temperature be also increased, say from 15° C. to 25° C., how will the volume be changed, and to what extent?

Consider the pressure first. This becomes less; therefore the volume becomes greater, and in this proportion

$$50,000 \times \frac{30}{29} = 51,724$$
 cubic feet.

Next consider the temperature, which has increased, and therefore causes increased volume.


From Charles's law this will be seen to be

$$\frac{51,724 \times (273 + 10)}{273} = 53,618$$
 cubic feet,

or (combining the two calculations or corrections for pressure and temperature in one)

$$\frac{50,000 \times 30 \times 283}{29 \times 273} = 53,618 \text{ cubic feet.}$$

That gases expand on heating may be clearly proved by the following experiment: Procure a small glass flask, and flt it with a good cork, through which a clean cut hole has been bored to receive a piece of glass tubing bent twice at



right angles. The end of this tube dips under water in a glass vessel. On applying heat to the flask, even so slight as the warmth of the hand, the air will expand and bubble through the water in the vessel. More heat causes greater expansion, and on allowing the flask to cool down again the water will be drawn back into the tube and probably into the flask as well, showing that decrease of heat causes decrease of volume. Instead of a flask, the bulb and tube, as shown in Fig. 6, can be used.

Gases as a rule are so light, compared with solids and liquids, that we are accustomed to regard them as having no weight. As we have seen, the air itself possesses

weight; and it may be proved by using the same apparatus that the other gases with which we are acquainted have each of them densities and specific gravities peculiar to themselves. When the density of a gas is spoken of, it is understood to be compared with hydrogen gas as a standard, taken as 1. Thus the density of air is 14.47, and of oxygen 16.0. That is, air and oxygen are respectively 14.47 and 16 times as heavy as hydrogen.

When the specific gravity of a gas is mentioned, it is understood that the comparison is made with air as a

standard. Thus the specific gravity of CO₂ (black damp) is 1.5, and of C CH₄ (fire damp) .56, one being 11 times as heavy, the other approximately half as heavy, as air.

The densities or specific gravities of all gases are affected by the temperature. If the temperature be increased the densities are lowered. and if the temperature be decreased Fig. 7.—Tube for determining densities of the densities are increased. The pressure also affects the volume, and



gases.

therefore the weight, if the gas be free to expand or contract. Therefore the comparison of all densities and specific gravities are understood to have been made at one standard temperature and pressure, namely-

0° Centigrade and 760 millimetres barometer.

The density or specific gravity of gases may also be determined in the apparatus shown in Fig. 7. These U tubes are made to contain a certain volume of gas, usually 25 c.c., but their volume should always be checked by filling with mercury and measuring the volume of mercury used. The gases whose density is to be determined are first very carefully dried and freed from impurities, and the purified gas allowed to stream through them until all air or other gas has been expelled, then carefully weighed—the temperature and pressure being noted at the time (avoid handling too much with warm hand; carry carefully by the capillary tubes)—and afterwards corrected to the standard temperature and pressure. In this way comparative weights of equal volumes of different gases at the same tempera-




FIG. 8.—Apparatus to show lowered boiling point.

ture and pressure are obtained, from which their density may be got.

The Effect of Pressure on the Boiling Point of Water and Liquids generally.—The effect of pressure upon the boiling point of a liquid is a very remarkable and important one. The result of observation goes to prove that the boiling point of liquids is raised by increasing the pressure on the surface of the liquid, and lowered by decreasing the pressure. The boiling point is always

arrived at when the tension or elastic force of the vapour (say steam) is able to overcome the atmospheric pressure, or other pressure to which the liquid may be subject. It follows from this that the temperature of the water in a steam boiler is much higher than the temperature of water boiling at ordinary atmospheric pressure (i.e. 100° C. or 212° F.); and conversely, if the pressure be lessened, then the boiling point is lowered.

This may be made the subject of an interesting experiment, as follows:—

Take a round-bottomed flask (Fig. 8) (so that it will stand a fair amount of pressure) and half fill it with water, placing over the flame to boil. Have fitted to it a sound cork. through which passes a tube having a pinch-cock attached. When the water boils and steam issues from the tube. close the pinch-cock and remove the source of heat. Turn the flask upside down and place on a suitable support. There will be now a space above the water filled with steam, and if a little cold water be sprinkled on the flask, condensation takes place, a partial vacuum is produced, and consequently diminished pressure on the surface of the water, and the latter commences to boil briskly, although its temperature is by this time much below 212° F. or 100° C. Also, by reducing the pressure on the surface of water by means of an air-pump, water may be made to boil at a much lower temperature than under ordinary conditions.

At high altitudes, where the atmospheric pressure is less than at sea level, the boiling point is correspondingly lower, and special apparatus has to be used for cooking purposes, so that the chemical changes necessary in cooking the food material in use on the occasion may be effected. At a height of $3\frac{1}{2}$ miles the density of the air is only one-half what it is at the sea level, and at 7 miles only one-third.

The presence of solids dissolved in the water raises the boiling point. Sea water, for instance, does not boil at 212°, and it is often an advantage to add certain salts to water in order to maintain a uniform temperature, higher than the normal boiling point (212°).

Heat is a Form of Energy.—It has long been known that heat could generate mechanical power, and also that mechanical power could generate heat. Dr Joule actually measured the amount of heat that was given to a certain weight of water by a certain amount of mechanical power, and from this the amount of work which could be got from a certain amount of heat; and he proved that the quantity



FIG. 9.—Apparatus to test expansion of metal ball.

of heat produced is always equal to the quantity of work expended in producing it.

The following changes usually accompany the application of heat to matter. The solid expands, then changes to liquid; the volume of the liquid expands, the liquid becomes converted into gas, and the gas or vapour expands. That heat causes cubical expansion may be shown

by means of a metal ball, which just passes through a ring when at ordinary temperatures (Fig. 9). On heating the ball, it is found that it will no longer pass through the ring because of increased volume, due to heat.

Each metal has its own co-efficient of expansion—that is to say, it expands a definite amount for a definite increase in temperature. The co-efficient of expansion of iron, for instance, is 'C000122, which means that for every 1° C. heated, it increases in length (linear expansion) '0000122 of its original length.

For example.—A bar of iron 20 feet long is heated from 15° C. to 95° C. How much will it increase in length? For the 80° C. increase in temperature it will expand $\cdot 0000122 \times 80 = \cdot 000976$ of its length.

20 feet = 240 inches.

 $\frac{976}{1,000,000} \times 240 = .234$ inches increase in length, or nearly $\frac{1}{4}$ of an inch.

The total increase in volume or bulk (cubical expansion) will be three times this—namely, .702 cubic inches.

Fig. 10 is an illustration of the apparatus used to test the linear expansion of a metal bar when heated.




FIG. 10.—Apparatus to test linear expansion of metal rod.

The Effects of Heat on Solids are put to many practical applications. Iron rods are made to brace up buildings, and other structures, by being first heated and then screwed up tightly at the ends, and allowed to cool and contract or shrink. This force of contraction is irresistible, as may be shown by using the apparatus shown in Fig. 11, in which a heated iron bar is placed and screwed tightly up; on cooling, the bar is broken in pieces by the contractile force.

Iron tyres are shrunk on to wheels by being heated first and allowed to cool on the wooden rim, the spokes, rim, and hub being thus firmly bound together. In the metal work of bridges, and other structures, allowance must be made for expansion of material due to heating (see problem on expansion); and the sections of rails on a railway are always laid a small distance apart at their ends: otherwise the expansion on a hot summer's day would be sufficient to cause a disaster, owing to twisting of the track.

The reason why thick glass vessels will not stand heat is, therefore, easily explained; the glass on heating becomes expanded, but being a bad conductor (see "Conduction") is not able to transmit the heat quickly enough, and the two portions of the glass are in unequal strain and consequently crack, since the glass is not elastic enough



FIG. 11.—Apparatus to show effect of contraction on heated metal bar.

to prevent this. Thin glass vessels, such as are used in chemical operations, cause no such trouble, and liquids are constantly boiled in them.

Heat is conveyed from one substance to another in several ways — by conduction, by convection, and by radiation.

By Conduction the heat is transferred from one particle of the substance to another, the particles having a higher temperature giving up heat to those near to them having a lower temperature, until the heat is equalised.

Substances vary much in their power of conducting heat. Good conductors are those which readily transmit heat from one part of their substance to another. This may be shown by taking bars of iron and copper, for instance, of the same dimensions, and fixing on them at

intervals, by means of paraffin wax, small wooden balls (Fig. 12). On heating the bars, as shown in the figure, the metals take up the heat and transfer it according to their conductivity, the wax melts, and allows the balls to drop as the temperature rises. It will be found that the balls will drop off the copper bar before the iron, thus proving its greater conducting power for heat.

Gases and liquids are bad conductors of heat, as are many solids, except the metals. Asbestos is a particularly bad conductor, and this, in conjunction with its power of resisting fire, makes it a valuable material for fire prevention and fire-proofing.

In Convection the heat is carried from one portion to



FIG. 12.—Experiment to show conducting power of metals.

another by actual movement of the particles. This may be well shown by sprinkling sawdust in a flask partly filled with water, and then applying heat, whereupon the particles of sawdust move about and show the direction of the convection currents. Convection can only take place in liquids and gases.

Radiation.—When we stand near a source of heat, say a fire or furnace, we feel the warmth which is radiating from that source. If a screen be placed between, the difference is at once noticed, which proves that the sensation is not due simply to the air itself being hot. Radiation is going on in a greater or lesser degree from the surfaces of all bodies, and the intensity varies according to the intensity of the source, and also with the distance from it, and the radiating power of the heated surface or body.

Heat can be reflected, just as light can. This may be proved by means of two concave mirrors arranged as shown in Fig. 13. In the focus of one of the mirrors is placed a source of heat, such as a hot metal ball: in the focus of the opposite mirror is placed a small piece of phosphorus or some inflammable material, the latter (it will be seen) being readily set on fire by the reflected and focussed heat. The heating effect produced by the sun's rays through an ordinary double convex lens is well known.




FIG. 13.—Arrangement of mirrors, so as to focus heat.

The reflection from plane (flat) surfaces may be shown by means of an air thermometer (see description, p. 22). Bodies which best reflect heat naturally absorb it least, and substances which take up heat most readily are the worst reflectors; consequently light-coloured clothing in summer is cooler than black. On the other hand, it has been proved that bodies which best absorb heat also radiate it best, and on this account vessels which are required to hold or retain their heat should be kept brightly polished, so as to prevent radiation as much as possible.

Heat also promotes chemical action, and affects

the conductivity of metals for heat and electricity. Bodies vary greatly in the amount of heat they can take up—that is, in their capacity for heat, generally spoken of as their specific heat.

Water is taken as the standard whereby specific heats are compared, since it has the highest capacity for heat of all known substances; and the standard being 1, the specific heat of mercury (quicksilver), for instance, is $\cdot 033$, which is practically $\frac{1}{30}$. The meaning of this is that it requires thirty times as much heat to raise one pound of water 1° as it does to raise one pound of mercury 1°. This explains the great efficiency of hot water as a means of heating the air in a room.

Thus: The specific heat of air is 0.237, that of water being 1. Hence 1 lb. of water in cooling through 1° C. heats $\frac{1}{0.237}$ lbs. = 4.2 lbs. of air 1° C.

Again: Water is 770 times heavier than air; therefore 1 cubic foot of water in cooling through 1° C. heats $(770 \times 4.2) = 3234$ cubic feet of air 1° C.

Latent Heat.—If a pound of water at 80° C. be mixed with a pound of water at 0° C., the result would be two pounds of water at 40° C.; but if one pound of water at 80° be mixed with one pound of *ice* at 0°, the result would be two pounds of water at 0°. Neither the temperature nor the volume of the ice has been increased; it has simply become liquefied to water, and the 80° heat has become *latent* or has apparently disappeared. Thus 80° is known as the latent heat of water. It is the amount of heat necessary to convert ice at 0° into water at 0°.

Again, when heat is applied to water the temperature rises until the boiling point is reached, when the continued application of heat causes no increase in temperature. A thermometer placed in the vapour (steam) does not indicate more than 100° C., however much heat is applied to the water. The heat being thus expended is being used

up in converting the water at 100° C. into steam at 100° C., and this is known as the latent heat of steam. If the steam be passed into water, its latent heat is converted into sensible heat again.

For example: 20 lbs. of steam at 100° C. are passed into 200 lbs. of water at 10° C., and condensed. The temperature of the total water finally is 67° C. What is the latent heat of the steam?

Heat lost by steam. = Heat gained by water. If l represents the latent heat, then—

20 l + 20 (100 − 67) 200 (67-10)

20 l + 660 = 11400

∴ 20 l = 11400 − 660


∴ l = 537

Hence by this experiment the latent heat of steam has been found to be 537.

Heat and its Measurement.—Instruments used to measure the *intensity* or *degree* of heat are called thermometers, and those used to measure the *amount* or *quantity* of heat are called calorimeters.

The ordinary thermometer (Figs. 14 and 15) consists of a glass stem through which passes a capillary (i.e. very fine) tube, and has a bulb at one end which serves as a reservoir for the liquid employed, mercury or alcohol, which latter remains liquid at a much lower temperature than mercury does. Mercury is dsed because it is a liquid, and remains so for a fair range of temperature; it is easily heated and expands regularly. This bulb and tube are filled with mercury by alternately heating and cooling the bulb and keeping the end of the fine tube under mercury. The tube is sealed up by a blowpipe flame when a suitable length of it is filled.

It is next necessary to graduate the stem, which is done by taking two fixed points, the freezing and boiling points of water. By placing the thermometer in a suitable apparatus, these points are obtained and their position marked on the stem. Fig. 16 shows the apparatus used to determine and mark the point at which water boils. The thermometer bulb is surrounded by steam from the water which is kept boiling in the vessel. The freezing point is determined by surrounding the bulb by melting



Figs. 14, 15. — Common forms of thermometers.




FIG. 16.—Apparatus for graduating thermometers at the boiling point of water.

ice. The space between the two is divided according to the scale decided upon. If the Centigrade graduation, the freezing point is marked 0° and the boiling point 100°, and the stem is divided into 100 equal parts between these two points. If the Fahrenheit scale, then the freezing point is made 32° and the boiling point 212°, and the intervening space divided into 180 equal parts. The other system of graduation due to Reaumur is never used in this country. On it the freezing point is 0° and the boiling point 80°.

22 PHYSICS & CHEMISTRY OF MINING.

A delicate and useful means of measuring heat effects is that devised by Sir John Leslie. It depends for its action upon the expansion or contraction of a volume of air. The instrument, as shown in the illustration (Fig. 17), consists of two bulbs connected by a glass tube, and fitted on a stand. The bulbs contain air, and the glass tube is partly filled with coloured liquid. On bringing a source of heat near




Fig. 17.-Leslie's air thermometer.

one of the bulbs, or by placing the warm hand on it, expansion of the air takes place and causes the liquid column to move. The stem is graduated into divisions according to experiments made at known temperatures.

It is often desirable to know the lowest temperature, and also the highest, that has prevailed during a certain time, say twenty-four hours. An instrument called the maximum (greatest) and minimum (least) thermometer has been constructed for this purpose. As shown in the illustration (Fig. 18), it consists of two thermometers of

special shape fitted on a suitable support. In one the liquid is mercury, in the other alcohol, the former being the maximum thermometer, and the latter the minimum. The maximum has a small piece of iron rod moving freely in the tube; as the mercury expands it pushes this small rod before it, and it remains at the furthest or highest point thus reached, and therefore shows the maximum temperature reached in a given period. The minimum thermometer has a small glass tube moving freely in it. When the alcohol expands, it simply flows through this index tube without moving it; but when it contracts the small index is drawn back by the receding liquid, when




Fig. 18.-Maximum and minimum thermometers.

the end of the alcohol column is reached, by force of cohesion or capillary action. In this way the index always remains at the lowest temperature touched by the alcohol thermometer.

It has been pointed out (p. 9) that according to Charles's law 273 volumes of gas (or air, of course), when raised in temperature 1° C. become 274 volumes—that is,

$$273 + \left(\frac{1}{273} \text{ of } 273\right).$$

Assume that a gas occupies 273 volumes, measured at 0° C.

This would become 274 , , at 1° C. 275 .. at 2° C.

On the contrary 273 volumes measured at 0° C.

would become 272 ,, ,, -1°
271 ,, ,, -2°
171 ,, ,, -100°
and theoretically, nil ,, ,, -273°

So that, in theory, the gas would disappear altogether at a temperature of -273° C. This is impossible, practically. As a matter of fact, long before this temperature is reached, the gas becomes either liquefled or solidified, and Charles's law fails to operate. Nevertheless, the point -273° C. is always spoken of as the absolute zero of temperature.

Conversion of Degrees.—For the conversion of degrees Fahrenheit into degrees Centigrade, and vice versa, the subjoined rules may be followed:—

To convert F.° into C.° subtract 32 from the original number, and divide the remainder by 1.8. Thus 176° F. $-32 \div 1.8 = 80^{\circ}$ C.

To convert C.° into F.° multiply by 1.8 and add 32. Thus 80° C. \times 1.8 + 32 = 176° F.

Taking the melting point of copper as 1100° C. what is this on Fahrenheit scale?

$$\frac{1100 \times 9}{5} + 32 = 2012^{\circ} \text{ F.}$$

The ignition point of an explosive mixture of fire-damp and air is 1230° F. What degree does this represent on the Centigrade scale?

$$\frac{1230 - 32}{1.8} = \frac{1198}{1.8} = 665^{\circ} \text{ C}.$$

(It should be noted that $\frac{9}{5}$ is equal to 1.8.)

CHAPTER III.

THE DIFFUSION OF GASES.

THE property that all gases have, of diffusing or spreading one into the other, is a very important one in Nature, and especially so to those connected with mining.

Diffusion of Gases, how illustrated.—It is well illustrated by filling two gas jars-one with carbon-dioxide, the other with hydrogen; one a very heavy gas, the other extremely light. Then place the jars mouth to mouth, the one containing the hydrogen being upper-It would be expected that, owing to the great difference in their densities (carbon-di-oxide is twenty-two times heavier than hydrogen), the two gases would remain as placed, the light one resting on top of the heavy one, but this is not the case. It will be found in a very short time that some of the hydrogen has diffused into the carbon-di-oxide, and also that the latter has diffused into the hydrogen; and before long the gases become so intimately mixed, that the composition of the gas in the lower jar is the same as that in the higher jar. Further, these gases will never separate out again into a heavy and a light layer, as they were at the beginning of the experiment.

This effect takes place in the case of all gases or mixtures of gases, whatever their difference in density; and strangely enough, the greater the difference between the densities of the gases, the more rapidly the diffusion goes on.

A knowledge of this law explains why it is that a heavy gas like carbon-di-oxide is not always found on the floor of a mine, but equally diffused throughout the atmosphere. Fire-damp also, although collecting at first in the highest parts of the roof, soon diffuses out into the heavier atmosphere, and forms an explosive mixture unless sufficiently diluted with air.

Testing Diffusion of Gases.—The principle of gaseous diffusion is well illustrated by the apparatus shown in Fig. 19.

It consists of a porous cell (of the kind used in electric



Fig. 19.—Apparatus for diffusion experiment.

batteries), fastened to one limb of a U-shaped tube. The tube is filled with water to the same level in both limbs. On bringing a glass vessel containing hydrogen, or coal-gas, or firedamp, over the porous cell, the gas in the vessel diffuses through into the porous cell more quickly than the air can escape, and consequently produces pressure inside the cell, which is shown by the forcing out of the water from the open end of the U tube.

An ingenious application of the principle has been made in the case of Ansell's firedamp indicator. On placing the apparatus, consisting of porous cell and U tube, in a suspected atmosphere, if fire-damp be present it diffuses through more rapidly than the air can escape, and causes pressure, which is made to act on a column of mercury (instead of water). The mercury rising in the open limb makes electrical contact with a platinum wire fused through the side of the tube, and completes an electric circuit, in which is a

bell. The other terminal is a wire in the bend of the U tube.

The Hygrometer and its Use.—The importance of a certain amount of moisture in the air of a mine cannot be over-estimated, since the presence of coal dust in the atmosphere seriously increases the likelihood of an explosion.

Mr Henry Hall's experiments with coal dust proved that

when the flame from a blown-out gunpowder shot, or the ignition of a small quantity of fire-damp, passes through an atmosphere containing even a moderate quantity of dry coal dust, the dusty atmosphere will explode with great violence, and that the explosion passes on throughout any length of such atmosphere, increasing in force as it progresses. Further, that coal dust from several seams in various districts is almost as sensitive to explosion as gunpowder itself.

The probable cause of this explosive action, chemically, is the extremely fine condition of the coal dust, rich in carbon and hydrogen (see later for their properties), only waiting opportunity to combine with oxygen from the air. Such opportunity is afforded by an increase in temperature from any cause such as a blown-out shot or slight ignition of fire-damp, more especially if carbonic oxide be present also.

The mine manager, therefore, should have at his disposal an instrument for indicating the amount of watery vapour, humidity, or dampness in the air. The presence of aqueous vapour in the air is not alway readily recognised by the senses, but can be clearly proved to be present by its action on various chemical substances which greedily absorb it. In summer, though the air may feel dry, there is really more moisture in it than on a winter's day, when air is said to be damper, the warmth of the atmosphere helping it to hold more vapour. Sulphuric acid (oil of vitriol) on exposure to the air soon increases in bulk; and the solid, calcium chloride, takes up water so readily that it liquefles itself in a very short time. Another useful agent is known as anhydrous copper sulphate. dry it is white, but on absorbing moisture becomes blue, so that it readily shows the presence of moisture in air or any gas. By using suitable substances of this kind. and noting the increase in weight when a known volume of air is passed over them, the amount of moisture in a given volume of air is readily estimated.

28 PHYSICS & CHEMISTRY OF MINING.

By means of the apparatus shown in Fig. 20, the amount of moisture in the atmosphere may be measured. The tubes a contain calcium chloride, the volume of the aspirator b is known, and the air is filtered through cotton wool in the tube c to separate dust. The gain in weight of the tubes a represents the moisture in the volume of air drawn through them by the aspirator.

This method, however, would be too lengthy and inconvenient in the mine, and an instrument called a hygrometer is used.¹





FIG. 20.—Apparatus for moisture estimation.

The apparatus illustrated in Figs. 21, 22 is known as Mason's wet and dry bulb hygrometer and consists of two thermometers placed side by side on a stand, so that the air can circulate freely about them: round the bulb of one of them is fastened a piece of absorbent cotton wick, the ends of which dip in a small vessel of water. The water is drawn up the threads by capillary action, and spread over the surface of the thermometer bulb by means of the wick. Evaporation takes place from the surface, more or less rapidly according to the amount of watery vapour in the atmosphere of the

¹ This should not be confused with the *hydrometer*, an instrument used for measuring the density of liquids.

mine. The more vapour present, the more slowly the water evaporates from the thermometer bulb, and consequently the less the cooling effect upon it; the less vapour present in the air, the more rapid the evaporation from the surface of the wick on the thermometer bulb, and consequently the greater the cooling effect on it.



Figs. 21 and 22.—Mason's hygrometer.

Evaporation is always accompanied by loss of heat. It is evident, then, that the *greater* the difference between the readings of the two thermometers, the *less* aqueous or watery vapour present in the air of the mine. Tables have been constructed showing the dampness of the air from its temperature, and from the difference in the two thermometer indications.

Another form of hygrometer is that known as Daniell's (Fig. 23). It consists of a tube bent twice at right angles,

and having a bulb at each end. One bulb is of black glass, and in it is a thermometer and a little ether (a liquid which very readily evaporates). The other bulb is of clear glass, and has a piece of muslin wrapped round it. When ether is poured on this muslin, rapid evaporation takes place, pro-



Fig. 23.—Daniell's hygrometer.

ducing cold, and thus causes the ether in the black bulb to evaporate also, and consequently its temperature is lowered. Moisture or dew then begins to deposit on the outer surface of the black bulb. When this is noticed the thermometer is read, and the instrument left to itself until the dew disappears again; the thermometer is again read, and the average of the two results taken as the temperature of the dew-point. This is an indication of the amount of moisture in the air; the lower the temperature necessary to

produce dew on the bulb, the less the amount of water-vapour in the air.

The amount of vapour which will saturate a cubic foot of air under standard pressure of the barometer (760 millimetres, practically 30 inches) is as follows:—

At 32°	F.			abo	ut 2	grains
50°	F.			,,	4	,,
6 0°	F.	•	•	,,	6	,,
70°	F.			,,	8	,,

and a difference of about 5° between the readings of the wet and dry bulb thermometers is equal to about 75 per cent. of saturation, which is held to be a healthy amount.

CHAPTER IV.

COMPOSITION OF THE ATMOSPHERE.

THE ancients observed that when certain metals were exposed to the air they lost their lustre and brilliancy, and became coated with a film of something different from the metal altogether; and further, they proved that this alteration was accompanied by an increase in weight.

Oxygen and Nitrogen.—Priestley and Lavoisier investigated the matter still more fully, and proved by using mercury, that the film at first produced on the metal when heated in air, could be again decomposed, on further heating, into the metal mercury and a gaseous substance which had evidently been derived from the atmosphere, and is now known as oxygen. It was also proved that a certain amount of gas remained unaltered by the mercury, and incapable of forming any further film of oxide, and thus the air was shown to consist of two gases which came to be called oxygen and nitrogen. Modern investigations have shown that there are other constituents also, in small quantities, to which the names argon and helium have been given, but they are of but passing interest in these notes.

An interesting experiment to show the composition of air is made as follows:—Take a small piece of candle and fasten it on a cork, or in a small porcelain basin, and float it in a shallow tray of water. Now light the candle and place a bell-jar over it; the candle burns with a gradually decreasing flame and finally goes out, and the water will be found to have risen in the jar. The oxygen of the

air has been used up by the burning candle until there was none left to support the combustion, when the candle flame was necessarily extinguished.

A more accurate way of showing the composition of the atmosphere, is to take a measured volume in a glass tube



FIG. 24.—Apparatus for testing the composition of the air.

known as a eudiometer, which is sealed at one end and has divisions marked and numbered on it (see Fig. 24). Fasten a piece of phosphorus (which should be handled with great care under water because of its inflammable nature) on the end of a piece of wire bent as shown, and introduce it into the air space, the volume of which was previously noted, and leave it thus for a few hours, having a few inches depth of water in the outer vessel. phosphorus takes up the oxygen from the air, forming a substance (oxide of phosphorus) which readily dissolves in the water. Finally, nothing remains but nitrogen, the volume of which can be measured.

In an actual experiment, the air measured 250 volumes before putting in the phosphorus, and, after the action was finished, the residue measured 198 volumes, which calculates out to 20.8 per cent. of oxygen.

The average composition of pure dry air is practically 21 volumes of oxygen

gas mixed with 79 volumes of nitrogen gas, and it has been found to vary only within narrow limits in all parts of the globe, and at various altitudes. The air of crowded rooms, theatres, etc. has naturally less oxygen, and the same remark applies to ill-ventilated mines, the oxygen in which may fall almost one per cent below the normal.

If the gases oxygen and nitrogen, separately prepared, be mixed in the above proportions, the mixture possesses the same properties as ordinary air. When chemical action takes place between the nitrogen and the oxygen of the air, as caused by an electric discharge through them, a reddish-brown gas is produced in which no life could exist. The properties of these two gases are now to be considered.

Preparation and Properties of Oxygen Gas.—Oxygen may be made by the method used by Lavoisier and Priestley—namely, by heating mercuric oxide—but the method is not very practicable, and is costly compared with others that are available. The most ready method is as follows (see Fig. 25):—Procure a glass test-




FIG. 25.—Diagram illustrating the preparation of oxygen gas.

tube, about $6'' \times \frac{3}{4}''$, and fit it with a good sound cork, through the centre of which a hole has been bored of suitable size to take a piece of bent glass delivery tube. Fill the test-tube about $\frac{1}{3}$ full of a mixture of potassium chlorate and manganese-di-oxide (4 parts chlorate to 1 part oxide). Now attach to the glass tube fitted through the cork a suitable length of indiarubber tubing, so that the end of the latter may be brought under the shelf of a pneumatic trough, in which an inverted jar is placed filled with water. On applying heat (by means of a Bunsen burner or a spirit lamp) to the contents of the tube, oxygen gas will soon be given off, and will bubble up through the water in the inverted glass jar or cylinder until all the water is displaced, and the jar full of gas. By placing a flat glass plate under the mouth

of the jar, the latter may be removed from the trough, and another one, filled with water, substituted. In this way collect two or three jars full.

By means of a piece of stout wire, bent into a cup shape at one end (called a deflagrating spoon), introduce a piece of burning sulphur into one of the jars. Notice the increased brilliance with which the sulphur burns. Similarly, on placing a piece of glowing charcoal into the gas, it burns with very much increased brightness. A piece of wood, first lit and then partly extinguished, leaving a red-hot spark on the end, on being introduced into the gas at once bursts into flame; and a piece of fine iron wire, tipped with sulphur to start the action, will burn brilliantly in the gas, throwing out sparks of oxide of iron at a white heat.

Several processes have been proposed to obtain pure oxygen from the atmosphere, and one of the most successful of these depends upon the use of a substance—barium oxide—which, when heated in air to a certain degree, takes up oxygen. On increasing the temperature, this combined oxygen is given up again, leaving the original substance to be used over and over again. The gas is largely used in a compressed form, in strong steel cylinders made to withstand a pressure of many atmospheres. One of the most important purposes for which it is used in connection with mining is for restoring a person who has been overcome by noxious gases. In a compressed form it is one of the essential parts of a pneumatophore, an appliance by means of which a person may enter and exist in a noxious atmosphere.

Oxygen gas has very powerful chemical properties, and (so far as we know at present) the chief purpose of the nitrogen gas in the air is to dilute or weaken the action of the oxygen. If breathed alone for any appreciable time it produces feverish symptoms.

In every 18 lbs. of water there are 16 lbs. of oxygen, and almost one-half of the weight of the rocks composing

the earth's crust consists of oxygen, combined with silica, alumina, iron, lime, magnesia, potash and soda, in varying amounts. Most of the chemical actions brought about by the atmosphere are due to its oxygen. Instances are found in the rusting of metals, the breathing of men and animals, the decay and decomposition of animal and vegetable matter—all being processes in which oxygen plays a most important part.

Oxygen is the only gas which will support respiration, and unless it be present in the free state, respiration and life are not possible. Oxygen gas is soluble in water, a matter of vital importance to fish life, it being as necessary to their existence as to ours. Hence the need of aerating the water in aquaria. Fish cannot live in water from which the air has been expelled by boiling, or in which the oxygen has been used up in any way.

Nitrogen and its Properties.—The other constituent of the atmosphere, nitrogen, is the exact opposite, in chemical properties, to its companion oxygen. Though entering into the composition of certain very active chemical reagents (e.g. nitric acid, ammonia, etc.), it is itself very inert, or inactive, chemically, and most of its properties are negative. We have seen that it is widely distributed in Nature, forming (as it does) four-fifths of the atmosphere by volume. It enters largely into the composition of plants and animals, some plants having the power of absorbing this atmospheric nitrogen by means of bacteria on their roots.

Nitrogen will neither burn itself, nor allow anything to burn in it, and it will not support life. This latter is an important fact to remember, because, as will be shown later, nitrogen is a large constituent of after-damp. Nitrogen is only very slightly soluble in water, and combines directly with very few substances. The gas may be made by depriving air of its oxygen, as already shown; also by several other processes, which are too purely chemical to describe here.

CHAPTER V.

SUNDRY CONSTITUENTS OF THE ATMOSPHERE.

The composition of *pure dry air* has been previously given, but air in this condition is a rarity, and under ordinary circumstances it always contains, besides oxygen and nitrogen, more or less of the following compounds:—

Aqueous (watery) vapour.

Carbon-di-oxide (commonly called carbonic acid).

Ozone.

Nitric acid.

Ammonia.

Sulphur compounds.

It is well to consider why and how these substances are always present in variable amounts.

Aqueous Vapour.—The amount of aqueous vapour present in the air depends upon climatic conditions, and upon the temperature. When the air is holding as much vapour as it possibly can, it is said to be saturated, and if when in this condition the air be cooled, some of the vapour will be deposited in the form of dew or rain. There is always more vapour present in the atmosphere in summer than in winter, because the warmer air can hold more in suspension.

The great source of water vapour in the air is from the evaporation from large surfaces of water which is constantly going on. It is a matter of common observation that after a long period of dry weather the level of large sheets of water is perceptibly lower, due to evaporation,

The liquid has gone into the atmosphere, in the form of aqueous vapour. Another source is in the breathing of men and animals, and another in the burning of any substance containing hydrogen (such as the various oils, coal gas, etc.). This latter process is illustrated in Fig. 26, where at B water collects, which is produced from the hydrogen of the coal gas and the oxygen of the air. It is a common experience that if one breathes on a mirror the moisture is condensed on its cool surface; or if a cold surface, say of metal, be held over any gas flame, it becomes wet, because the moisture, produced by the hydrogen of the burning gas, is condensed; and in a crowded room one sees water trickling down the windows and walls especially if the temperature outside be low.

It will be seen from this how useless and insanitary it is to attempt to dry, or *air*, an apartment by lighting gas in the room. The air becomes charged with moisture and also with the impure products of combustion (chiefly carbon-di-oxide, moisture, and sulphur compounds).

Carbon-di-oxide (Carbonic acid gas).—This gas is usually present in air to the extent of about 04 per cent. It is being continually produced in all processes of burning carbonaceous matter (e.g. coal, wood, oils, etc.); in the putrefaction and decay of organic matter; also by the breathing of men and animals.

By drawing the products of combustion of a gas flame through lime water, as in A, Fig. 26, a milkiness is produced in the latter, proving the presence of carbon-di-oxide. Also by breathing through lime water the same effect is produced, due to the same cause (see also p. 57).

Now since all these sources of carbon-di-oxide are at work, continually discharging the gas into the air, the question naturally arises, What becomes of it all? The answer is that plant-life in general has the remarkable property (in presence of sunlight) of decomposing or splitting up carbon-di-oxide, using the carbon for its

structures, and giving us oxygen back again, for purposes of respiration. This may be readily proved by the following experiment.

Fill a tall narrow bell-jar, having a stopper ground into it, with water, then immerse a good sized bunch of fresh mint, or fresh green leaves of any kind, in the water. Invert the whole in a dish of water and place in the sunlight; bubbles of gas will appear on the leaves, and then detach themselves, collecting at the top of the bell-jar. On applying a glowing chip to this gas, it will be found to be oxygen.




Fig. 26.—Drawing the products of a gas flame through lime-water.

It has been noticed that at high altitudes the amount of carbon-di-oxide increases, no doubt because there is very little plant-life in those regions.

The other properties of carbon-di-oxide are considered later on (p. 56).

Ammonia is a compound of nitrogen gas and hydrogen gas, and is produced naturally by the decomposition of bodies containing nitrogen. Its pungent smell can be readily recognised on entering a stable, the door of which has been closed for some little time. It is more likely to be found in air near towns than in fresh country air. The

small amount present in air contributes to plant-life, on account of its nitrogen.

Nitric Acid.—This is formed in the air whenever a thunderstorm is in progress, and rain water examined after a storm of that kind is always richer in nitrates than ordinary rain water. These nitrates are a valuable plant food. In some parts of the world, notably in Chili (South America) large deposits of nitrates occur which have been formed by bacterial action (or nitrification).

Ozone is never found in the neighbourhood of towns, but only in the freshest country air, and in sea air. It is easily destroyed by decaying or putrefying organic substances of all kinds. The amount varies in country air, but is fairly constant in sea air. It is produced by electrical discharges in the atmosphere, and also (it is supposed) by the evaporation of sea water. In many of its properties it resembles hydrogen peroxide, and no doubt it is often mistaken for this substance.

Sulphur compounds are chiefly found in the neighbourhood of towns or works, and are due to the burning of fuel or other substances containing sulphur. Certain sulphur compounds are also due to the decay of animal and vegetable matter containing sulphur (see sulphuretted hydrogen or stink damp).

Sulphur or brimstone itself is found in the free state or native condition, naturally, and has therefore been known from the earliest times. It is generally found in volcanic districts, and there are mines of sulphur near Sicily. Many of the ores of metals are compounds of sulphur, as for instance, iron pyrites (bisulphide of iron); galena (sulphide of lead); copper pyrites (sulphide of copper and iron).

When sulphur is heated in presence of air, it burns and forms sulphur-di-oxide, a very pungent smelling gas; but

if heated out of contact with air or in closed vessels it goes off in the form of vapour, and then recondenses on the first cold surface it comes in contact with. This action is called *sublimation*, and is a similar process to the *distillation* of a liquid.

Sulphur is like carbon in the respect of having allotropic modifications (see under "Carbon"). That is to say, it may exist in several different forms, thus—rhombic and prismatic sulphur (so-called because of the crystalline shape), plastic sulphur (so-called because of its being able to be moulded like clay in the fingers), and amorphous (without shape) sulphur, are all varieties of one and the same element. Sulphur, like carbon, forms two compounds with oxygen—namely, sulphur-di-oxide and sulphur-tri-oxide, the former already mentioned, the latter forming when combined with water the well-known oil of vitriol or sulphuric acid.

CHAPTER VI.

WATER.

Water 1 was formerly classed among the elements, but is now readily proved to be a compound of hydrogen and oxygen. By passing an electric current through water,




Fig. 27.—Apparatus for decomposing water.

the latter is decomposed, and the two gases which compose it are collected in the two tubes of the voltameter, as the instrument is called. It is found that the volumes of the gases collected are in the proportion of

¹ Chemical formula H₂O. Density (in the form of steam), 9. Composed of 2 parts by weight of Hydrogen combined with 16 parts by weight of Oxygen. By volume, as water vapour or steam, it contains 2 volumes of Hydrogen combined with 1 volume of Oxygen.

two to one, and that the gas with the larger volume is By taking the gases thus produced into one hydrogen. vessel, and passing an electric spark through them, they re-combine, with an explosion, forming water again.

Another method of proof is to use some substance having a greater affinity or attraction for oxygen than hydrogen has, and which is therefore able to decompose water. Such a substance is found in the metals potassium and sodium, which on being thrown on to water at once decompose it, causing hydrogen gas to be liberated. enclosing the metal in a kind of gauze spoon, and holding a cylinder filled with water over the bubbles of gas, they may be collected and proved to be hydrogen.

Further, if steam be passed through a red-hot iron




FIG. 28.—To illustrate decomposition of steam.

pipe, it (the steam) is decomposed into its elements. the oxygen combining with the iron and forming iron oxide (magnetic), and the hydrogen gas passing on in the free Thus $3 \text{ Fe} + 4\text{H}_{0}\text{O} = \text{Fe}_{2}\text{O}_{4} + 4\text{H}_{0}$. It may be condition. readily collected over water, and proved to answer to all the tests for hydrogen gas (see Fig. 28).

When water is cooled down it obeys the usual law of contraction up to a certain point, 4° C., but at that temperature it begins to expand until the freezing point 0° C. is reached. (Hence at 4° C. water has its maximum density.) This expansion is responsible for the bursting of water pipes. and for the breaking down of masses of rock and the crumbling of soils. The water, after filling the crevices of the rocks, expands when frozen with an irresistible force.

Bomb-shells have been burst by filling them with water and then exposing them to the temperature of freezing point, or below it.

Pure Water, and Natural Waters.—Pure water is a product of the laboratory, for water is never found absolutely pure in Nature. The nearest approach to it is rain water, which is really produced by a process of natural distillation. The heat of the sun evaporates water from the sea and other sources; it is carried into the atmosphere as vapour or moisture, and is condensed by cool winds, falling again as rain. But the rain water becomes contaminated by impurities in the air through which it has passed, especially in the neighbourhood of towns.

Water is generally purified by distillation, which consists in converting the liquid into steam and condensing the latter by suitable means, generally by passing through a tube or pipe, round the outside of which cold water circulates (see Figs. 29, 30). By these means the solid impurities are left behind in the boiler or retort.


Filtration, which is resorted to as a purifier of water, does not remove matter which is actually in solution, or dissolved in the water, but only that which is in suspension in the liquid. For the supply of towns, water is filtered through beds of sand and gravel. Since water is the most universal solvent we know of, it follows that all water that has been in contact with the earth or other solid matter is liable to be contaminated by various substances. Most river waters are turbid or muddy, owing to the presence of finely-divided solid matter in suspension. This would settle out if allowed to do so, but the clear water would still contain more or less solid matter dissolved in it. The dissolved substances have been derived from the land, the rocks and strata, over and through which the

AA PHYSICS & CHEMISTRY OF MINING.

has passed, and they vary in nature and in amount with the kind of rocks traversed. Water passing over magnesian limestone contains, roughly, ten times as much solid matter in solution as that which passes over a granite formation.

Not only is there the solvent action of the water itself, but the latter in passing through the air takes up carbonic acid, which enables the water to dissolve carbonates from any deposits containing them; and thus in many waters are found lime and magnesia carbonates and sulphates, to which substances the *hardness* of water is due.

Temporary and Permanent Hardness of Water.—



FIGS. 29, 30.—Condensers.

The hardness caused by lime carbonate and magnesia carbonate can be removed by boiling, or by the addition of milk of lime, the reason being that the carbonic acid, by whose agency they are held in solution, is either driven off (by boiling) or neutralised (by milk of lime). Such hardness is called *temporary*.

The sulphates of lime and magnesia do not owe their presence to the action of carbonic acid, but simply to the solvent action of the water itself. Consequently they are not precipitated on boiling, and are said to cause permanent hardness.

Water may be sometimes so highly charged with carbonate of lime that objects placed in it become, in time, coated with a layer of it, causing petrifaction. In most cases the shells of shell-fish are built up of this substance, which has been assimilated from the water by their organisms. Again, water charged with carbonate of lime and magnesia, in dripping from the roof of a cavern, deposits lime by degrees, forming a growth from the roof known as a stalactite, and a corresponding growth on the floor where the water drops called a stalagmite; eventually the two meet, and form a sort of pillar of lime and magnesia carbonates.

Certain springs—for instance, those at Epsom, in Surrey—are charged with magnesium sulphate (hence the name Epsom salts); others (such as the chalybeate springs found in various parts of the country) contain salts of iron, etc.; and the writer had a particular case under examination some little time ago, where very decided amounts of manganese (not magnesia) were found in solution in a natural water, probably as bicarbonate.¹

Water for Boiler Purposes.—The importance of these facts to persons identified with mining lies in the circumstance that all waters, which have to be dealt with in mines, are contaminated, more or less, by salts of different kinds and in varying quantities; and upon the nature and amount of these solids it depends whether a given water can be used for boiler purposes. This is a matter which can only be thoroughly decided by analytical examination. Not only should the total solids be known, but also the nature of those solids, and the hardness of

¹ See Chemical News, October 1901.

the water. Further, it is necessary to know whether the water is acid, or not.

A water containing, say, 60 or 70 grains per gallon of sulphate of soda, or carbonate of soda, would not be nearly so objectionable as one containing 8 or 10 grains per gallon of carbonate or sulphate of lime or magnesia. Sulphate of lime is a most objectionable constituent, as it forms such a hard, compact scale on the boiler plates.

The following are analyses of boiler scales, which have been formed in boilers fed with waters from various districts:—

	No. 1. p. cent.	No. 2. p. cent.		No. 4. p. cent.		
Silica (sandy matter) }		2.50				
Iron oxide and aluminia (clayey matter)	- •50	•50	4.8	1.60	6.50	2.0
		traces				
Lime sulphate .		82.5	·87	trace	11.6	traces
Magnesia carbon-	98.0	14.5	18-1	10-4	29·2	20.0

Waters containing magnesium chloride are to be avoided, as at high temperatures hydrochloric acid is liable to be produced, which, of course, would corrode the boiler plates.

A thin scale in a boiler is not undesirable, as it tends to neutralise, or destroy, any acids that may be formed. The water from a peaty moorland is often found to be acid, and many pit waters are very decidedly so with sulphuric acid, due to the weathering of coal-brasses, or iron pyrites, a compound of iron and sulphur. Ochrey waters are often acid.

When the use of waters containing lime and magnesium salts is unavoidable, methods are often made use of for the removal of these objectionable scale-forming substances. These methods are many and varied. The principle underlying some is to precipitate

or throw down the lime and magnesia salts, by means of suitable chemicals, generally in the form of carbonate of soda, caustic soda, phosphate of soda, milk of lime, used singly, or mixed, to suit the particular needs of the water to be treated. The precipitated matter is allowed to settle in tanks, and the clear liquid is siphoned or pumped off; or the sediment is separated by passing through a series of partitions in which are baffle plates and filtering medium, such as wood pulp, shavings, or coarse matting.

Most of these processes, as a rule, give good results, provided that they have proper attention, and that the supply of chemicals be properly regulated according to circumstances. After a wet period most water supplies require less chemicals per 1000 gallons than they do in a dry period, as in the latter case the solids in the water are getting concentrated. After treatment, the water is said to be softened. It is, as a rule, preferable to treat the water before going into the boiler, when this is practicable.

Besides the chemical reagents above mentioned, other substances are used, such as tannate of soda, argol (a crude tartrate of potash), petroleum, and tannery refuse. Zinc plates are, in some cases, suspended in the boiler, the galvanic action set up between the zinc and the iron being said to have a beneficial effect in scale prevention. Oyster shells and even potatoes are used in many cases. Greases are, as a rule, to be avoided, as they are liable to give rise to acid substances at the temperature which exists in the steam boiler.

The pitting or corrosion of boilers may be due to the presence of acid (sulphuric acid as before mentioned), also of hydrochloric acid from magnesium chloride. It is also thought possible that *local action* may cause it in some cases—that is, a slight difference in chemical composition between two adjacent plates, giving rise to galvanic action; or a difference brought about in punching

or shearing the plates, whereby the material near the punched hole is altered somewhat, physically, from the rest of the plate, again giving rise to galvanic action.

The external corrosion of boilers is sometimes a cause of weakening. This is, of course, more likely to occur when the boiler is out of use. When in use, the sulphurous acid gas from the pyrites of the coal is an active agent of corrosion on the parts of the boiler farthest removed from the fire, upon which dampness or moisture may condense at some time. Soot and dirt on these parts encourage the retention of water, and therefore increase the tendency to corrosion, since they help to retain the acid fumes. Hence the boiler should be inspected regularly, and kept as clean and dry outside as possible.

Hydrogen.—It is important that this gas, which with oxygen forms water, should have here a description of its properties and methods of formation.

A curious and interesting sight is to see the liberation of hydrogen from water by means of the metals potassium and sodium. The water appears to take fire owing to the flame produced due to the ignition of the liberated hydrogen.

The most general method of making hydrogen is by decomposing an acid, such as hydrochloric or sulphuric acid, by means of the metals zinc or iron. Fig. 31 shows the apparatus used for this purpose. The zinc is placed in the flask, fitted, as shown, with a safety funnel, down which the diluted acid is poured. The gas begins to come off immediately, but time must be allowed for the air in the flask to be expelled before collecting. It is collected over water in a glass cylinder placed on a beehive shelf, as shown.

Hydrogen is the lightest substance known, being about 14½ times lighter than air. On this account it is used for filling navigable balloons, etc., though in some cases coalgas is used for cheapness' sake. It may be collected in a

WATER.

vessel held upside down, and poured upwards from one vessel to another. It is supposed to be the vapour of a very volatile metal to which the name hydrogenium has been given. Certain metals, for instance platinum, palladium, and even iron, absorb the gas or occlude it, and many useful applications are based upon this property with regard to the first two metals above named.

Those interesting objects known as meteorites, which fall from time to time on our sphere, often contain




Fig. 31.—Apparatus for the preparation of hydrogen gas.

occluded hydrogen gas, and we know beyond doubt (by means of spectroscopic observations) that the atmosphere surrounding the sun (more correctly called the *photosphere*) is one huge volume of hydrogen gas in an incandescent state.

Hydrogen is necessary to the constitution of all true acids, though many substances are commonly called acid which do not contain hydrogen (notably carbon-di-oxide).

One-fourth of the weight of marsh gas or fire-damp is due to hydrogen. It is very inflammable, and forms a highly explosive mixture with air or oxygen. When it burns, water is produced. The gas has no poisonous or shearing the plates, whereby the material near the punched hole is altered somewhat, physically, from the rest of the plate, again giving rise to galvanic action.

The external corrosion of boilers is sometimes a cause of weakening. This is, of course, more likely to occur sulphurous acid gas from the pyrites of the coal is an active agent of corrosion on the parts of the boiler farthest removed from the fire, upon which dampness or moisture may condense at some time. dirt on these parts encourage the retention of water, and therefore increase the tendency to corrosion, since they help to retain the acid fumes. should be inspected regularly, and kept as clean and dry outside as possible.

Hydrogen.—It is important that this gas, which with oxygen forms water, should have here a description of its properties and methods of formation.

A curious and interesting sight is to see the liberation of hydrogen from water by means of the metals potassium and sodium. The water appears to take fire owing to the flame produced due to the ignition of the liberated hydrogen

The most general method of making hydrogen is hy decomposing an acid, such as hydrochloric or sulphull acid, by means of the metals zinc or iron. Pig. 31 sh

the apparatus used for this purpose. The zinc is in the flask, fitted, as shown, with a safety funn which the diluted acid is poured. The one come off immediately, but time must air in the flask to be expelled before collected over water in a glass cylinhive shelf, as shown.

Hydrogen is the lightest substan 141 times lighter than air. filling navigable balloons, gas is used for cheapness

17.17.

vessel held upside down, and power were vessel to another. It is success.

very volatile metal to while the many been given. Certain metal to while the many ladium, and even mon, and the many useful applications 22. The many useful applications are many useful applications are many useful applications are many useful applications.

contact with as harmless. ains $\frac{3}{4}$ of its xide contains le), $\frac{3}{11}$ of its hich he toils, bon is a large f his flesh and

and calcium, in thole mountain e compounds of compounds as a ch of chemistry, y. Formerly the th chemical proas in their varied ds good, since the atory, by chemical rly believed to be bon on steel is very of this element are of steel. Within a of carbon, all the fured, from the softest

ments that carbon is a

exists as carbon alone in very different forms (spoken of as allotropic modifications). For instance, the diamond, graphite (from which pencils are made), and charcoal, can be easily proved to be different forms of the same element, carbon. When burnt in oxygen gas they each form the same compound, carbon-di-oxide. A weighed quantity of diamond produces the same quantity of gas as the same weight of pure charcoal does. Other common forms of carbon are lampblack, gas-carbon, animal charcoal, wood-charcoal, etc.

Lampblack is made by burning substances rich in carbon, such as oils, tar, tallow, etc., with as little air supply as possible; and the smoke from them, which is chiefly carbon in a very fine state of division, is condensed in some suitable way in cool chambers, from which it is collected afterwards.

Gas-Carbon, as its name implies, is a product of the gasworks, and has been slowly deposited on the sides of the retorts in which the coal is distilled for gas-making purposes. It is a very pure form of carbon, for a commercial product, and contains little ash. It is used for making carbon rods for electric lighting and for electric battery purposes, also for recarburising, or adding carbon to molten steel.

Coke is a much more impure form of carbon, and contains all the mineral matter which was originally present in the coal from which it was made. It contains, on an average, about 88 to 90 per cent. carbon (see under "Fuels").

Animal Charcoal, or Bone Black, is made by heating bones in vessels from which air is excluded. It contains very little carbon. About 90 per cent. of it is phosphate of lime, but owing to its peculiar condition it forms a sort of carbon sponge. It is used for clarifying certain liquids,

e.g. in sugar refining, and for various other purposes of decolourising.

Ordinary Charcoal is made by heating wood in closed vessels, no air being allowed to enter. It bears the same relationship to wood that coke does to coal, and retains all the mineral matter originally present in the wood, this forming the ash. Charcoal has the remarkable property of absorbing gases in its pores, and on this account is able to prevent certain foul gases becoming injurious. A layer of charcoal spread over decaying or decomposing matter of any sort will at once arrest the smell.

Charcoal is added to soils, in some cases in order to keep them sweet and pure, and trays containing this substance are often placed in the ventilators over sewer pipes to absorb ill-smelling vapours. The reason why charcoal and porous cinders will float on water is because of the air contained in their pores. If this be removed under an air pump they will sink.

The compounds of carbon and oxygen next claim attention. There are two, namely, carbon-mon-oxide, and carbon-di-oxide.

Carbon-mon-Oxide, Carbonic Oxide, or White-Damp.—Chemical formula CO. Density 14. Specific gravity 967. It is composed of 12 parts by weight of carbon combined with 16 parts by weight of oxygen; by volume it contains one volume of carbon vapour combined with one volume of oxygen. This is the most treacherous gas with which the miner has to deal. There are no ready means of detecting its presence. It has no colour, no taste, no distinct smell; yet the presence of so small a quantity as 1 per cent., if breathed for any length of time, is sufficient to cause death. It cannot be too forcibly realised that this gas is as much a poison as prussic acid and arsenic, and does not kill by suffocation, or because of the deprivation of oxygen, as some gases do.

54

The following effects are produced when carbonic oxide is breathed:-

Percentage of gas.	Effect.
·05	After half an hour or more, slight giddiness on exertion.
•10	After half an hour or more, inability to walk.
•20	After half an hour or more, loss of consciousness, and perhaps final death.
1.00	After a few minutes, loss of consciousness, and final death.

Oxygen gas is the best antidote to administer to a person who has been "gassed" with carbonic oxide.

In the pure state the gas will burn, forming the other oxide (CO₂), and in certain proportions it forms an explosive mixture with air. The most explosive mixture is two volumes of CO with five volumes of air. This gas can be often seen burning with a blue flame on the top of a caked coal fire, and is always produced under similar conditions to these-namely, when carbon in any form burns with a limited or deficient supply of air. This may be experimentally proved by passing the di-oxide through a red-hot tube packed with charcoal (using the same apparatus as shown in Fig. 26), packing the tube with charcoal instead of iron; carbon-mon-oxide issues from the other end of the tube. In the fire-grate the gas CO, is formed at first, but on passing up through the hot mass of coal it takes up more carbon, and becomes carbonic oxide (CO)—thus $CO_2 + C = 2CO$.

Dense black smoke is, as a rule, accompanied by carbonic oxide, and this means a loss of fuel in two ways—namely, the carbon, forming the black particles to which the smoke owes its colour; and the carbonic oxide, which is unburnt Both of these substances, if burnt, would give out their proportion of heat.

White-Damp is not found naturally in the air of the

mine, but is formed in the explosion of certain compounds used for breaking down the coal. It is also produced by gob fires, in which carbon, in the form of coal, is burning with a limited supply of air, and is present in after-damp—that is, the mixture of gases formed by an explosion of fire-damp in the mine. In many cases, those who have escaped the direct effects of an explosion have been overcome and poisoned by this gas. The suicide, who seals himself up in a room in which a charcoal stove is burning, owes his death to white-damp. The gas from blast furnaces used in iron smelting contains, roughly, 30 per cent. of white-damp, which was formerly allowed to escape into the atmosphere, but is now conducted under boilers and there burnt, and its heat of combustion made use of.

No very ready test for the presence of carbonic oxide is available, especially for recognising such small amounts as may be fatal to life. If present in any quantity, the cuprous chloride reaction may be used, but this is only the case where the actual amount is to be estimated. The gas is soluble in this reagent (cuprous chloride solution).

The most practicable method of recognising the presence of small (or large) quantities of the gas depends on the action of the latter upon the blood. If a few drops of blood be added to water a pale yellow colour is produced, and if this be shaken up with carbonic oxide gas the colour changes to pink. The effect on blood is also readily seen by means of the spectroscope, an instrument, however, which could scarcely be used under the requisite conditions for testing a noxious atmosphere in the mine.

Dr Haldane suggests the use of a mouse or a bird, by noticing the effects on which creatures the safety (or otherwise) of an atmosphere can be gauged. The effect of carbonic oxide on these animals is much quicker than on a human being, and thus gives timely warning.

Carbon-di-oxide, Black-Damp, Choke-Damp or Stythe, commonly known as carbonic acid gas. Chem-

ical formula CO₂. Density 22, specific gravity 1.527. It contains 12 parts by weight of carbon combined with 32 parts by weight of oxygen, or one volume carbon vapour combined with two volumes of oxygen.

In the atmosphere of the mine this gas is always present in greater or less quantity, being produced continually by the breathing of men and animals, and also by the burning of the lamps; and it is often given off from the It is always found in after-damp, having been formed by the explosion of marsh gas or fire-damp, a substance rich in carbon. Carbon-di-oxide is a colourless invisible gas, with a very slightly acid taste and smell, but it is rarely in sufficient amount to be recognised by these properties: in fact, such an atmosphere would not support life. It will not burn itself, nor allow anything to burn in it. The sparkling of aerated waters is due to the escape of this gas, which has been forced into the water Its weight enables it to be poured, under pressure. siphoned, or ladled from one vessel to another, as though it were a liquid, since it is 11 times as heavy as air.

By balancing a glass vessel at one end of a chemical balance, and then displacing the air in it by carbon-dioxide gas, the increase in weight is readily seen.

The property that this gas has of extinguishing a light has been made use of in fire-extincteurs, the constituents of which give out carbon-di-oxide. It is also used in a compressed form in strong cylinders for the same purpose, and has been made use of for extinguishing fires in mines. Large tanks are built at the surface, pipes from which lead the heavy gas into the workings. The gas is generated by the action of hydrochloric acid on limestone or chalk.

It must not be supposed that, on account of its weight, the carbonic acid is always found on the floor of a mine (though it is often found lying in holes or pockets in the ground and in lower level workings). This would be so were it not for gaseous diffusion, which has been already explained (Chapter III.).

In some cases, however, such a phenomenon is to be noted, as in wells, and in certain districts where the gas issues in continuous discharge from the earth (from subterranean sources), notably in the Poison Valley of Java, where a kind of lake of the gas exists, fed from the earth. In such cases the safety of the atmosphere for breathing is readily tested by lowering a lighted candle into it. If it continues to burn, then carbon-di-oxide cannot be present in dangerous quantity. It is possible to exist for a while in an atmosphere which will not support the combustion of a candle, but it is extremely dangerous. When the amount of carbon-di-oxide gas reaches 8 to 10 per cent., the atmosphere will not support life long.

In a paper read before the Society of Chemical Industry, in April 1895, by Clowes and Feillman, it was pointed out that there was a marked similarity in the composition of the gases produced by breathing, and by combustion. Thus air from the lungs, after the breath had been held for forty seconds, gave on analysis—

14.9°/, oxygen; 81.4°/, nitrogen; 3.7°/, carbon-di-oxide.

The gases produced by the burning of an alcohol flame contained—

14.9°/, oxygen; 80.7°/, nitrogen; 4.3°/, carbon-di-oxide; and from a burning candle—

15.7°/, oxygen; 81.1°/, nitrogen; 3.2°/, carbon-di-oxide.

It was stated, on the authority of Dr Haldane, that atmospheres such as the above did not produce any noticeable inconvenience when breathed. It therefore follows that atmospheres which extinguish any flame ordinarily used may yet be perfectly safe to breathe. This does not apply to a hydrogen flame, which is only extinguished in an atmosphere which is quite incapable of supporting life—namely, 5.5 per cent. oxygen and 94.5 per cent. nitrogen.

The following table shows the results from the presence of the stated percentages of carbon-di-oxide:

Per cent. Carbon-Effects on Respiration and Combustion. di-oxide Gas. 3.5 Breathing deepens. Lights still burn. 6.0 Marked panting. Lights still burn. Severe distress. Lights still burn. 10.0 15.0 Partial loss of consciousness. extinguished. 25.0 Death.

Carbon-di-oxide is readily absorbed by a solution of potassium hydrate (or by the solid itself, commonly known as caustic potash). This property is made use of in pneumatophores, the carbon-di-oxide produced by the breathing of the person wearing the apparatus being taken up by the potash. (For description of pneumatophores, see pp. 96-7).

A ready test for the presence of carbon-di-oxide is found in lime-water, which is made by shaking up freshly-burnt lime, or quicklime, with water, and allowing it to settle, using the clear liquid which remains. On breathing through this clear solution for a few seconds, a milkiness is produced in it, expired air containing about 4 per cent. of the gas CO, under ordinary conditions. The milkiness is produced by this carbon-di-oxide combining with the lime in solution in the lime-water, forming carbonate of lime. If the blowing be continued long the milkiness disappears, but is re-formed on boiling, and in this experiment we imitate the process by which carbonate of lime gets into water, causing temporary hardness (see under "Water").

Carbon-di-oxide does not exert a poisonous action like carbonic oxide does, but deprives one of life by suffocation, on account of the absence of free oxygen. Angus Smith devised a rough test for the amount of carbon-di-oxide in an atmosphere thus: He took a bottle of $10\frac{1}{2}$ ounces capacity, and added } ounce of clear lime-water, shaking up well. If no milkiness be produced, then the sample of air in the bottle at the time could not have contained more than .06 per cent. of carbon-di-oxide:—

Preparation of Carbon-di-Oxide or Black-damp.

—The ordinary method is to decompose limestone with hydrochloric acid, in an apparatus similar to that used in preparation of hydrogen, but almost any carbonate (for instance, washing soda) may be used, and an acid such as vinegar. Many interesting experiments may be made with it, not requiring much apparatus. It may be generated from the above-named materials in a jug or bottle, and *poured* into other vessels as though it were a liquid. In this way the extinction of flame, the effect on lime-water, and its great density, may be readily shown.

No doubt it appears curious, if not impossible, that an invisible gas such as this should contain the black substance, carbon, but this also may be clearly proved by collecting a jar of gas, and plunging a piece of burning magnesium wire into it. The latter metal has a greater affinity or attraction for the oxygen of the gas, than carbon has; consequently, the gas is decomposed, and carbon in the form of small, black, solid particles is liberated, and is readily seen. The white substance (magnesia, or oxide of magnesium) which is produced at the same time may be separated by adding a little dilute acid, then leaving the black particles of carbon more plainly visible still.

CHAPTER VIII.

FIRE DAMP.—COMBUSTION.—COAL DUST AND ITS ACTION.

Methane, Marsh Gas, Light Carburetted Hydrogen, Fire-damp.—Chemical formula CH₄. Density, 8. Specific gravity 55. Composed of 12 parts by weight of carbon combined with 4 parts by weight of hydrogen, or one volume carbon vapour combined with four volumes of hydrogen.

This gas is one of a numerous class of compounds of carbon with hydrogen, called by the general name of hydrocarbons. Of all these, fire-damp is the one which contains the largest amount of hydrogen. It is very like hydrogen in its properties, and though eight times denser than hydrogen, yet compared with air it is an extremely light gas. Because of this lightness, it tends to collect in the highest places in the roof of the mine, unless thoroughly swept out and diluted by the ventilating current, assisted by diffusion.

Fire-damp often goes by the name of marsh gas, because it is the gas liberated when the decomposing vegetable matter or deposit at the bottom of ponds or marshes is stirred up. It is evidently the result, in nature, of the decomposition of vegetable organic matter. In this way it has been generated during the formation of the coal measures, countless ages ago, and after being long pent up escapes from the coal and adjoining strata when these are disturbed. Mixing with the air, it gives rise to the extremely explosive mixture, the ignition of which has caused so many disastrous effects in mines throughout the world. The most explosive mixture is about 9.4 per cent., by volume, of fire-damp, mixed with

90.6 per cent. of air. Fire-damp, along with carbon-di-oxide, is often met with, even in sinking through strata, before the coal is reached.

The gas exerts no poisonous action, but will not support life, because of the absence of *free* oxygen. It will burn itself, but will not allow a light to burn in it.

Though pure methane, chemically prepared, has no smell, fire-damp has a slight one, due to the presence of small amounts of other hydrocarbons. When the gas burns it produces carbon-di-oxide and water vapour—the same products, it will be noticed, as in ordinary breathing—and when fire-damp explodes, the products are the same, since, as we shall see, explosion is really a very rapid burning.

Gases produced by an Explosion of Fire-damp.— At this point it will be well to consider what gases are produced by an explosion of fire-damp.

The elements present before the explosion are:-

Carbon Hydrogen constituting fire-damp.

Oxygen Nitrogen constituting the air.

When the explosion takes place, the carbon of the firedamp combines with the oxygen of air, producing carbondi-oxide or black-damp, and possibly some carbonic oxide or white-damp (depending on conditions prevalent at the time of the explosion). The hydrogen of the fire-damp combines with the oxygen of the air to form water, and the nitrogen gas is left unaltered.

The latter fact is sometimes lost sight of in considering the gaseous products of an explosion; but, as we have seen, since it cannot support life, it is quite as deadly as black-damp or white-damp. It is also left in large quantity, since it forms four-fifths of the volume of the air originally present. So that after-damp, as the gaseous

products of an explosion of fire-damp and air are called, consists of a mixture of black-damp, white-damp, nitrogen, and water vapour.

Laboratory Preparation of Methane.—Methane may be prepared in the laboratory by heating a mixture of sodium acetate and sodium hydrate, with the addition of some lime to prevent the other materials from melting.

Thus prepared the gas has no distinctive smell, no taste, and burns with a slightly luminous flame (probably due to particles of soda salts suspended in it). Its properties may be well illustrated by means of ordinary coal-gas, which it resembles in composition.

Tests for the Presence of Fire-damp in Mine.—The presence of fire-damp is recognised by its peculiar action upon the flame of a safety lamp. Persons having an intimate knowledge of the mine, and of the most likely places for the gas to accumulate, carefully raise a lighted safety lamp into the suspected atmosphere. If the flame suddenly lengthens, it denotes the presence of fire-damp in dangerous quantity; at the same time the flame becomes less luminous and the interior of the lamp cylinder becomes filled with burning gas, giving out a peculiar faint bluish light, known in some districts as the corpse-light.

In case the flame does not alter in appearance, there may be still a decided amount of fire-damp present, though perhaps not in dangerous quantity. Under these circumstances a further test is made by means of a very low flame in the lamp, when if fire-damp be present, a sort of cap of pale blue flame surmounts that of the lamp. The quantity of gas that can be recognised in this way may be as low as 2 per cent.

It is pretty generally recognised that the presence of fire-damp is shown on the lower flame of an ordinary Davy lamp when it exceeds 2 per cent., as a pale blue "cap" or halo, and the flame increases in length until about 6 per cent. of fire-damp is present; from 8 to 15 per cent., the mixture will explode in the lamp; and if the proportion of fire-damp reaches as high as 30 per cent. the lamp flame is extinguished. It has been noted, in considering the properties of hydrogen gas, that it, also, will not support combustion, although burning itself and forming a very explosive mixture with air.

It may be necessary, sometimes, to know the amount of dilution with air required to make a certain volume of fire-damp harmless. The following is an example:—

A mixture of 50,000 cubic feet of air and fire-damp contains 10 per cent. of the latter. How much air must be added to it so as to prevent the "cap" showing in an ordinary safety lamp?

The 50,000 cubic feet of mixed gases must consist of

45,000 cubic feet air 5,000 cubic feet fire-damp

50,000

Assuming that $2\frac{1}{2}$ per cent. of fire-damp can be recognised by an ordinary safety lamp but that 2 per cent. cannot, it will be necessary to dilute with air so that the fire-damp be present only to this extent (2 per cent.).

The 5000 cubic feet of fire-damp then must be diluted, so as to be $\frac{1}{10}$ part of the total volume.

 $5000 \times 50 = 250,000$

But there are already 45,000 cubic feet of air present, therefore the amount to be added is

250,000 - 45,000 = 205,000 cubic feet air.

In the first testing, before any idea of the conditions is known, great care must be taken not to tilt the lamp, but to keep it quite straight (perpendicular): otherwise the lamp flame may heat the gauze of the lamp, possibly to the extent necessary to allow of combustion, and so cause explosion.

Explanation of the Flame Test for Fire-damp.—After many careful observations, it has been found that the size of a flame is governed to a great extent by the proportion of oxygen present in the atmosphere in which it burns. If this proportion be increased, then the size of the flame is decreased: if the proportion of oxygen be decreased, then the size of the flame is increased. Hence the lengthening of the lamp flame when introduced into an atmosphere containing fire-damp, in which there is less oxygen than in air. It is really as though the combustible gas, whatever it is (oil vapour or hydrocarbons, in the case of a pit lamp), has to search for food in the shape of oxygen, and the less the supply of oxygen the greater need for an extended surface of flame.

In a paper read before the British Association in 1892, Dr Clowes described a miner's safety lamp in which an ordinary flame can at will be replaced by a hydrogen flame, and the use of the latter enables the miner to detect readily, and with certainty, the presence of fire-damp when in quantities ranging from ·25 to 3·0 per cent., and to measure the amount. The lamp is available both for testing for the presence of gas, and also for illuminating purposes (when the delicate testing for gas is done), by means of an ordinary oil-flame. Hence, the latter alone can be used if necessary for the detection of amounts of fire-damp greater than 3 per cent.

The hydrogen gas is carried in a compressed form in a small strong steel or copper cylinder, and is led into the lamp through a fine metal tube which terminates near the wick (see Fig. 32). Experiments were made to compare the flames of alcohol, benzoline, and hydrogen of equal heights when exposed to an atmosphere containing 1 per cent. of coal gas. In the case of the hydrogen flame the cap was nearly four times as high as that seen over the benzoline flame, and half as high again as that over the alcohol flame. The lamp proved a useful test in atmospheres charged with petroleum or naphtha vapour, which

form an explosive mixture with air. $\frac{1}{36}$ th of the amount necessary to form an explosive mixture can be detected by the flame.

It was also explained that the amount of inflammable gas in air was measured not only by the size of the flame but also by its appearance, which changes considerably as the percentage of gas rises. Since the presence of coal dust lessens very much the amount of gas necessary for an explosion, a delicate test for the presence of gas is necessary. The presence of a cap over the lamp flame is caused by the increased temperature, enabling a mixture of fire-damp and air to burn (really helping the combustion), although it would not do so at ordinary temperatures. Consequently the *increased* heat, and the *decreased* light of the hydrogen flame, both tend to make the indications of fire-damp more readily seen.

The most recent development of this lamp (Clowes and Redwood's patent) is illustrated in Fig. 32. It is a modified Gray oil lamp. The lamp is charged with a mixture, in equal proportions, of colza and paraffin oils. An upright strip about an inch in breadth of the inside of the lamp glass is smoked dead black by a wax taper, so as to form a background for observing the flame caps. An upright graduated gauge-wire is inserted in the wick holder to read off the heights of the caps.

In testing for gas down to 3 per cent., the sleeve or the pillar of the lamp having been pushed up, the opening thus exposed is closed by the thumb. The lamp, which takes its air supply near the top, is then gradually raised towards the roof, and the behaviour of the flame is noted. If the flame seems likely to be extinguished by gas, the thumb is removed to allow the air-feed to be taken from a lower level, and thus to save the flame. A rough test is thus made in the ordinary way, and serves to detect the larger percentages of gas. If it is wished to measure the percentage of gas present, the oil flame is pulled down by the "pricker" until it just loses its bright tip, and the cap is

looked for against the black smoked glass as a background.

3 per cent. yields a cap of ·3 inch.

- 6 per cent. yields a cap which just reaches the top of the glass. (See Fig. 33.)

In testing for less than 3 per cent., if no distinct cap is




FIG. 32.—Clowes's hydrogen lamp.

seen over the reduced oil-flame, this does not necessarily prove the absence of gas. The hydrogen flame, however, detects and measures gas down to .25 per cent. The cylinder containing the compressed hydrogen serves as a convenient handle to the lamp (see Fig. 33). The hydrogen gas is gradually admitted to the jet in the lamp. As soon as the hydrogen gas becomes ignited the oil flame is extinguished. By turning the valve, the tip of the hydrogen flame is made exactly level with the top of the upright wire, or with the first cross wire if the scale be used. The flame is now of standard height. Careful observation is made to see if any cap is


visible over the flame. If any cap shows, then the percentage of gas present may be judged by the height and appearance of the "cap."

1/4 per cent. of gas gives ·7 inch cap (the cap being pale and

					nazy in outline).
$\frac{1}{2}$,,	,,	•7	,,	(more definite in appear-
					ance and outline).
1	,,	,,	.9	,,	(cap becomes not only
2	,,	,,	1.2	,,	larger but also more
3	,,	,,	2.1	,,	visible and definite).

When the test with the hydrogen flame is finished, the wick is pushed up by the pricker and becomes kindled by the hydrogen flame, which is then shut off.

The hydrogen test will probably be applied principally to the "main return," and possibly to "district returns,"



The tip of the cap is 0.2 inch above the horizontal wire except for 6 p.c

FIG. 33.—Illustrating heights of flame "caps."

to ascertain their condition, and to regulate the ventilation current and its distribution accordingly. It will be understood that neither the oil nor hydrogen flame must be extinguished until the other flame is burning satisfactorily in the lamp.

Several lamps of various forms have been devised which will detect as little as $\frac{1}{4}$ per cent. of fire-damp in an atmo-

sphere. Most of these are only intended to be used after an ordinary lamp test has failed to give any indication of fire-damp. The alcohol flame of the Pieler lamp will detect per cent. of fire-damp readily. The flame gives out no light, and is chiefly used for gas testing. Some lamps use benzoline, and are useful in that they give a fair amount of illumination, as well as testing for presence of gas. As a rule, those in which inflammable liquids are used have a sponge in the oil tank, which soaks up the liquid, any excess of which is drained off.

An ingenious method for indicating fire-damp has also been used by Liveing, based upon the fact that if the metal platinum be warmed, and then placed in an atmosphere of hydrogen, or of coal-gas, or of fire-damp, the platinum becomes still hotter, and finally glows with a full red heat. Two spirals are made of this wire, one enclosed in a sealed tube full of air, the other fitted alongside of it, but exposed to any gaseous atmosphere into which the apparatus may be placed. On sending a mild electric current through both, they become heated, but the one in the "gassy" atmosphere glows much more brightly than the one in the sealed tube of air, and the greater the proportion of fire-damp present, the more brightly it glows. The appliance is very sensitive, and is said to detect \(\frac{1}{4}\) per cent. of gas.

A device depending upon similar principles (the action of hydrogen or fire-damp on platinum) forms the subject of a patent taken out by Mackie of Pennsylvania. The greater the proportion of fire-damp in the suspected atmosphere, the greater the distance from the lamp-flame, at which a coil of platinum wire begins to glow with heat. Through a sheath which passes through the base of the lamp, there slides a vertical graduated support, the top of which is bent so as to support the platinum spiral over the oil flame. When the lamp is brought into the suspected atmosphere, the support is pushed up or down, until the point is determined at which the platinum begins to glow,

and the corresponding percentage of fire-damp is shown by a graduated scale on the support.

The following test has been suggested also for the presence of fire-damp:—

If an ordinary tuning-fork, when sounded in air, gives out a certain note, it will be found that, when placed in a vessel containing carbon-dioxide, the sound is slightly louder. On the contrary, when placed in an atmosphere of hydrogen or fire-damp, the sound becomes fainter. In other words, the sound is affected by the density of the atmosphere in which the fork vibrates. Though perfect in principle, it is somewhat doubtful whether this test could be made of practical use in the mine.

Purpose of the Gauze in a Safety Lamp. — All metals are good conductors of heat, and, as we have seen, this property varies with different metals. (See under "Conduction.") Now, the purpose of the gauze of a safety lamp—which is made of metal, and therefore is a good conductor—is to rob the gases of their heat. A certain temperature is necessary before any gas, or mixture of gases, will inflame or explode, and if the temperature be kept down below this point, then ignition cannot take place.

The principle upon which the safety lamp is based is well illustrated in Fig. 34. The gauze conducts the heat away from the flame so rapidly that the temperature does not rise to the point required to ignite the gas on the other side. The cooling effect is also helped by the number of small holes (mesh) of the gauze, which cause the heated gases to be spread over a large extent of cooling surface; this effect is greatly assisted by the action of Radiation (which see).

The gauze used in the safety lamp is usually of a standard size—namely, 28 meshes to the linear inch—and the wire forming the gauze is of 28 gauge in thickness, the metal used being iron or copper. This was the size of the gauze used by Davy (784 apertures per square inch). The

Belgian Mueseler lamp, authorised by the Belgian Government, has a gauze with 900 apertures per square inch. The original Marsaut lamp had a gauze with 934 apertures per square inch.

The old Davy lamp was not safe in an explosive mixture of fire-damp and air, if the current was moving at a rate of 5 or 6 feet per second. Modern lamps are protected by shields or bonnets, and are so arranged that it is impossible




FIG. 34.—Illustrating the action of gauze on flame.

for a rapid current of air to pass through a lamp, even when exposed to a current of high speed. A properly constructed bonneted Mueseler should stand a current of 50 feet per second without passing the flame, and this represents about an average figure, though some lamps would withstand much more. The flame of a Davy lamp may not only be blown against the gauze so as to heat it considerably, and so make it unsafe, but the wave of air produced by a blown-out shot is quite capable of forcing the flame suddenly through the gauze, even at some distance from the place where the shot blew out; and if an explosive mixture should be present in the atmosphere at the time, disastrous results might follow.

Ignition Point.—It is necessary, before chemical action, resulting in combustion or explosion, can take place, that a certain temperature be reached, depending upon the nature of the chemical action, and upon that of the substances taking part in it. This temperature varies within very wide limits for the many chemical actions which are possible, and the point or temperature which must be reached in order to bring about these chemical changes is spoken of as the "ignition point."

Certain inflammable substances—for instance, turpentine, carbon-di-sulphide, ether, etc.—have low ignition points, that of carbon-di-sulphide being about 250° Fahrenheit; and, similarly, various gases and gaseous mixtures have their particular ignition point, below which temperature, combustion, or explosion cannot take place. The purpose of the gauze in the safety lamp is to help to keep the temperature of the gases, in an explosive mixture of fire-damp and air, below the ignition point, by conducting away the heat. The ignition point of an explosive mixture of coal-gas and air is 1200° Fahrenheit; that of fire-damp and air, 1230° Fahrenheit.

That combustion depends upon temperature may be proved by suddenly lowering the temperature of a burning gas, when it becomes extinguished. This principle is made use of in certain "safety-jet" appliances where the oxyhydrogen flame is being used. In case of any back suction the gases are bound to pass through a space packed with metallic gauze, which absorbs their heat so rapidly as to bring them below their combustible or ignition point.

Flash Point of Oils.—Various illuminating oils—vegetable, animal, and mineral—are used in safety lamps. Some are of very low flashing points—that is, their vapour is inflammable at fairly low temperatures. For ordinary safety-lamps which do not burn spirit, but heavy oils such as colza, a mixture of two parts pure colza and one part best petroleum gives the best results. The

objection to the use of colza alone is the formation of a crust on the wick, after the lamp has burnt a while. petroleum prevents this to a great extent, and, at the same time, a whiter light is given out. Two gallons of this mixture are sufficient to fill about 160 lamps of average size for 10 hours' burning.

There is naturally more danger in the use of an oil which has a low flash point than in one with a fairly high flash point, because the former gives off vapour readily, forming an explosive mixture with air. Unless under very special circumstances, none should be used having a flash point below 73° Fahrenheit. The flash point of mineral oils ranges from about 75° F. to 140° F. When low flash




Fig. 35.-Naylor's safety-lamp.

oils are used, the practice is to absorb the oil in sponge or similar material, and not to fill the oil chamber with the liquid itself.

The flash point of oils is raised by exposure to the air. Lamps which burn paraffin or petroleum have been regarded suspicion, and often justly so. There is also a tendency to compare the disastrous results often attending the use of an ordinary house lamp burning paraffin, with the possibility of similar results in the mine. Paraffin has got a bad name on this account, but there is really no comparison between the two cases.

A miner's lamp, burning paraffin only, has been devised by Mr Naylor, of Wigan. The oil chamber and wick holders are so constructed that the oil is quite unable to be spilled or upset, even if the lamp be held upside down. It will be seen from the diagram (Fig. 35), that the tubes carrying the wick AA pass nearly to the bottom of the oil reservoir B, and the principle is really that of the "unspillable" ink-bottle. The burning of petroleum in this lamp is rendered safe by having a partition, or division plate, in the oil chamber, thus really converting it into two chambers. The wicks used are two in number and circular in form, and Fig. 36 shows a method of electrically igniting them, if desirable, but the lamp is also made without this attachment. The electrical ignition is effected by bringing the knob κ in contact with one term-




FIG. 36.—Electrical ignition of Naylor's lamp.

inal of a secondary battery or accumulator, and the part x in contact with the other terminal. This completes an electrical circuit, in which is a piece of platinum wire, o, held in position near the wicks. The passage of the current causes the platinum to glow with a full red heat, and ignites the wicks. The black portion, I, shows the insulation of the rod, kn, by means of vulcanite or ebonite. With a half-inch flame in this lamp, $2\frac{1}{2}$ per cent. of firedamp can be readily detected; with 11 per cent. the flame is extinguished. The lamp will burn 14 or 15 hours with practically no attention.

The candle-power from an ordinary size of miner's lamp varies from .25 to .75. The light emitted by this paraffin lamp is 1.1 candle-power, a very considerable advantage. Naylor's lamp has been described because of

its lighting power being much above the average, due to the use of petroleum combined with a special form of wick and wick holder. It is quite beyond the scope of this book to describe other lamps—such as the Marsaut, Mueseler, Hepplewhite-Gray, etc.—since they are dealt with in great detail in books dealing with coal mining.

Lighting Powers of Lamps.—The illuminating powers of different sources of light are compared by instruments called *photometers*, or *light measurers*. The standard, or practical unit for comparison, is a sperm candle (six to the pound) burning 120 grains per hour.

In Rumford's photometer, the lighting powers from two different sources are compared by adjusting the two lights



FIG. 37.—Rumford's photometer.

to be tested, so that they throw shadows of the same depth on a fixed screen. The shadow is cast by a vertical rod (see Fig. 37) which is placed between the screen and the sources of light. The brighter light will have to be placed at a greater distance from the screen, than the other. When the shadows are of equal depth, then the intensities of the lights will be directly as the squares of their distances from the screen. For

instance, suppose that one light is distant 12 inches and the other 18 inches from the screen, then the lighting powers are as $18^2: 12^2 = 324: 144$. Therefore the light, which is 18 inches distant from the screen, has $\frac{324}{144} = 2.25$ times the illuminating power of that which is at 12 inches from the screen.

Most of the photometers in use at present are based upon a method originally used by Bunsen (Fig. 38). If a piece of white paper be soaked in melted spermaceti wax, so as to cover all the surface except a small circle in the centre, on holding it up to a source of light the portion soaked with sperm is fairly transparent, and appears lighter than the unsoaked portion. If, however, the light be between the paper and the eye, then the soaked portion appears darker than the other, because the more opaque portion reflects the light better than the transparent part does. It follows, therefore, if the waxed paper be placed between two lights which are to be compared for intensity, that by moving the paper until it is equally




Fig. 38.—Bunsen's photometer.

lighted on both sides, no central spot will be visible. The distance of each light from the waxed paper is then accurately measured and squared, giving the comparative intensities of the two lights. The waxed paper is usually mounted in a box between two small mirrors placed at such an angle that the person making the test can see both sides of the paper at once, and thus adjust the distance to a nicety.

By means of these photometers, also, the candle-power of safety lamps can be gauged if desired.

The photometric tests of safety lamps are made by these means; but it must be remembered that they are made under the best conditions—namely, when the lamps are perfectly clean: consequently the results thus obtained are always higher than can be expected when the lamps have been in use a short time, and exposed to the action of coal dust, grease, and dirt generally. Further, it is the horizontal rays from the lamp which are measured by a photometric test, whereas the most useful part of the light to the miner is that which is thrown upwards. In the Hepplewhite-Gray lamp a reflector is used, so as to throw the rays in the most useful direction.

Lamps burning acetylene gas (whose high illuminating power is well-known) are used on the Continent in mining, and are said to be more economical than electric lamps.

Stink-Damp. — Chemical formula H₂S. Molecular weight, 34. Density, 17. Specific gravity, 1·183. Composition by weight, 2 parts of hydrogen combined with 32 parts of sulphur. By volume—2 volumes hydrogen combined with 1 volume of sulphur vapour.

One of the earliest acquaintanceships which the chemical student makes in the laboratory is with the gas known there as sulphuretted hydrogen, and called by the miner *stink-damp*—a term denoting its most evident property, generally likened to the smell of rotten eggs.

It is a colourless gas, and has distinctly poisonous properties when inhaled in anything like a pure condition; even when diluted with air it produces headache and giddiness. Compared with such gases as oxygen, hydrogen, fire-damp, white-damp, it is very soluble in water, the solution having similar properties to the gas. It is important to remember that it is a combustible gas, and in certain proportions may form an explosive mixture with air.

A familiar example of the action of this gas is seen in its effect upon metallic silver ornaments, which become covered by a bluish-black deposit after being exposed to the air for some time, due to the union of the silver with sulphur, forming silver sulphide. For similar reasons, paints consisting largely of white lead gradually turn

brown or black, owing to formation of lead sulphide. The decomposition of many organic substances containing sulphur results in the production of this gas along with others.

Though objectionable in many respects, stink-damp proves sometimes a good friend to the miner. Its characteristic smell is so readily noticed, even when in small quantities, that it cannot fail to attract attention. Now, the production of this gas is usually a forerunner of gob-fires, and is also an indicator of the coal heating spontaneously. Further, it is a valuable indication to the miner to be on the look-out for the deadly white-damp, which, together with black-damp, is always given off from gob-fires.

Ventilation.—From the consideration we have given to the properties of the various gases met with in mines, and the dangers they give rise to if allowed to accumulate, it will be readily understood how necessary is thorough ventilation to the safety and well-being of persons employed in the mine.

Not only is it necessary to have a sufficient atmospheric current to dilute and sweep out accumulations of fire-damp and noxious gases, but it is also essential that every human being and animal in the mine should have an ample supply of air for healthy breathing, and that the products of their breathing, and also of the burning of lamps, should be carried away. When doing no work, an average man breathes out at least 500 cubic inches per minute of respired air, which is rich in carbon di-oxide. Much more of the latter gas is contained in the breath if the man is working hard, because he is using up more carbon. Further, the surface of the coal should be kept cool by currents of air, so as to prevent spontaneous combustion.

It is evident, then, that a large volume of air will have to be introduced into the mine from without. The amount varies with conditions of the mine, whether deep or shallow, hot or cold, gassy or otherwise, and may be anything from 100 to 500 cubic feet of air per man per minute. The powerful fans used for ventilating purposes at the present time in Great Britain are able to supply as much as 500,000 cubic feet of air per minute if necessary.

The subject of ventilation is a very important one, and in its entirety is quite beyond the scope of this book; at the same time its principles depend upon certain laws in physics, and therefore a brief outline may be attempted. The question of any kind of mine ventilation is a matter of effecting a difference, by some means, in the density of the air in two shafts. (The method of ventilation by furnace is almost obsolete now.) It depends upon heating the column of air in one shaft, and thus lowering its density and causing it to ascend. Charles's law explains the action in this case.

In ventilating by fan, the pressure is either lessened (by exhausting) or increased (by forcing) by mechanical means. In either case the action depends on Boyle's law.

In two shafts forming part of a ventilating system, the weight of the column of air in one exceeds the weight of the column of air in the other, by an amount which represents the "ventilating pressure" per square foot. This weight or pressure is that of the "motive column" as it is called, usually measured by an ordinary water gauge. The "motive column," then, is a column of air of such a height as will give a weight equal to the ventilating pressure.

Since 1 cubic foot of water weighs 62.4 lbs., and $\frac{62.4}{12} = 5.2$ lbs. is the weight of 1 square foot of water 1 inch deep, then taking the weight of 1 cubic foot of air as .075 lbs., $\frac{5.2}{.075} = 69.3$ feet of air column equal to a weight of 5.2 lbs. as shown by 1 inch of water gauge.

This is approximately 70 feet of motive column per inch of water gauge.

The water gauge above mentioned is a glass tube, of U shape, often in metal fittings, so arranged that one of the limbs may be attached to a pipe connected with the fan-drift, or return air-way. Water is placed in the tube to a certain level, equal in both limbs, of course; by noting the effect on the level of this water produced by the pressure, the amount of the latter is measured, each inch denoting, as stated, 5.2 lbs. pressure per square foot.

Combustion.—In a wide sense, whenever chemical action goes on, accompanied by heat and light, combustion is said to take place, though in all cases the formation of heat and light is not necessarily brought about by chemical action. We usually speak of a substance being combustible with regard to air. For instance, we learn that ordinary coal gas is combustible, or will burn in air, but that coal gas will not support combustion nor allow a light to burn in it.

The very fact of the combustion of coal gas in air shows that there must be chemical action going on between them, and one naturally asks, If coal gas will burn in air, owing to chemical action, cannot the process be reversed and air be made to burn in coal gas? The answer to this question is, that it certainly can.

In Fig. 39, air is represented burning in an atmosphere of coal gas. The latter is supplied through the pipe A and is ignited at B, where there is an outlet in a small piece of asbestos mill-board placed on top of the lamp glass. Then on pushing a lighted taper up the tube c, through which air is being drawn, the latter takes fire and burns as shown.

To take a further illustration of the point, suppose that our atmosphere, instead of being composed of ordinary air as it is, were composed of coal gas (and that human existence were possible under such conditions), then if the gasometers at the gas works supplied air to the houses instead of gas, on applying a light to the air issuing from

the pipes it would become ignited and burn, and the timehonoured custom of searching for an escape of air with a light would be attended by the same disastrous results as now—namely, explosion. It will be seen from this that the terms "combustible" and "supporter of combustion" are purely relative, and depend upon conditions existing at the time.

At a meeting of the Chemical Industry Society, in




Fig. 39.—Air burning in coalgas.

December 1894, the results of experiments by Clowes and Feillman were given, in connection with the power of certain gases to extinguish flames. They proved that carbon-di-oxide is a more powerful extinguisher of flame than nitrogen is, probably on account of its density.

Attention was called, further, to the great practical advantage which is derivable from the large proportion of carbon-di-oxide (58 per cent.) necessary to extinguish the hydrogen flame.

In the Clowes lamp (see Fig. 32), a hydrogen flame can be burnt at will, instead of the oil flame. It is found that by burning the hydrogen flame besides the oil flame, in parts of the mine where the atmosphere might contain large amounts of carbon-di-

oxide, the extinction of the oil flame is not attended by loss of flame in the lamp, since the hydrogen flame never goes out, and serves to rekindle the wick in fresh air after the oil flame has been extinguished by a foul atmosphere. This has proved to be a great convenience to exploring parties in a mine after a fire or explosion, and is in conse-

quence of the power that the hydrogen flame has, to resist extinction in carbon-di-oxide.

Spontaneous Combustion.—The spontaneous combustion of coal is due to chemical action between the coal and the oxygen of the air. Other cases of spontaneous combustion occur, due to similar causes. Thus, heaps of oily cotton waste have been known to cause disastrous fires by firing spontaneously. The chemical action begins slowly at first, and develops a little heat: this heat is developed more quickly than it can be dispersed, and gradually increases, until it causes smouldering of the mass; and finally the heat rises to a point necessary for the chemical action to be accompanied by light and further heat. This may be illustrated more rapidly by means of phosphorus, a very inflammable substance. If a heap of small pieces be exposed to the air, fumes first come off (denoting chemical action), and while this is going on the heat is increasing, until the temperature is reached at which the phosphorus melts; more active combustion goes on; and finally the phosphorus bursts into flame and burns brilliantly.

A similar process goes on during the stages which finally bring about the spontaneous combustion of coal. It is a very remarkable fact, and one not easy of explanation, that the spontaneous combustion of coal goes on better in darkness than in light; other favourable causes are a warm and moist atmosphere. Vigorous ventilation tends to prevent the spontaneous combustion, because it cools the surface of the coal. It is sometimes stated that the presence of iron pyrites (coal brasses) in the coal, helps its spontaneous combustion, and to some extent this is no doubt true; but it must be remarked that in certain mines which are most troublesome in this respect there is a marked freedom from pyrites.

When the heating action commences it is usually indicated by stink-damp (sulphuretted hydrogen) being formed,

which is readily detected by its smell. This is, of course, produced by the sulphur in the pyrites, owing to the decomposition of the latter, in presence of moisture and warm air. For a similar reason, stink-damp is a forerunner of gob-fires, being in that case usually associated with the deadly white-damp (carbonic oxide).

Spontaneous combustion is usually only troublesome in the case of bituminous coals. Anthracite, and steam coals generally, are free from this liability.

Coal Dust and its Action.—Dr Philips Bedson, in a paper read before the British Association in 1893, pointed out that coal dust contains enclosed gases. specially led to investigate this property on account of observations which had been made, that the dust produced when screening coal at Ryhope Colliery, in county Durham, would often fire at the lamps used for lighting the screen, and thus produce a kind of explosion. was found, on exposing the dusts to various temperatures in a vacuum, that gases were given off, varying in nature and amount with the temperature. At between 80° C. and 100° C., hydro-carbon compounds came In further investigating the same subject, Mr M'Connell had found that, even after the coal had been heated to 180° C, the dust from it, when crushed, gave off further amounts of hydro-carbon gases. Some dusts examined by him yielded carbon-di-oxide, oxygen, and nitrogen only; others contained a small amount of combustible gas in addition; while a third class gave off gas similar to that found with the Ryhope seam, and contained some other combustible gases (hydro-carbons) besides methane (fire-damp, commonly called).

No doubt the existence of these occluded or enclosed gases in coal dust plays an important part in determining its explosive action, since whereas the most explosive mixture of methane (fire-damp) and air is one of the former to ten of the latter, one volume of the hydro-carbons found

in this dust requires 23 volumes of air to form the most explosive mixture. Hence a more dilute mixture is more explosive.

Many explosions have occurred in which it was practically impossible to have had fire-damp as an explosive agent, and coal dust from certain seams appears to be almost as explosive as gunpowder. The richer the coal, and the freer from mineral matter (ash and dust), the greater the tendency to explosion. These conclusions were arrived at after a series of experiments made in a disused shaft at White Moss, Skelmersdale, by Mr Hall. H.M. Inspector of Mines. It was also concluded that a brisk ventilation has the effect of making these coal-dust explosions more probable, and more severe. Experiments were, at the same time, made with certain "high" explosives (see "Explosives"), and it was found that it was impossible to fire coal dust by their explosion in a dusty atmosphere. but with blasting powder (a "low" explosive) violent explosions occurred.

Now, as explained in the next chapter, gunpowder and blasting powder, containing a deficient supply of oxygen for complete burning, always generate carbonic oxide, and, as pointed out by Mr Orsman, the inference is, that carbonic oxide is the cause of explosions of coal dust under these conditions. In some cases more than 30 per cent. of the gases produced by blasting powder, when exploded, consists of carbonic oxide.

At the time of these experiments by Mr Hall in 1892, Mr Orsman devised an ingenious method of obtaining a sample of the gas immediately after the explosion.

The composition of the gas was found to be-

Oxygen		3·9 p	er cent.
Nitrogen .	•	75 ·9	,,
Carbon-di-oxid	e .	12.1	,,
Carbonic oxide		8·1	,,

Hence it was proved that the presence of carbonic oxide, in

addition to its highly poisonous action, has the effect of very much increasing the danger of an explosion of coal dust.

In Mr Hall's report to the Secretary of State on the results of experiments carried out in 1893, he states "that a very small quantity of coal dust in suspension in the air would, along with that at rest on the timbers, be sufficient to bring about conditions, under which a colliery explosion might happen, through the firing of a gunpowder shot; and even without dust in suspension, enough could be dislodged from timbering, and other lodging places, to cause violent explosions. At the same time, he does not imply that all colliery explosions are due to dust, many being undoubtedly due to fire-damp, but these are never so destructive nor so widespread as the ones caused by coal dust."

We gather from this that an explosion may occur at one particular point, owing to the presence of fire-damp, and the explosive wave so formed may ignite, in the immediate vicinity, a mixture of air and coal dust, and so be carried on indefinitely, so long as air and coal dust are present. It has been found that the primary explosion causes a disturbance in the air, similar to that of a sound wave, and this wave, travelling in front of the explosive mixture, causes fresh dust to come into suspension in the air; consequently this explosive wave feeds itself, so to speak, from the disturbance of the atmosphere which goes on in front.

It has also been noticed that coal dust renders an explosive mixture of fire-damp and air more sensitive to explosion, and even one per cent. of fire-damp can be caused to burn when fine coal dust is present. This would point to the necessity of having a lamp which will indicate the presence of such an amount of fire-damp, since an ordinary lamp will only recognise as little as 2 or $2\frac{1}{2}$ per cent. (see Clowes' lamp).

And it may be pointed out here, as stated under "Explosives," that various explosives—for example, those of the gunpowder and nitro-glycerine class which are

deficient in oxygen—are capable of producing gases containing a large proportion of carbonic oxide, which have the same effect as fire-damp in promoting explosive mixtures with air, especially in the presence of small quantities of coal-dust.

CHAPTER IX.

EXPLOSIVES.

Nature of Explosives.—Explosives are chemical compounds which are able to be very rapidly decomposed, upon the application of heat or shock. They suddenly generate, when thus decomposed, large volumes of gas, which at the same time are heated to a high degree, and are thus caused to expand greatly (see under Boyle's law). Most explosives in practical use are solid, a notable exception being nitroglycerine.

The necessary conditions for an explosive mixture are to have some substance, or substances, which will readily burn under suitable conditions, mixed with some other substance which will supply the necessary material for the burning or combustion—namely, oxygen. An explosive must therefore contain all the necessary ingredients for a rapid combustion.

Many substances rich in carbon have been suggested or used as explosives, when mixed with an oxidising agent. For instance, charcoal, sawdust, bran, resin, starch, sugar, wood pulp. Coal-tar products, etc., have been used along with oxidising agents, such as nitrates, chlorates, picrates, permanganates, etc. The science of explosives has been developed upon these broad principles, and the result is that a large variety of mixtures, each suited for its own particular work, are available for practical use.

Many explosives do not contain enough oxygen to completely burn up the substances contained in them—for instance, gunpowder, gun-cotton, and nitro-glycerine. The result is the production of carbonic oxide (white-

damp). This is very undesirable, not only on account of its very poisonous action (see under Carbonic oxide), but also because the presence of this gas in an atmosphere very much increases the danger of an explosion of coaldust. The reason for keeping down the supply of oxidising agents in the explosive, is to prevent too much heat being produced, and in attempting to tone down this temperature certain substances—such as wood-meal—have been added; this also causes the production of carbonic oxide. Nitrated oils—for example, linseed and castor oils treated with nitric acid—have been suggested as suitable for use in modifying the temperature, and reducing the shattering effect, produced by certain explosives.

When ammonium nitrate is employed as an oxidising agent it may easily be used in excess—that is, more than enough to supply oxygen to the materials to be oxidised—because on being decomposed it absorbs heat.

An explosive intended for use in coal or other flery mines should leave no solid matter after explosion—that is, the products should all be in the gaseous condition; and, further, these gases should be harmless, free from noxious properties of all kinds. It should also, in actual use, when properly tamped, be unable to fire an inflammable or explosive mixture of fire-damp and air, or of coal-dust and air.

It is generally admitted that the use of "high" explosives lessens the risk of explosion in mines. The mechanical effect of the explosion is also an important point; if it be too shattering, then the coal is broken up too much, which is an evident disadvantage; a tearing or rending effect is required, so as to break down the coal in sizes most suitable for commercial purposes.

Explosives may be classified thus:-

(a) Those depending upon the use of nitroglycerine, either mixed with some absorbent substance, or gelatinised by adding varying amounts of nitro-cellulose.

- (b) Those in which gun-cotton or nitro-cellulose is the basis.
- (c) Those in which a hydrocarbon, preferably nitrated, is used, along with an agent rich in oxygen, such as ammonium nitrate, often known as "Sprengel explosives."

All "high," explosives require a detonator to explode them, and the explosive effect is brought about by the combined action of heat and shock. "Low" explosives can be exploded with a fuse, without the use of a detonator. Some explosives require more powerful detonators than A detonator is a small metal cap, generally others. of copper, containing a substance called fulminate of mercury, usually mixed with a little chlorate of potassium. The fulminate is prepared by dissolving mercury (commonly called quicksilver) in nitric acid. The solution is cooled down and alcohol added to it, this causing fulminate of mercury to be produced as a powder in the liquid. solid is separated by suitable means, and thoroughly washed to purify it, and free it especially from acid. It is then carefully dried and highly compressed, forming a material which is most sensitive as regards explosion. The slightest friction, or moderate heat (about 300° F.), is sufficient to explode it.

Detonators can be fired with a time fuse if the conditions of the mine permit, but it must be remembered that in using a fuse it may give out sparks which are sufficient to ignite an explosive mixture of fire-damp and air. Further, it is obviously absurd to use a fuse which may bring this about, when using a safety explosive.

Undoubtedly the best and safest means of firing a detonator is the use of electricity. This may be done by a high-tension or low-tension current. In the former case a small current, at a high pressure, is used, by means of which electric sparks are caused to leap across a gap between the terminals of two wires, and thus ignite the "priming" with which they are surrounded. This in turn

causes the fulminate to explode, and to fire the cartridge. The priming is itself an explosive, depending, as all others do, on a substance to be oxidised (usually in these cases, sulphide of antimony) and an oxidising agent, usually potassium chlorate. Fig. 40 shows one form of high-tension exploder. In the case of low-tension firing, a comparatively large current at a low pressure is used, and this is made to pass through a fine platinum wire, which is thus raised to a red heat, owing to its



Fig. 40.-High-tension Exploder.

resistance to the passage of the current; this fires the priming and explodes the detonator.

The composition, properties, and preparation of some of the most commonly used explosives may now be considered.

Gunpowder, until comparatively recent years, had an average composition of potassium nitrate, 75 parts; charcoal, 15 parts; and sulphur, 10 parts; but this composition is now often much modified, and varies considerably (see Bobbinite and Special Bull-dog).

There are many objections to the use of gunpowder for mining purposes. Since it does not contain enough oxygen to burn the charcoal and sulphur completely, there is always carbonic oxide (white-damp) produced by its explosion (see under Carbonic oxide for conditions under which this gas is produced). The composition of the gases resulting from an explosion of gunpowder is:—

Carbon-di-oxide .		51.3 per cent.	
Carbonic oxide .		3.5	,,
Marsh gas and hydrogen		3.5	,,
Nitrogen	•	41.7	,,

Further, it produces much flame by its explosion, a most undesirable property in a flery or gassy mine. As a compensation for these drawbacks, it has the advantage in a coal mine of breaking down the coal in large masses, owing to the comparative slowness with which it explodes. According to Trauzl, 2.2 lbs. of gunpowder, occupying a space equal to a cube of 4 in. side, develops $1\frac{1}{2}$ million foot lbs. in $\frac{1}{100}$ part of a second; the same quantity of dynamite, occupying a space equal to a cube of $3\frac{1}{2}$ in. side, develops over $7\frac{1}{4}$ million foot pounds in $\frac{1}{50.000}$ part of a second. As a result of this, gunpowder fired on a stone slab, say, does not injure the slab, since the slow combustion enables it to spend its force in the air; but dynamite explodes so quickly that it has not time to expend its force thus, but shatters whatever it may be in contact with.

Gun-cotton is, chemically, a nitro-compound of cellulose, made by the action of nitro-sulphuric acids on cotton fibre. Unless very special precautions are taken in its manufacture, the cotton fibres retain small quantities of the acids used, and the material is then liable to explode spontaneously. Many disastrous accidents occurred before this was recognised. The actual oxidising agent is the nitric acid, the sulphuric acid being used simply to take up the water which is produced during the chemical reaction, in oxidising the cellulose.

Gun-cotton is a compound containing too little oxygen for complete combustion, and therefore carbonic oxide is produced by its explosion. It is necessary to use a detonator to bring about explosion, which is accompanied by much heat, causing enormous expansion of the gaseous products. It is never used in the mine alone as a blasting agent, although mixed with barium nitrate it constitutes the explosive Tonite (which see).

Nitro-glycerine is made by the action of nitro-sulphuric acid on glycerine. It is a liquid, and in this form there are many objections to its use; it is not used for blasting purposes in the mine. Nobel used a solid substance called kieselguhr to absorb or soak up the liquid. Kieselguhr is a siliceous earth found on the Continent, and is principally composed of the shells of minute sea animals. The mass formed by the mixture of this earth with nitro-glycerine is the well-known explosive dynamite.

In some cases, more active substances are used instead of kieselguhr to mix with the nitro-glycerine, such as sulphur, magnesia, carbon in some form (sawdust, woodpulp, etc.), also nitrates and chlorates. Such mixtures constitute very powerful explosives, known under a variety of names (Rack-a-rock, Hellhoffite, etc.) which are principally used for blasting or shattering purposes.

Gelignite consists of a mixture of nitro-glycerine, nitro-cellulose, wood-meal, and nitre.

Tonite has for its basis gun-cotton, with which is mixed nitrate of barium, the use of the latter being to supply oxygen to the mixture, since the gun-cotton itself does not contain sufficient for complete combustion.

Roburite contains 86 to 89 per cent. of ammonium nitrate, mixed with 9 to 13 per cent. of di-nitro-benzol, and small amounts of chloro-naphthalene (see List of Permitted Explosives, pp. 94-96).

The gases produced by its explosion consist of 32 per

cent. carbon-dioxide, and 68 per cent. nitrogen, and are therefore free from the objectionable and highly dangerous carbonic oxide.

Ammonite consists of $87\frac{1}{2}$ per cent. ammonium nitrate and $12\frac{1}{2}$ per cent. di-nitro-naphthalene, another organic coal-tar product.

The gaseous products of the explosion of this compound are free from carbonic oxide, and consist of carbon-dioxide and nitrogen.

Bellite is yet another admixture containing ammonium nitrate, and an organic body—di-nitro-benzol. Its gases are free from carbonic oxide, and are entirely carbon-dioxide and nitrogen.

In Westphalite the substance to be oxidised is resin, present to the extent of about 5 per cent., mixed with 95 per cent. ammonium nitrate. The gaseous products are the same as from the three last-named explosives.

The use of ammonium nitrate is one of the comparatively recent developments in the manufacture of explosives. It is especially useful in several ways. There is no solid residue left after heating or exploding; when decomposed it does not give out heat, but absorbs it, and therefore sufficient can be used in a mixture to completely burn up or oxidise the materials used, without producing an excessive amount of heat in doing so. This is the reason why no carbonic oxide is produced, by an explosion of those compounds containing this nitrate. Again, the ammonium nitrate explosives are not so quick in their action as the nitro-glycerine compounds are, and are therefore more suited for breaking down coal.

The principle upon which the manufacture of smokeless powders is based is to have a substance, such as nitrocellulose, which leaves no ash when burnt (that is, its products are entirely gaseous), and a nitrate, such as ammonium, which also leaves no solid residue. Hence

such substances can have nothing but gaseous products when exploded, and these gases, containing no solid matter in suspension, are invisible.

Lime Cartridges.—In very flery or gassy mines these are sometimes used. They consist of quicklime (that is. freshly burnt lime) compressed into cartridge form; they are usually about 5 in. x 21 in., and have to be kept in air-tight cases (as the limes used for oxy-hydrogen lighting have): otherwise the moisture and carbon-di-oxide which are absorbed from the air rapidly spoil them for their purpose. Their action depends upon the "hydration" of the quicklime—that is, its combination with water. The oxide of lime becomes converted into hydrate of lime, and in doing so expands with great force, and breaks down the coal. No explosive effect or flame is produced. Objection is sometimes made to the appearance of the coal brought down by these means, but its quality is not affected at all. Though absolutely safe, the use of lime is nothing like so extensive as that of the "safety" explosives.

One of the suggested uses to which liquid air could be put, is as an explosive agent. In combination with carbonaceous substances it forms an explosive mixture. An objection to its use would be that the cartridge would have to be fired in a short time after removal from the liquid air. It has been used, but so far results have not been very encouraging.

As we have already seen under "Water," when a current of electricity is passed through water, the latter is decomposed into the gases oxygen and hydrogen; these are spoken of as electrolytic gases, and have been used as an explosive agent on the Continent. The force generated when these mixed gases are exploded is very considerable, but they have the disadvantage, in some cases, of causing the "firing" of a gassy or explosive atmosphere. The actual cost of the gases is not great.

94 PHYSICS & CHEMISTRY OF MINING.

Permitted Explosives.—The following is a list of some of the explosives officially sanctioned for use in coal mines, which will serve to illustrate the different types:—

Ammonite—		
Nitrate of Ammonium		87 to 89 per cent.
Di-nitro-naphthalene .		11 ,, 13 ,,
Moisture		 ,, ·5 ,,
Amvis—		
Nitrate of Ammonium		88 to 91 per cent.
Wood-meal	•	4 ,, 6 ,,
Moisture		— " ·5 "
Di-nitro-benzol		A C
Chlorinated Naphthalene)	•	4 ,, 6 ,,
Carbonite—		
Nitro-glycerine .		25 to 27 per cent.
Nitrate of Barium		20 20
Nitrate of Potassium)	•	30 ,, 36 ,,
Wood-meal		39 ,, 42 ,,
Sulphuretted Benzol .		— " ·5 "
Carbonate of Sodium		. e
Carbonate of Calcium	•	— " ·5 "
Dragonite—		
Nitro-glycerine .		34 to 37 per cent.
Nitro-cotton		2 ,, 3 ,
Nitrate of Potassium.		43 ,, 46 ,,
Vaseline		5 ,, 6 ,,
Wood-meal)		
Charcoal $\}$.	•	11 ,, 13.5 ,,
Nobel Ardeer Powder—		
Nitro-glycerine .		31 to 34 per cent.
Kieselguhr		11 ,, 14 ,,
Sulphate of Magnesium		47 ,, 51 ,,
Nitrate of Potassium.		4 ,, 6 ,,
Carbonate of Ammonium		— "·5 "
Carbonate of Calcium.		— " ·5 "

Bobbinite —					
Potassium Nitrate	•		62 to	65 per	r cent.
Charcoal .	•			19·Š	,,
Sulphur .			1.5 "	2.5	,,
Sulphur Sulphate of Ammoni Sulphate of Copper	um)				
Sulphate of Copper	. }	•	13 "	17	,,
Moisture .			,,	2.5	,,
The sulphate of ammoni	ium no	t to e	xceed	11 per	cent.,
by weight, of the finished ex	plosive	2.		-	
Coronite or Permitite—					
Nitro-glycerine	_		38 to	40 per	r cent.
Nitro-cotton .	•	•		1·5	,,
Nitrate of Ammonius	m m	-	26 to		"
Nitrate of Potassium			3 ,,	-	"
Stearate of Aluminiu		•	11 "		"
Rye-flour .	•		8 "		,,
Wood-meal .	•		2 ,,		"
Liquid Hydrocarbon	of Para	ffin)			.,
series .		.}	2 ,,	4	**
Moisture .			— ,,	2.5	,,
The hydrocarbon is to	have :	a flasl	h-point	of no	
than 200° F.			•		
The stearate of aluminium	m is to	be fre	e from	minera	al acid.
Westphalite—					
Nitrate of Ammonius	m		94 to	96 per	r cent.
Resin			4 "	6	,,
Moisture .	•		— ,,	•5	,,
Negro Powder—					
Nitrate of Ammonium	n		86 to	90 pe	r cent.
Tri-nitro-toluol			9 "		"
Graphite .	•	•	1 ,,	_	,,
Colouring matter				•1	,,
Moisture .		•	- ,,	4 4	,,
Roburite No. 3—					
Nitrate of Ammonius	m	_	86 to	89 per	r cent.
Millace of Imminorial	•••	•	30 10	oo pe	· CCIIC.

The chloro-naphthalene to contain not more than one part of chlorine.

Special Bull-do	g—				
Nitrate of F	otassiu	ım .	84 to	86 per	cent.
Carbonate o	f Magn	esium	2.5 "	3.5	,,
Charcoal		•	12 "	13	,,
Moisture			— "	2	,,

Ammonal-

Nitrate of A	nmoniu	n	94 to	96 per	r cent.
Metallic Alui	ninium		2.5 ,,	3.5	,,
Charcoal	•		2,,	3	,,
Moisture				1	

Apparatus for use in Atmospheres which will not support Life.—The necessity of having to go into the workings of a mine, after an explosion of fire-damp, to render aid to those who have suffered from the direct effects of the explosion, or have been overcome by the gases resulting from it, has led to the device of appliances called pneumatophores, by using which a person is able to exist in any atmosphere of noxious gases, for a reasonable time. These consist, in principle, of a kind of mask or headdress similar to that which a diver uses. By means of tubes and valves suitably arranged, the wearer is able to supply himself with oxygen, which he carries in a compressed form in a strong steel, or copper, cylinder. At the same time the carbon-di-oxide which he is continually breathing out, is being absorbed by caustic potash, in the form of sticks or rods, and contained in a bag connected with the mask. The rods of potash form a large absorbing surface, and take up the carbon-di-oxide almost as quickly as it is breathed out. The nitrogen in the original air remains constant and unaltered throughout, and serves its usual

purpose of diluting the oxygen, supplied from the gas cylinder.

In an Austrian colliery much subject to gob fires, eighty sets of apparatus of this kind were in constant use.

The oxygen gas contained in the cylinders is under a pressure of one hundred atmospheres. It is necessary to use the apparatus with caution, and only experienced men should make use of them, otherwise they may prove veritable death traps. Their limitations should be known, and the wearer should always leave himself an ample supply of oxygen for his return journey from any exploring. It is in fact advisable that two oxygen cylinders be used, one for the outward journey, and the other for the return. It has been suggested, too, that compressed air be used instead of oxygen, and that it be discharged from the apparatus instead of breathing it over and over again.

A weak point in connection with the use of compressed oxygen is that it often contains nitrogen, in which case the latter gradually accumulates, and may cause the wearer to be overcome before he is aware of the danger.

Pneumatophores are very useful appliances, but it should be realised that they have their dangers.

CHAPTER X.

COMPOSITION OF VARIOUS COALS AND FUELS.

Nature of Coal.—All the different kinds of coal have been produced by the decomposition of vegetable matter which grew and flourished in remote ages. The chemical changes have occupied very long periods, and have been complex, the final products of these changes being coal in its various forms, water, marsh gas (fire-damp), and carbon-di-oxide. These pent-up gases are continually being met with in the coal measures and adjoining strata.

All coals contain varying quantities of the following substances: moisture, ash or mineral matter, sulphur, carbon, hydrogen, oxygen, and nitrogen—some of these being valuable constituents, others the opposite. To form an estimate of the value of a particular sample of coal, it is necessary to know the proportions of moisture, ash, sulphur, volatile hydrocarbons, fixed carbon, its calorific value (or heating power), and also its specific gravity—that is, its weight compared with water, bulk for bulk—from which an estimate may be formed of the space which a certain weight of coal will occupy. The determination of these constituents is described later.

What is called an ultimate or elementary analysis of coal would include carbon (total), hydrogen, oxygen, nitrogen, sulphur, ash, and moisture. Though the knowledge of total carbon is for some purposes useful, most generally a knowledge of the amounts of fixed carbon and volatile hydrocarbons is more important, because one coal may contain a greater proportion of carbon than another, and still yield less coke.

It is now proposed to describe the distinguishing properties of different kinds of coals.

Anthracite contains from 90 to 95 per cent. of total carbon, which is a greater amount than in any other kind of coal. It is probably bituminous coal which has been considerably altered by the action of heat and pressure. A seam containing anthracite may merge into one of bituminous coal at some point, just as cannel and bituminous coals are known to exist in the same seam. It does not soil the fingers like ordinary coal does, and gives out very little flame or smoke on burning. On heating, it decrepitates or crackles. Anthracite is hard and dense, breaking with a hollow, shell-like fracture. Its chief use is as a steam coal, though it is also used as a source of carbon, in re-carburising steel during its manufacture.

Anthracite coal is not so dangerous to work in the mine as bituminous coal, since the physical condition of the former does not allow pent-up gases to escape as freely as they do from the latter class.

Analyses of anthracite coal follow:-

Carbon		1	ī.	2.		
			89·96 p	er cent.	88·72 p	er cent.
Hydrogen			3.10	,,	3.41	,, '
Oxygen			1.63	,,	2.54	"
Nitrogen			·27	,,	•39	,,
Sulphur			1.06	,,	·87	,,
Ash .			1.96	,,	1.56	"
Moisture			2.00	"	2.50	"

As a rule, anthracites contain from-

88	to 95	per cent	. Carbon
2	to 4.0	,,	Hydrogen
1.5	5 to 3·0	,,	Oxygen
.25	to ·75	,,	Nitrogen
• {	5 to 1.5	,,	Sulphur
	1 to 3	"	Ash

100 PHYSICS & CHEMISTRY OF MINING.

An analysis of anthracite also gave the following results—

Fixed carl	oon	•		84·60 p	er cent.
Volatile h	ydroc	arboi	ns	12.40	,,
Sulphur				·95	,,
Ash .				2.00	,,

Cannel has a dull black appearance, not so bright as anthracite or bituminous coals. Its chief use is in gas manufacture, because of its richness in hydrogen. Cannel contains from 40 to 50 per cent. of volatile hydrocarbons, and one ton of Wigan cannel produces about 10,850 cubic feet of gas, other cannels ranging from 9000 to 15,000 cubic feet; the lighting power of the gas varies from 20 to 40 candle power. It is remarkable that the analysis of many cannels gives a similar composition to that of other coals; the difference appears to be largely a physical one, probably due to the combined action of heat and pressure.

Analyses of cannel gave the following results:-

				I.		2.	
Ash .				2·30 pe	er cent.	1.60 p	er cent.
Sulphur		•		1.30	,,	•58	"
Volatile h	ydro	carbo	ons	40.56	,,	48.85	"
Fixed cart	on			56.50	,,	49.25	,,

An ultimate analysis of cannel would average as follows:—

Carbon .		•		80.0	per cent.
Hydrogen			•	5.5	,,
Oxygen .				8.0	,,
Nitrogen				2.0	,,
Sulphur .				·75 to 1·5	,,
Ash.	•			2,,4	,,

The ash in some cannels is very high, reaching as much as 20 to 25 per cent. The coke resulting from cannel is usually much inferior to that from a "caking" coal.

The Bituminous or Flaming Coals are divided into a caking and non-caking class. A caking coal is one, as the name implies, the particles of which tend to soften and fuse together into one mass on heating. As a rule non-caking coals, or such as do not alter their shape on heating, contain more carbon and hydrogen than the caking varieties. A caking coal produces much better coke than a non-caking, or than those which burn freely.

Certain coals seem to combine some of the properties of both caking and non-caking fuels, and the kind of coke left by them varies considerably in physical properties, such as density, compactness and friability. Non-caking coals are sometimes called "splint" coals; they splinter up on heating, and do not conglomerate or mass together. The caking appears to be a physical peculiarity of the coal, since with coals having almost the same chemical composition, some will cake and others will not.

For steam and house coals, the desirable qualities are the production of as much heat as possible with little residue of ash. Steam coals are such as are mostly used for the generation of steam, and generally burn freely, with comparatively little smoke; a good house coal should be readily set alight, and be fairly free from ash. In both kinds of coal, sulphur compounds should not be high, and the smoke produced by their combustion should not be too great.

With regard to the latter point—smoke production—this is to a great extent controllable by the consumer, especially in steam-raising. As a general rule, the higher the amount of volatile hydrocarbons, the greater the tendency to produce smoke, if the conditions of firing are the same. The anthracites, for instance, burn with practically no smoke, and have a correspondingly low volatile matter. But with coals, generally speaking, everything depends upon the firing. Careless firing, with a coal of low volatile matter, will produce more smoke than a high volatile coal more carefully and economically stoked.

As previously pointed out, dense black smoke is usually accompanied by carbonic oxide, which means a loss of heat-production. Black smoke also causes a deposit of carbon or soot on the boiler, and on the tubes. This carbon is a very bad conductor of heat, and therefore prevents a free passage of heat through it to the surface to be heated.

The following figures represent average analyses of coals:—

Specific gravity		. '		1.28	to	1.35	per cent.
Ash					,,	6.0	·. ,,
Sulphur			•	•50	,,	2.5	,,
Volatile hydrocarbon	ns			32.0	,,	40.0	,,
Fixed carbon				50	,,	65	"
Calorific value .		•		7000	,,	8000	heat units
No. of lbs. of water e	evap	orate	d				
by 1 lb. of fuel .	•			13	,,	15	
Total or ultimate car				77	,,	90 pe	er cent.

Coke is made by carbonising coal in suitable ovens, in which it is heated out of contact with air, or with the admission of as little air as possible. The old type of "beehive" oven is being displaced by more modern forms, such as the Semet-Solvay, Otto-Hofman, Simon-Carvé, Coppée, etc., in which the coal is carbonised in chambers, by hot gases which circulate outside them. The gases thus used are produced from the coal itself. The products given off when the coal is heated are drawn through scrubbers and condensers, and the tar, light oils, and ammonia compounds thus separated; after which the gases, deprived of these valuable by-products, are led back to the ovens and distributed in the surrounding

the coking chamber, where they a heated air. The gas is rich in hyd and has a high calorific value. Their heating effect in the flues, are me generation, before being allow

gas, fter for he

COMPOSITION OF STATE -

The Birminous of Framme Law 7 colors a capture and knowledge makes a value of the first topology of the makes at least to the first topology of the makes at least to the first topology of the makes at least to the first topology of the makes at least to the first topology of the makes at least topology of the first topology of the first topology of the makes at least to

to non take at the properties of non-constitution and a properties, some are constitution and a constitution

TO SEEZ Z DE ATTENDE DE ATTENDE COMPARATIVE DE ATTENDE COMPARATIVE DE ATTENDE DE ATTENDE



of silvery appearance, largely composed of carbon, and practically free from ash.

All the mineral matter present in the original coal remains in the coke. Its proportion is of course increased, since volatile matters have been driven off during the coking. For instance, if a coal contains 5 per cent. of ash, and gives off on coking, 50 per cent. of volatile matter, it is evident that the amount of ash in the coke will be 10 per cent., or double that in the original coal.

The sulphur of the coal is not all retained by the coke, some passing off in a volatile form on heating, and being included with the volatile hydrocarbons. There is no fixed rule as to how much is retained by the coke, as this varies with the kind of coal used. The only means is to test the coal for sulphur, and to test also the coke resulting from it. The sulphur driven off in coking is mainly the organic sulphur, together with some derived from the pyrites in the coal.

The phosphorus in coke is rarely present in very appreciable quantity—from traces to ·02 per cent.—though in some districts the coal may yield a coke containing ·10 to ·15 per cent. Such an amount would be a very serious objection to the use of the coke as a metallurgical fuel, especially in iron smelting.

Coke always retains small amounts of hydrogen, nitrogen, and oxygen, so that all the nitrogen present in the coal is not obtained in recovery processes for conversion into ammonia sulphate or chloride. The amount found in the coke ranges from about ·3 to 1·0 per cent.

An analysis of an average quality of coke is as follows:—

Ash 6 to 12 per cent.

Sulphur 1 ,, 2.5 ,,

Volatile matter . . . nil ,, 2.0 ,,

Peat is an accumulation of partially decomposed

vegetable matter, a damp, marshy ground and moderate temperature being favourable conditions for its production. In its ordinary condition it retains a large amount of moisture (at least 20 to 25 per cent.), but its general composition varies with its age, an older formation containing more carbon than a more recent one does. Peat also contains a large amount of ash or mineral matter, in which are found phosphates and sulphur compounds, so that it cannot be used in the manufacture of high grade iron, even if the objectionable moisture be not considered, and if the physical condition of the peat itself be altered so as to make it less friable and tender.

Lignite is a kind of intermediate product between peat and bituminous coal. It is darker in colour than peat, and is richer in carbon; it retains much moisture, and is worked more on the Continent than in the British Isles. In the change from vegetable matter to bituminous coal, the carbon gradually increases from about 50 per cent. in wood to 75 to 85 per cent. in bituminous coals, and 95 per cent. in anthracite.

Wood.—The chief constituent of wood is a substance named cellulose, which consists of carbon, hydrogen, and oxygen. The amount of mineral matter or ash it contains varies with the kind of wood, but is rarely more than 3 or 4 per cent., often as low as 1 per cent. It retains a good amount of moisture, but is not so objectionable in this respect as peat is, being also more readily dried.

The carbon it contains is best utilised in the form of charcoal, which is made by heating the wood either out of contact with air, or with admission of as little air as possible. It is very useful in metallurgical operations, where a pure fuel is desirable, and where substances like sulphur and phosphorus would completely spoil the product.

Liquid Fuels have an advantage over coal in districts where oil is plentiful. The oils are all hydrocarbon compounds, and most of them, petroleum oils in particular, have a greater heating effect than anthracite.

They burn when supplied with oxygen, forming carbondi-oxide and water. They have the very great advantage of being practically free from ash, and contain very little sulphur (almost nil), though in some cases this may be as high as 4 or 5 per cent., and, moreover, being usually sprayed into the combustion chamber, a very complete combustion is possible. Very little, if any, of the oil escapes burning, and consequently the greatest possible heat efficiency is obtained.

Undesirable Elements in Coal and other Fuels.— There are certain elements and compounds the presence of which affects the value of coal for many purposes.

If oxygen be present in a fuel, the heating effect of the latter is lowered, since, being combined with the carbon and hydrogen, these substances do not give out their full amount of heat. Had they not been already combined with oxygen they would have been at liberty to unite with the oxygen of the air and thus produce heat.

Some coals are practically free from oxygen, others contain 10 per cent. or more.

Ash, if present in appreciable quantity, is very objectionable in a coal, because it tends to form "clinker," a fusible compound, produced either by the ash itself, or by the combination of the substances composing the ash, with oxide of iron from the firebars. This clinker prevents free passage of air through the fuel, and tends to the production of carbonic oxide, and therefore loss of heat. It is evident, too, that the higher the amount of ash, the lower the calorific or heating value of the coal.

Sulphur and Phosphorus are both objectionable,

especially if the fuel is to be used for metallurgical work, since practically all the phosphorus and a large proportion of the sulphur go into the resulting metal and contaminate it. Sulphur is further objectionable, because it forms corrosive gases, and tends to become converted into sulphuric acid. The escaping gases from a sulphury fuel, also, contaminate the atmosphere and act injuriously on animal and plant life in the neighbourhood.

Sulphur exists in three different conditions in coal:—

- (1) The most common form is as iron pyrites (chemically bisulphide of iron FeS₂), commonly called "coal brasses," and is, as the name implies, the "brassy" looking mineral often seen in coal.
- (2) As sulphate of lime, the common name for which is "gypsum," also sometimes as sulphate of alumina.
- (3) As an organic compound with carbon and hydrogen. Of these forms, the sulphur existing as sulphate of lime is the least objectionable. It is "fixed" by the lime, so to speak, and does not produce any noxious or corrosive gases on firing.

The iron pyrites is objectionable, not only because of the corrosive and noxious gases it produces, but because the remaining iron (in the form of oxide) fuses with the silica of the coal ash and increases the amount of clinker and helps to make it more readily fusible. Devices for getting rid of this objectionable element form the basis of many patents. The most successful methods depend upon washing the coal and separating the shaley and pyritic portions by means of their specific gravity.

The sulphur, which is in organic combination, is mostly converted into bisulphide of carbon through coming in contact with heated carbon during combustion. This refers principally to processes of coking and of gas manufacture where destructive distillation is going on, with little or no air present.

Nitrogen in Coal.—The element nitrogen cannot

be classed as an undesirable one in coal. The amount varies from ·25 to 3·0 per cent. as a rule. It is probably due to animal remains from the periods at which the coal measures were in process of formation, and also some of it is derived from the atmosphere existing at the time. When the coal is heated, this nitrogen combines with some of the hydrogen of the fuel and forms ammonia (chemical formula NH₈). It will be readily seen that in making coke from coal, considerable quantities of this compound, ammonia, must be produced.

Of late years, the recovery of this important compound (formerly allowed to escape and waste) has become a very important problem in the economy of a coking plant, and very few modern works can afford to neglect the recovery of this and other by-products, such as tar and various oils. The ammonia is first given from the coal, on burning, as a gas. This is converted into a solid by passing it through a solution of sulphuric acid or hydrochloric acid, whereby sulphate or chloride of ammonia is produced in a marketable form. These compounds are then used for the manufacture of ammonia salts, and also largely for manurial purposes, the nitrogen which they contain forming a valuable plant food.

Briquettes.—The manufacture of briquettes is a useful process, especially in working coal seams of inferior quality, where the waste may sometimes amount to 20 per cent., and also for converting into a workable form small coal of all kinds which is unavoidably produced in the mining and subsequent handling of coal.

In briquette form such coals are much improved, both for use and storage and also for transport. The space occupied by them is about one-half that required for coal of the same weight.

Some kind of binding material has to be used along with the fine coal. The most generally successful agent has been coal-tar, or pitch, or both. The subject forms the

basis of many patents, and all manner of binding materials have been suggested, such as glucose, waste glue products, starchy compounds, molasses, silicate of soda, oily materials, waste oil, crude linseed oil, sea-weed extracts, and gelatinous substances of all kinds. Resin is often successfully used alone or with other binding material.

It is preferable that the binding material used should, if possible, help or increase the burning qualities of the briquette, and should itself be as free from ash as possible. Magnesia cement is said to make a very strong briquette, but it has the disadvantage of increasing the amount of ash, though this increase need not be more than about 3 per cent.

Briquettes can be used as fuel for locomotives as well as for domestic purposes.

CHAPTER XI.

METHODS OF ANALYSIS OF COAL.

Specific Gravity.—By the specific gravity of a solid is meant its weight compared with an equal volume of water at a standard temperature.

The specific gravity of coal may be determined by first weighing a piece in air on a chemical balance, and then in water, suspending it in the latter by means of a looped horse hair.

The coal loses weight when immersed in the water, and Weight in air

Loss of weight in water = specific gravity.

Unless great care be taken, the piece of coal used may be unduly contaminated with shale or pyrites, which would give too high a specific gravity, and several determinations on different pieces should be made, taking the mean or average result.

In cases where a large representative sample is taken, it is better to make the determination on the powdered sample, another method being, of course, necessary then. This is done in a specific gravity bottle, which is a small glass flask holding a known weight of water at a constant temperature (60° F.). A weighed portion of the powdered coal is placed in the flask, and water (at 60° F.) added until the flask is full, allowing a little time for the coal to become thoroughly wet and free from air bubbles. The stopper of the flask is then inserted, and any excess of water is forced through a fine hole specially made in the centre of the stopper, the flask carefully dried outside and weighed.

The coal has displaced its own volume of water, and therefore

Weight of coal taken

Weight taken + weight flask and water = specific gravity.
- flask, water, and sample.

The specific gravity of coals ranges from about 1.2 to 1.4; and since 1 cubic foot of water weighs 62.5 lbs., the weight of a cubic foot of coal will range from 62.5×1.2 to 62.5×1.4 in lbs.

A bunker for storing coal measures 12 feet long, 10 feet wide, 8 feet high. The specific gravity of the coal to be stored in it is 1.25. How much will the bunker hold?

1 cubic foot water weighs 62.5 lbs.

... 1 cubic foot of this coal weighs $62.5 \times 1.25 = 78.1$ lbs. Cubic capacity of bunker = $12 \times 10 \times 8 = 960$ cubic feet. But if 1 cubic foot coal weighs 78.1 lbs..

960 cubic feet coal weigh $78.1 \times 960 = 74,976$ lbs.

 $\begin{array}{c}
\cdot \cdot \cdot \frac{74,976}{2,240} \text{ (lbs. in ton)} = \frac{33.47 \text{ tons}}{\text{(practically } 33\frac{1}{2} \text{ tons)}}.$

The Moisture in Coal is estimated by taking a weighed quantity in a copper dish, and exposing it to a temperature not exceeding 100°C. or 212°F. in a water bath, which is a small oven surrounded by a water jacket. The water is kept boiling by suitable means, and the temperature is constant and never exceeds the boiling point. The coal should be thus dried for eight or ten hours, depending on the amount taken, and also as to whether the sample is unusually wet or not.

It is advisable not to have the coal finely powdered for this test; the coarse sample should be used, otherwise there is a possibility of driving off volatile hydrocarbons as well. A too prolonged heating is undesirable, as the pyrites tends to oxidise, both effects giving too high a result for moisture. The loss in weight can be easily calculated into percentage. The safest method is to expose a weighed portion of the coal under a glass bell jar in which sulphuric acid-is placed, in a tray, for twenty-four hours. The loss in weight represents moisture.

The Determination of Ash is made by taking a weighed quantity, usually 1 or 2 grammes, and placing on a flat porcelain lid. (Platinum should not be used, as the carbon acts upon it in time, and causes it to crack and become brittle.) Heat gently at first over Bunsen flame or at a safe distance in front of the muffle furnace, and gradually increase the temperature until the sample can be safely placed inside the muffle at the front. Allow a plentiful supply of air, and finally place in a hotter part of the furnace for a few minutes. When all the carbonaceous matter has burnt away, take the dish out of the furnace, allow to cool, and weigh the ash. The percentage may be readily obtained thus—

2 grammes of coal left a residue of ash weighing ·104 grammes: therefore 100 grammes would leave

$$\frac{\cdot 104 \times 100}{2} = 5.2 \text{ per cent.}$$

The colour of the ash varies from white to reddish brown, and often affords a valuable indication as to the contents of sulphur in the coal. A reddish-brown ash owes its colour to iron oxide, which denotes that iron sulphide or pyrites was present in the coal before burning; the sulphur has combined with oxygen of the air and gone off as a gas, but leaves the tell-tale iron oxide behind. A white ash, as a rule, denotes comparative freedom from sulphur in the coal from which it has been produced.

Chemical Composition of the Ash.—This varies with the kind of coal, and also with the district in which it is found; but all ashes contain silica, alumina, iron oxide, lime, magnesia, sulphuric acid (in the form of sulphate).

phosphoric acid (in the form of phosphate), potash and soda. The amounts usually vary as follows:—

Silica	•		•	•	30 t	o 60	per cent.
Alumina a	nd O	xide	of Iro	n	35 ,	, 55	- ,,
Lime .		•	•		5,	, 10	,,
Magnesia	•			. tr	aces,	, 2	,,
Sulphuric	Acid	•	•	•	3,	, 8	,,
Phosphori	c Aci	đ			·5 ,	, 1.5	,,
Potash an	d Soc	la	•		2.	, 4	••

The Volatile Hydrocarbons are those compounds which are driven off at a full red heat when the fuel is heated out of contact with air.

A weighed quantity of fuel being taken (1 gramme coal, 2 to 5 grammes coke), in a weighed porcelain or platinum crucible, the cover of the latter is put on and the whole placed inside a larger crucible, and covered with coarsely powdered coke and the cover of the larger crucible, then put on over all (see Fig. 41). The fuel (if coal) is



FIG. 41.—Estimation of volatile matter.

heated over a straight Bunsen flame, as long as any smoke is seen issuing from the crucible. It is then transferred quickly to a gas muffle at a red heat and the door closed to exclude air, and the heating continued from two to three minutes. Remove from muffle, cool under a bell jar (dessicator), and weigh loss of weight of inner crucible and contents. This loss represents the volatile matter, and the residue in the crucible is the coke produced. The appearance of the latter should be carefully noticed, as to whether it has coked well, or is hard or soft, etc.

The calculation is simple, e.g.:

1 gramme of coal, loses, on being thus treated .387 grammes = 38.7 per cent. volatile and 1.00 - .378 = .613 = 61.3 per cent. coke produced.

The volatile matter in a coke is estimated in the same way, but is, of course, much lower, varying from nil to 2.0 per cent.

The Estimation of Sulphur in coal or coke, for practical purposes, usually includes that from all three of the sources mentioned before—that is to say, the *total* sulphur.

There are several good reliable methods available for its estimation, but they require considerably more skill and care and knowledge of chemical action, than do those used for ash, moisture, or volatile determinations. Two methods, of different types, will now be described.

The principle in both depends upon converting the sulphur into a definite chemical compound (barium sulphate), the exact composition of which is known. It contains 13.73 per cent. of sulphur.

Method 1.—A weighed quantity of the coal or coke is intimately mixed with sodium carbonate and nitre (1 gramme coal + 3.5 grammes soda + 9.0 grammes nitre) and heated gently in a platinum crucible until fusion and chemical action begin. (Common salt is sometimes used instead of carbonate of soda.) The heating is continued until the mass becomes quiescent, and when cool the result is dissolved out in distilled water and transferred to a glass vessel (called a beaker.) Hydrochloric acid is then added until no further effervescence takes place and the solution is then boiled and filtered. All the coal or coke ought to have been oxidised. If any quantity remains on the paper, this should be washed and weighed, and its amount deducted from the original weight of fuel; or, better still. it should be fused with a little more fusion mixture and the result added to the first main portion.

The clear filtered solution is then boiled and barium chloride solution added to it. This reacts with the sulphate in solution (into which form all the sulphur has been converted), and a white substance (called a precipitate) appears

in the liquid, consisting of the above-mentioned barium sulphate. Thus—

Barium chloride + Sodium sulphate = Barium sulphate + Sodium chloride.

A case of mutual interchange.

It remains then to allow this precipitate to settle out, to filter it off through filtering paper (Swedish quality is necessary), wash away all soluble matter by means of a wash-bottle, first using dilute acid and finally hot water alone, leaving the pure barium sulphate on the filter. The latter is burnt off in a platinum dish, and weighed (allowing from 1 to 2 milligrammes for the ash of the paper).

Then e.g. — If the barium sulphate produced from 1 gramme of the fuel weighs ·123 grammes, and the barium sulphate is known, beyond doubt, to contain 13·73 per cent. sulphur.

Therefore 13.73 per cent. of 123 is the amount of sulphur in 1 gramme of fuel.

 \therefore 13.73 \times .123 = 1.68 is the percentage.

Method 2.—This consists in heating the fuel in contact with magnesia and carbonate of soda or with lime, in an open dish, whereby the whole of the sulphur becomes sulphate of magnesia, soda or lime, as the case may be. The mass is transferred, after heating long enough to thoroughly decompose the fuel, to a beaker, dissolved in water and a slight excess of hydrochloric acid, with a few drops of bromine, filtered if necessary, any coal not acted upon being weighed, or reheated with lime or magnesia, the filtrate boiled and barium chloride added to it as before. The final operations being exactly the same as in method 1.

Method 2 is in very general use, and is to be preferred to the other for general purposes. In both methods the materials used must be themselves free from sulphur compounds, or these will cause too high a result. A blank test should be made, that is, by using all the materials except the coal or coke, and precipitating the

solution thus obtained with barium chloride and deducting the weight of any precipitate thus found from the other result.

The Calorific Value or Heating Power of Coal is determined by means of an apparatus known as a calorimeter, of which there are several modifications.

The principle of them all depends on either (1) burning the coal by oxidising chemical reagents, such as nitrates and chlorates, substances rich in oxygen; or (2) by burning the fuel in an atmosphere of oxygen gas. In both cases the heat produced is measured by delicate thermometers.




FIG. 42.—Calorimeter (showing details and calorimeter in action).

In the first-named method a weighed portion of the fuel is taken and intimately mixed with potassium nitrate and chlorate. The mixture is placed in a small copper crucible or tube closed at one end, and a piece of fuse inserted (lamp wick soaked in nitre solution, and dried).

The whole is then fixed on a special piece of apparatus which can be immersed in a measured quantity of water, without the water coming in actual contact with the contents of the crucible. The exact temperature of the water being taken by means of an accurate thermometer, the fuse is lit and the apparatus quickly immersed in the water. When the fuse gets down to the mixture of coal and oxidising agents, vigorous chemical action takes place,

due to the burning up of the coal by the oxygen of the nitrate and chlorate. The resulting gases, before they can escape, have to pass through the water surrounding the apparatus, and in doing so, give up their heat to it. When the combustion is complete, water is admitted to the inside of the apparatus, which is naturally very hot, and takes up the heat therefrom, so that the total heat evolved by the combustion of the coal is given up to the water. The apparatus itself absorbs some of the heat, and a constant allowance is made for this, usually 10 per cent. Knowing the volume of water and the number of degrees increase in temperature, caused by the burning fuel, it is possible to calculate its calorific value, and from this its evaporative power.

When oxygen gas is used, the apparatus is similar in construction, except that an appliance is fitted whereby the coal can be ignited by an electric current passing through a fine platinum wire, which becomes red-hot. Oxygen gas is led into the space surrounding the coal, instead of using the solid oxidising agents as described in method 1, and ignition once started by means of the hot wire, the fuel burns completely away, the escaping gases, as before, passing through the surrounding water, and giving up their heat to it.

In an actual test the temperature of water in the cylinder was 14.2° C. before the combustion and 21.3° C. after.

The increase in temperature therefore was 7.1° C.

2 grammes of coal were used, and the volume of the water was 2000 cubic centimetres.

On adding 10 per cent. for absorption of heat by the apparatus, the actual increase in temperature was $7\cdot1^{\circ} + \cdot71^{\circ} = 7\cdot81^{\circ}$ C.

This multiplied by 1000 = heat units or calories = 7810,

and
$$\frac{7810}{537}$$
 = 14.54 lbs. of water

converted into steam by 1 lb. of the fuel (537 being the latent heat of vaporisation of water).

In the more elaborate apparatus known as the bomb calorimeter, the oxygen gas is supplied to the fuel in a compressed form, and the combustion takes place under several atmospheres' pressure. The combustion is started electrically, and the bomb has to be very strongly made to withstand the high pressure of the oxygen, increased by the temperature of the combustion. The bulk of metal employed necessitates a careful correction for the heat absorbed by the apparatus itself.

The calorific or heating value of fuel can be calculated if its chemical composition be known, but the theoretical results thus obtained are always higher than the results obtained in practice. Radiation and absorption of heat partially account for this, as do also certain chemical actions which require heat for their completion.

When carbon burns completely to carbon-di-oxide it produces 8080 heat units, and every 1 lb. of carbon requires 11.57 lbs. of air.

Hydrogen, when burnt to form water, produces 34500 heat units, and 34.7 lbs. of air are required for its combustion.

Sulphur, when burnt, produces 2220 heat units, and every lb. requires 4.35 lbs. of air.

Carbonic oxide, burning to form carbon-di-oxide, generates 2403 heat units, and requires 2.48 lbs. of air per lb. of gas.

A calorie, or heat unit, is the quantity of heat required to raise 1 kilogramme of water 1° C., and a British Thermal unit is the amount of heat required to raise 1 lb. water 1° F., hence 1 calorie is equal to 3.968 British Thermal units.

The increase in temperature of the water is usually taken as being from 0° C. to 1° C., but so long as the temperature is below 100° finally, it is not material. After what has been said about latent heat (which see), it would be absurd to take the amount of heat required to raise the temperature of water from 100° C. or 212° F.

(its boiling point) to 101° C. or 213° F., because we know that unless the pressure be increased or solids added to the water, that the latter is not increased in temperature once the boiling point is reached.

If the increase in temperature be measured in Pahrenheit degrees, then the numbers representing the calorific powers, as expressed by Centigrade degrees, must be increased in the proportion of 9:5.

The heating power of a fuel depends upon the carbon and hydrogen which are available for combustion.

If any oxygen be present (and there always is some proportion in coals), that oxygen is taken to be already combined with its share of hydrogen, and therefore is useless for heat production when the fuel is burnt. It has been shown already that oxygen is combined with \$\frac{1}{8}\$th its weight of hydrogen to form water, and when a fuel containing oxygen burns, it uses up this proportion of hydrogen, and this is always allowed for in calculating the heating power of a fuel from its analysis.

For instance, assume an analysis of coal to show-

Carbon .		•	•	80 p	er cent.
Hydrogen			•	5	,,
Oxygen.			•	8	,,
Nitrogen				2	"
Ash .	•	•	•	5	,,

Then 100 lbs. of this fuel contain 80 lbs. of carbon, 5 of hydrogen, and 8 of oxygen.

The 8 lbs. of oxygen will require 1 lb. of hydrogen, and this leaves 4 lbs. hydrogen available for heat production, and the calculated heating power of this fuel will be—

Heat due to carbon .
$$8080 \times 80 = 646400$$

, hydrogen . $34500 \times 4 = 138000$
Total heat units . 784400
 \therefore 1 lb. of this fuel would generate $\frac{784400}{100} = 7844 \cdot 00$

heat units.

120 PHYSICS & CHEMISTRY OF MINING.

A certain deduction would have to come off this again, for the heat which becomes latent in converting the water (formed by the union of the oxygen and hydrogen in the fuel) into steam.

If the coal be wet, then a further amount of heat is lost in converting this moisture into steam—

			Centigrade heat units produced.	Lbs. of air required by 1 lb. of the substance.	
Carbon, whe	n burnt	8080	11.57		
Hydrogen,	,,	H ₂ Õ	34500	34.7	
CO,	,,	CÔ,	2403	2.48	
CH ₄ ,	,,	CO, and H,O	13063	17:35	
Sulphur,	••	SO, 1	2220	4.35	

CHAPTER XII.

STRATA ADJOINING THE COAL MEASURES.

THE strata adjoining the coal measures consist of shales and clays of various kinds, clay ironstones, ganister, etc., more or less valuable for working purposes according to their composition.

Chemically considered, clay is a compound of silica (the chief constituent of sand), with alumina (the oxide of the now well-known metal, aluminium), and combined water. In other words, it is a hydrated silicate of alumina. In addition to these substances, there are always varying amounts of iron oxide, lime, magnesia, and the alkalies, potash and soda.

All clays have been formed by the decomposition of felspathic rocks. These are silicates of alumina, potash and soda. When exposed to the weathering action of rain, wind, frost, running water, carbon-di-oxide and oxygen, they gradually decompose, and certain of their constituents (sodium and potassium) become carbonates, which are soluble in water, and therefore are washed away. This leaves the silicate of alumina in a more or less pure condition, often contaminated with oxide of iron, but the purer clays (e.g. china clay) are free almost from this constituent. The colour of a clay is a good indication of the amount of iron it contains, a reddish-brown clay being richer in iron than one of a paler colour. China clay is almost white.

Suitability of Clays for various purposes.—The clays are suitable for various purposes according to their composition; that which would be satisfactory for making

building bricks would be absolutely useless for making a refractory brick, that is one which will withstand intense heat, such as that required in metallurgical processes.

A good clay for refractory purposes should contain 50 to 60 per cent. silica and from 20 to 30 per cent. alumina; there should be very small amounts, if any, of lime, magnesia, and especially alkalies, potash and soda. Small amounts of iron may be present, but should not exceed 2 or 3 per cent. of oxide. Iron in the form of pyrites is very objectionable. Lime, magnesia, potash, and soda all tend to lower the fusing or melting point of the brick, since they form readily fusible silicates with the silica. Potash and soda are especially objectionable on this account. In clays to be used for building-bricks, the presence of these impurities is not so serious. The oxide of iron present determines the colour of the brick, and much more lime, magnesia, and alkalies may be tolerated than in a fire-clay.

It has been previously stated that clays contain combined water, usually about 10 per cent. To this they owe their plasticity, that is the property of being moulded into various forms. If this combined water be driven off by heat, the clay never regains its plastic power. A practical method of testing the refractory nature of a clay is to mould a portion into the shape of a rectangle, or cube, or pyramid with sharp edges; after carefully and slowly drying, the test piece is subjected to a high temperature. A clay of high refractory quality ought not to show the slightest rounding-off or fusing of the sharp edges.

Many things have to be considered in dealing with refractory bricks, especially the purposes and uses to which they are intended to be put. For instance, a brick may consist principally of silica (silica brick), containing as much as 98 per cent. pure silica, and such a brick subjected alone to a very intense heat would be unaltered, practically. If, however, a slag containing much lime, or if lime itself or ferrous oxide be brought into contact with the brick, fusible

compounds, silicates of lime or iron, would be formed, and cause the brick to "run." Similarly, lime and magnesia alone are infusible, even at the most intense temperatures, but if they come into contact with siliceous substances they melt fairly easily.

The following are analyses of refractory materials:—

			Fire-clay.	Fire-clay.	Fire-brick	Magnesite . Brick.	Silica Brick.
			Per cent.	Per cent.	Per cent.	Per cent.	Per cent.
Silica.			63.80	50.20	58.00	2.40	96.80
Alumina		•	22.20	31.71	34.8	•50	·60
Iron Oxide	•		2.97	2.78	3.8	·40	1.50
Manganese	: Ox	ide	traces.	traces.	traces.		
Lime .	•	•	1.00	1.00	1.0	·10	-80
Magnesia		•	traces.	traces.	1.4	95.8	•20
Alkalies, and S		$\left. iggr_{\cdot}^{\mathrm{ash}} ight\}$	•52	•91	1.0	not estd.	•50
Combined and omatter	orga	ter nic	9.50	13.40	nil.	•50	nil.

Aluminous Shales.—The shales are also compounds of silica and alumina, and they are often treated for the alumina they contain.

Alum shale is a coaly mineral, containing pyrites (bisulphide of iron). On roasting this shale and then "weathering," the sulphur of the pyrites becomes partially converted into sulphuric acid, which acts upon the silicate of alumina, forming sulphate of alumina. The mass is washed with water (lixiviated or leached) to get out all the soluble matter, and potassium sulphate is added in sufficient quantity to form ordinary alum, which is a double sulphate of aluminium and potassium. Certain iron compounds are formed at the same time, but being more soluble in water they remain dissolved, while the less soluble alum is allowed to crystallise out in vats.

Some bituminous shales are subjected to distillation to

recover oils from them, and most of them are now worked for ammonia as well, and this latter forms an important branch of the shale industry. The principle underlying this recovery is practically the same as that referred to under by-product recovery in coking.

The shales richest in hydrocarbons probably contain more vegetable matter than those which are rich in ammonia; the latter probably contain a greater proportion of animal remains.

Iron Pyrites has been referred to several times previously. It is commonly met with in and near the coal measures. It is a compound of iron and sulphur, and is often used as a source of sulphur in various manufacturing processes, e.g. in sulphuric acid making, the residue (which is chiefly oxide of iron) being then used for the iron which it contains. The pyrites is also, in some cases, converted into "copperas" or "green vitriol" by weathering. The name "copperas" for the sulphate of iron produced is somewhat misleading. The sulphur of the pyrites takes up oxygen forming sulphate and at the same time free sulphuric acid is produced (see acid waters); this free acid is neutralised and converted into more sulphate of iron by the addition of scrap iron or steel. The salt produced is crystallised out in vats.

Ganister is a rock met with in certain districts near the coal measures. It is almost entirely silica (at least 95 or 96 per cent.), and is very refractory, being consequently used for purposes where great heat has to be withstood, such as lining the Bessemer converter in which steel is made by the acid process. An analysis of a brick made of ganister was as follows:—

Silica.			96.0
Alumina			1.0
Iron Oxide	•		.9
Lime .			1.2
Magnesia			•6

Ironstones.—The strata near the coal measures often contain workable amounts of iron, generally in the form of carbonate. They are sometimes associated with silica and alumina, and usually a fair amount of carbonate of lime, with phosphoric acid and sulphur.

The analyses given below show the differences between the various kinds of ironstones, and especially the composition of those associated with the coal measures. The iron in the latter, it will be noticed, is mainly in the form of carbonate, while others have their iron principally in the form of peroxide.

It is generally advantageous to calcine (that is, heat strongly in a kiln) ironstones in which the iron is as carbonate, before smelting. This drives off carbon-di-oxide and combined water, and the final result of such heating, in the case of the "cockle-shell" bed (analysis No. 8), would be to more than double the amount of metallic iron (29.47 per cent.), the actual loss due to heating being 51.3 per cent. Clay ironstones vary in colour from pale brown to black, the latter caused by coaly or carbonaceous matter mixed with them, sometimes in sufficient quantity to enable them to be smelted without the use of further fuel.

Analyses of Ironstones (Ten Varieties).1

1					1		ı			
	I	2	3	4	5	6	7	8	9	10
	Per	Per	Per	Per	Per	Per	Per	Per	Per	Per
1 .	cent.	cent.	cent.	cent.	cent.	cent.	cent.	cent.	cent.	cent.
Silica .	1.00	8.40	3.60	3.00	7.32	17.80	22.I	1.90	10.75	28.30
Alumina	•50	6.00	1.0	4.0	5.85	9.50	2.25	1.00	4.62	10.10
Iron peroxide	98.1			3.2	43-27	44.50	.64	2.86		
Iron protoxide.	nil.	44.50	54.0	45.0	•••	•••	38.50	15.80	18.97	30-47
Manganese								1	-	
oxide	.25	2.10	1.5	1.7	1.40	•75	•••	1.30	•••	-93
Lime carbonate	trace	2.05	traces	5.0	31.60	15.00	1.4	29.60	35-71	1.80
Magnesia car-					-	-		1		
bonate	trace	3.51	traces	•75	traces	trace	1.93	trace	5.81	9.20
Phosphoric acid	trace	.20	.10	.05	1.15	.86	.30	.42	.42	•••
Sulphuric acid.	nil.	2'10	3.2	.65	.10	•••	.čo	.65	.50	•••
Organic matter and combined			٠,							
water	nil.	4.0	4.0	8.0	•••	nil.	trace	30.37	14.5	20.60
Iron carbonate	nil.	71.80	87.0	72.5		•••	62.0	25-47	30.5	49.10
Metallic iron .	68.70	3-40	42.0	35.0	30.3	31.13	30.0	14-35	14-76	23.70

¹ See next page.

126 PHYSICS & CHEMISTRY OF MINING.

The ironstones referred to in the foregoing Table are the following:—

- 1. Purest hematite ore from Cumberland district.
- 2. Clay ironstone.
- 3. Black clay ironstone from coal measures.
- 4. Blackband ironstone.
- 5. Lincolnshire ore.
- 6. Fossiliferous stone from Lincoln ore.
- 7. Material found between two beds of coal near St Helens, Lancashire.
 - 8. Cockle-shell bed, above the Arley Mine.
- 9. Dark shale from cockle-bed, 67 yards above the Arley Mine. Full of shells.
 - 10. Material found under fire-clay, below yard coal.

Granite.—This rock is so called because it is readily seen to be made up of small grains, and it consists of three minerals: quartz, felspar, and mica. Quartz is almost pure silica. Felspar and mica are compounds of silica with alumina iron oxide, lime, magnesia, potash and soda. By "weathering," these constituents become disintegrated, and gradually crumble away; the quartz grains thus freed go to form sand, and the silicates of alumina, etc., from the felspar and mica, become converted into the various clays, as already described.

CHAPTER XIII.

MAGNETISM AND ELECTRICITY.

It is altogether beyond the scope of this book to presume to deal in detail with the various applications of electricity in connection with mining operations. The purpose, in adding a few notes on elementary magnetism and electricity, is to explain in as short a manner as possible the principles underlying the more important operations, and thus enable the student to more readily understand the appliances.

Magnetism and its Effects.—The natural magnet commonly known as a lodestone is one of the oxides of iron, and is, in fact, one of the purest forms in which iron ore is found. It has the power of attracting or drawing iron or steel towards itself. Further, if a small lump of lodestone be suspended by a fine string, it will turn so as to place itself in a position pointing magnetic north and south. There are objections to the use of the natural magnet in practice, and artificial magnets are made of steel bars and rods. When hard steel is rubbed with a piece of lodestone or with another magnet, or has a current of electricity passed round it by means of a coil of wire, the steel takes up magnetic properties permanently—that is, becomes magnetised.

A small strip of steel, suitably balanced on a point and magnetised, becomes a magnetic needle, and is used in a variety of ways. The end of the needle pointing north is usually marked in some way. On bringing a bar magnet to one end of this needle, the latter is either attracted or repelled, according to the "poles" which are near each other: unlike poles attract, like poles repel each other. The action of magnetism goes on through substances which are not magnetic. By holding a piece of card or stiff paper above a bar magnet, and sprinkling iron filings on the paper, the filings arrange themselves in well-marked lines, which are taken to indicate the lines of magnetic force. Although one end of a bar magnet has north-seeking magnetism, and the other south, it is impossible to break a bar so as to isolate one from the other. However small the pieces be broken, each one is still a small magnet, or is said to have polarity.

Though the magnetic needle points north and south, it is found that the direction does not quite coincide with the geographical north and south. The difference varies from time to time, and this difference is spoken of as the "declination" of the needle. Again, if a needle be balanced so as to swing vertically, and then magnetised, it is found to be no longer truly balanced, but to incline or dip downwards with its north-seeking end. This is spoken of as the "inclination" or "dip" of the magnetic needle, and (like the declination) varies from time to time. Fig. 43 illustrates a dipping needle.

Chemical Properties of the Electric Current.—When a plate of pure zinc or a plate of amalgamated zinc is dipped in dilute sulphuric acid there is no action, and similarly with a plate of copper or platinum foil; but if the portions of the metals outside the liquid be joined by a wire, bubbles of hydrogen gas begin to come off from the platinum or copper plate, and if the wires from the plates be attached to a galvanometer or current indicator, it indicates the passage of a current. The chemical energy has been transformed into electrical energy. Similar reactions take place between couples of other metals when a current of electricity, sufficiently strong, is passed through acidu-

lated water. The latter is decomposed or split up into the two gases which compose it—oxygen and hydrogen.

This effect of the current is called *electrolysis*, and takes place not only with water, but with many other solutions. The metals potassium and sodium were discovered by electrolysis, and this principle underlies many

manufacturing operations at the present day—notably the production of the wonderful metal aluminium.

The operation of electroplating is one of electrolysis, the gold or silver or nickel solution, etc. being decomposed by the current and its metal deposited on the object to be coated, the metal being supplied, as fast as deposited, by a strip of the same kind of metal, suspended in the solution, and connected to one end of the battery, the object to be plated being attached to the other end. Electrotyping is conducted on the same principles.



Fig. 43.—Dipping needle.

Magnetic Effects of a Current.—A current of electricity passing through a wire causes that wire to have magnetic properties, and if such a wire be held over a magnetic needle, the latter is deflected or turned aside, and takes up a position almost at right angles to its original one. Instruments applying this principle are used to recognise the presence of electric currents. They are called galvanometers, and consist of two needles, one above the other, the lower one surrounded by coils of insulated copper wire (copper wire is insulated by covering it with silk, cotton, or gutta-percha, so as to prevent the current leaking from one turn of wire to another). The coils of wire multiply the action of the current by induction (see p. 133), and by means of a

pointer attached to the needle-support, indicate when a current is passing through the galvanometer.

When a length of wire conveying a current is coiled round a piece of iron or mild steel, the latter becomes magnetised. On cutting off the current the magnetism at once ceases. If a hard steel has been used the magnetism remains, or becomes permanent.

Effects of Currents upon each other.—Currents passing through wires have certain effects on each other.



FIG. 44.—Solenoid.

If they run alongside of one another in the same direction, they attract one another; but if in opposite directions. repel one another.

A coil of wire wound in form of a helix, through which a current passes.

acts just like a bar magnet, and has north and south polarity, also setting itself, if free to do so, in the direction of magnetic north and south. Such a coil of wire is called a solenoid (Fig. 44).

An ordinary bar magnet held near the end of a solenoid attracts or repels it according to the poles, just as another magnet would be attracted or repelled, and one solenoid will attract or repel another solenoid.

Electro-Magnets are usually of the horse-shoe shape. in one piece, or consist of two rods joined at the ends by a strap of iron. They should be made of soft iron rods, or better, of bundles of soft iron wire. Very powerful electromagnets can be made, their strength depending, up to certain limits, upon the number of coils of wire round them, and also upon the strength of the current passing through the wire (see Figs. 45 and 46).

Use of Electro-Magnets.—The principle of the electro-magnet is applied in many ways-for instance, in electric bell construction, in the magnetic concentration of iron ores, in the construction of induction machines, etc. In the electric bell (Fig. 47), the striker is so arranged




FIG. 45.—Electro-magnet.

that a small electro-magnet attracts the rod carrying the striker towards the poles of the magnet, and in doing so cuts off the electric current automatically. The current being cut off, the electro-magnet is no longer magnetic

and the striker falls back to its original position, when contact is again made, and the process repeated. This goes on very rapidly, and causes the bell to be rung by the striker. Locks for safety lamps have been devised, which require the use of a strong magnet to unlock them. Such lamps cannot, of course, be opened without a special appliance, and are therefore very safe in that respect.



Fig. 46. - Electro-magnet.

Primary Batteries. - The batteries supplying the electrical energy for purposes of bell-ringing, signalling, telephony, and so on, depend on

132 PHYSICS & CHEMISTRY OF MINING.

chemical principles, and are generally primary batteries. We have seen that a battery or cell of a battery under simple conditions has one of its plates coated with bubbles of hydrogen gas. This gaseous layer causes a back current, and therefore tends to destroy the effect of the primary current. The main object of most of the




Fig. 47.—Electric bell.

chemical agents used in primary cells is to neutralise or destroy this hydrogen gas.

Primary Cells in common use.—The cells in most general use are either of the Leclanché (Fig. 48), Daniell, or bichromate type (Fig. 49.) In the Leclanché cell, the liquid used is a solution of sal-ammoniac, or ammonium chloride, and the agent used to destroy the hydrogen, or the depolarising agent, is peroxide of manganese. In the Daniell cell, copper sulphate is used for the same purpose, metallic copper being produced. In the bichromate cell, the depolarising agent is chromic acid, which gives up its oxygen and destroys the hydrogen.

With other cells, not often used for bell or signalling work, the depolarising agent is nitric acid (Bunsen's and Grove's cells) (Fig. 50).

Induction.—It has been shown that a coil of wire through which a current is passing, passed round an iron

or steel bar, causes the latter to become magnetised. Now the converse also applies, namely, that if a permanent magnet be pushed into a coil of wire (Fig. 51) a momentary current of electricity is produced in that wire, and further, a momentary current is also produced when the bar is withdrawn. These are spoken of as induced currents, and have many important practical applications. Though these currents are momentary or practically instantaneous, they have all the properties of ordinary currents.



Fig. 48.—Leclanché cell.

In the Induction Coil (Fig. 52), a small original primary current is built up by induction into a powerful secondary current. As shown in the illustration, the coil consists of two necessary parts—a primary coil (the thin cylinder) and a secondary coil (the outer cylinder); the illustration shows the inner coil pulled out, but when in use its position is inside the larger coil. The primary wire is only a few feet in length, while the secondary may be at least a mile in length, each layer or strand of wire being insulated from its neighbour by paraffin wax or shellac varnish. means of a "make and break" contact, like that on an electric bell, a rapid series of currents is sent along the primary wire; these induce currents in the secondary wires, and the number of coils multiplies the effect. The induced current is collected from the terminals of the secondary wires, and may be used for exploding gases or detonators, or displaying vacuum tubes, etc., and bringing about chemical decomposition.

134 PHYSICS & CHEMISTRY OF MINING.

The Principle of the Telephone.—The telephone depends for its properties upon induction. A permanent magnet has on one end of it a bobbin containing a coil of fine wire, the ends of which are connected in a closed electrical circuit. Opposite this end of the magnet is fixed a thin plate of soft iron (ferrotype). This disc or diaphragm




Fig. 49.—Bichromate or Daniell battery.

is magnetised by the current passing through the coil on the bobbin. The disc being fixed in the mouth of the telephone vibrates when spoken into, so that it moves to and fro, the movements varying with the sound which produces them. The to and fro movement causes induced currents to be set up and produce alterations in the magnetism of the permanent steel magnet, and hence currents are set up also in the coil of wire, which are transferred to the receiving end of the telephone, where similar effects are produced in the reversed order, the currents in this case causing the disc to vibrate and reproduce faithfully every sound.

Magneto - Electric Machines.—When a conductor moves in a magnetic field—that is, in an area in which lines of magnetic force are acting—currents are produced in the conductor. Upon this principle, most magneto - electric



FIG. 50.—Bunsen or Grove's cell.



FIG. 51.—Illustrating induction.

machines are constructed. These machines are used in shot firing, and are usually constructed so that a number of coils of insulated copper wire, suitably wound, are made to revolve before the poles of a powerful permanent magnet.

Dynamo Construction.—Permanent steel magnets, as used in magneto-electric machines, are supplanted by soft iron or electro-magnets. A small amount of residual magnetism, always present in the soft iron, is found to

generate a small amount of electricity in the revolving coils of wire (called the *armature*); and this induced current, acting upon the electro-magnet, increases its magnetism, and therefore increases the number of lines of force in the magnetic field. The current is thus very rapidly multiplied to a maximum, depending up to certain limits upon the speed at which the armature is revolving, upon the number of coils on the armature, and upon the intensity of the magnetic field. Such a machine is




FIG. 52.—Induction coil.

called a dynamo, and is therefore a machine for changing mechanical work into electrical energy.

In an electric motor, the electric energy derived from a dynamo is changed again into mechanical energy. A dynamo and motor are therefore the opposite of one another. In the former the armature is made to revolve by mechanical energy in a magnetic field; in the latter the magnetic field, produced by current from the dynamo, causes the armature to revolve, and be available for mechanical work.

Secondary Batteries or Accumulators.—We have seen that when a current of electricity is sent through water, the latter is decomposed into its elements hydrogen and oxygen. If these gases be collected separately in tubes containing a platinum plate or *electrode*, under certain conditions a reverse current is established, and a battery has been devised by Groves on these principles called a gas battery.

Upon these lines most secondary batteries or accumulators are constructed (Fig. 53). They all involve chemical action, and one of the commonest forms consists of leaden plates in dilute sulphuric acid. On passing a current into a cell containing two such plates, electrolysis is set up; oxygen is liberated at one plate and converts the metallic




Fig. 53.—Secondary battery accumulator.

lead into peroxide of lead; at the other plate hydrogen is liberated. After a time the current is reversed, then the lead peroxide becomes reduced by the hydrogen which is now liberated at that plate, while the other plate becomes coated with peroxide. This is carried on for some time with occasional changing of the current, and finally the plates remain, one coated with spongy lead, the other with peroxide. The spongy condition of the metal is one of the necessary features of the cell, and it is brought about by the reduction of lead peroxide. No mechanical means could prepare it in such a suitable condition. It is now found to be better to give the leaden plates a preliminary coating of lead oxide before passing the current.

The secondary cell thus produced (or series of cells forming a battery) may be charged from a dynamo, or from a primary battery, as required. The Sussman electric lamp

is an example of one mounted on a secondary battery. will maintain its lighting power for eight or nine hours, and is practically the same weight as an ordinary oil safety lamp. It is recharged as required from a dynamo.

Lighting Effect of the Electric Current.—As regards the lighting effect of the current, two forms of lamps are, broadly speaking, in general use, the incandescent and the arc. Both primary and secondary batteries are used as a source of the chemical energy, which is transformed into light in the case of the incandescent lamp. As a rule primary batteries are unsatisfactory for this purpose, and most secondary batteries have the disadvantage of No doubt this difficulty will be eventually weight. overcome.

The incandescent light is caused by the passage of a current of electricity from a primary or secondary battery, or from a dynamo, through a fine filament or thread of At one time these filaments were made from carbon. bamboo fibre, which had many imperfections and disadvantages. Many improvements have been effected, and the filament is now usually made by dissolving cellulose in chloride of zinc, which produces a semi-solid substance. This is "squirted" or forced through small holes, and in this form is very like hard white of egg in appearance. By heating this material out of contact with air a filament of carbon is left, and this is suitably mounted in a glass globe, which is then emptied of air. The resistance of this carbon thread to the passage of the current causes it to become white-hot. It is, of course, absolutely necessary that no air has access to it, otherwise the filament would burn away almost instantly. Incandescent lights are usually considered one of the safest methods of lighting in the mine, but under some conditions may be dangerous.

Messrs Couriot and Meunier (Comptes Rendus, 1898) experimented with an explosive mixture of fire-damp and air (9.5 per cent. methane) and 10-candle power lamps run with a voltage of 15 to 110 volts; no explosion could be produced provided the filament of the lamp remained unbroken. Water and carbon dioxide were produced, and only on one occasion was there explosion. On investigating this case it was found that the filament was broken, and explosion was probably caused by sparking between the ends of the broken filament. Other attempts to produce an explosion were unsuccessful.

Heise and Theim found, when experimenting with a mine gas in Westphalia (1898) with a 500-volt current, that the gaseous mixture always exploded when the glass was carefully removed and the filament exposed. When the glass was broken the gas was sometimes ignited, but not always. With arc lamps and with sparks from machines the conclusions arrived at were that all visible naked sparks are dangerous. In mines lighted by glow lamps precautions should be taken to ensure that the filament gets completely broken if the lamp-glass breaks.

The Nernst incandescent electric lamp is one in which the filament, instead of being enclosed in a vacuous flask or globe, glows in the open air. The filament consists of certain rare earths, similar to those used in the manufacture of incandescent mantles—namely, thoria These substances are what are called and zirconia. "secondary conductors," that is, they require to be heated before an electric current can be passed through them. The heating is done by heaters in the form of hollow cylinders made of kaolin, or best fire-clay, round which platinum wire is wound. When the current is first turned on it passes through the heater, which imparts its heat to the filament, until the latter is hot enough to allow of the passage of the current through it, causing incandescence. The current is then cut off automatically from the heater.

Ordinary arc lights consist of two pointed carbon rods fitted in suitable machinery whereby they are automatically kept at a certain distance from each other. The regulator of this distance is usually worked by an electro-

magnet. When the points of the rods are placed together the current meets with great resistance at these points, and makes them white-hot; on separating them slightly a brilliant light continues to be given out.

Electrical Welding.—The welding together of metals by means of electricity is a very useful application of the heating effect that the current possesses. The operation can be made use of not only with the metal iron, but with others, such as brass, copper, zinc, etc., and can be applied not only to metals of the same kind, but with others—for example, brass to tin or copper, etc.

The process can be used when ordinary methods of welding would not be possible. Thus as in the case of cracked portions of machinery, such as fly-wheel arms, etc., the cracks may be filled with filings or fine drillings, and the welding done on the spot. This is a great advantage, especially when the machinery is underground, and when, if ordinary welding had to be done, the part would have to be removed to the surface.

It would not be advantageous to erect a generating plant especially for welding purposes, but where current is already being used, say coal cutting, the necessary addition for welding purposes would not be a very serious item. As most large modern collieries are using electricity extensively, no doubt electrical welding will be more generally used before long.

Chemical Welding.—In connection with the subject of welding, it is worthy of note that a chemical method is in use which can be applied in situ also.

The principle depends upon the fact that when oxide of iron is intimately mixed with powdered or granulated aluminium, under suitable conditions a very intense chemical action takes place, which develops an enormous amount of heat. The aluminium is oxidised at the expense of the iron oxide, and the heat is the result of the chemical change.

Any portion of machinery or structural work which it is desired to weld has a suitable amount of the mixture (called thermite) placed round the part to be welded, and then fired. It is found that it is sufficient to start the chemical action at one spot only, by means of a kind of fuse, really a mixture of barium peroxide and aluminium, which is fired by a short piece of magnesium wire; once commenced, the action spreads throughout the whole mass of thermite, and raises the material which it surrounds to a welding heat. The process was devised by Goldschmidt.

APPENDIX.

I. USEFUL TABLES, ETC.

Conversion of thermometer degrees from one scale to another.

```
C.° to F.°—Multiply by 9, divide by 5, add 32.
```

F.° to C.°—Subtract 32, multiply by 5, divide by 9.

Rough estimation of temperatures—

Just glowing in the dark, about 525° C.

Dark red . . , 700° ,, Cherry red . . , 910° ,,

Bright cherry red . ,, 1000° ,, 0000° , 1160° ,, 1160° ,,

White . . , 1300° ,, Dazzling bluish white . , 1500° ,

Electric arc . . ,, 3500°,

Area of circle . = radius squared \times 3·1416 Area of square . = length of one side squared Volume of a sphere = radius cubed \times 3·1416 \times $\frac{4}{3}$ Surface of sphere . = diameter squared \times 3·1416 Volume of a cylinder = area of base \times height Volume of a cube . = length of edge, cubed One atmospheric pressure = $\begin{cases} 14.7 \text{ lbs. per square inch,} \\ \text{or 2116 lbs. per square foot} \end{cases}$

Specific gravities of common metals-

Platinum	•	21.5	Mercury			13.6
Gold	•	19.3	Lead	•	•	11.4
142						

U.	SEFUL TA	BLES, ETC.	143			
Silver .	. 10.5	Chromium .	. 7.3			
Copper .	. 8.9		6.9			
Nickel .	. 8.8		. 2.7			
Manganese.	. 8.0		. 1.75			
Iron .	. 7.8	Potassium .	86			
Tin	. 7.3					
Melting points—						
Aluminium .	700° C.	Waanaai	. 500° C.			
	11000	Magnesium	000			
Copper Gold	10059	Mercury . Nickel .	15000			
Cast iron (white)	10000	Platinum	10050			
	10000	011	0000			
Cast iron (grey) Wrought iron.	15500	m.	0000			
a. 1	10550	Zinc .	4100			
7 1	2000	Zinc .	. 412 ,,			
Lead	320 ,,					
Common name	es of chemic	al substances—				
Chemical na	me.	Common	name.			
Potassium, alumi	nium sul-	Alum.				
phate.		D1 1.11				
Copper sulphate.		Blue vitriol or blue stone.				
Iron sulphate.		Copperas or green vitriol.				
Zinc sulphate.		White vitriol.				
Mercurous chloric		Calomel.				
Mercuric chloride	•	Corrosive sublimate.				
Nitric acid.	! . !	Aqua fortis.				
Nitro-hydrochloric Phenol.	c acia.	Aqua regia. Carbolic acid.				
	. 4.	•••••••				
Magnesium sulpha Sodium or potassi		Epsom salts.				
Bisulphide of iron		Caustic soda or potash. Coal brasses, iron pyrites.				
Tin binoxide.	1.	Putty powder.				
Iron per oxide.		Rouge.				
Silver nitrate.		Lunar caustic.				
Sulphuric acid.		Oil of vitriol.				
Carphanic acidi		OII OI VILLIOII				

144 PHYSICS & CHEMISTRY OF MINING.

Chemical name.	Common name,
Ammonium chloride.	Sal-ammoniac.
Potassium nitrate.	Nitre or saltpetre.
Calcium hydrate.	Slaked lime.
Calcium oxide.	Quicklime.
Calcium sulphate.	Plaster of Paris.
Calcium carbonate.	Chalk, marble, limestone.
Sodium sulphate.	Glauber's salt.
Acetate of copper.	Verdigris.
Ammonia.	Spirits of hartshorn.
Hydrochloric acid.	Spirits of salts or muriatic acid.
Nitrous oxide.	Laughing gas.
Sodium carbonate.	Soda.
Acetic acid (dilute).	Vinegar.
Sodium chloride.	Common salt (table salt).

English equivalents of Metric System units-

- 1 Metre = 39.37 English inches.
- 1 Kilogramme (kilo) = 2.20 pounds.
- 1 Litre (1 cubic decimetre) = 1.76 pints (61.02 cubic inches).
- 1 Gramme = 15.43 grains.
 - 1 Gallon of water weighs 10 lbs. = 70,000 grains.
 - .. 224 Gallons weigh 1 ton.

Symbols and specific gravities of common gases—

Symbol.	Spec. gravity, air being 1.		
H	·06926		
CH₄	.5592		
CO_2	1.529		
CO	·9678		
H_2S	1.1748		
SO_2	2.247		
O	1.1056		
N	·9713		
	H CH ₄ CO ₂ CO H ₂ S SO ₂		

Coefficients of linear expansion between 0° and 100° C.

Brass		•	•	·00001878
Gold				.00001466
Copper				·00001718
Iron				.00001220
Steel				·00001079
Lead				·00002857
Tin				.000021730
Silver				·000019097
Zinc				.000029417

The coefficients for cubical expansion are three times those for linear.

To find the weight of a gas in lbs. per cubic foot at standard temperature and pressure, multiply half the molecular weight by 00557.

II. MISCELLANEOUS QUESTIONS.

["B. of E." denotes that the question has been given at the Board of Education Examination in Mining. Questions marked "C. M." have been set at various examinations for Colliery Manager's certificates.]

- 1. What gases are met with in mines? What are their chief properties?
 - 2. Explain the action of the siphon.
- 3. How does the gauze cylinder in a safety lamp act as a preventive of explosion?
 - 4. What is meant by gaseous diffusion?
- 5. What is black-band ironstone? How does it differ from hematite iron ore?
- 6. Explain how a siphon is sometimes used for draining a mine, and state conditions which limit its usefulness.
- 7. Describe the Clowes Hydrogen lamp, and state the amounts of fire-damp which can be recognised by it.
- 8. Three specimens of fuel A, B, and C gave when analysed the results shown in the table below. What would you call each of these fuels? Note any peculiarities of composition which strike you as likely to affect the calorific value of the fuels. (B. of E.)

		Α	В	C
Carbon .		. 36.0	44.8	39.58
Hydrogen		. 2.55	3.9	3.19
Oxygen .		. 12·16	10.6	16.35
Nitrogen		57	•6	· 4 5
Sulphur .			•7	_
Water .	•	30.79	33.9	32.26
Ash .		. 17.93	5.5	8.17
146				

- 9. State what you know concerning the manufacture of briquettes or patent fuel.
- 10. Which will diffuse the more quickly, black-damp with air, or fire-damp with air?
- 11. A mixture of fire-damp and air measures 20,000 cubic feet and contains 8 per cent. of fire-damp. How much air will have to be added so as to form a mixture which will not show a cap with an ordinary safety lamp?
- 12. A bunker for storing coal measures 20 feet long, 15 feet wide, and 10 feet deep. How much coal will this contain of specific gravity if the latter be taken as 1.3?
- 13. What reasons are there for concluding that coal dust is a most dangerous element in coal mining? State when it is most and least dangerous.
- 14. What is the composition of anthracite, cannel and bituminous coals, and of coke?
 - 15. Describe the principle of the safety lamp.
- 16. A piece of coal weighing 20.65 ounces when immersed in water weighs 4.13 ounces. What is its specific gravity and its weight per cubic foot?
- 17. Why is water such a useful medium for heating purposes?
- 18. What would be the effect upon the height of the mercury column of an ordinary barometer if taken down into a deep mine?
- 19. How can air be proved to have weight? How would you compare the relative weights of various gases?
- 20. Describe the construction and use of an ordinary mercury barometer. If water or glycerine be used instead of mercury, how is the length of the column effected? What is the advantage in using glycerine?
- 21. The tube of a thermometer has a very narrow bore, but the bulb has a large one. Why is this?
- 22. Why is mercury used in making thermometers? Is any other liquid used for this purpose? If so, why?
- 23. How can it be proved that solid liquids and gases expand when heated?

- 24. Explain how the boiling point and freezing point are determined on an ordinary thermometer, and how it is graduated.
- 25. Explain the terms "Conduction," "Convection," "Radiation" of heat, and "Specific Heat."
- 26. The specific heat of mercury is said to be .033. What does this mean?
- 27. Describe an experiment to prove that water is a bad conductor of heat.
- 28. 1 lb. of water and 1 lb. of iron are heated to the same They are then both placed on a block of ice. Which will melt most of the ice, and why?
- 20. How much fire-damp would have to be given off to foul a current of 6000 feet of fresh air per minute sufficiently to allow the presence of the gas to be detected by the flame of a safety lamp? (C. M.)
- 30. State the most important laws and principles affecting the ventilation of mines. (C. M.)
- 31. Account for rise of the air in an upcast shaft, and show the relation of the movement to the action of the siphon. (C. M.)
- 32. Describe and sketch a safety lamp suitable for a fiery mine, and able to withstand a velocity of 30 feet per second. (C. M.)
- 33. Describe, with sketches, the form of safety lamp which you consider best for use in fiery mines with a high velocity of ventilating current, also lamps with which you are acquainted for testing for small quantities of gas. (C. M.)
- 24. What explosives would you employ in a fiery mine? Give details of when and how you would use it. (C. M.)
- 35. What, in your opinion, is the best explosive now in use in coal mines? Give your reasons, stating its leading characteristics; mention any disadvantages, and say what are your views as to substitutes for explosives. (C. M.)
- 36. State what you know about the explosive properties of coal dust, and what precautions you would take in working a dry and dusty mine. (C. M.)
 - 37. When fire-damp at its most explosive point is fired,

what takes place? What are the resultant gases, in what proportions, and what are their properties? (C. M.)

- 38. Describe a method, or methods, of testing for small percentages of fire-damp, such that the presence of gas cannot be detected by the means of an ordinary safety lamp.
- 39. Name the chief constituents of pure air, and give their chemical properties. Give the chemical properties of firedamp and choke-damp, and their weights compared with atmospheric air.
- 40. What effects may coal dust produce in a mine, and how would you guard against them?
- 41. What gases are given off in a coal mine from spontaneous combustion or gob-fires, from the coal itself, from lamps, and from shot-firing? What are their properties and chemical compositions?
- 42. What do you understand by the "pitting" of boiler plates, and how is it caused?
- 43. Which is the most likely part of a working place to find fire-damp accumulating? What is the most explosive mixture of fire-damp and air? What effect has fire-damp, unmixed with air, upon the flame in a lamp?
- 44. How would you detect the presence of fire-damp, and how would you estimate the proportion of gas present? Describe how you would search for this gas in a drawing-road and in a working place. (B. of E.)
- 45. What is the effect of coal dust on the atmosphere of fiery mines, and what special precautions are required in working such mines? (B. of E.)
- 46. Describe the Clowes lamp, and state how small a percentage of fire-damp can be detected with it.
- 47. Describe the general principles of "pneumatophores," and the conditions which have to be fulfilled to make the appliances of practical use.
- 48. What is the cause of acid water in mines, and what precautions are necessary for raising it? (B. of E.)
- 49. Given the analyses of a number of samples of coalcarbon, hydrogen, oxygen, and nitrogen, calculated as per-

- centages, independently of ash, sulphur, phosphorus and moisture, and the moisture given as a percentage of the whole, how would you be able to distinguish in a general way between lignite, long-flaming bituminous coal, caking coal, semi-bituminous coal, and anthracite? (B. of E.)
- 50. Express the chemical composition of the following gases by means of the usual symbols: Carbon dioxide (carbonic acid gas), carbon monoxide (carbonic oxide), marsh gas (fire-damp), sulphuretted hydrogen. Under what circumstances may one or more of these gases occur in a mine? How can the presence of each be detected in a summary manner? What effect is produced if any one of them is allowed to accumulate in a mine in which naked lights are used? (B. of E.)
- 51. What is the composition of (a) dynamite, (b) blasting-powder? What is the essential difference between their modes of ignition? (B. of E.)
- 52. What are the two most deleterious gases most commonly met with in coal mining; their chief properties, special danger from each; in what places are they most likely to be found, and how is their presence detected? (C. M.)
- 53. What is atmospheric air? Describe its chemical composition; give weight of a cubic foot of air when temperature is 32°. Describe uses of barometer and thermometer. (C. M.)
- 54. What is the specific gravity of nitrogen gas? Describe its properties and state its effect on the oxygen of the atmosphere. (C. M.)
- 55. What is oxygen gas? State specific gravity and various properties of the gas. (C. M.)
- 56. What is carbonic acid gas? Give the different names of this gas in connection with mining, and state how it is produced. State the chemical composition of this gas, viz., by atoms and by weight. What percentage of this gas mixed with air renders it dangerous to life to breathe, and to extinguish lights? What is the specific gravity of the gas, and where is it likely to be found in mines and shafts? (C. M.)

- 57. Proto-carburetted Hydrogen.—What is this gas called in mining; what is its chemical composition, by atoms and by weight, and its specific gravity? Can it be breathed in the pure state; what percentage of this gas is required to be mixed with air to enable you to detect its presence in the flame, and what proportion of air to the gas renders the explosive force greatest? State what gases, when present, lessen the explosive force of the gas. Where would you expect to find this gas in a mine? (C. M.)
- 58. What is after-damp? What are the gases contained in this gas? Will this gas support either life or combustion? (C. M.)
- 59. What is carbonic oxide? State the composition by atoms and weight. What is the specific gravity; what effect has it on animal life; is this an inflammable gas, and does it support combustion; how is this gas produced? (C. M.)
- 60. What is spontaneous combustion, or gob-fires in a mine; how are they produced? (C. M.)
- 61. Suppose in making an examination of workings, wastes or old roads, you discovered a gas near the roof of a mine, which extinguished your lamp without exploding, what gas would this be? (C. M.)
- 62. Explain the action of the siphon, and its use and application in draining mines. (C. M.)
- 63. Describe the gases you expect to meet in a mine. (C. M.)
- 64. What part of a mine would you expect to find carbonic acid or black-damp, and how would you deal with a body of the gas? State its effects on animal life. (C. M.)
- 65. What is carbonic oxide? How is this gas produced in mines, and what effect has it on animal life? (C. M.)
- 66. State fully how you would examine a place for gas. What is the smallest proportion that will show a cap? At what proportion does it begin to explode, and what proportion will extinguish a light? (C. M.)
- 67. If the air in a mine contains enough fire-damp to show a "cap" which is only just perceptible, what additional per-

centage of gas will suffice to make the mixture highly explosive? (C. M.)

- 68. How do spontaneous fires occur in mines; how is their presence first detected? (C. M.)
- 69. State your experience with the barometer and thermometer in connection with mining. Suppose you have a mine 100 yards in depth and another 250 yards in depth; what will the difference in the reading of the two depths be? What is a thermometer, and how is the ventilation of the mine affected by the changes of this instrument? (C. M.)
- 70. What is atmospheric air? Describe its chemical composition. (C. M.) Is there any variation of this air? If so, how does it affect the ventilation of mines?
- 71. State your experience in regard to blasting in fiery and dusty mines, and in non-dusty mines. Name the explosive you have been accustomed to. What examinations are necessary before blasting in gassy and dusty mines? (C. M.)
- 72. What is the difference between furnace and fan ventilation? (C. M.)
 - 73. What is a "dynamo" and what is a "motor"? (C. M.)
- 74. In what way may danger arise from coal dust in collieries? (C. M.)
- 75. If 100 cubic inches of air weigh 31 grains Troy under a barometric pressure of 30", what will 100 cubic inches weigh at a higher altitude, where the barometer stands at 26" without any change of temperature? (C. M.)
- 76. To what extent will 2000 volumes of gas expand if the barometric pressure fall from 30.15" to 29.30"? (C. M.)
- 77. Certain mixtures of fire-damp and air explode feebly, while others again are highly explosive. How is this so? Give chemical formula for a perfect explosion. (C. M.)
- 78. A volume of air measures 30,000 cubic feet, and consists of 79 per cent. nitrogen, 20.9 per cent. oxygen, and .1 per cent. carbon dioxide. How many cubic feet of each gas is present?
- 79. Enumerate the noxious gases found in collieries, and state the composition of each. (C. M.)

INDEX.

A BSOLUTE zero, 24 Absorbents of moisture, 27 Accumulators, 136, 137 Acetylene lamps, 76 Acid in boilers, 47 - waters, 46 Acids, constitution of, 49 After-damp, 61 — CO in, 55 - CO₂ in, 56 — N in, 35 Air, amount required in burning, 120 - humidity of, 27 - estimation of moisture in, 27 - saturation of, 30, 36 - chemical properties, 31 - composition of, 31 oxygen got from, 34 - substances present in, 36 - impurities in, 37 - ammonia in, 38 - nitric acid in, 39 - ozone in, 39 - sulphur compounds in, 39 - amount breathed out, 7 supply in ventilation, 78 - and combustion, 79 - burning in coal gas, 79 - thermometer, 22 – liquid, as explosive, 93 Alum, 123 Aluminous shales, 123 Ammonal, 95 Ammonia in air, 38 — from coal, 102, 108 – sulphate of, 108 Ammonite, 92, 93 Ammonium nitrate in explosives, 87, 88, 92

Amvis, 93 Animal charcoal, 52 - test for CO, 55 Ansell's detector, 26 Anthracite, 99 and spontaneous combustion, 82 Antidote for CO poison, 54 Aqueous vapour, 36 Arc lamp, 138, 139 Ash in wood, 105 - in coal, 98, 101, 102, 106, 112 - in coke, 104 — in cannel, 100 - colour of, 112, 113 — in peat, 105 Atmosphere, 1 - weight of, I - pressure of, 2 BAROMETER, 3 - aneroid, 4 - glycerine, 4 — use of, 5 - water, 4 Batteries, primary, 131, 132 - secondary, 136, 137 Beehive oven, 103 Bellite, 92 Bichromate cell, 132 Bisulphide of carbon, 107 – of iron, 137 Bituminous coal, 99, 101

- coal and spontaneous combus-

tion, 82

— shales, 123 Black damp, 55, 58

— smoke, 102

— smoke, CO in, 54, 102 — smoke and loss of heat, 54 Blackband ironstone, 126 Blast furnace, coke in, 103 - furnace gas, CO in, 55 Blasting powder and CO, 83 Blood test for CO, 55 Blown out shot, and sound wave, 70 Bobbinite 95 Boiler scale, 46 - water, treatment of, 47 - zinc plates in, 47 Boilers, grease in, 47 - pitting of, 47 - water for, 45 Boiling-point and pressure, 12 Bone black, 52 Boyle's law, 8 - law and ventilation, 78 Breathing, products of, 57 - amount respired, 77 Bricks, refractory, 122 - silica, 122 Briquettes, 108 British thermal units, 118 Brimstone, 39 Bull-dog, special, 95 Bunsen battery, 133 Bunsen's photometer, 75

`ALCINATION, 125 Calorific value, 102, 116, 117 Calorimeter, 116, 118 Candle-power, 73 Cannel, 100 Capacity for heat, 19 Carbon, 51 — in steel, 51 — air consumed by, 120 - filament, 138 — in coal, 98 - bisulphide, 107 — in peat and wood, 105 - heating effect of, 118 — in black damp, 58 Carbon dioxide, 37, 55 - dioxide at high altitudes, 38 - dioxide in after-damp, 56 — dioxide and flame extinction, 80

- dioxide in aerated waters, 56

- dioxide in fire extincteurs, 56

- dioxide, effects of, on life, 58

- doixide, dangerous amount of, 57

- dioxide, diffusion of, 56

 dioxide in air after breathing, 57, dioxide, preparation of, 58 Carbonate of iron, 125 Carbonates, 44, 45 Carbonic oxide, 53, 54, 118 oxide, air consumed by, 120 - oxide and black smoke, 54, 102 - oxide, antidote for, 54 - oxide from gob fires, 55 - oxide in after-damp, 55 oxide in blast-furnace gas, 55 - oxide, tests for, 55 - oxide and blasting-powder, 83 - oxide, effect of, on coal dust, 83, 84 Carbonite, 95 Carburetted hydrogen, 60 Cartridges, lime, 92 Cells, 132, 133 Cellulose, 105 Centigrade degrees, 21 Charcoal, 52, 53, 105 — animal, 52 absorbent power of, 53 Charles's law, 9 - law and ventilation, 78 Chemical welding, 140, 141 Chemicals, common names of, 143 China clay, 121 Choke damp, 55 Clay ironstones, 125 Clays, 121-123 Clinker, 106, 107 Clowes' lamp, 64-66 Coal, 98 - carbon in, 98, 102 — specific gravity of, 98, 102, 110, – total carbon in, 98 bituminous, 99, 101 - flaming, 101 — caking and non-caking, 101 — splint, 101 - steam, 101 — house, 101 — firing, 101 - ash in, 98, 101, 102, 106, 112 calorific value of, 102 — tar from, 102 — ammonia from, 102, 108

— brasses, 46, 81, 107

Carbon dioxide, tests for, 58

Coal, organic sulphur in, 107 -- washing, 107 - nitrogen in, 98, 107, 108 - carbon and hydrogen in, 98 - sulphur in, 98, 114 — oxygen in, 98, 106, 119 phosphorus in, 107 dust and its action, 82 — dust, dangers of, 27 - dust, enclosed gases in, 82 - dust, explosions of, 82-85 — dust and ventilation, 83 - dust and explosives, 83 - dust and fire damp, 84 - gas, air burning in, 79 gas and air, ignition point, 71 Coefficient of expansion, 14 Coil, induction, 133 Coke, 52, 102, 113 — yield of, 98, 103 — from cannel, 100 - from slack, 103 in blast furnace, 103 and spontaneous combustion, 103 - ash, S.P. and N. in, 104 — volatile matter in, 104 Colza oil, 71 Combustion defined, 79 - spontaneous, 81 — effects of temperature on, 65 Common names of chemicals, 143 Combined water, 122 Compressed air, 97 - hydrogen, 64 – oxygen, 34 Condensers, 43 Conduction, 16 Conductors, secondary, 139 Contraction, 15 Convection, 17 Copperas, 124 Coronite, 95 Corpse light, 62 Corrosion of boilers, 47, 48 Cubical expansion, 14 Current, magnetic, effects of, 129 - primary and secondary, 133 — velocity of air, 70

Dangers of coal dust, 27 Davy lamp, size of gauze, 69 Declination, 128
Density, maximum, of water, 42
— of gases, 11
Detonators, 88
Dew point, 30
Diamond, 52
Diffusion of CO₂, 56
— of gases, 25
Dip of needle, 128
Distillation, 43
Dragonite, 95
Dust, coal, 27, 82, 84
Dynamite, 90, 91
Dynamo, 135

EARTH'S crust, 35 Elastic force of vapour, 13 Electric bell, 131 — lamps in explosive 138,139 - current, chemical properties of, 128 — firing, 88, 89 – welding, 140 Electrical ignition of lamp, 73 Electrolysis, 129, 137 Electrolytic gas as explosive, 93 Electro-magnets, 130 – plating, 129 - typing, 129 English units and metric system, Epsom salts, 45 Expansion of water, 42 cubical and linear, 14 – coefficient of, 14 Experiments with coal dust, 83 Exploder, high tension, 89 Explosion, gases produced by, 61 of coal dust, 82, 83 Explosive, liquid air as, 93 - wave transference, 84 - mixture, conditions for, 86 force of gunpowder, 90 - dynamite, 90 - mixture of fire-damp and air, - mixture, electric lamps in, 138, Explosives, chemistry of, 86 - deficient in O, 86

Explosives, properties of, 87

— high, 87, 88

— mechanical effect, 87

— classification of, 87

— Sprengel, 88

— Low, 88

— composition, preparation, and properties, 89-96

— and coal dust, 84

— permitted, 93

FAHRENHEIT degrees, 21, 24 Filament carbon, 138 Filtration, 43 Fire extinguishers, 56 Fire-damp, 60 — and coal dust, 84 - gases produced by explosion, 61 - tests for, 62, 65, 67 — action on flame, 62, 65 - dilution with air, 63 — indicators, 26, 68, 69 - action on platinum, 68 - and air, ignition point, 71 – amount of air to burn, 120 Firing, electrical, 88, 89 Firing of coal, 101 Flame, products of, 37, 57 – action of O on, 64 Flaming coals, 101 Flash-point of oils, 72 Fuels, liquid, 106 Fulminate of mercury, 88 Furnace ventilation, 78 Fuse and safety explosives, 88

GALVANIC action, 48
Galvanometer, 129
Ganister, 124
Gas, occluded, 49
— carbon, 52
— from ponds, 60
—per cent.shown by Clowes' lamp, 66
Gaseous diffusion, 25
Gases and flame extinction, 80
— effect of pressure on, 8
— effect of temperature on, 9
— density of, 11

- specific gravity of, 11, 144

Gases produced by flame, 37, 57 — enclosed in coal dust, 82 - after explosion of coal dust, 83 - produced by gunpowder, 89 - produced by breathing, 57 Gauze, purpose of, in lamp, 69 size of, for lamps, 69, 70 Gelignite, 91 Gob fires and stink damp, 77 — fires, carbonic oxide from, 55 Graduation of thermometers, 20 Granite, 126 Graphite, 52 Green vitriol, 124 Grove's cell, 133 Guncotton, 90 Gunpowder, 89, 90

Gypsum, 107

JALL'S, Mr, experiments with coal dust, 83 Hard scale, 46 Hardness of water, 44 Heat, effect on solids, 15 - produced by explosives, 87 — conduction of, 16 - specific, 19 - latent and sensible, 19, 20 - convection and radiation, 18 - reflection of, 17 - measurement of, 20 - quantity and intensity of, 20 - unit, 118 Heating effect of oils, 106 value of coal, 102 power of fuel, 116, 117 - power, calculation of, 118 - power of carbon, etc., 118, 120 Hellhoffite, 91 High explosives, 87, 88 — tension firing, 88, 89 House coal, 101 Humidity of air, 27 Hydration of lime, 92 Hydrocarbons, 60, 82, 102, 103, 113 Hydrogen, 48 — compressed, 64 — lamp, 64 — in coal, 98

— heating power of, 118 — and flame, 57, 80 Hydrogen from water, 48

— preparation and properties, 48

Hygrometer, Daniell's, 29

— Mason's, 26

I GNITION point, 71
Illuminating oils, 71
Impurities in air, 37
Incandescent lamp, 138, 139
Inclination, 128
Indicator for CH4, 68
Induction, 133
Insulation, 129
Iron carbonate, 125
— pyrites, 39, 81, 107, 124
Ironstones, 125

KIESELGUHR, 90

AMP, arc, 138, 139 - oil, 65, 72 – Clowes', 64 — Naylor's, 72 - Nernst, 139 - Sussman, 137 incandescent, 138, 139 — candle-power of, 73 - electrical ignition, 73 — experiments with, 138, 139 Lampblack, 52 Latent heat, 19 Leclanche cell, 132 Leslie's thermometer, 22 Lignite, 105 Lime cartridges, 92 — phosphate of, 52 - sulphate of, 44, 107 Limestone, 51 Lime-water test, 58 Linear expansion, 14 Liquid air, 93 - fuels, 106 List of permitted explosives, 93 Liveing's indicator, 68 Local action, 47 Locks, magnetic, 131 Lodestone, 127

Low explosives, 88 Low-tension firing, 88, 89

MACKIE'S indicator, 68 Magnesium sulphate, 45 – chloride, 46 Magnet, natural, 127 polarity of, 128 – electro-, 130 Magnetic oxide of iron, 42 — needle, 127 — attraction, 128 - effects of current, 129 — locks, 131 - field, 135 Magnetism, permanent, 130 Magneto-electric machine, 135 Marsaut lamp gauze, 70 Marsh gas, 60 gas, amount of air to burn, 120 Mason's hygrometer, 26 Maximum density of water, 42 - thermometer, 22 Measurement of heat, 20 Melting-points, 143 Mercury, specific heat, 19 - uses of, 20 – fulminate, 88 Metals, action of water, 42 - rusting of, 35 - specific gravity of, 142 Meteorites, 49 Methane, 60, 62 Mineral matter, 98-104 Minimum thermometer, 22 Moisture absorbents, 27 estimation of, 27 — in coal, 98, 111 - in peat and wood, 105 Motive column, 78 Motor, 135 Mueseler lamp gauze, 70

Naylor's lamp, 72 Naylor's lamp, 72 Negro powder, 95 Nernst lamp, 139 Nitrogen, properties of, 35 — in after-damp, 35, 61 Nitrogen in compressed O, 97
— in coal, 98, 107, 108
— in coke, 104
— and flame, 80
Nitro-cellulose, 87, 88
Nitro-glycerine, 86, 87, 91
Nobel-Ardeer powder, 95
Non-caking coals, 101

CCLUSION of gas, 49 Ochrey waters, 46 Oil for lamps, 65 Oil of vitriol, 40 Oils, heating effect of, 106 - sulphur in, 106 — shale, 124 - illuminating, 71 - flash-point of, 72 - petroleum, 51 Organic sulphur in coal, 107 Oxidising agents, 86, 87 Oxygen, preparation and properties, 33, 34 — from air, 34 — solubility in water, 35 deficiency in explosives, 86 - compressed, N in, 34, 97 - in coal, 98, 106, 119 - in pneumatophores, 96 - action of, on flame, 64 Ozone in air, 39

PAINT, blackening of, 76 Peat, 105 Permanent hardness, 44 — magnetism, 130 Permitite, 95 Permitted explosives, 93 Petrifaction, 45 Petroleum oils, 51 Phosphate of lime, 52 Phosphorus in coal, 107 - in coke, 104 - in peat, 105 Photometers, 74, 75 Photosphere of sun, 49 Pieler lamp, 68 Plants, effect on air, 37 Plasticity of clays, 122

Platinum, action of CH₄ on, 68
Pneumatophores, 34, 96, 97
Poison valley, 57
Poisonous action of white damp, 53
Polarity of magnets, 128
Powder, smokeless, 92
Pressure, ventilating, 78, 79
Primary batteries, 131
— current, 133
Priming, 89
Pure water, 43
Pyrites, iron, 81, 107, 124

RACK-A-ROCK, 91
Radiation, 17
Rain water, 43
Rates of explosion, 90
Reaumur scale, 21
Reflection of heat, 17
Refractory materials, 123
Respiration, air used in, 77
River water, 43
Roburite, 91, 95
Rocks, weathering of, 121, 126
Rumford's photometer, 74
Rusting of metals, 35
Ryhope Colliery, dust at, 82

SAFETY explosives and fuse, 88 Safety-lamp gauze, 69 Saturation of air, 30, 36 Scale, boiler, 46 Secondary batteries, 136, 137 current, 133 – conductors, 139 Semet-Solvay, 102, 103 Shale oils, 124 Shales, 121, 123 Silica brick, 122 Silicates, 121 Silver, tarnishing of, 76 Siphon, 5 Skelmersdale, experiments at, 83 Slack, coke from, 103 Smoke, black, 102 - production, 101 Smokeless powder, 92 Solenoid, 130 Solids in water, 13, 43, 46

Sound wave from shot, 70 Special bull-dog, 96 Specific gravity of coal, 98, 102, 110, 111 gravity of gases, 11, 144 - gravity of metals, 142 – heat, 19 Splint coals, 101 Spontaneous combustion, 81 – and ventilation, 77 - and various coals, 82 - and coke, 103 - and coal brasses, 81 Spring waters, 45 Sprengel explosives, 88 Stalactite, stalagmite, 45 Standard temp. and pressure, 11 Steam, decomposition of, 42 - coals, 101 - raising coke for, 103 Steel, carbon in, 51 Stink damp, 76, 77 Stythe, 55, 58 Sublimation, 40 Sulphate of lime, 44 - of magnesia, 45 — of alumina, 107 — of ammonia, 108 - of lime, 107 — of barium, 114, 115 Sulphides, 39 Sulphur in coal, 98, 102, 104, 107, — in coke, 104 - in oils, 106 — compounds in air, 39 — forms of, in coal, 107 - air required by, 120 — dioxide, 39 Sulphuretted hydrogen, 76 Sulphuric acid, 40, 107 — in boilers, 47

TARNISHING of silver, 76
Telephone, principle of, 134
Temperature and combustion, 65
Temperatures, estimation of, 142
Temporary hardness, 44
Tension of vapour, 13

Sun's photosphere, 49

Susmann lamp, 137

Thermal units, 118
Thermite, 141
Thermometers, 20, 22
Time fuse, 88
Tonite, 91
Total carbon in coal, 98
Tuning-fork test, 69

ULTIMATE analysis of coal, 98
Useful tables, 142

[7 ALUATION of coal, 98 Vapour, aqueous, 26 - tension, 13 Velocity of air current, 70 Ventilation, need for, 77 - and coal dust, 83 - by furnace, 79 - and spontaneous combustion, 77 - volume of air supply, 78 — and Boyle's law, 78 – and Charles's law, 78 Ventilating pressure, 78 Vitriol, 40 Vitriol, green, 124 Volatile matter and firing, 101 hydrocarbons, 102, 103, 113 Volume of air-supply, 79

X/ASHING of coal, 107 Waste gases in coking, 102 Water, combined, 122 - gauge, 78, 79 — solids in, 13, 43 — heating efficiency of, 19 — expansion of, 42 — rain, 43 - suspended matter in, 43 — river, 43 solids dissolved by, 43 — action of, on carbonates, 44, 45 — hardness of, 44 spring, 45 — iron in, 45 - manganese in, 45 - for boilers, 45 - peaty, 46 - acid. 46

Water, ochrey, 46
— treatment of, 46

- treatment of, 40
- softened, 47
- hydrogen from, 48
- composition of, 41, 42
- action of metals on, 42
Weathering action, 121, 126
Welding, chemical, 140, 141

Welding, electrical, 140 Westphalite, 92, 95 White damp, 53 Wood, 105

ZERO, absolute, 24 Zinc in boilers, 47

CROSBY LOCKWOOD & SON'S Catalogue of Scientific, Technical and Industrial Books.

PAGE	PAGE
MECHANICAL ENGINEERING . 1	OARPENTRY & TIMBER 29
CIVIL ENGINEERING 10	DECORATIVE ARTS 81
MARINE ENGINEERING, &c 17	NATURAL SCIENCE 88
MINING & METALLURGY 19	CHEMICAL MANUFACTURES . 84
COLLIERY WORKING, &c 21	INDUSTRIAL ARTS 86
ELECTRICITY 28	COMMERCE, TABLES, &c 41
ARCHITECTURE & BUILDING . 26	AGRICULTURE & GARDENING . 48
SANITATION & WATER SUPPLY 28	AUCTIONEERING, VALUING, &c. 46
	ANEOUS 47

MECHANICAL ENGINEERING, ETC.

THE MECHANICAL ENGINEER'S POCKET-BOOK.

Comprising Tables, Formulæ, Rules, and Data: A Handy Book of Reference for Daily Use in Engineering Practice. By D. KINNEAR CLARK, M. Inst. C.E., Fifth Edition, thoroughly Revised and Enlarged. By H. H. P. Powles, A. M.I C.E., M.I.M.E. Small 8vo, 700 pp., bound in flexible Leather Cover, rounded corners.

[Just Published. Net 6/0]

TOUNDED COTHERS.

SUMMARY OF CONTENTS:—MATHEMATICAL TABLES.—MASSUREMENT OF SURFACES AND SOLIDS.—ENGLISH WEIGHTS AND MEASURES.—FRENCH METRIC WEIGHTS AND MEASURES.—FRENCH METRIC WEIGHTS AND MEASURES.—BONDEYS.—SPECIFIC GRAVITY, WEIGHT, AND VOLUME.—MANUFACTURED METALS.—STEEL FIPES.—BOLTS AND NUTS.—SUNDRY ARTICLES IN WOUGHT AND CAST IRON, COPPER, BRASS, LEAD, TIN, ZINC.—STERINGTH OF MATERIALS.—STRENGTH OF TIMBER.—STRENGTH OF COPPER, LEAD, &C. PRESISTANCE OF STONES AND OTHER BUILDING MATERIALS.—RIVETED JOINTS IN BOILER PLATES.—BOLLER SHELLS.—WIRE ROPES AND HEMP ROPES.—CHAINS AND CHAIN CABLES.—FRANMING.—HARDINES OF METALS, ALLOYS, AND STONES.—CHAINS AND CHAIN CABLES.—FRANMING—HARDINES OF METALS, ALLOYS, AND STONES.—ACCELERATING MOR RETARADING FOR SHAPTING, &C. —TERNSISSION OF MOTIVE POWER.—HEAT.—COMBUSTION: FUELS.—WARMING, VENTILATION, COOKING STOVES.—STEAM.—STEAM BRICHES AND BOILERS.—RAILWAYS.—TRAMWAYS.—STEAM SHIPS.—FUMPING STEAM ENGINES AND PUMPS.—COAL GAS, GAS ENGINES, &C.—AIR IN MOTION.—COMPRESSED AIR.—HOT AIR HEIGHISS.—WATER POWER.—STEED OF CUTTING TOOLS.—COLOURS.—ELECTRICAL ENGINEERING.

"Mr. Clark manifests what is an innate perception of what is likely to be useful in a dockse-

"Mr. Clark manifests what is an innate perception of what is likely to be useful in a pocketbook, and he is really unrivalled in the art of condensation. It is very difficult to hit upon any sechanical engineering subject concerning which this work supplies no information, and the excellent index at the end adds to its utility. In one word, it is an exceedingly handy and efficient tool, possessed of which the engineer will be saved many a wearisome calculation, or yet more weerisoms hunt through various text-books and treatises, and, as such, we can heartily recommend it to our readers."—The Engineer.

"It would be found difficult to compress more matter within a similar compass, or produce a book of 700 pages which should be more compact or convenient for pocket reference. . . . Will be appreciated by mechanical engineers of all classes."—*Practical Engineers*.

MR. HUTTON'S PRACTICAL HANDBOOKS.

THE WORKS' MANAGER'S HANDBOOK.

Comprising Modern Rules, Tables, and Data. For Engineers, Millwrights, and Boiler Makers; Tool Makers, Machinists, and Metal Workers; Iron and Brass Founders, &c. By W. S. HUTTON, Civil and Mechanical Engineer, Author of "The Practical Engineer's Handbook." Sixth Edition, carfelly Revised, and Enlarged. In One handsome Volume, medium 8vo, strongly bound

The Author having compiled Rules and Data for his own use in a great wariety of modern engineering work, and having found his notes extremely useful, decided to publish them—revised to date—believing that a practical work, suited to the DAILY REQUIREMENTS OF MODERN ENGINEERS, would be favourably received.

"The auther treats every subject from the point of view of one who has collected workshop notes for application in workshop practice, rather than from the theoretical or literary aspect. The volumes contains a great deal of that kind of information which is gained only by practical experience, and is seldom written in books."—The Engineer, June 5, 1882, and is seldom written in books."—The Engineer, June 5, 1882, and the first experience of this edition we may repeat the appreciative remarks we made upon the first and third. Since by this edition we may repeat the appreciative remarks we made upon the first and third. Since by the experience of the experience of the total number of pages remains after expressions after the second of the experience of the total number of pages remains after experience. The first states in the workshop and drawing office data."—The Engineer, May 10, 1895. (Second Notice).

"The volume is an exceedingly useful one, brimful with angineers nets, memoranda, and rules, and well worthy of being on every mechanical engineers' bookshelf."—Machanical World.

"The Information is precisely that Ilkely to be required in practice. . . . The work forms a desirable addition to the library not only of the works' manager, but of any one connected with general engineering."—Mining Journal.

"Brimful of useful information, stated in a concise form, Mr. Hutton's books have met a pressing want among engineers. The book must prove extremely useful to every practical man possessing a copy."—Practical Engineer.

THE PRACTICAL ENGINEER'S HANDBOOK.

Comprising a Treatise on Modern Engines and Boilers, Marine, Locomotive, and Stationary. And containing a large collection of Rules and Practical Data relating to Recent Practice in Designing and Constructing all kinds of Engines, Roilers, and other Engineering work. The whole constituting a comprehensive Key to the Board of Trade and other Examinations for Certificates of Competency in Modern Mechanical Engineering. By WALTER S. HUTTON, Civil and Mechanical Engineer, Author of "The Works' Manager's Handbook for Engineers." &c. With upwards of 420 Illustrations. Sixth Edition. Revised and Enlarged. Medium 8vo, nearly 560 pp., strongly bound. 18/0

This Work is designed as a companion to the Author's "Works' MANGER'S HANDROOK." It possesses many new and original features, and contains, like its predecessor, a quantity of matter not originally intended for publication but collected by the Author for his own use in the construction of a great variety of MODERN ENGINEERING WORK.

The information is given in a condensed and concise form, and is illustrated by upwards of 420 Engravings: and comprises a quantity of tabulated matter of great value to all engaged in designing, constructing, or estimating for Emolines, Boilers, and OTHER ENGINEERING WORK.

"We have kept it at hand for several weeks, referring to it as occasion arose, and we have not on a single occasion consulted its pages without finding the information of which we were in quest."

on a single occasion consumer.

Alternation.

"A thoroughly good practical handbook, which no engineer can go through without learning "A thoroughly good practical handbook, which no engineer can go through without learning something that will be of service to him."—Marine Engineer.

"An excellent book of reference for engineers, and a valuable text-book for students of

engineering."—Scotiman.
"This valuable manual embodies the results and experience of the leading authorities on

"This valuable manual embodies the results and experience of the leading authorities on mechanical engineering."—Building News.

"The author has collected together a surprising quantity of rules and practical data, and has shown much judgment in the selections he has made.

"A mass of information set down in simple language, and in such a form that it can be seen."

"A mass of information set down in simple language, and in such a form that it can be seen."

"A mass of information set down in simple language, and in such a form that it can be seen."

"A mass of information set down in simple language, and in such a form that it can be seen."

"A mass of information in the seen."—Practical Engineers shelves, where it will rank as one of the most useful books of reference."—Practical Engineers.

"Full of useful information, and should be found on the office shelf of all practical engineers

—English Michanic.

MR. HUTTON'S PRACTICAL HANDBOOKS-continued.

STEAM BOILER CONSTRUCTION.

A Practical Handbook for Engineers, Boiler-Makers, and Steam Users. Containing a large Collection of Rules and Data relating to Recent Practice in the Design, Construction, and Working of all Kinds of Stationary, Locomotive, and Marine Steam-Boilers. By WALTER S. HUTTON, Civil and Mechanical Engineer, Author of "The Works' Manager's Handbook," "The Practical Engineer's Handbook," &c. With upwards of 500 Illustrations. Fourth Edition, carefully Revised, and Enlarged. Medium 8vo, over 680 pages, cloth strongly bound [Just Published. 18/0 cloth, strongly bound.

THIS WORK is issued in continuation of the Series of Handbooks written by the Author, vis.:—"The Works' Manager's Handbook" and "The Practical Engineer's Handbook," which are so highly appreciated by engineers for the practical nature of their information; and is consequently written in the same style as those works.

The Author believes that the concentration, in a convenient form for easy reference, of such a large amount of thoroughly practical information on Steam-Boilers, will be of considerable service to those for whom it is intended, and he trusts the book may be deemed worthy of as favourable a reception as has been accorded to its bredecessors.

"One of the best, if not the best, books on boilers that has ever been published. The information is of the right kind, in a simple and accessible form. So far as generation is concerned, this ks, undoubtedly, the standard book on steam practice."—Blackrical Review.

"Every detail, both in boiler design and management, is clearly laid before the reader. The volume shows that boiler construction has been reduced to the condition of one of the most exact scleance; and such a book is of the umost value to the fin de stitcle Engineer and Works Manager."

aciences; and such a book is or the unnow value to the property of the propert

PRACTICAL MECHANICS' WORKSHOP COMPANION.

Comprising a great variety of the most useful Rules and Formulæ in Mechanical Science, with numerous Tables of Practical Data and Calculated Results for Facilitating Mechanical Operations. By WILLIAM TEMPLETON, Author of "The Engineer's Practical Assistant," &c., &c. Eighteenth Edition, Revised, Modernised, and considerably Enlarged by WALTER S. HUTTON, C.E., Author of "The Works' Manager's Handbook," "The Practical Engineer's Handbook," &c. Fcap, 8vo, nearly 500 pp., with 8 Plates and upwards of 250 Illustrative Diagrams, strongly bound for workshop or pocket wear and tear. 6/0

"In last modernised form Hutton's 'Templeton' should have a wide sale, for it contains much valuable information which the mechanic will often find of use, and not a few tables and notes which emight look for in vain in other works. This modernised edition will be appreciated by all who have learned to value the original editions of 'Templeton.'"—*English Mechanic*.

"It has met with great success in the engineering workshop, as we can testify; and there are a great many men who, in a great measure, owe their rise in life to this little book."—*Building News*.

a great many men who, in a great many men who is a mental service to the every-day requirements of engineers, milwrights, and the various trades connected with engineering and building. The new modernised edition is worth its weight in gold."—Building News. (Second Notice.)

"This well-known and largely-used book contains information, brought up to date, of the mental information has been introduced as

"This well-known and largely-used book contains information, brought up to date, of the sort so useful to the foreman and draughtsman. So much fresh information has been introduced as to constitute it practically a new book. It will be largely used in the office and workshop."—

Machanical World.

"The publishers wisely entrusted the task of revision of this popular, valuable, and useful book to Mr. Hutton, than whom a more competent man they could not have found."—Iron.

ENGINEER'S AND MILLWRIGHT'S ASSISTANT.

A Collection of Useful Tables, Rules, and Data. By WILLIAM TEMPLETON Eighth Edition, with Additions. 18mo, cloth 2/6

"Occupies a foremost place among books of this kind. A more suitable present to an apprentice to any of the mechanical trades could not possibly be made."—Building News.

"A deservedly popular work. It should be in the 'drawer' of every mechanic."—Bnglish

THE MECHANICAL ENGINEER'S REFERENCE BOOK.

For Machine and Boiler Construction. In Two Parts.

ENGINEERING DATA. Part II. BOILER CONSTRUCTION.

With 51 Plates and numerous Illustrations. By Nelson Folley, M.I.N.A. Second Edition, Revised throughout and much Enlarged. Folio, half-bound. Net 23 &.

PART I.—MEASURES.—CIRCUMPRERINCES AND AREAS, &c., SQUARES, CUERS, FOURTH POWERS.—SQUARE AND CUBE ROOTS.—SURFACE OF TURES.—RECIPROCALS.—LOGARITHMS.—MENSURATION.—EXPANSION AND CONTRACTION.—EXPANSION OF POWER.—HEAT.—COMBUSTION.—EXPANSION AND CONTRACTION.—EXPANSION OF GASES.—STRALL—STATIC FORCES.—GRAVITATION AND ATTRACTION.—EXPANSION OF GASES.—STRALL—STATIC FORCES.—GRAVITATION AND ATTRACTION.—MOTION AND STRENGTH OF MATERIALS.—ELASTICITY.—TEST SHEETS OF METALS.—FRICTION.—TRANSMISSION OF FOWER.—FLOW OF LIQUIDS.—FLOW OF GASES.—AIR PUMPS, SURFACE CONDENSERS, &c.—SPEED OF STREMSHIPS.—PROPELLERS.—CUTTING TOOLS.—FLANGES—COPPER SHEETS AND TURES.—SCREWS, NUTS, BOLT HEADS, &c.—VARIOUS RECIPROMED MATTER.—WITH DIAGRAMS FOR VALVE-GAR, BELTING AND ROPES, DISCHARGE AND SUCTION PIPES, SCREW PROPELLERS, AND COPPER PIPES.

PART II.—TREATING OF POWER OF BOILERS.—USEFUL RATIOS.—NOTES ON CONSTRUCTION.—CYLINDRICAL BOILER SHELLS.—CIRCULAR FURNACES.—FLAT PLATES.—STAYS.—GIRDERS.—SCREWS.—HYPRAULIC TESTS.—RIVETING. BOILER SETTING, CHIMNEYS, AND MOUNTINGS.—FUELS, &c.—EXAMPLES OF BOILERS AND SPEEDS OF STEAMSHIPS.—NOMINAL AND NORMAL HORSE POWER.—WITH DIAGRAMS FOR ALL BOILER CALCULATIONS AND DRAWINGS OF MANY VARIETIES OF BOILERS.

"Mr. Foley is well fitted to compile such a work. The diagrams are a great feature of the work. It may be stated that Mr. Foley has produced a volume which will undoubtedly fulfil the desire of the author and become indispensable to all mechanical engineers."—Morine Engineer.

"We have carefully examined this work, and pronounce it a most excellent refe for the use of marine engineers."— Journal of American Society of Naval Engineers.

TEXT-BOOK ON THE STEAM ENGINE.

With a Supplement on Gas Engines and Part II. on Heat Engines. By T. M. GOODEVE, M.A., Barrister-at-Law, Professor of Mechanics, at the Royal College of Science, London; Author of "The Principles of Mechanics," "The Elements of Mechanism," &c. Fourteenth Edition. Crown 8vo, cloth . 6/O

"Professor Goodeve has given us a treatise on the steam engine, which will bear compassion with anything written by Huxley or Maxwell, and we can award it no higher praise."—*Engineer*. "Mr. Goodeve's text-book is a work of which every young engineer should possess himself."

—Mining Yournal.

ON GAS ENGINES.

"Like all Mr. Goodeve's writings, the present is no exception in point of general excellence. It is a valuable little volume,"—Mechanical World.

GAS AND OIL ENGINE MANAGEMENT.

A Practical Guide for Users and Attendants, being Notes on Selection, Construction, and Management. By M. Powis Bale, M. I. M. E., A. M. I. C. E. Author of "Woodworking Machinery," &c. Crown 8vo, cloth. Uust Published. Net 3/6

THE GAS-ENGINE HANDBOOK.

A Manual of Useful Information for the Designer and the Engineer. By E. W.

A TREATISE ON STEAM BOILERS.

Their Strength, Construction, and Economical Working. By R. WILSON, C.E. Fifth Edition. 12mo, cloth 6/0 "The best treatise that has ever been published on steam boilers."—Engineer,

THE MECHANICAL ENGINEER'S COMPANION.

Of Areas, Circumferences, Decimal Equivalents, in inches and feet, millimetres, squares, cubes, roots, &c.; Strength of Bolts, Weight of Iron, &c.; Weights, Measures, and other Data. Also Practical Rules for Engine Proportions. By R. Edwards, M. Inst. C.E. Fcap. 8vo, cloth.

"A very useful little volume. It contains many tables, classified data and memoranda generally useful to engineers."—Engineers.

"What it professes to be, 'a handy office companion, giving in a succinct form a variety of information littly to be required by mechanical engineers in their everyday office work."—Nessers.

A HANDBOOK ON THE STEAM ENGINE.

With especial Reference to Small and Medium-sized Engines. For the Cook Engine Makers, Mechanical Draughtsmen, Engineering Students, and users of Steam Power. By Herman Haeder, C.E. Translated from the German with additions and alterations, by H. H. P. Powles, A.M.I.C.E., M.I.M.E. Third Edition, Revised. With nearly 1,100 Illustrations. Crown 8vo, Net 7/6

"A perfect encyclopædia of the steam engine and its details, and one which must take a permanent place in English drawing-offices and workshops."—A Foreman Pattern-maker.

"This is an excellent book, and should be in the hands of all who are interested in the construction and design of medium-sized stationary engines. . . A careful study of its contents and the arrangement of the sections leads to the conclusion that there is probably no other book like it in this country. The volume aims at showing the results of practical experience, and it certainly may claim a complete achievement of this idea."—Nature.

"There can be no question as to its value. We cordially commend it to all concerned in the design and construction of the steam engine."—Mechanical World.

BOILER AND FACTORY CHIMNEYS.

Their Draught-Power and Stability. With a chapter on Lightning Conductors, By ROBERT WILSON, A.I.C.E., Author of "A Treatise on Steam Boilers," &c. . 3/6 Crown 8vo, cloth

"A valuable contribution to the literature of scientific building."-The Builder,

BOILER MAKER'S READY RECKONER & ASSISTANT.

With Examples of Practical Geometry and Templating, for the Use of Platers, Smiths, and Riveters. By JOHN COURTNEY, Edited by D. K. CLAKK, M.I.C.E. Fourth Edition, 480 pp., with 140 Illustrations. Fcap. 7/0

"No workman or apprentice should be without this book,"-Iron Trade Circular,

REFRIGERATION, COLD STORAGE, & ICE-MAKING:

A Practical Treatise on the Art and Science of Refrigeration. By A. J. WALLIS-TAYLER, A.M. Inst. C. E., Author of "Refrigerating and Ice-Making Machinery." 600 pp., with 360 Illustrations. Medium 8vo, cloth. Net 15/0

"The author has to be congratulated on the completion and production of such an important work and it cannot fail to have a large body of readers, for it leaves out nothing that would in any way be of value to those interested in the subject." "Steamship." No one whose duty it is to handle the mammoth preserving installations of these latter days can afford to be without this valuable book." "Glasgow Hevald."

THE POCKET BOOK OF REFRIGERATION AND ICE-

By A. J. WALLIS-TAYLER, A.M. Inst. C.E. Author of "Refrigerating and Ice-making Machinery," &c. Third Edition, Enlarged. Small Crown 8vo, cloth. [Just Published. Net 3/6

REFRIGERATING & ICE-MAKING MACHINERY.

A Descriptive Treatise for the Use of Persons Employing Refrigerating and Ice-Making Installations, and others. By A. J. Wallis-Tayler, A.-M. Inst. C.E. Third Edition, Enlarged. Crown 8vo, cloth 7/6

"Practical explicit, and profusely illustrated."—Glasgrow Heraid.
"We recommend the book, which gives the cost of various systems and illustrations showing details of parts of machinery and general arrangements of complete installations."—Builder.

May be recommended as a useful description of the machinery, the processes, and of the facts, figures, and tabulated physics of refrigerating. It is one of the best compilations on the subject.—Engineer.

ENGINEERING ESTIMATES, COSTS, AND ACCOUNTS.

"This is an excellent and very useful book, covering subject-matter in constant requisition in every factory and workshop. . . The book is invaluable, not only to the young engineer, but also to the estimate department of every works." —Builder.
"We accord the work unqualified praise. The information is given in a plain, straightforward manner, and bears throughout evidence of the intimate practical acquaintance of the author with every phase of commercial engineering."—Buchanical World.

THE MECHANICAL HANDLING OF MATERIALS.

A Comprehensive Treatise on Lifting and Conveying Machinery and Appliances. By G. F. ZIMMER, Consulting Engineer. Super Royal 8vo, with over 200 Illustrations.

[In the Press. Price about 25/0 net.]

HOISTING MACHINERY.

An Elementary Treatise on. Including the Elements of Crane Construction and Descriptions of the Various Types of Cranes in Use. By JOSEPH HORNER, A.M. I.M.E., Author of "Pattern-Making," and other Works. Crown 8vo, with 215 Illustrations, including Folding Plates, cloth. Net 7/6

AËRIAL OR WIRE-ROPE TRAMWAYS.

Their Construction and Management. By A. J. WALLIS-TAYLER, A.M. Inst. C.B. With 81 Illustrations. Crown 8vo, cloth . "An excellent volume, an 1 a very good exposition of the various systems of rope transmission in use, and gives as well not a little valuable information about their working, repair, and manage nent We can safely recommend it as a useful general treatise on the subject."—Engineer.

MOTOR CARS OR POWER-CARRIAGES FOR COMMON ROADS.

By A. J. WALLIS-TAYLER, A.M. Inst. C.E. 212 pp., with 76 Illustrations. Crown 8vo, cloth "A work that an engineer thinking of turning his attention to motor-carriage work, would do well to read as a preliminary to starting operations,"—Engineering.

PLATING AND BOILER MAKING.

A Practical Handbook for Workshop Operations. By JOSEPH G. HORNER, A.M.I.M.E. 380 pp. with 338 Illustrations. Crown 8vo, cloth . . 7/6

"This work is characterised by that evidence of close acquaintance with workshop methods which white render the book exceedingly acceptable to the practical hand. We have no hesitation in commending the work as a serviceable and practical bandbook on a subject which has not hitherto received much attention from those qualified to deal with it in a satisfactory manner."—Mechanical World.

PATTERN MAKING.

Embracing the Main Types of Engineering Construction, and including Gearing, Engine Work, Sheaves and Pulleys, Pipes and Columns, Screws, Machine Parts, Pumps and Cocks, the Moulding of Patterns in Loam and Greensand, Weight of Castings, &c. By J. G. HORNER, A.M.I.M.E. Third Edition, Enlarged. With 486 Illustrations. Crown 8vo, cloth. Net 7/8

"A well-written technical guide, evidently written by a man who understands and hasy citied what he has written about. . . We cordully recommend it to engineering students, young journeymen, and others desirous of being initiated into the mysteries of pattern-making."—Builder.

"An excellent vade mecum for the apprentice who desires to become master of his trade."

-English Mechanic.

MECHANICAL ENGINEERING TERMS

(Lockwood's Dictionary of). Embracing those current in the Drawing Office,

"Just the sort of handy dictionary required by the various trades engaged in mechanical enine-ring. The practical engineering pupil will find the book of great value in his studies, and every
foreman engineer and mechanic should have a copy."—Building News.

TOOTHED GEARING.

A Practical Handbook for Offices and Workshops. By J. HORNER, A.M.I.M.E. Second Edition, with a new Chapter on Recent Practice. With 184 Illustrations. Crown 8vo, cloth. tions. Crown 8vo, cloth.

"We give the book our unqualified praise for its thoroughness of treatment, and recommend it to all interested as the most practical book on the subject yet written."—Mechanical World.

FIRES, FIRE-ENGINES, AND FIRE BRIGADES.

With a History of Fire-Engines, their Construction, Use, and Management; Foreign Fire Systems; Hints on Fire-Brigades, &c. By C. F. T. YOUNG, C.E. 8vo, cloth . £1 4s.

"To such of our readers as are interested in the subject of fires and fire apparatus we can most heartily commend this book."—Engineering.

AËRIAL NAVIGATION.

RIAL NAVIGATION.

A Practical Handbook on the Construction of Dirigible Balloons, Aërostats, Aëroplanes, and Aëromotors. By FREDERICK WALKER, C.E., Associate Member of the Aëronautic Institute. With 104 Illustrations. Large Crown New 7/6

STONE-WORKING MACHINERY.

A Manual dealing with the Rapid and Economical Conversion of Stone. With Hints on the Arrangement and Management of Stone Works. By M. Powis BALE, M.I.M.E. Second Edition, enlarged. Crown 8vo, cloth . "The book should be in the hands of every mason or student of stonework."-Celliery

"A capital handbook for all who manipulate stone for building or ornamental purposes."—

Machinery Marks.

PUMPS AND PUMPING.

A Handbook for Pump Users. Being Notes on Selection, Construction, and Management. By M. Powis Bale, M.I.M.E. Fourth Edition. Crown 8vo, cloth . . 3/6

"The matter is set forth as concisely as possible. In fact, condensation rather than diffuseness has been the author's aim throughout; yet he does not seem to have omitted anything likely to be of use, "-Journal of Gas Lighting."
"Thoroughly practical and clearly written."—Glasgow Herald.

MILLING MACHINES AND PROCESSES.

A Practical Treatise on Shaping Metals by Rotary Cutters. Including Information on Making and Grinding the Cutters. By PAUL N. HASLUCK, Author of "Lathe-Work." With upwards of 300 Engravings. Large crown 8vo, . 12/6

"A new departure in engineering literature. . . . We can recommend this work to all interested in milling machines; it is what it professes to be—a practical treatise."—*Engineer*.

"A capital and reliable book which will no doubt be of considerable service both to those who are already acquainted with the process as well as to those who contemplate its adoption."—

Industries.

LATHE-WORK.

A Practical Treatise on the Tools, Appliances, and Processes employed in the Art of Turning. By PAUL N. HASLUCK. Eighth Edition. Crown 8vo,

"Written by a man who knows not only how work ought to be done, but who also knows how it, and how to convey his knowledge to others. To all turners this book would be valuable."—

to the state of the student it will convey a great deal of useful information."—*Engineer*.

SCREW-THREADS,

And Methods of Producing Them. With numerous Tables and complete Directions for using Screw-Cutting Lathes. By PAUL N. HASLUCK, Author of "Lathe-Work," &c. Sixth Edition. Waistcoat-pocket size 1/6

"Full of useful information, hints and practical criticism. Taps, dies, and screwing tools generally are illustrated and their action described."—Mechanical World.

"It is a complete compendium of all the details of the screw-cutting lathe; in fact, a multium-im-parse on all the subjects it treats upon."—Carpenter and Builder.

TABLES AND MEMORANDA FOR ENGINEERS, MECHANICS, ARCHITECTS, BUILDERS, &c.

Selected and Arranged by Francis Smith. Seventh Edition, Revised, including ELECTRICAL TABLES, FORMULÆ, and MEMORANDA. Waistcoat-pocket size, limp leather. [Just Published. 1/6

"It would, perhaps, be as difficult to make a small pocket-book selection of notes and formulae to sult ALL engineers as it would be to make a universal medicine; but Mr. Smith's waistcoatten by the booked upon as a successful attempt. "Engineer." Engineer.

"The best example we have ever seen of 270 pages of useful matter packed into the dimensions of a card-case." Envision News. "A veritable pocket treasury of knowledge." - 170m.

POCKET GLOSSARY OF TECHNICAL TERMS.

English-French, French-English; with Tables suitable for the Architectural, Engineering, Manufacturing, and Nautical Professions. By JOHN JAMES FLETCHER. Third Edition, 200 pp. Waistcoat-pocket size, limp leather 1/6

"It is a very great advantage for readers and correspondents in France and England to have so large a number of the words relating to engineering and manufactures collected in a liliputan volume. The little book will be useful both to students and travellers." —A related:

"The glow-ary of terms is very compute, and many of the Tables are new and well arranged. We cordially commend the book." —Meanward if well.

THE ENGINEER'S YEAR BOOK FOR 1905.

Comprising Formula, Rules, Tables, Data and Memoranda in Civil, Mechanical, Electrical, Marine and Mine Engineering. By H. R. Kempe, A. M. Inst. C. E., M. I. E. E., Principal Technical Officer, Engineer-in-Chief's Office, General Post Office, London, Author of "A Handbook of Electrical Testing," "The Electrical Engineer's Pocket-Book," &c. With 1,000 Illustrations, specially Engraved for the work. Crown 8vo, 924 pp., leather. [Just Published. 8/0]

"Kempe's Year Book really requires no commendation. Its sphere of usefulness is widely known, and it is used by engineers the world over."—The trapineer.
"The volume is distinctly in advance of most similar publications in this country."—

Engineering.

"This valuable and well-designed book of reference meets the demands of all descriptions of engineer."—Saturday Review.

"Teems with up-to-date information in every branch of engineering and construction."—

"Teems with up-to-date information in every branch of engineering and construction."—
Bretileien News..

"The needs of the engineering profession could hardly be supplied in a more admirable,
complete and convenient form. To say that it mere than sustains all comparisons is praise of the
highest sort, and that may justly be said of it."—Aftering Yournes.

"There is certainly room for the new comer, which supplies explanations and directions, as
well as formules and tables. It deserves to become one of the most successful of the technical
annuals."—A rehited.

"Brings together with great skill all the technical information which an engineer has to use
day by day. It is in every way admirably equipped, and is sure to prove successful."—Scattmens.

"The up-to-dateness of Mr. Kempe's complication is a quality that will not be lost on the bury
people for whom the work is intended."—Glasgow Herald.

THE PORTABLE ENGINE.

"This is a work of value to those who use steam machinery. . . . Should be read by every one who has a steam engine, on a farm or elsewhere."—Mark Lane Express.

IRON AND STEEL.

A Work for the Forge, Foundry, Factory, and Office. Containing ready, useful, and trustworthy Information for Ironmasters and their Stock-takers; Managers of Bar, Rail, Plate, and Sheet Rolling Mills; Iron and Metal Founders; Iron Ship and Bridge Builders; Mechanical, Mining, and Consulting Engineers; Architects, Contractors, Builders, &c. By Charles Hoars, Author of "The Slide Rule," &c. Ninth Edition. 32mo, leather . . . 6/0

CONDENSED MECHANICS.

A Selection of Formulæ, Rules, Tables, and Data for the Use of Engineering Students, &c. By W. G. C. Hughes, A.M.I.C.E. Crown 8vo, cloth. 2/6 "The book is well fitted for those who are preparing for examination and wish to refresh their knowledge by going through their formulæ again."—Marine Engineer.

THE SAFE USE OF STEAM.

Containing Rules for Unprofessional Steam Users. By an Engineer. Eighth Edition. Sewed "If steam-users would but learn this little book by heart, boiler explosions would become ensations by their rarity."—*English Machanic*.

THE CARE AND MANAGEMENT OF STATIONARY ENGINES.

A Practical Handbook for Men-in-charge. By C. HURST. Crown 8vo. Net 1/O

THE LOCOMOTIVE ENGINE.

The Autobiography of an Old Locomotive Engine. By ROBERT WEATHER-BURN. M.I.M.E. With Illustrations and Portraits of GEORGE and ROBERT STEPHENSON. Crown 8vo, cloth. Net 2/8

THE LOCOMOTIVE ENGINE AND ITS DEVELOPMENT.

A Popular Treatise on the Gradual Improvements made in Railway Engines between 1803 and 1003. By CLEMENT E. STRETTON, C.E. Sixth Edition, Revised and Enlarged. Crown 8vo, cloth. [Just Published. Net 4/6]

"Students of railway history and all who are interested in the evolution of the modera ecomotive will find much to attract and entertain in this volume."—The Times.

TOOLS FOR ENGINEERS AND WOODWORKERS.

A Practical Treatise including Instruments of Measurement. By Joseph Horner, A.M. Inst. M. E., Author of "Pattern Making," "Hoisting Machinery," &c. Demy 8vo, with 450 Illustrations.

[In the Press. Price about 9/0 net

MODERN MACHINE SHOP TOOLS.

A Practical Treatise describing in every detail the Construction, Operation and Manipulation of both Hano and Machine I ools; being a work of Practical Instruction in all Classes of Machine Shop Practice, including Chapters on Filing, Fitting and Scraping Surfaces; on Drills, Reamers, Taps and Dies; the Lathe and its Tools; Planers, Shapers and their Tools; Milling Machines and Cutters; Gear Cutters and Gear Cutting; Drilling Machines and Drill Work; Grinding Machines and their Work; Hardening and Tempering, Gearing, Belting, and Transmission Machinery; Useful Data and Tables. By William H. Van Derwoort, M.E. Fourth Edition. Illustrated by 673 Engravings of Latest Tools and Methods, all of which are fully described. Medium 8vo, cloth.

LOCOMOTIVE ENGINE DRIVING.

A Practical Manual for Engineers in Charge of Locomotive Engines. By MICHARL REVNOLDS, formerly Locomotive Inspector, L. B. & S. C. R. Eleventh Edition. Including a KEY TO THE LOCOMOTIVE ENGINE. Crown 8vo, cloth

"Mr. Reynolds has supplied a want, and has supplied it well. We can confidently recommend the book not only to the practical driver, but to everyone who takes an interest in the performance of locomotive engines." —The Engineer.

"Mr. Reynolds has opened a new chapter in the literature of the day. This admirable practical treatise, of the practical utility of which we have to speak in terms of warm commendation."

THE MODEL LOCOMOTIVE ENGINEER.

"We should be glad to see this book in the possession of everyone in the kingdom who has ever laid, or is to lay, hands on a locomotive engine."—Iron.

CONTINUOUS RAILWAY BRAKES.

A Practical Treatise on the several Systems in Use in the United Kingdom: their Construction and Performance. By M. REYNOLDS. 8vo, cloth 9/0

"A popular explanation of the different brakes. It will be of great assistance in forming public opinion, and will be studied with benefit by those who take an interest in the brake."—Englich Mechanic.

STATIONARY ENGINE DRIVING.

A Practical Manual for Engineers in Charge of Stationary Engines. By MICHAEL REYNOLDS. Sixth Edition. With Plates and Woodcuts. Crown 8vo, cloth . 4/8

"The author's advice on the various points treated is clear and practical."—*Engineering*.
"Our author leaves no stone unturned. He is determined that his readers shall not only know something about the stationary engine, but all about it."—*Engineer.*

ENGINE-DRIVING LIFE.

Stirring Adventures and Incidents in the Lives of Locomotive Engine-Drivers. By MICHAEL REVNOLDS. Third Edition. Crown 8vo, cloth . 1/6 "From first to last perfectly fascinating." Wilkie Collins's most thrilling conceptions are into the shade by true incidents, endless in their variety, related in every page. — North

THE ENGINEMAN'S POCKET COMPANION.

And Practical Educator for Enginemen, Boiler Attendants, and Mechanics. By MICHAEL REVNOLDS. With 45 Illustrations and numerous Diagrams Fourth Edition, Revised. Royal 18mo, strongly bound for pocket wear. 3/6

"A most meritorious work, giving in a succinct and practical form all the information an e-minder desirous of mastering the scientific principles of his daily calling would require."—

CIVIL ENGINEERING, SURVEYING, ETC.

PIONEER IRRIGATION.

A Manual of Information for Farmers in the Colonies. By E. O. MAWSON, M.Inst.C.E., Executive Engineer. Public Works Department, Bombay. With Additional Chapters on Light Railways by E. R. CALTHROP, M.Inst.C.E., M.I.M.E. Illustrated by Numerous Plates and Diagrams. Demy 8vo, cloth [Just Published. Net 10/6]

SUMMARY OF CONTENTS:—VALUE OF IRRIGATION, AND SOURCES OF WATER SUPPLY.—DAMS AND WEIRS.—CANALS.—UNDERGROUND WATER.—METHODS OF IRRIGATION.—SEWAGE IRRIGATION.—IMPERIAL AUTOMATIC SLUICE GATES.—THE CULTIVATION OF IRRIGATED CROPS, VI-CETABLES, AND FRUIT TREES.—LIGHT RAILWAYS FOR HEAVY TRAFFIC.—USEPUL MEMORANDA AND DATA.

TUNNELLING.

A Practical Treatise. By CHARLES PRELINI, C.E. With additions by CHARLES S. HILL, C.E. With 150 Diagrams and Illustrations. Royal 8vo.

PRACTICAL TUNNELLING.

Explaining in detail Setting-out the Works, Shaft-sinking, and Heading-driving, Ranging the Lines and Levelling underground, Sub-Excavating, Timbering and the Construction of the Brickwork of Tunnels. By F. W. SIMMS, M. Inst. C.E. Fourth Edition, Revised and Further Extended, including the most recent (1895) Examples of Sub-aqueous and other Tunnels, by D. KINNEAR CLARK, M. Inst. C.E. With 34 Folding Plates. Imperial 8vo, cloth £2 2s.

"The present (1896) edition has been brought right up to date, and is a work to wrich civil engineers should have ready access, and engineers who have construction work can hardly afford to be without, but which to the younger memores of the profession is invaluable, as from its pages they can learn the state to which the science of tunnelling has attained."—Railway News.

THE WATER SUPPLY OF TOWNS AND THE CON-STRUCTION OF WATER-WORKS.

A Practical Treatise for the Use of Engineers and Students of Engineering.

WITH WATER-WORKS.

APPENDIX I. By PROF. JOHN MILNE, F.R.S.—CONSIDERATIONS CONCERNING THE PROBABLE EFFECTS OF EARTHQUAKES ON WATER-WORKS, AND THE SPECIAL PERCAUTIONS TO BE TAKEN IN EARTHQUAKE COUNTRIES.

APPENDIX II. By JOHN DE RIJKE, C.E.—ON SAND DUNES AND DUNE SAND AS A SOURCE OF WATER SUPPLY.

"The chapter upon filtration of water is very complete, and the details of construction well illustrated. . . . The work should be specially valuable to civil engineers engaged in work in Japan, but the interest is by no means confined to that locality."—Bugsweer.

"We congratulate the author upon the practical commonsense shown in the preparation of this work. . . . The plates and diagrams have evidently been prepared with great care, and cannot fall to be of great assistance to the student."—Builder.

RURAL WATER SUPPLY.

A Practical Handbook on the Supply of Water and Construction of Waterworks for small Country Districts. By Allan Greenwell, A.M.I.C.E., and W. T. Curry, A.M.I.C.E., F.G.S. With Illustrations. Second Edition. Revised. Crown 8vo, cloth . 5/0

"We conscientiously recommend it as a very useful book for those concerned in obtaining water for small districts, giving a great deal of practical information in a small compass."—Buellers.

The volume contains valuable information upon all matters connected with water supply,

It is full of details on p-ints which are continually before water-works engineers."—Names.

THE WATER SUPPLY OF CITIES AND TOWNS.

By WILLIAM HUMBER, A. M. Inst. C.E., and M. Inst. M.E., Author of "Cast and Wrought Iron Bridge Construction," &c., &c. Illustrated with 50 Double Plates, 1 Single Plate, Coloured Frontispiece, and upwards of 250 Woodcuts, and containing 400 pp. of Text. Imp. 4to, elegantly and substantially half-bound in morocco.

Net 26 6a.

half-bound in motocco

LIST OF CONTRIS:—I. HISTORICAL SKETCH OF SOME OF THE MEANS THAT HAVE BEEN ADOPTED FOR THE SUPPLY OF WATER TO CITIES AND TOWNS.—II. WATER AND THE FOREIGN MATTER USUALLY ASSOCIATED WITH IT.—III. RAINFALL AND EVAPORATION.—IV. SPRINGS AND THE WATER-BEARING FORMATIONS OF VARIOUS DISTRICTS.—V. MEASUREMENT AND ESTIMATION OF THE FLOW OF WATER.—VI. ON THE SELECTION OF WATER.—X. PUMPS.—XI. PUMPING MACHINERY.—XII. CONDUITS.—XIII. DISTRICTS. TON OF WATER.—XIV. METERS, SERVICE PIPES, AND HOUSE FITTINGS.—XV. THE LAW AND ECONOMY OF WATER WORKS.—XVI. CONSTANT AND INTERMITTENT SUPPLY. XVIII. DESCRIPTION OF PLATES.—APPENDICES, GIVING TABLES OF RATES OF SUPPLY, VELOCITIES, &C., &C.. TOGETHER WITH SPECIFICATIONS OF SEVERAL WORKS ILLUSTRATED, AMONG WHICH WILL BE FOUND: ABBEDBERN, BIDHFORD, CANTERBURY, DUNDER, HALIFAX, LAMBETH, ROTHERHAM, DUBLIN, AND OTHERS.

"The most systematic and valuable work upon waters uponly hitherto produced in English, or

"The most systematic and valuable work upon water supply hitherto produced in English, or in any other language. Mr. Humber's work is characterised almost throughout by an exhaustiveness much more distinctive of French and German than of English technical treatises."

Respirator.

THE PROGRESS OF ENGINEERING (1863-6).

By WM. HUMBER, A. M. Inst. C.E. Complete in Four Vols. Containing 148 Double Plates, with Portraits and Copious Descriptive Letterpress. Impl. 4to, half-morocco. Price, complete, £12 12s.; or each Volume sold separately at £3 3s. per Volume. Descriptive List of Contents on application.

HYDRAULIC POWER ENGINEERING.

A Practical Manual on the Concentration and Transmission of Power by Hydraulic Machinery. By G. CROYDON MARKS, A.M. Inst. C.E. With Dearly 200 Illustrations. 8vo, cloth. **Yet 900.**

SUMMARY OF CONTENTS:—PRINCIPLES OF HYDRAULICS.—THE FLOW OF WATER.—
HYDRAULIC PRESSURES.—MATERIAL.—TEST LOAD.—PACKINGS FOR SLIDING SURFACES.
—PIPE JOINTS.—CONTROLLING VALVES.—PLATFORM LIFTS.—WORKSHOP AND FOUNDRY
CRANES.—WARBHOUSE AND DOCK CRANES.—HYDRAULIC ACCUMULATORS.—PRESS
FOR BALING AND OTHER PURPOSS.—SHBET METAL WORKING AND FORGING MACHINERY.
—HYDRAULIC RIVETERS.—HAND AND POWER PUMPS.—STEAM PUMPS.—TURBINES.—
MPULSE TURBINES.—REACTION TURBINES.—DESIGN OF TURBINES IN DETAIL.—WATER
WHERLS.—HYDRAULIC ENGINES.—RECENT ACHIEVEMENTS.—PRESSURE OF WATER.—
ACTION OF PUMPS, &c.

WHRES.—HYDRAULIC ENGINES.—RECENT ACHIEVEMENTS.—FRESSURE OF WATER.—ACTION OF PUMPS, &C. Dut praise for this thoroughly valuable work. The author has succeeded in rendering his subject interesting as well as instructive."—Practical Engineer.

"Can be unbesitatingly recommended as a useful and up-to-date manual on hydraulic trans mission and utilisation of power."—Mcchanical World.

HYDRAULIC TABLES, CO-EFFICIENTS, & FORMULÆ.

For Finding the Discharge of Water from Orifices, Notches, Weirs, Pipes, and Rivers. With New Formulæ, Tables, and General Information on Rain-fall, Catchment-Basins, Drainage, Sewerage, Water Supply for Towns and Mill Power. By John Neville, C.E., M.R.I.A. Third Edition, revised, with additions. Numerous Illustrations. Crown 8vo, cloth 14/0 "It is, of all Engish books on the subject, the one nearest to completeness."—Archive.

HYDRAULIC MANUAL

WATER ENGINEERING.

A Practical Treatise on the Measurement, Storage, Conveyance, and Utilisation of Water for the Supply of Towns, for Mill Power, and for other Purposes. By Charles Slagg. A.M. Inst. C.E. Second Edition. Crown 8vo, cloth. 7/6

"As a small practical treatise on the water supply of towns, and on some applications of waterpower, the work is in many respects excellent."—Engineering.

THE RECLAMATION OF LAND FROM TIDAL WATERS.

A Handbook for Engineers, Landed Proprietors, and others interested in Works of Reclamation. By A. BEAZELEY, M.Inst. C.E. 8vo, cloth. Net 10/6

"The book shows in a concise way what has to be done in reclaiming land from the sea, and the best way of doing it. The work contains a great deal of practical and useful information which annot fail to be of service to engineers entrusted with the enclosure of salt marshes, and to land-owners intending to reclaim land from the sea."—The Engineer.

"The author has carried out his task efficiently and well, and his book contains a large amount of information of great service to engineers and others interested in works of reclamation."

MASONRY DAMS FROM INCEPTION TO COMPLETION.

"Contains a good deal of valuable data. Many useful suggestions will be found in the remarks on site and position, location of dam, foundations and construction,"—Building News.

RIVER BARS.

The Causes of their Formation, and their Treatment by "Induced Tidal Scour"; with a Description of the Successful Reduction by this Method of the Bar at Dublin. By I. J. Mann, Assist. Eng. to the Dublin Port and Docks Board. Royal 8vo, cloth .

"We recommend all interested in harbour works—and, indeed, those concerned in the wements of rivers generally—to read Mr. Mann's interesting work."—Business.

TRAMWAYS: THEIR CONSTRUCTION AND WORKING.

Embracing a Comprehensive History of the System; with an exhaustive Analysis of the Various Modes of Traction, including Horse Power, Steam, Cable Traction, Electric Traction, &c.; a Description of the Varieties of Rolling Stock; and ample Details of Cost and Working Expenses. New Edition, Thoroughly Revised, and Including the Progress recently made in Tramway Construction, &c., &c. By D. KINNEAR CLARK, M. Inst. C.E. With 400 Illustrations. 8vo, 780 pp., buckram.

"The new volume is one which will rank, among tramway engineers and those interested in tramway working, with the Author's world-famed book on railway machinery."—The Engineer.

SURVEYING AS PRACTISED BY CIVIL ENGINEERS AND SURVEYORS.

Including the Setting-out of Works for Construction and Surveys Abroad, with many Examples taken from Actual Practice. A Handbook for use in the Field and the Office, intended also as a Text-book for Students. By JOHN WHITE-LAW, Jun., A.M. Inst C.E., Author of "Points and Crossings." With about 260 Illustrations Demy 8vo, cloth .

"This work is written with admirable lucidity, and will certainly be found of distinct value both to students and to those engaged in actual practice."—The Builder.

PRACTICAL SURVEYING.

A Text-Book for Students preparing for Examinations or for Survey-work in the Colonies. By George W. Usill, A.M.I.C.E. Eighth Edition, thoroughly Revised and Enlarged, by Alex Beazelley, M. Inst. C.E. With 4 Lithographic Plates and 360 Illustrations. Large crown 8vo, 7E. cloth; or, on Thin Paper, leather, gilt edges, rounded corners, for pocket use

"The best forms of instruments are described as to their construction, uses and modes of employment, and there are innumerable hints on work and equipment such as the author, in his experience as surveyor, draughtsman and teacher, has found necessary, and which the student in his inexperience will find most serviceable. "Engineer."

"The first book which should be put in the hands of a pupil or Civil Engineering."—

AID TO SURVEY PRACTICE.

For Reference in Surveying, Levelling, and Setting-out; and in Route Surveys of Travellers by Land and Sea. With Tables, Illustrations, and Records. By L. D'A. Jackson, A.M.I.C.E. Second Edition. 8vo, cloth 12/6

"Mr. Jackson has produced a valuable vade-mecum for the surveyor. We can recommend this book as containing an admirable supplement to the reaching of the accomplished surveyor."—

Athenaum.

"The author brings to his work a fortunate union of theory and practical experience which, aided by a clear and lucid style of writing, renders the book a very useful one."—Builder,

SURVEYING WITH THE TACHEOMETER.

A practical Manual for the use of Civil and Military Engineers and Surveyors. Including two series of Tables specially computed for the Reduction of Readings in Sexagesimal and in Centesimal Degrees. By NEIL KENNEDY, M. Inst. C. E. With Diagrams and Plates. Second Edition. Demy 8vo, cloth. [Just Published. Net 10/8

"The work is very clearly written, and should remove all difficulties in the way of any surveyor desirous of making use of this useful and rapid instrument."—Nature.

ENGINEER'S & MINING SURVEYOR'S FIELD BOOK.

Consisting of a Series of Tables, with Rules, Explanations of Systems, and use of Theodolite for Traverse Surveying and plotting the work with minute accuracy by means of Straight Edge and Set Square only; Levelling with the Theodolite, Setting-out Curves with and without the Theodolite, Earthwork Tables, &c. By W. Davis Haskoll, C.E. With numerous Woodcuts. Fourth Edition, Enlarged. Crown 8vo, cloth 12/0

"The book is very handy; the separate tables of sines and tangents to every minute will make useful for many other purposes, the genuine traverse tables existing all the same."—Atherwise.

LAND AND MARINE SURVEYING.

"This book must prove of great value to the student. We have no hesitation in recommending it, feeling assured that it will more than repay a careful study."—Mechanical World.

"A most useful book for the student. We can strongly recommend it as a carefully-written and valuable text-book. It enjoys a well-deserved reputs among surveyors."—Butlete.

PRINCIPLES AND PRACTICE OF LEVELLING.

Showing its Application to Purposes of Railway and Civil Engineering in the Construction of Roads; with Mr. Telford's Rules for the same. By Frederick W. Simms, M. Inst. C.E. Eighth Edition, with Law's Practical Examples for Setting-out Railway Curves, and Tralutwine's Field Practice of Laying-out Circular Curves. With 7 Plates and numerous Woodcuts.

"The text-book on levelling in most of our engineering schools and colleges."—Engineer.
"The publishers have rendered a substantial service to the profession, especially to the younger sembers, by bringing out the present edition of Mr. Simm's useful work."—Engineering.

AN OUTLINE OF THE METHOD OF CONDUCTING A TRIGONOMETRICAL SURVEY.

TABLES OF TANGENTIAL ANGLES AND MULTIPLES.

For Setting-out Curves from 5 to 200 Radius. By A. BEAZELEY, M. Inst. C.E. 6th Edition Revised. With an Appendix on the use of the Tables for Measuring up Curves. Printed on 50 Cards, and sold in a cloth box, waistcoatpocket size .

"Each table is printed on a small card, which, placed on the theodolite, leaves the hands free to mentpulate the instrument—no small advantage as regards the rapidity of work."—Engineer. "Very handy: a man may know that all his day's work must fall on two of these cards, which he puts him his own card-case, and leaves the rest behind."—4 thensum.

HANDY GENERAL EARTH-WORK TABLES.

Giving the Contents in Cubic Yards of Centre and Slopes of Cuttings and Embankments from 3 inches to 80 feet in Depth or Height, for use with either 66 feet Chain or 100 feet Chain. By J. H. WATSON BUCK, M. Inst. C.E. On a Sheet mounted in cloth case .

EARTHWORK TABLES.

A MANUAL ON EARTHWORK.

By ALEX. J. GRAHAM, C.E. With numerous Diagrams. Second Edition

THE CONSTRUCTION OF LARGE TUNNEL SHAFTS.

A Practical and Theoretical Essay. By J. H. WATSON BUCK, M. Inst. C.S., Resident Engineer, L. and N. W. R. With Folding Plates, 8vo, cloth 12/0 "Many of the methods given are of extreme practical value to the mason, and the observa-tions on the form of arch, the rules for ordering the stone, and the construction of the templates, will be found of considerable use. We commend the book to the engineering profession."—

"Will be regarded by civil engineers as of the utmost value, and calculated to save much me and obviate many mistakes."—Colliery Guardies.

CAST & WROUGHT IRON BRIDGE CONSTRUCTION

(A Complete and Practical Treatise on), including Iron Foundations. In Three Parts.—Theoretical, Practical, and Descriptive.

By WILLIAM HUMBER,
A. M. Inst. C.E., and M. Inst. M.E. Third Edition, revised and much improved, with 115 Double Plates (20 of which now first appear in this edition) and numerous Additions to the Text. In 2 vols., imp. 4to, half-bound in morocco.

26 16s. 6s.

"A very valuable contribution to the standard literature of civil engineering. In addition to elevations, plans, and sections, large scale details are given, which very much enhance the instructive worth of those illustrations."—Civil Engineer and Architect Jewrend.

"Mr. Humber's stately volumes, lately issued—in which the most important bridges exected during the last five years, under the direction of the late Mr. Brunel, Sir W. Cubitt, Mr. Hawkshaw, Mr. Page, Mr. Fowler, Mr. Hemana, and others among our most eminent engineers, are drawn and specified in great detail."—Engineers, are drawn and specified in great detail.

ESSAY ON OBLIQUE BRIDGES

(Practical and Theoretical). With 13 large Plates. By the late George WATSON BUCK, M.I.C.E. Fourth Edition, revised by his Son, J. H. WATSON BUCK, M.I.C.E.; and with the addition of Description to Diagrams for Facilitating the Construction of Oblique Bridges, by W. H. BARLOW, M.I.C.E. 12/0 Royal 8vo, cloth

"The standard text-book for all engineers regarding skew arches is Mr. Buck's treatise, and it would be impossible to consult a better."—Engineer.
"Mr. Buck's treatise is recognised as a standard text-book, and his treatment has divested the subject of many of the intricacies supposed to belong to it. As a guide to the engineer as architect, on a confessedly difficult subject, Mr. Buck's work is unsurpassed."—Budding News.

THE CONSTRUCTION OF OBLIQUE ARCHES

(A Practical Treatise on). By JOHN HART. Third Edition, with Plates. Imperial 8vo. cloth .

GRAPHIC AND ANALYTIC STATICS.

In their Practical Application to the Treatment of Stresses in Roofs, Solid Girders, Lattice, Bowstring, and Suspension Bridges, Braced Iron Arches and Piers, and other Frameworks. By R. Hudson Graham, C.E. Containing Diagrams and Plates to Scale. With numerous Examples, many taken existing Structures. Specially arranged for Class-work in Colleges and Universities. Second Edition, Revised and Enlarged. 8vo, cloth 16/0 "Mr. Graham's book will find a place wherever graphic and analytic statics are used or d."—Engineer.

"The work is excellent from a practical point of view, and has evidently been prepared with much care. The directions for working are ample, and are flustrated by an abundance of well-selected examples. It is an excellent text-book for the practical draughtsmans."—Attensess.

WEIGHTS OF WROUGHT IRON & STEEL GIRDERS.

A Graphic Table for Facilitating the Computation of the Weights of Wrought

GEOMETRY FOR TECHNICAL STUDENTS.

An Introduction to Pure and Applied Geometry and the Mensuration of Surfaces and Solids, including Problems in Plane Geometry useful in Drawing By E. H. Sprague, A.M.I.C.E. Crown 8vo, cloth. [Just Published. Net 1/0]

PRACTICAL GEOMETRY.

"No book with the same objects in view has ever been published in which the clearness of the rules laid down and the illustrative diagrams have been so satisfactory."—Scottman.

THE GEOMETRY OF COMPASSES.

EXPERIMENTS ON THE FLEXURE OF BEAMS.

Resulting in the Discovery of New Laws of Failure by Buckling. By Albert E. Guy. Medium 8vo, cloth Net 9/0

HANDY BOOK FOR THE CALCULATION OF STRAINS

"The formulæ are neatly expressed, and the diagrams good."—Athenaum.
"We heartly commend this really handy book to our engineer and architect readers."—
Engish Machanic.

TRUSSES OF WOOD AND IRON.

Practical Applications of Science in Determining the Stresses, Breaking Weights, Safe Loads, Scantlings, and Details of Construction. With Complete Working Drawings. By WILLIAM GRIFFITHS, Surveyor. Oblong 8vo, cloth.

"This handy little book enters so minutely into every detail connected with the corstruction of roof trusses that no student need be ignorant of these matters."—Practical Engineer.

THE STRAINS ON STRUCTURES OF IRONWORK.

A TREATISE ON THE STRENGTH OF MATERIALS.

"Valuable alike to the student, tyro, and the experienced practitioner, it will always rank n future as it has hitherto done, as the standard treatise on that particular subject."—Engineer,

SAFE RAILWAY WORKING.

A Treatise on Railway Accidents, their Cause and Prevention; with a Description of Modern Appliances and Systems. By CLEMENT E. STRETTON, C.E. With Illustrations and Coloured Plates. Third Edition, Enlarged. Crown 8vo, cloth 3/6

EXPANSION OF STRUCTURES BY HEAT.

"The aim the author has set before him, viz., to show the effects of heat upon metallic and or structures, is a laudable one, for this is a branch of physics upon which the engineer or arcastect can find but little reliable and comprehensive data in books."—Butilder.

PUBLICATIONS OF THE ENGINEERING STANDARDS COMMITTEE.

THE ENGINEERING STANDARDS COMMITTEE is the outcome of a Committee appointed by the Institution of Civil Engineers at the instance of Sir John Wolfe Barry, K.C.B., to inquire into the advisability of Standardising Rolled Iron and Steel Sections.

The Committee is supported by the Institution of Civil Engineers, the Institution of Mechanical Engineers, the Institution of Naval Architects, the Iron and Steel Institute, and the Institution of Electrical Engineers; and the value and importance of its labours has been emphatically recognised by his Majesty's Government, who have made a liberal grant from the Public Funds by way of contribution to the financial resources of the Committee.

The subjects already dealt with, or under consideration by the Committee, include not only Rolled Iron and Steel Sections, but Tests for Iron and Steel Material used in the Construction of Ships and their Machinery, Bridges and General Building Construction, Railway Rolling Stock Underframes, Component Parts of Locomotives, Railway and Tramway Rails, Electrical Plant, Insulating Materials, Screw Threads and Limit Gauges, Pipe Flanges, Cement, &c.

Reports already Published :-

- BRITISH STANDARD SECTIONS.

 List I. EQUAL ANGLES.—List 2. UNEQUAL ANGLES.—List 3. BULB ANGLES.

 List 4. BULB TERS.—List 5. BULB PLATES.—List 7. CHANNELS.—List 8.

 [Just Published. Net 1/0]
- 2. BRITISH STANDARD TRAMWAY RAILS AND FISH PLATES: STANDARD SECTIONS AND SPECIFICATION. F'cap. folio, sewed. [Just Published. Net 21/0
- 3. REPORT ON THE INFLUENCE OF GAUGE LENGTH AND SECTION OF TEST BAR ON THE PERCENTAGE OF ELONGATION. By Professor W. C. Unwin, F.R.S. F'cap. folio, sewed.

 [Just Published. Net 2/8]
- 4. PROPERTIES OF STANDARD BEAMS. Demy 8vo, sewed. [Just Published. Net 1/0
- 6. PROPERTIES OF BRITISH STANDARD SECTIONS. Embracing Diagrams, Definitions, Tables, and Formulæ Demy 8vo, cloth.

 [Just Published. Net 5/0]
- 7. BRITISH STANDARD TABLES FOR COPPER CON-DUCTORS AND THICKNESSES OF DIELECTRIC. F'cap. folio, sewed. [Just Published. Net 2/6
- BRITISH STANDARD SPECIFICATION FOR TUBU-LAR TRAMWAY POLES. F'cap. folio, sewed. [Just Published. Net 5/0
- 9. BRITISH STANDARD SPECIFICATION AND SEC-TIONS FOR BULL HEADED RAILWAY RAILS F'cap. folio, sewed. [Just Published. Net 10/6
- BRITISH ENGINEERING STANDARDS CODED LIST. Rolled Sections for Constructional Iron and Steel Tram Rails. Compiled by ROBERT ATKINSON. 476 pp., 4to, cloth. Net 21/0

MARINE ENGINEERING. SHIPBUILDING. NAVIGATION. ETC.

MARINE ENGINES AND BOILERS.

Their Design and Construction. A Handbook for the Use of Students, Engineers, and Naval Constructors. Based on the Work "Berechnung u.d. Konstruktion der Schiffsmaschinen und Kessel," by Dr. G. BAUER, Engineerin-Chief of the Vulcan Shipbuilding Yard, Stettin. Translated from the Second German Edition by E. M. DONKIN, and S. BRYAN DONKIN, A.M.I.C.E. Edited by LESLIE S. ROBERTSON, Secretary to the Engineering Standards Committee, M.I.C.E., M.I.M.E., M.I.N.A., &c. With numerous Illustrations and Tables. Medium Svo, cloth. [Nearly Ready, Price about 32]- Net.

and Tables. Medium 8vo, cloth . [Nearly Ready, Price about 32]- Net.

Summary of Contents:—Part 1.—Main Engines.— Determination of cylinder Dimensions.—The Utilisation of 5 yeam in the Engine.—Stroke of Piston.—Number of Revolutions.—Turning Momen.—Balancing of the Moung Parts.—Arrangement of Main Engines.—Details of Main Engines.—The Cylinder.—Valves.—Various Kinds of Valve Gear.—Piston Rods.—Pistons.—Connecting Rod and Crosshead.—Valve Gear.—Piston Rods.—Pistons.—Connecting Rod and Turning Gear. Fart II.—Pumps.—Air, Circulating Feed, and Auxiliary Pimps. Part III.—Shafting, besistance of 5 hips, profellers.—Thrust Shaft and Thrust Block.—Tunnel Shafts and flurmer Blocks.—Thrust Shaft and Thrust Block.—Tunnel Shafts and flurmer Blocks.—Thaft Couplings.—Stern Tuee.—The Screw Profeller.—Constaution of the Screw. Part IV.—Pipes and Connections.—General Remarks, Flange, Valves, &c.—Under Water, Bilgs, Main Stam, Auxiliary Stram, and Exhaust Piping.—Feed water, Bilgs, Balladt and Circulating Pipes. Part V.—Steam Bollers.—Firms and the General Coomotive Boilers.—Water-lube Boilers.—Small Tuer Water-lube Boilers.—Moke Bus.—Funnel and Boiler Lagging.—Focto Draught.—Boiler Fittings and Mountings. Part VI.—Measuring Instruments. Part VII.—Various Details.—Boilts, Nuts, Screw Threads, &c.—Platforms, Gratings, Ladders.—Found Figure Rooms.—Rules for Spare Gear, Part VII.—Additional Tables. ROOMS.—RULES FOR SPARE GRAR. PART VIII.—ADDITIONAL TABLES.

ARCHITECT'S AND SHIPBUILDER'S NAVAL POCKET-BOOK

"In these days of advanced knowledge a werk like this is of the greatest value. It contains a vast amount of information. We unhesitatingly say that it is the mest valuable compilation for inspectic purpose that has ever been printed. No naval architect, engineer, surveyor, seaman, wood or iron shipbuilder, can afford to be without this work."—Nassitation Magnasius. "Should be used by all who are engaged in the construction or design of vessels. ... Will be found to coatsain the most useful tables and formulæ required by shipbuilders, collected from the best authorities, and put together in a popular and simple form. It is of acceptional merit."—

Engineer.

"A pocket-book of this description must be a necessity in the shipbuilding trade. It contains a mass of useful information clearly expressed and presented in a handy form."—Marine

WANNAN'S MARINE ENGINEER'S GUIDE

"The book is clearly and plainly written and avoids unnecessary explanations and formulas, a consider it a valuable book for students of marine engineering."—Nautical Magarite.

WANNAN'S MARINE ENGINEER'S POCKET-BOOK.

Containing Latest Board of Trade Rules and Data for Marine Engineers.

By A. C. Wannan. Third Edition, Revised, Enlarged, and Brought up to
Date. Square 18mo, with thumb Index, leather

"There is a great deal of useful information in this little pocket-book. It is ofte rule-ofthumb order, and is, on that account, well adapted to the uses of the see-going engineer."—

THE SHIPBUILDING INDUSTRY OF GERMANY.

Compiled and Edited by G. LEHMANN-FELSKOWSKI. With Coloured Prints, Art Supplements, and numerous Illustrations throughout the text. Superroyal 4to, cloth. [Just Publishea. Net 1016

SEA TERMS, PHRASES, AND WORDS

"This volume will be highly appreciated by seamen, engineers, pilots, shipbuilders and ship-owners. It will be found wonderfully accurate and complete."—Sectiones.

MARINE ENGINEER'S POCKET-BOOK.

"We recommend it to our readers as going far to supply a long-felt want."—Naval Science.
"A most useful companion to all marine engineers."—United Service Gazette.

ELEMENTARY MARINE ENGINEERING.

A Manual for Young Marine Engineers and Apprentices. By J. S. Brewer. Crown 8vo, cloth 1/6

PRACTICAL NAVIGATION.

Consisting of THE SAILOR'S SEA-BOOK, by J. GREENWOOD and W. H. ROSSER; with Mathematical and Nautical Tables for Working the Problems, by H. Law, C.E., and Professor J. R. Young. 12mo, half-bound . 7/0

THE ART AND SCIENCE OF SAILMAKING.

By SAMUEL B. SADLER, Practical Sailmaker, late in the employment of Messrs. Ratsey and Lapthorne, of Cowes and Gosport. Plates. 4to, cloth. 12/6

"This extremely practical work gives a complete education in all the branches of the manu-facture, cutting out, roping, seaming, and goring. It is copiously illustrated, and will form a first-rate text-book and guide,"—Pertuneul Times.

CHAIN CABLES AND CHAINS.

AIN CABLES AND CHAINS.

Comprising Sizes and Curves of Links, Studs, &c., Iron for Cables and Chains, Chain Cable and Chain Making, Forming and Welding Links, Strength of Cables and Chains, Certificates for Cables, Marking Cables, Prices of Chain Cables and Chains, Historical Notes, Acts of Parliament, Statutory Tests, Charges for Testing, List of Manufacturers of Cables, &c., &c. By Thomas W. Traill, F.E.R.N., M.Inst.C.E., Engineer-Surveyor-in-Chain, Board of Trade, Inspector of Chain Cable and Anchor Proving Establishments, and General Superintendent, Lloyd's Committee on Proving Establishments, With numerous Tables, Illustrations, and Lithographic Drawings. Folio, cloth

MINING, METALLURGY, AND COLLIERY WORKING.

THE OIL FIELDS OF RUSSIA AND THE RUSSIAN PETROLEUM INDUSTRY.

PETROLEUM INDUSIKY.

A Practical Handbook on the Exploration, Exploitation, and Management of Russian Oil Properties, including Notes on the Origin of Petroleum in Russia, a Description of the Theory and Practice of Liquid Fuel, and a Translation of the Rules and Regulations concerning Russian Oil Properties. By A. Berby Trompson, A.M.I.M.E., late Chief Engineer and Manager of the European Petroleum Company's Russian Oil Properties. About 500 pp. With numerous Illustrations and Photographic Plates, and a Map of the Balakhany-Saboontchy-Romany Oil Field. Super-royal 8vo, cloth.

[/wst Published. Net 23 8s.

MACHINERY FOR METALLIFEROUS MINES.

"Deals exhaustively with the many and complex details which go to make up the sum total of machinery and other requirements for the successful working of metalliferous mines, and as a book of ready reference is of the highest value to mine managers and directors."—Mining Journal.

THE DEEP LEVEL MINES OF THE RAND.

And their Future Development, considered from the Commercial Point of View. By G. A. DENNY (of Johannesburg), M.N.E.I.M.E., Consulting Engineer to the General Mining and Finance Corporation, Ltd., of London, Berlin, Paris, and Johannesburg. Fully Illustrated with Diagrams and Folding Plates. Royal 8vo, buckram

"Mr. Denny by confining himself to the consideration of the future of the deep-level mines of the Rand breaks new ground, and by dealing with the subject rather from a commercial standpoint than from a scientific one, appeals to a wide circle of readers. The book cannot fail to prove of very great value to investors in South African mines."—Mining Journal.

PROSPECTING FOR GOLD.

A Handbook of Practical Information and Hints for Prospectors based on Personal Experience. By Daniel J. Rankin, F. R.S.G.S., M.R.A.S., formerly Manager of the Central African Company, and Leader of African Gold Prospecting Expeditions. With Illustrations specially Drawn and Engraved for the Work. Fcap. 8vo, leather . . Net 7/6

"This well-compiled book contains a collection of the richest gems of useful knowledge for the prospector's benefit. A special table is given to accelerate the spotting at a glance of minerals associated with gold."—Mining Fournal.

THE METALLURGY OF GOLD.

numerous Folding Plates. Medium 8vo, cloth

"This book thoroughly deserves its title of a 'Practical Treatise.' The whole process of gold mining, from the breaking of the quartz to the assay of the bulkon, is described in clear and orderly narrative and with much, but not too much, fulness of detail."—Saturday Review.

THE CYANIDE PROCESS OF GOLD EXTRACTION.

And its Practical Application on the Witwatersrand Gold Fields and elsewhere. By M. Eissler, M. Inst. M.M. With Diagrams and Working Drawings. Third Edition, Revised and Enlarged. 8vo, cloth .

"This book is just what was needed to acquaint mining men with the actual working of a process which is not only the most popular, but is, as a general rule, the most successful for the extraction of gold from tailings."—Missing Journal.

DIAMOND DRILLING FOR GOLD & OTHER MINERALS.

A Practical Handbook on the Use of Modern Diamond Core Drills in Prospecting and Exploiting Mineral-Bearing Properties, including Particulars of the Costs of Apparatus and Working. By G. A. DENNY, M.N.E. Inst. M.E., M. Inst. M.M. Medium 8vo, 168 pp., with Illustrative Diagrams 12/8

"There is certainly scope for a work on diamond drilling, and Mr. Denny deserves grateful ecognition for supplying a decided want."—Moning Journal.

GOLD ASSAYING.

A Practical Handbook, giving the *Modus Operandi* for the Accurate Assay of Auriferous Ores and Bullion, and the Chemical Tests required in the Processes of Extraction by Amalgamation, Cyanidation, and Chlorination. With an Appendix of Tables and Statistics. By H. JOSHUA PHILLIPS, F.I.C., F.C.S., Assoc.Inst.C.E., Author of "Engineering Chemistry," etc. With Numerous Illustrations. Large Crown 8vo, cloth. [Just Published, Net 7]

FIELD TESTING FOR GOLD AND SILVER.

A Practical Manual for Prospectors and Miners. By W. H. MERRITT. M. N.E. Inst. M.E., A.R.S.M., &c. With Photographic Plates and other "As an instructor of prospectors' classes Mr. Merritt has the advantage of knowing exactly the information likely to be most valuable to the miner in the field. The contents cover all the details of sampling and testing gold and silver ores. A useful addition to a prospector's kt."—Missing Fournal.

THE PROSPECTOR'S HANDBOOK.

"Will supply a much-felt want, especially among Colonists, in whose way are so often thrown many mineralogical specimens the value of which it is difficult to determine."—Bagineer.

"How to find commercial minerals, and how to identify them when they are found, are the leading points to which attention is directed."—Mining Tournal.

THE METALLURGY OF SILVER.

A Practical Treatise on the Amalgamation, Roasting, and Lixiviation of Silver Ores. Including the Assaying, Melting, and Refining of Silver Bullion. By M. EISSLER, M. Inst. M.M. Third Edition. Crown 8vo, cloth . 10/6 . 10/6 "A practical treatise, and a technical work which we are convinced will supply a long-felt want amongst practical men, and at the same time be of value to students and others indirectly connected with the industries."—*Missing Tourna*.

THE HYDRO-METALLURGY OF COPPER.

Being an Account of Processes Adopted in the Hydro-Metallurgical Treatment of Cupriferous Ores, Including the Manufacture of Copper Vitriol, with Chapters on the Sources of Supply of Copper and the Roasting of Copper Ores. By M. EISSLER, M. Inst. M.M. 8vo, cloth Net 12/6 'In this volume the various processes for the extraction of copper by wet methods are fully detalled. Costs are given when available, and a great deal of useful informati in about the copper industry of the world is presented in an interesting and attractive manner."—Mining Fournal.

THE METALLURGY OF ARGENTIFEROUS LEAD.

A Practical Treatise on the Smelting of Silver-Lead Ores and the Refining or Lead Bullion. Including Reports on various Smelting Establishments and Descriptions of Modern Smelting Furnaces and Plants in Europe and America. By M. EISSLER, M. Inst. M.M. Crown 8vo, cloth . . 12/6

"The numerous metallurgical processes, which are fully and extensively treated of, embrace all the stages experienced in the passage of the lead from the various natural states to its issue from the refinery as an article of commerce."—Practical Engineer.

METALLIFEROUS MINERALS AND MINING.

By D. C. DAVIES, F.G.S. Sixth Edition, thoroughly Revised and much Enlarged by his Son, E. HENRY DAVIES, M.E., F.G.S. 600 pp., with 173 "Neither the practical miner nor the general reader, interested in mines, can have a better book for his companion and his guide."—Mining Yournal.

EARTHY AND OTHER MINERALS AND MINING.

By D. C. Davies, F.G.S., Author of "Metalliferous Minerals," &c. Third Edition, Revised and Enlarged by his Son, E. Henry Davies, M.E., F.G.S. With about 100 Illustrations. Crown 8vo, cloth . 12/6 "We do not remember to have met with any English work on mining matters that contains the same amount of information packed in equally convenient form,"—Academy.

BRITISH MINING.

A Treatise on the History, Discovery, Practical Development, and Future Prospects of Metalliferous Mines in the United Kingdom. By ROBERT HUNT, F.R.S., late Keeper of Mining Records. Upwards of 950 pp., with 230 Illustrations. Second Edition, Revised. Super-royal 8vo, cloth \$22 2s.

POCKET-BOOK FOR MINERS AND METALLURGISTS.

Comprising Rules, Formulæ, Tables, and Notes for Use in Field and Office Work. By F. Danvers Power, F.G.S., M.E. Second Edition, Corrected. Fcap. 8vo, leather . "This excellent book is an admirable example of its kind, and ought to find a arge sale ngst English-speaking prespectors and mining engineers."—Engineering.

THE MINER'S HANDBOOK.

A Handy Book of Reference on the subjects of Mineral Deposits, Mining Operations, Ore Dressing, &c. For the Use of Students and others interested in Mining Matters. Compiled by JOHN MILNE, F.R.S., Professor of Mining in the Imperial University of Japan. Third Edition. Fcap. 8vo, leather 7/8 "Protessor Milne's handbook is sure to be received with favour by all connected with mining, and will be extremely popular among students."—Athenaum

IRON ORES of GREAT BRITAIN and IRELAND.

Their Mode of Occurrence, Age and Origin, and the Methods of Searching for and Working Them. With a Notice of some of the Iron Ores of Spain. By J. D. KENDALL, F.G.S., Mining Engineer. Crown 8vo, cloth .

MINE DRAINAGE.

HORIZONTAL PUMPING ENGINES.—ROTARY AND NON-ROTARY HORIZONTAL ENGINES.—SIMPLE AND COMPOUND STEAM PUMPS.—VERTICAL PUMPING ENGINES.—ROTARY AND NON-ROTARY VERTICAL ENGINES.—SIMPLE AND COMPOUND STEAM PUMPS.—PULSATING STEAM PUMPS.—PULSATING STEAM PUMPS.—PULSATING STEAM PUMPS.—PUMPS.—PULSATING STEAM PUMPS.—PU PUMPS. — TRIPLE-EXPANSION STEA VALVES.—SINKING PUMPS, &c., &c.

"This volume contains an immense amount of important and interesting new matter. The book should undoubtedly prove of great use to all who wish for information on the sabett."—The Engineer.

ELECTRICITY AS APPLIED TO MINING.

By ARNOLD LUPTON, M.Inst.C.E., M.I.M.E., M.I.E.E., late Professor or Coal Mining at the Yorkshire College, Victoria University, Mining Engineer and Colliery Manager; G. D. ASPINALL PARR, M.I.E.E., A.M.I.M.E., ASSOCIATE of the Central Technical College, City and Guilds of London, Head of the Electrical Engineering Department, Yorkshire College, Victoria University; and HERBERT PERKIN, M.I.M.E., Certificated Colliery Manager, Assistant Lecturer in the Mining Department of the Yorkshire College, Victoria University. With about 170 Illustrations. Medium 8vo, cloth.

For SUMMARY OF CONTENTS, see page 23.)

THE COLLIERY MANAGER'S HANDBOOK.

A Comprehensive Treatise on the Laying out and Working of Collieries, Designed as a Book of Reference for Colliery Managers, and for the Use of Coal-Mining Students preparing for First-class Certificates. By CALER PAMELY, Mining Engineer and Surveyor; Member of the North of England Institute of Mining and Mechanical Engineers; and Member of the South Wales Institute of Mining Engineers. With over 1,000 Diagrams, Plans, and other Illustrations. Fifth Edition, Carefully Revised and Greatly Enlarged. 1,200 pp. Medium 8vo, cloth.

Unit Published. Net 21 5s.

MEGIUM 8VO, CIOIN.

GBOLOGY.—SBARCH FOR COAL—MINERAL LEASES AND OTHER HOLDINGS.—
SHART SINKING.—FITTING UP THE SHAFT AND SURFACE ARRANGEMENTS.—STRAM
BOILERS AND THEIR FITTINGS.—TIMBERING AND WALLING.—NARROW WORK AND
METHODS OF WORKING.—UNDERGROUND CONVEYANCE.—DRAINAGE.—THE GASES
MET WITH IN MINES; VENTILATION.—ON THE FRICTION OF AIR IN MINES.—THE
PRIESTMAN OIL ENGINE; PETROLEUM AND NATURAL GAS.—SURVEYING AND
PLANNING.—SAPETY LAMPS AND FIREDAMP DETECTORS.—SUNDRY AND INCIDENTAL
OPERATIONS AND APPLIANCES.—COLLIERY EXPLOSIONS.—MISCELLANBOUS QUESTIONS
AND ANSWERS.—Appendix; SUMMARY OF REPORT OF H.M. COMMISSIONERS ON
ACCIDENTS IN MINES.

"Mr. Pamely's work is eminently suited to the purpose or which it is intended, being clear, mercesting, exhaustive, rich in detail, and up to date, giving descriptions of the latest machines in wery department. A mining engineer could scarcely go wrong who followed this work."—Colliery Chapteriers.

"Mr. Pamely has not only given us a comprehensive reference book of a very high order satisable to the requirements of mining engineers and colliery managers, but has also provident mining students with a class-book that is as interesting as it is instructive."—Colliery Manager.

"This is the most complete 'all-round' work on coal-mining published in the English language.... No library of coal-mining books is complete without it."—Colliery Register Scranton, Pa, U.S.A.).

PRACTICAL COAL-MINING.

An Elementary Class-Book for the Use of Students attending Classes in Preparation for the Board of Education and County Council Examinations, or Qualifying for First or Second Class Colliery Managers' Certificates. By T. H. COCKIN, Member of the Institution of Mining Engineers, Certificate Colliery Manager, Lecturer on Coal-Mining at Sheffield University College. With Map of the British Coal-fields and over 200 Illustrations specially Drawn and Engraved for the Work. Crown 8vo, 440 pp. [Just Published. Net 4'6

COLLIERY WORKING AND MANAGEMENT.

Compassing the Duties of a Colliery Manager, the Oversight and Arrangement of Labour and Wages, and the different Systems of Working Coal Seams. By H. F. Bulman and R. A. S. Redmanne. 350 pp., with a8 Plates and other Illustrations, including Underground Photographs. Medium 8vo, cloth.

"This is, indeed, an admirable Handbook for Colliery Managers, in fact it is an indispensable adjunct to a Colliery Managers's education, as well as being a most useful and interesting work on the subject for all who in any way have to do with coal mining. The underground protographs are an attractive feature of the work, being very lifelike and necessarily true representations of the scenes they depict."—Callery Geardian.

"Mr. Bulman and Mr. Redmayne, are to be congratulated on having supplied an authoritative work dealing with a side of the subject of coal mining which has hitherto received but scant treatment. The illustrations are excellent."—Nature.

COAL AND COAL MINING.

NOTES AND FORMULÆ FOR MINING STUDENTS.

By John Herman Merivale, M.A., Late Professor of Mining in the Durham College of Science, Newcastle-upon-Tyne. Fourth Edition, Revised and Enlarged. By H. F. Bulman, A.M.Inst.C.E. Small crown 8vo, cloth. 2/6

"The author has done his work in a creditable manner, and has produced a book that will be of service to students and those who are practically engaged in mining operations."—Engineer,

INFLAMMABLE GAS AND VAPOUR IN THE AIR

(The Detection and Measurement of). By Frank Clowes, D.Sc., Lond., F.I.C. With a Chapter on The Detection and Measurement of Petro-Leum Vapour, by Boverton Redwood, F.R.S.E. Crown 8vo, cloth. Nat 5/0

"Professor Clowes has given us a volume on a subject of much industrial importance...

Those interested in these matters may be recommended to study this book, which is easy of comprehension and contains many good things."—The Engineer.

COAL & IRON INDUSTRIES of the UNITED KINGDOM.

ASBESTOS AND ASBESTIC.

16/0

GRANITES AND OUR GRANITE INDUSTRIES.

By GEORGE F. HARRIS, F.G.S. With Illustrations. Crown 8vo, cloth 2/6

TRAVERSE TABLES.

For use in Mine Surveying. By WILLIAM LINTERN, C.E. With two plates Small crown 8vo, cloth Net 3/0

ELECTRICITY. ELECTRICAL ENGINEERING, ETC.

THE ELEMENTS OF ELECTRICAL ENGINEERING.

A First Year's Course for Students. By Tyson Sewell, A.I.E.E., Assistant Lecturer and Demonstrator in Electrical Engineering at the Polytechnic, Regent Street, London. Second Edition, Revised, with Additional Chapters on Alternating Current Working, and Appendix of Questions and Answers. 450 pages, with 274 Illustrations. Demy 8vo, cloth. [Just Published. Net 7/6]

450 pages, with 274 Illustrations. Demy 8vo, cloth. [/wst Published. Net 7/6]
Ohm's Law.—Units Employed in Electrical Engineering.—Series and
Parallel Circuits; Current Density and Potential Drop in the CircuitThe Heating Effect of the Electric Current.—The Magnetic Effect of an
Electric Current.—The Magnetisation of Iron.—Electro-Chemistry; Primary
Batteries.—Accumulators.—Indicating; Instruments; Ambeters, Ohmmeters.—Electricity Supply Meters.—Measuring Instruments, and the
Measurement of Electrical Resistance.—Measurement of Potential Difperence, Capacity, Current Strength, and Permeability.—Arc Lamps.—IncanDescent Lamps; Manufacture and Installation; Photometry.—The ConTinuous Current Dynamo.—Direct Current Motors.—Alternating Currents.
—Transformers, Alternators, Synchronous Motors.—Polyphase Working.—
Appendix of Questions and Answers.

"An excellent reating for sudgest of the elementary facts, connected with electros."

"An excellent treatise for students of the elementary facts connected with electrical engineering."—The Electrician.
"One of the best books for those commencing the study of electrical engineering. Everything is explained in simple language which even a beginner cannot fail to understand."—Engineer.
"One welcomes this book, which is sound in its treatment, and admirably calculated to give students the knowledge and information they most require."—Nature.

THE ELECTRICAL TRANSMISSION OF ENERGY.

A Manual for the Design of Electrical Circuits. By ARTHUR VAUGHAN ABROTT, C.E., Member American Institute of Electrical Engineers, Member American Institute of Mining Engineers, Member American Society of Civil Engineers, Member American Society of Mechanical Engineers, &c. With Jen Folding Diagrams and Sixteen Full-page Engravings. Fourth Edition, entirely Re-Written and Enlarged. Royal 8vo. cloth.

[/ust Published. Net 300

CONDUCTORS FOR ELECTRICAL DISTRIBUTION.

CONDUCTOR MATERIALS—ALLOVED CONDUCTORS—MANUFACTURE OF WIRE—WIRE-FINISHING—WIRE INSULATION—CABLES—CALCULATION OF CIRCUITS—KELVINISHING—CONDUCTORS—MULTIPLE ARC DISTRIBUTION—ALTERNATING CURRENT CALCULATION—OVERHEAD LINES—POLE LINE—LINE INSULATORS—UNDERGOUND CONDUCTORS.

WIRELESS TELEGRAPHY:

Its Origins, Development, Inventions, and Apparatus. By CHARLES HENRY SEWALL. With 85 Diagrams and Illustrations. Demy 8vo, cloth. [Just Published. Net 10/8]

ELECTRICITY AS APPLIED TO MINING.

By Arnold Lupton, M.Inst C.E., M.I.M.E., M.I.E.E., late Professor of Coal Mining at the Yorkshire College, Victoria University, Mining Engineer and Colliery Manager; G. D. ASPINALL PARR, M.I.E.E., A.M.I.M.E., Associate of the Central Technical College, City and Guilds of London, Head of the Electrical Engineering Department, Yorkshire College, Victoria University; and Herrare Perrin, M.I.M.E., Certificated Collery Manager, Assistant Lecturer in the Mining Department of the Yorkshire College, Victoria University. With about 170 Illustrations. Medium 8vo, cloth. Net 9/-

VICTORIA UNIVERSITY. With about 170 Illustrations. Medium 8vo, cloth. Net 9/=
INTRODUCTORY. — DYNAMIC ELECTRICITY. — DRIVING OF THE DYNAMO. — THE
STEAM TUREBUR.—DISTRIBUTION OF ELECTRICAL ENERGY.—STARTING AND STOPPING
ELECTRICAL GENERATORS AND MOTORS.—ELECTRIC CARLES.—CENTRAL ELECTRICAL
PLANTS.—ELECTRICITY APPLIED TO PUMPING AND HAULING.—ELECTRICITY APPLIED TO COALCUTTING.—TYPICAL ELECTRIC PLANTS RECENTLY ERRCTED.—ELECTRICITY
AND COMPARED WITH OTHER MOLES OF TRANSMITTING POWER.—
DANGERS OF ELECTRICITY,

DYNAMO, MOTOR AND SWITCHBOARD CIRCUITS FOR ELECTRICAL ENGINEERS.

A Practical Book dealing with the subject of Direct, Alternating and Polyphase Currents. By WILLIAM R. BOWKER, C.E., M.E., E.E., Consulting Tramway Engineer. 8vo, cloth. [Just Published. Net 6/0]

DYNAMO ELECTRIC MACHINERY: its CONSTRUC-TION, DESIGN, and OPERATION.

By SAMUEL SHELDON, A M., Ph.D., Professor of Physics and Electrical Engineering at the Polytechnic Institute of Brooklyn, assisted by Hobart MASON, B.S.

Vol. II.-ALTERNATING CURRENT MACHINES. Large crown 8vo. 260 pages, with 184 Illustrations .

Designed as Text-books for use in Technical Educational Institutions, and by Engineers of one work includes the handling of Direct and Alternating Current Machines respectively, and for Students proficient in mathematics.

ARMATURE WINDINGS OF DIRECT CURRENT DYNAMOS.

ELECTRICAL AND MAGNETIC CALCULATIONS.

For the Use of Electrical Engineers and Artisans, Teachers, Students, and all others interested in the Theory and Application of Electricity and Magnetism. By A. A. Atkinson, Professor of Electricity in Ohio University. Crown 8vo.

"To teachers and those who already possess a fair knowledge of their subject we can recommend this book as being useful to consult when requiring data or formulæ which it is neither convenient nor necessary to retain by memory."—The Electrician.

SUBMARINE TELEGRAPHS.

Their History, Construction, and Working. Founded in part on WÜNSCHENDORFF'S "Traité de Télégraphie Sous-Marine," and Compiled from Authoritative and Exclusive Sources. By CHARLES BRIGHT, F.R.S.E., A.M.Inst.C.E.,
M.I. E.E., 780 pp., fully Illustrated, including Maps and Folding Plates.
Royal 8vo, cloth. Net 23 3a.

"There are few, if any, persons more fitted to write a treatise on submarine telegraphy than Mr. Charles Bright. He has done his work admirably, and has written in a way which will as neal as much to the layman as to the engineer. This admirable volume must, for many years to come, hold the position of the English classic on submarine telegraphy."—Engineer:

"This book is full of information. It makes a book of reference which should be in every engineer's library."—Nature.

THE ELECTRICAL ENGINEER'S POCKET-BOOK.

Consisting of Rules, Formulæ, Tables, and Data. By H. R. Kempe, M.I.E.E., A.M.Inst.C.E., Technical Officer Postal Telegraphs, Author of "A Handbook of Electrical Testing," &c. Second Edition, thoroughly Revised, with Additions. With numerous Illustrations. 33mo, leather 5/0

It is the best book of its kind."—*Electrical Engineer*.
"The Electrical Engineer's Pocket-Book is a good one."—*Electrician*.
"Strongly recommended to those engaged in the electrical industries."—*Electrical Review*.

POWER TRANSMITTED BY ELECTRICITY.

And applied by the Electric Motor, including Electric Railway Construction. By P. Atkinson, A.M., Ph.D. Third Edition, Fully Revised, and New Matter added. With 94 Illustrations. Crown 8vo, cloth . . . Net 9/0

DYNAMIC ELECTRICITY AND MAGNETISM.

By PHILIP ATKINSON, A.M., Ph.D., Author of "Elements of Static Electricity." &c. Crown 8vo, 417 pp., with 120 Illustrations, cloth . 10/6

THE MANAGEMENT OF DYNAMOS.

HANDBOOK FOR THE USE OF ELECTRICIANS.

In the Operation and Care of Electrical Machinery and Apparatus of the U. S. Sea-Coast Defences. By Geo. L. Anderson, A.M., Captain U. S. Artillery. Prepared under the direction of the Lieutenant-General Commanding the U. S. Army. Royal 8vo, cloth Net 21/0

THE STANDARD ELECTRICAL DICTIONARY.

A Popular Encyclopedia of Words and Terms Useu in the Financian Supering Containing upwards of 3,000 definitions. By T. O'CONOR SLOAME, A.M., Ph.D. Third Edition, with Appendix. Crown 8vo, 690 pp., Net 7/6

300 Mill. A. M., Fil.D. I first Edition, with Appendix. Grown vot, out of the control of the con

ELECTRIC LIGHT FITTING.

A Handbook for Working Electrical Engineers, embodying Practical Notes on Installation Management. By J. W. URQUHART. With numerous Illustrations. Fourth Edition, Revised. Crown 8vo, cloth
"This volume deals with the mechanics or electric lighting, and is addressed to men who are already engaged in the work, or are training for it. The work traverses a great deal of ground, and may be read as a sequel to the author's useful work on Electric Light." "Bleevictian."

ELECTRIC LIGHT.

Its Production and Use, Embodying Plain Directions for the Treatment of

DYNAMO CONSTRUCTION.

A Practical Handbook for the Use of Engineer-Constructors and Electriciansin-Charge. Embracing Framework Building, Field Magnet and Armature
Winding and Grouping, Compounding, &c. By J. W. URQUHART. Second
Edition, Enlarged, with rxt Illustration. Crown 8vo, cloth . 7/8

"Mr. Urquhart's book is the first one which deals with these matters in such a way that the
engineering student can understand them. The book is very readable, and the author leads his
realers up to difficult subjects by reasonably simple tests."—Engineering Review.

ELECTRIC SHIP-LIGHTING.

ELECTRIC LIGHTING (ELEMENTARY PRINCIPLES OF).

ELECTRIC LIGHT FOR COUNTRY HOUSES.

HOW TO MAKE A DYNAMO.

A Practical Treatise for Amateurs. Containing Illustrations and Detailed Instructions for Constructing a Small Dynamo to Produce the Electric Light. By ALFRED CROFTS. Sixth Edition, Revised. Crown 8vo, cloth . 2/0

THE STUDENT'S TEXT-BOOK OF ELECTRICITY.

By H. M. Ngap, F.R.S. 650 pp., with 470 Illustrations. Crown 8vo, cloth.

ARCHITECTURE, BUILDING, ETC.

SPECIFICATIONS IN DETAIL.

By Frank W. Macry, Architect, Author of "Conditions of Contract. Second Edition, Revised and Enlarged, containing 644 pp., and 2,000 Illustrations. Royal 8vo, cloth.

[] ust Published. Net 21/0

tions. Royal 8vo, cloth.

Summary of Contents:—General Notes (including Points in Specification)
Writing, The Order of a Specification, and Notes on Items offen Omitted
From a Specification,—Form of Outside Cover to a Specification,—Specification,
From a Specification,—Form of Outside Cover to a Specification,—Specification,—Specification,—Specification,—Specification,—Specification,—Preliminary Items (including
Shoring and House Breaker),—Dranmage (including Rain-water Wells and
Reports),—Excavator (including Concrete Floors, Roofs, Stairs, and Walls),
—Pavior,—Bricklayer (including Concrete Floors, Roofs, Stairs, and Walls),
—Pavior,—Bricklayer (including Concrete Floors, Roofs, Stairs, and Walls),
—Mason.—Cappenter, Joiner and Irommonger (including Fencing and Piling),
Mason.—Cappenter, Joiner and Irommonger (including Fencing and Piling),
Smith and Founder (including Heating, Fire Hydrants, Stabe and Cow-House
Fittings).—Slater (including Slate Mason).—Tiler.—Stone Tiler.—Shingler.—
Thatcher, —Plumber (including Hot-water work).—Zincworker.—Copper.
Smith.—Plasterer.—Gaspeitter.—Bellhanger.—Glazier.—Painter.—Paper.
Hanger.—General Repairs and Alterations.—Ventilation.—Road-making.—
Electric Lighting.—Index.

PRACTICAL BUILDING CONSTRUCTION.

A Handbook for Students Preparing for Examinations, and a Book of Reference for Persons Engaged in Building. By John Parnell Allen, Surveyor, Lecturer on Building Construction at the Durham College of Science, Newcastle-on-Type. Fourth Edition, Revised and Enlarged. Medium 8vo, 570 pp., with over 1,000 Illustrations, cloth.

[Just Published. Net 7/8

"The most complete exposition of building construction we have seen. It contains all that is eccessry to prepare students for the various examinations in building construction."—Building

News. "The author depends nearly as much on his diagrams as on his type. The pages suggest the hand of a man of experience in building operations—and the volume must be a blessing to many teachers as well as to students."—The Architect.

PRACTICAL MASONRY.

A Guide to the Art of Stone Cutting. Comprising the Construction, Setting Out, and Working of Stairs, Circular Work, Arches, Niches, Domes, Pendentives, Vaults, Tracery Windows, &c.; to which are added Supplements relating to Masonry Estimating and Quantity Surveying, and to Building Stones and Marbles, and a Glossary of Terms. For the Use of Students, Masons, and Craftsmen. By WILLIAM R. PURCHASE, Building Inspector to the Borough of Hove. Fifth Edition, Enlarged. Royal 8vo, 226 pp., with 32 Lithographic Plates, comprising over 400 Diagrams, cloth.

[Just Published. Net 7/6]

The book is a practical treatise on the subject, the author himself having commenced as an operative mason, and afterwards acted as foreman mason on many large and important buildings prior to the attainment of his present position. Most of the examples given are fi.m actual work carried out. It should be found of general utility to architectural sudents and others, as well as those to whom it is specially addressed."—Journal of the Repail Institute of British Architectur.

MODERN PLUMBING. STEAM AND HOT WATER HEATING.

A New Practical Work for the Plumber, the Heating Engineer, the Architect, and the Builder. By J. J. LAWLER, Author of "American Sanitary Plumbing, &c. With 284 Illustrations and Folding Plates. 4to, cloth . Net 21/-

HEATING BY HOT WATER,

VENTILATION AND HOT WATER SUPPLY.

By WALTER JONES, M.I.M.E. 360 pages, with 140 Illustrations.

(Just Published. Net 6/0

CONCRETE: ITS NATURE AND USES.

A Book for Architects, Builders, Contractors, and Clerks of Works. By GEORGE L. SUTCLIFFE, A.R.I.B.A. Second Edition, thoroughly Revised and Enlarge 1. 396 pp., with Illustrations. Crown 8 vo, clot. [Just Published. Net 9/0]

"The author treats a difficult subject in a lucid manner. The manual fills a long-felt gap. It is careful and exhaustive; equally useful as a student's guide and an architect's book of reference."— Journal of the Reyal Institute of Parisits Architects,

LOCKWOOD'S BUILDER'S PRICE BOOK for 1008.

A Comprehensive Handbook of the Latest Prices and Data for Builders, Architects, Engineers, and Contractors. Re-constructed, Re-written, and Greatly Enlarged. By Francis T. W. Miller. 800 closely-printed pages, crown 8vo, cloth.

"This book is a very useful one, and should find a place in every English office connected with the building and engineering professions."—Instastries.

"An excellent book of reference."—Architect.
"Cumpre sensive, reliable, well arranged, legible, and well bound."—British Architect.

MEASURING AND VALUING ARTIFICERS' WORK

(The Student's Guide to the Practice of). Containing Directions for taking Dimensions, Abstracting the same, and bringing the Quantities into Bill, with Tables of Constants for Valuation of Labour, and for the Calculation of Areas and Solidities. Originally edited by E. Dosson, Architect. With Additions by E. W. Tarn, M.A. Seventh Edition, Revised. Crown 8vo, cloth. 7/6 "The most complete treatise on the principles of measuring and valuing artificers' work.

-Building News.

TECHNICAL GUIDE, MEASURER, AND ESTIMATOR.

For Builders and Surveyors. Containing Technical Directions for Measuring Work in all the Building Trades, Complete Specifications for Houses, Roads, and Drains, and an Easy Method of Estimating the parts of a Building collectively. By A. C. Braton. Ninth Edition. Waistcoat-pocket size. 1/6 "No builder, architect, surveyor, or valuer should be without his 'Beaton,' "-Building News.

THE HOUSE-OWNER'S ESTIMATOR.

Or, What will it Cost to Build, Alter, or Repair? A Price Book for Un-professional People as well as the Architectural Surveyor and Builder. By J. D. SIMON. Edited by F. T. W. MILLER, A.R.I.B.A. Fifth Edition. Carefully Revised. Crown 8vo, cloth. . Net 3/6 "In two years it will repay its cost a hundred times over."-Field.

SPECIFICATIONS FOR PRACTICAL ARCHITECTURE.

A Guide to the Architect, Engineer, Surveyor, and Builder. Upon the Basis of the Work by A BARTHOLOMEW, Revised, Corrected, and greatly added to by F. ROGERS, Architect. Third Edition. 8vo, cloth 15/0 "One of the books with which every young architect must be equipped."-Architect.

ARCHITECTURAL PERSPECTIVE.

"It is the most intelligible of the treatises on this ill-treated subject that I have met with . I. INGRESS BELL, ESQ., in the R.I.B.A. Journal.

PRACTICAL RULES ON DRAWING.

For the Builder and Young Student in Architecture. By G. PYNE. 4to. 2/6

THE MECHANICS OF ARCHITECTURE.

A Treatise on Applied Mechanics, especially Adapted to the Use of Architects. By E. W. Tarn, M.A., Author of "The Science of Building," &c. Second Edition, Enlarged. Illustrated with 125 Diagrams. Crown 8vo, cloth 7/6 "The book is a very useful and helpful manual of architectural mechanics."-Builder.

A HANDY BOOK OF VILLA ARCHITECTURE.

Being a Series of Designs for Villa Residences in various Styles. With Outline Specifications and Estimates. By C. Wickes, Architect, Author of "The Spires and Towers of England," &c. 61 Plates, 4to, half-morocco, gilt . £1 11s. 6s.

DECORATIVE PART OF CIVIL ARCHITECTURE.

THE ARCHITECT'S GUIDE.

Being a Text-book of Useful Information for Architects, Engineers, Surveyors, Contractors, Clerks of Works, &c. By F. Rogers. Crown 8vo. . 3/6

SANITATION AND WATER SUPPLY.

THE PURIFICATION OF SEWAGE.

Being a Brief Account of the Scientific Principles of Sewage Purification, and their Practical Application. By SIDNEY BARWISE, M.D. (Lond.), B.Sc., M.R.C.S., D.P.H. (Camb.), Fellow of the Sanitary Institute. Medical Officer of Health to the Derbyshire County Council. Second Edition, Revised and Enlarged, with an Appendix on the Analysis of Sewage and Sewage Effluents. Wi h numerous Illustrations and Diagrams. Demy 8vo, cloth.

[Inst published. Net 10/6

THE HEALTH OFFICER'S POCKET-BOOK.

A Guide to Sanitary Practice and Law. For Medical Officers of Health, Sanitary Inspectors, Members of Sanitary Authorities, &c. By EDWARD F. WILLOUGHBY, M.D. (Lond.), &c. Second Edition, Revised and Enlarged. Net Fcap. 8vo, leather

"A mine of condensed information of a pertinent and useful kind. The various subjects of which it treats remy succinctly but fully and scentifically dealt with."—The Lance.
"We recommend all those engaged in practical sanitary work to furnish themselves with a copy for reference."—Sanitary Journal.

WATER AND ITS PURIFICATION.

A Handbook for the Use of Local Authorities, Sanitary Officers, and others interested in Water Supply. By S. RIDRAL, D.Sc. Lond., F.I.C. Second Edition, Revised, with Additions, including numerous Illustrations and Tables. Large Crown 8vo. cloth .

RURAL WATER SUPPLY.

A Practical Handbook on the Supply of Water and Construction of Water-works for Small Country Districts. By ALLAN GREENWELL, A.M.I.C.E., and W. T. Curry, A.M.I.C.E. Revised Edition. Crown 8vo, cloth 5/0

THE WATER SUPPLY OF CITIES AND TOWNS.

By WILLIAM HUMBER, A.M. Inst. C.E., and M.Inst. M.E. Imp. 4to, halfbound morocco. (See page 11.) . Net £6 6s.

THE WATER SUPPLY OF TOWNS AND THE CONSTRUCTION OF WATER-WORKS. By PROPESSOR W. K. BURTON, A.M. Inst. C.E. Second Edition, Revised

and Extended. Royal 8vo, cloth. (See page 10.) .

WATER ENGINEERING.

A Practical Treatise on the Measurement, Storage, Conveyance, and Utilisation of Water for the Supply of Towns. By C. SLAGG, A.M. Inst. C.E. 7/8

SANITARY WORK IN SMALL TOWNS AND VILLAGES. By CHARLES SLAGG, A. M. Inst. C.E. Crown 8vo, cloth . . .

PLUMBING.

A Text-book to the Practice of the Art or Craft of the Plumber. By W. P. Buchan. Ninth Edition, Enlarged, with 500 Illustrations. Crown 8vo, 3/6

VENTILATION.

A Text-book to the Practice of the Art of Ventilating Buildings. By W. P. · 3/6

CARPENTRY, TIMBER, ETC.

THE ELEMENTARY PRINCIPLES OF CARPENTRY.

A Treatise on the Pressure and Equilibrium of Timber Framing, the Resistance A Treatise on the Pressure and Equilibrium of Timber Framing, the Resistance of Timber, and the Construction of Floors, Arches, Bridges, Roofs, Uniting Iron and Stone with Timber, &c. To which is added an Essay on the Nature and Properties of Timber, &c., with Descriptions of the kinds of Wood used in Building; also numerous Tables of the Scantlings of Timber for different purposes, the Specific Gravities of Materials, &c. By Thomas Tredold, C. With an Appendix of Specimens of Various Roofs of Iron and Stone, Illustrated. Seventh Edition, thoroughly Revised and considerably Enlarged by E. Wyndham Tarn, M.A., Author of "The Science of Building," &c. With 67 Plates, Portrait of the Author, and several Woodcuts. In One large Vol.. 420. cloth Vol., 4to, cloth .

"Ought to be in every architect's and every builder's library."—Builder.

"A work whose monumental excellence must commend it wherever skilful carpentry is concerned. The author's principles are rather confirmed than impaired by time. The additional plates are of great intrinsic value."—Building News

WOODWORKING MACHINERY.

Its Rise, Progress, and Construction. With Hints on the Management of Saw Mills and the Economical Conversion of Timber. Illustrated with Examples of Recent Designs by leading English, French, and American Engineers. By M. Powis Balls, A.M. Inst. C.E., M.I.M.E. Second Edition, Revised, with large Additions, large crown 8vo, 440 pp., cloth

"Mr. Bale is evidently an expert on the subject, and he has collected so such information that his book is all-sufficient for builders and others engaged in the conversion of timber."—Architect.
"The most comprehensive compendant of wood-working machinery we have seen. The author is a thorough master of his subject."—Building News.

SAW MILLS.

Their Arrangement and Management, and the Economical Conversion of Timber. By M. Powis Bale, A.M.Inst.C.E. Second Edition, Revised. Crown 8vo, cloth. . . .

"The administration of a large sawing establishment is discussed, and the subject examined rom a financial standpoint. Hence the size, shape, order, and disposition of saw mills and the like re gone into in detail, and the course of the timber is traced from its reception to its delivery in its converted state. We could not desire a more complete or practical treatine."—Builder.

THE CARPENTER'S GUIDE.

Or, Book of Lines for Carpenters; comprising all the Elementary Principles essential for acquiring a knowledge of Carpentry. Founded on the late PETER NICHOLSON'S standard work. A New Edition, Revised by ARTHUR ASHPITEL, F.S.A. Together with Practical Rules on Drawing, by GEORGE PYNE.
With 74 Plates, 4to, cloth

A PRACTICAL TREATISE ON HANDRAILING.

Showing New and Simple Methods for Finding the Pitch of the Plank, Drawing Showing New and Simple methods for Finding the Fitch of the Plank, Drawing the Moulds, Bevelling, Jointing-up, and Squaring the Wreath. By George Collings. Revised and Enlarged, to which is added A Treatise on STAIR-BUILDING. Third Edition. With Plates and Diagrams. 12mo, cloth. 2/6

"Will be found of practical utility in the execution of this difficult branch of Joinery."—Busilder.

"Almost every difficult phase of this somewhat intricate branch of Joinery is elucidated by the aid of planes and explanatory letterpress."—Furnitary Cassetts.

CIRCULAR WORK IN CARPENTRY AND JOINERY.

A Practical Treatise on Circular Work of Single and Double Curvature. By GEORGE COLLINGS. With Diagrams. Fourth Edition, 12mo, cloth . 2/6 "An excellent example of what a book of this kind should be. Cheep in price, clear in definition, and practical in the examples selected."—Builder.

THE CABINET-MAKER'S GUIDE TO THE ENTIRE CONSTRUCTION OF CABINET WORK. By RICHARD BITMEAD. Illustrated with Plans, Sections and Working

HANDRAILING COMPLETE IN EIGHT LESSONS.

On the Square-Cut System. By J. S. GOLDTHORP, Teacher of Geometry and Building Construction at the Halifax Mechanics' Institute. With Right Plates and over 150 Practical Exercises. 4to, cloth ... 3/6
"Likely to be of considerable value to joiners and others who take a pride in good work. The arrangement of the book is excellent. We heartly commend it to teachers and students."—The arrangement of the book is excellent.

TIMBER MERCHANT'S and BUILDER'S COMPANION.

Containing New and Copious Tables of the Reduced Weight and Measurement of Deals and Battens, of all sizes, and other Useful Tables for the use of Timber Merchants and Bullders. By WILLIAM DOWSING. Fourth Edition, Revised and Corrected. Crown 8vo, cloth 3/0

"We are glad to see a fourth edition of these admirable tables, which for correctness and simplicity of arrangement leave nothing to be desired."—Timber Trades Journal.

THE PRACTICAL TIMBER MERCHANT.

Being a Guide for the Use of Building Contractors, Surveyors, Builders, &c., comprising useful Tables for all purposes connected with the Timber Trade, Marks of Wood, Essay on the Strength of Timber, Remarks on the Growth of Timber, &c. By W. RICHARDSON. Second Edition. Fcap. 8vo, cloth . 3/8.

"This handy manual contains much valuable information for the use of timber weathers."

"This handy manual contains much valuable information for the use of timber merchants, builders, foresters, and all others connected with the growth, sale, and manufacture of timber."—

Fournal of Forestry.

PACKING-CASE TABLES.

"Invaluable labour-saving tables."—Ironmonger.
"Will save much labour and calculation."—Grocer.

GUIDE TO SUPERFICIAL MEASUREMENT.

Tables calculated from x to 200 inches in length by x to x08 inches in breadth. For the use of Architects, Surveyors, Engineers, Timber Merchants, Builders, &c. By James Hawkings. Fifth Edition. Fcap., cloth. 3/6
"These tables will be found of great assistance to all who require to make calculations of superficial measurement."—Engitish Mechanic.

PRACTICAL FORESTRY.

And its Bearing on the Improvement of Estates. By CHARLES E. CURTIS, F.S.I., Professor of Forestry, Field Engineering, and General Estate Management, at the College of Agriculture, Downton. Second Edition, Revised. Crown 8vo, cloth 3/6

Revised. Crown 8vo, cion

PREFATORY REMARKS. - OBJECTS OF PLANTING. - CHOICE OF A FORESTER. CHOICE OF SOIL AND SITE. - LAYING OUT OF LAND FOR PLANTATIONS. - PREPARATION
OF THE GROUND FOR PLANTING. - DRAINAGE. - PLANTATIONS. - PREPARATION
BUTION OF TREES IN PLANTATIONS. - TREES AND GROUND GAME. - ATTENTION AFTER
PLANTING. - THINNING OF PLANTATIONS - PRUNING OF FOREST TREES. - REALIZATION.
- METHODS OF SALE. - MEASUREMENT OF TIMBER. - MEASUREMENT AND VALUATION
OF LARCH PLANTATION. - FIRE LINES. - COST OF PLANTING.

"Mr. Curtis has in the course of a series of short pithy chapters afforded much information of a useful and practical character on the planting and subsequent treatment of trees."— Illustrated Carpenter and Builder.

THE ELEMENTS OF FORESTRY.

Designed to afford Information concerning the Planting and Care of Forest Trees for Ornament or Profit, with suggestions upon the Creation and Care of Woodlands. By F. B. HOUGH. Large crown 8vo, cloth 10/0

TIMBER IMPORTER'S, TIMBER MERCHANT'S, AND BUILDER'S STANDARD GUIDE.

By RICHARD E. GRANDY. Comprising:—An Analysis of Deal Standards, Home and Foreign, with Comparative Values and Tabular Arrangements for fixing Net Landed Cost on Baltic and North American Deals, including all intermediate Expenses, Freight, Insurance, &c., &c.; together with copious Information for the Retailer and Builder. Third Edition, Revised. 1200, 10th

"Everything it pretends to be: built up gradually, it leads one from a forest to a treenall, and throws in, as a makeweight, a host of material concerning bricks, columns, cisterns, &c."—English McAnsis.

DECORATIVE ARTS, ETC.

SCHOOL OF PAINTING FOR THE IMITATION OF WOODS AND MARBLES.

As Taught and Practised by A. R. VAN DER BURG and P. VAN DER BURG, As Taught and Fractised by A. R. van Dan Directors of the Rotterdam Painting Institution. Royal folio, 18½ by 12½ in., Illustrated with 24 full-size Coloured Plates; also 12 plain Plates, comprising van Figures. Fourth Edition cloth.

154 Figures. Fourth Edition cloth.

1. Various Tools Required for Wood Painting.—4, 2 Walnut; Preliminary Staces of Graining and Finished Specimen.—4, Tools Used for Marbe Painting and Method of Manifulation.—5, 6, 57. Remi Marbel farlier Operations and Finished Specimen.—7, Methods of Sketching Different Grains, Knots, &c.—8, 6, ASI; Preliminary Staces and Finished Specimen.—10, Methods of Vertching Marbels Gradus.—11, 12. Berche Marbels Preliminary Chains, Company of 34. 35. 36. \SPECIMENS.

"Those who desire to attain skill in the art of painting woods and marbles will find advantage in consulting this book. . . . Some of the Working Men's Clubs should give their young men the opportunity to study it."—Builder.

"A comprehensive guide to the art. The explanations of the processes, the manipulation and management of the colours, and the beautifully executed plates will not be the least valuable to the student who aims at making his work a faithful transcript of nature."—Building News.

"Students and novices are fortunate who are able to become the possessors of so noble a work."—The Architects.

ELEMENTARY DECORATION.

HOUSE PAINTING, GRAINING, MARBLING, AND SIGN WRITING.

A Practical Manual of. By ELLIS A. DAVIDSON. Eighth Edition. With Coloured Plates and Wood Engravings. Crown 8vo, cloth . "A mass of information of use to the amateur and of value to the practical man,"-English

THE DECORATOR'S ASSISTANT.

A Modern Guide for Decorative Artists and Amateurs, Painters, Writers, Gilders, &c. Containing upwards of 600 Receipts, Rules, and Instructions; with a variety of Information for General Work connected with every Class of Interior and Exterior Decorations, &c. Eighth Edition. Cr. 8vo

"Full of receipts of value to decorators, painters, gilders, &c. The book contains the gist of larger treatises on colour and technical processes. It would be difficult to meet with a work so full of varied information on the painter's art."—Building News.

MARBLE DECORATION

"This most useful and much wanted handbook should be in the hands of every architect and builder,"—Busideng of orus.
"A carefully and usefully written treatise; the work is essentially practical."—Scottman,

DELAMOTTE'S WORKS ON ILLUMINATION AND ALPHABETS.

ORNAMENTAL ALPHABETS, ANCIENT & MEDIÆVAL.

From the Righth Century, with Numerals; inchading Gothic, Church-Text. large and small, German, Italian, Arabesque, Initials for Illumination, Monograms, Crosses, &c., for the use of Architectural and Engineering Draughtsmen, Missal Painters, Masons, Decorative Painters, Lithographers, Engravers, Carvers, &c., &c. Collected and Engraved by F. Delamotte, and printed in Colours. New and Cheaper Edition. Royal 8vo, oblong, ornamental boards

"For those who insert enamelled sentences round glided chalices, who biason shop legends
over shop-doors, who letter church walls with pithy sentences from the Decalogue, this book will be
useful."—Abenessus.

MODERN ALPHABETS, PLAIN AND ORNAMENTAL.

Including German, Old English, Saxon, Italic, Perspective, Greek, Hebrew, Court Hand, Engrossing, Tuscan, Riband, Gothic, Rustic, and Arabesque; with several Original Designs, and an Analysis of the Roman and Old English Alphabets, large and small, and Numerals, for the use of Draughtsmen, Surveyors, Masons, Decorative Painters, Lithographers, Engravers, Carvers, &c. Collected and Engraved by F. DELAMOTTE, and printed in Colours, New and Cheaper Edition. Royal 8vo, oblong, ornamental boards 2/6

"There is comprised in it every possible shape into which the letters of the alphabet and numerals can be formed, and the talent which has been expended in the conception of the various plain and ornamental letters is wonderful."—Suevalers!

MEDIÆVAL ALPHABETS AND INITIALS.

A PRIMER OF THE ART OF ILLUMINATION.

"The examples of ancient MSS, recommended to the student, which, with much good sense, the author chooses from collections accessible to all, are selected with judgment and knowledge as well as taste."—Atheraum.

THE EMBROIDERER'S BOOK OF DESIGN.

"The book will be of great assistance to ladies and young children who are endowed with the art of plying the needle in this most ornamental and useful pretty work."—East Anglian Times.

WOOD-CARVING FOR AMATEURS.

PAINTING POPULARLY EXPLAINED.

By THOMAS JOHN GULLICK, Painter, and JOHN TIMES, F.S.A. Including Fresco, Oil, Mosaic, Water-Colour, Water-Glass, Tempera, Encaustic, Miniature, Painting on Ivory, Vellum, Pottery, Enamel, Glass, &c. Fifth Edition. Crown 8vo, cloth

, Adopted as a Prize Book at South Kensington.

"Much may be learned, even by those who fancy they do not require to be taught, from the careful perusal of this unpretending but comprehensive treatise."—Art Yournel.

NATURAL SCIENCE, ETC.

THE VISIBLE UNIVERSE.		
Chapters on the Origin and Construction F.R.A.S., Author of "Star Groups," &c. and 12 Plates. Demy 8vo, cloth .	of the Heavens. By J. E. Gorn Illustrated by 6 Stellar Photograph 	i, s O
STAR GROUPS.		
A Student's Guide to the Constellations. M.R.I.A., &c., Author of "The Visible Heavens," &c. With 30 Maps. Small 4to	By J. ELLARD GORE, F.R.A.S. Universe," "The Scenery of the cloth	ŝ
AN ASTRONOMICAL GLOSSAR	Y.	
Or, Dictionary of Terms used in Astronom of Remarkable and Interesting Celestial F.R.A.S., Author of "The Visible University	y. With Tables of Data and List Objects. By J. ELLARD GORE se," &c. Small crown 8vo, cloth. 2/6	is L
THE MICROSCOPE.		
Its Construction and Management. Include and the Past and Future of the Microsco Re-Edited and Augmented from the Foundation of the Founda	pe. By Dr. HENRI VAN HEURCE th French Edition, and Translate	ċ.
A MANUAL OF THE MOLLUS		
A Treatise on Recent and Fossil Shells. F.G.S. With an Appendix on RECE. DISCOVERIES, by RALPH TATE, A.L.S. upwards of 300 Woodcuts. Reprint of cloth	By S. P. WOODWARD, A.L.S. NT AND FOSSIL CONCHOLOGICA S., F.G.S. With 23 Plates an Fourth Edition (1880). Crown 8v.	., Ld 0.6
THE TWIN RECORDS OF CRE	ATION.	
Or, Geology and Genesis, their Perfect By G. W. V. LE VAUX. 8vo, cloth		
LARDNER'S HANDBOOKS O	F SCIENCE.	
HANDBOOK OF MECHANICS	S.	
Enlarged and re-written by B. LOEWY,	F.R.A.S. Post 8vo, cloth . 6/	0
HANDBOOK OF HYDROSTAT	ICS AND PNEUMATICS	š.
Revised and Enlarged by B. Lozwy, F.	R.A.S. Post 8vo, cloth . 5/	0
HANDBOOK OF HEAT.		
Edited and re-written by B. LOEWY, F.	R.A.S. Post 8vo, cloth . 6/	0
HANDBOOK OF OPTICS.		
New Edition. Edited by T. OLVER HAI	RDING, B.A. Small 8vo, cloth 5/	0
ELECTRICITY, MAGNETISM	A, AND ACOUSTICS.	
Edited by GEO. C. FOSTER, B.A. Sms	ıll 8vo, cloth 5/	0
HANDBOOK OF ASTRONOM	Υ.	
Revised and Edited by EDWIN DUNKIN,	F.R.A.S. 8vo, cloth 9/	6
MUSEUM OF SCIENCE AND	D ART.	
With upwards of 1,200 Engravings. In S or half-morocco	ix Double Volumes, £1 1s. Clot	Ь, D.
NATURAL PHILOSOPHY FO	R SCHOOLS 3	6
ANIMAL PHYSIOLOGY FOR		
THE ELECTRIC TELEGRAP		_
Revised by E. B. Bright, F.R.A.S. F		e
	-	_

CHEMICAL MANUFACTURES. CHEMISTRY, ETC.

THE OIL FIELDS OF RUSSIA AND THE RUSSIAN PETROLEUM INDUSTRY.

A Practical Handbook on the Exploration, Exploitation, and Management A Practical randook on the Exporation, Exploitation, and Management of Russian Oil Properties, including Notes on the Origin of Petroleum in Russia, a Description of the Theory and Practice of Liquid Fuel, and a Translation of the Rules and Regulations concerning Russian Oil Properties. By A. Beedy Thompson, A. M. I. M. E., late Chief Engineer and Manager of the European Petroleum Company's Russian Oil Properties. About 500 pp., with numerous Illustrations and Photographic Plates, and a Map of the Balakhany-Saboontchy-Romany Oil Field. Super-royal 8vo, cloth.

[Just Published. Net &R 3a.

THE ANALYSIS OF OILS AND ALLIED SUBSTANCES.

THE GAS ENGINEER'S POCKET-BOOK.

Comprising Tables, Notes and Memoranda relating to the Manufacture, Distribution and Use of Coal Gas and the Construction of Gas Works. By H. O'CONNOR, A.M. Inst. C.E. Second Edition, Revised. 470 pp., crown 8vo.

fully Illustrated, leather.

"The book contains a vast amount of information. The author goes consecutively through the engineering details and practical methods involved in each of the different processes or parts of a gas-works. He has certainly succeeded in making a compilation of hard matters of fact also littly interesting to read."—Gas World.

"The volume contains a great quantity of specialised information, compiled, we believe, from trustworthy sources, which should make it of considerable value to those for whom it is specifically produced."—Engineer.

LIGHTING BY ACETYLENE

Generators, Burners, and Electric Furnaces. By WILLIAM E. GIBBS, M.E. With 66 Illustrations. Crown 8vo. cloth.

ENGINEERING CHEMISTRY.

A Practical Treatise for the Use of Analytical Chemists, Engineers, Iron Masters, Iron Founders, Students and others. Comprising Methods of Analysis and Valuation of the Principal Materials used in Engineering Work, with numerous Analyses, Examples and Suggestions. By H. Joshua Phillips, F.I.C., F.C.S. Third Edition, Revised and Enlarged. Crown 8vo, 4so pp., with Plates and other Illustrations, cloth.

Net 10/6

"In this work the author has rendered no small service to a numerous body of partical seen. . . The analytical methods may be pronounced most satisfactory, being as accurate as the despatch required of engineering chemists permits."—Chemical News.

"The analytical methods given are, as a whole, such as are likely to give rapid and trustworthy results in experienced hands. . There is much excellent descriptive matter in the work, the chapter on 'Olis and Lubrication' being specially noticeable in this respect."—Engineer.

NITRO-EXPLOSIVES.

A Practical Treatise concerning the Properties, Manufacture, and Analysis of Nitrated Substances, including the Fulminates, Smokeless Powders, and Celluloid. By P. GRALD SAMPORD, F.I.C., Consulting Chemist to the Cotton Powder Company, Limited, &c. With Illustrations. Crown 8vo, cloth. 9/0

"One of the very few text-books in which can be found just what is wanted. Mr. Sanford goes steadily through the whole list of explosives commonly used, he names any given explosives, and tells us of what it is composed and how it is manufactured. The book is excellent."—Briginese.

A HANDBOOK ON MODERN EXPLOSIVES.

A Practical Treatise on the Manufacture and Use of Dynamite, Gun-Cotton, Nitro-Glycerine and other Explosive Compounds, including Collodion-Cotton. With Chapters on Explosives in Practical Application. By M. Eissler, M. E. Second Edition, Enlarged. Crown 8vo, cloth 12/6

"A veritable mine of information on the subject of explosives employed for military, mining and blasting purposes."—Army and Navy Gasette.

A MANUAL OF THE ALKALI TRADE.

Including the Manufacture of Sulpburic Acid, Sulphate of Soda, and Bleaching Powder. By JOHN LOMAS, Alkali Manufacturer. With 232 Illustrations and Working Drawings. Second Edition, with Additions. Super-royal 8vo, cloth &1 10e.

"We find not merely a sound and luminous explanation of the chemical principles of the trade, but a notice of numerous matters which have a most important bearing on the successful conduct of alkali works, but which are generally overlooked by even experienced technological suthors."—Chemical Review,

DANGEROUS GOODS.

Their Sources and Properties, Modes of Storage and Transport. With Notes and Comments on Accidents arising therefrom. A Guide for the Use of Government and Railway Officials, Steamship Owners, &c. By H. JOSHUA PHILLIPS, F.I.C., F.C.S. Crown 8vo, 374 pp., cloth 9/0 "Merits a wide circulation, and an intelligent, appreciative study."—Chemical News.

THE BLOWPIPE IN CHEMISTRY, MINERALOGY, Etc.

Containing all known Methods of Anhydrous Analysis, many Working Examples, and Instructions for Making Apparatus. By Lieut. Colonel W. A. Ross, R.A., F.G.S. Second Edition, Enlarged. Crown 8vo, cloth . 5/0

"The student who goes conscientiously through the course of experimentation here ald down full gain a better insight into inorganic chemistry and mineralogy than if he had 'got up' any of the sex text-books of the day, and passed any number of examinations in their contents."—Chemical

THE MANUAL OF COLOURS AND DYE-WARES.

Their Properties, Applications, Valuations, Impurities and Sophistications. For the Use of Dyers, Printers, Drysalters, Brokers, &c. By J. W. SLATER. Second Edition, Revised and greatly Enlarged. Crown 8vo, cloth . 7/8
"There is no other work which covers precisely the same ground. To student. To students for examinations in dyeing and printing it will prove exceedingly useful."—Chemical News.

A HANDYBOOK FOR BREWERS.

Way be consulted with advantage by the student who is preparing himself for examinationa tests, while the scientific brewer will find in it a retrume of all the most important discoveries anodem times. The work is written throughout in a clear and concise manner, and the author takes great care to discriminate between vague theories and well-established facts "—Brewers' Fournal.

"We have great pleasure in recommending this handy book, and have no hesitation is saying that it is one of the best—if not the best—which has yet been written on the subject of beer-brewing in this country; it should have a place on the shelves of every brewer's library."—Brewer's Guerrian.

FUELS: SOLID, LIQUID, AND GASEOUS.

Their Analysis and Valuation. For the Use of Chemists and Engineers. By H. J. Phillips, F.C.S., formerly Analytical and Consulting Chemist to the G.E. Rlwy. Fourth Edition. Crown 8vo, cloth 2/0
"Ought to have its place in the laboratory of every metallurgical establishment and wherever fuel is used on a large scale."—Chemical News.

THE ARTISTS' MANUAL OF PIGMENTS.

Showing their Composition, Conditions of Permanency, Non-Permanency, and Adulterations, &c., with Tests of Purity. By H. C. STANDAGE. Third Edition. Crown 8vo, cloth 2/8

"This work is indeed multum-in-parse, and we can, with good conscience, recommend it to all who come in contact with pigments, whether as makers, dealers, or users."—Chemical Review.

A POCKET-BOOK OF MENSURATION AND GAUGING.

Should be in the hands of every practical brewer."-Brewers' Fournal.

INDUSTRIAL ARTS. TRADES. AND MANUFACTURES.

THE CULTIVATION AND PREPARATION OF PARA RUBBER.

By W. H. Johnson, F.L.S., F.R.H.S., Director of Agriculture, Gold Coast Colony, West Africa, Commissioned by Government in 1902 to visit Ceylon to Study the Methods employed there in the Cultivation and Preparation of Para Rubber and other Agricultural Staples for Market, with a view to Introduce them into West Africa. Demy 8vo, cloth. [Just Published. Net 716 Summary of Contents:—Introductory.—The Para Rubber Tree [Hevas Brasiliens] at Home and Abroad.—Cultivation of the Tree:—Propagation.—Site for Plantation.—Distance Apart to Plant the Trees.—Transplantion.—Site for Plantation.—Insect Pest's and Funcoid Dissasses.—Collecting the Rubber:—Various Methods Employed in Tapping Rubber Trees.—Flow of Later Increased by Wounding the Tree.—How to Tap.—The Preparation of Rubber From the Later:—Later.—Various Methods Employed in the Preparation of Para Rubber, Suggested Method for Preparing Rubber.—Scrap Rubber, Prield of Para Rubber, Gould Coast, West Africa.—Establishment and Maintenance of a Para Rubber and Cold Coast, West Africa.—Establishment and Maintenance of a Para Rubber and Chilidal Commission.—The Aid Carlother Am Achhilied and And The Para Eactophilies. By W. H. Johnson, F.L.S., F R.H.S., Director of Agriculture, Gold Coast

TEA MACHINERY AND TEA FACTORIES.

A Descriptive Treatise on the Mechanical Appliances required in the Cultivation of the Tea Plant and the Preparation of Tea for the Market. By A. J. WALLIS-TAYLER, A. M. Inst. C.E. Medium 8vo, 468 pp. With 218 . Net 25/0 Illustrations SUMMARY OF CONTENTS.

SUMMARY OF CONTENTS.

MECHANICAL CULTIVATION OR TILLAGE OF THE SOIL—PLUCKING OR GATHERING THE LEAF,—TEA FACTORIES.—THE DRESSING, MANUFACTURE, OR PREPARATION OF TEA BY MECHANICAL MEANS.—ARTIFICAL WITHERING OF THE LEAF,—MACHINES FOR ROLLING OR CURLING THE LEAF,—FERMENTING PROCESS.—MACHINES FOR THE AUTOMATIC DRYING OR FIRING OF THE LEAF,—MACHINES FOR NON-AUTOMATIC DRYING OR FIRING OF THE LEAF,—MACHINES.—BREAKING OR CUITING, AND SORTING MACHINES.—PACKING THE TEA.—MEANS.—BREAKING OR CUITING, AND SORTING MACHINES.—PACKING THE TEA.—MEANS.—HISCELLANBOUS MACHINERY AND APPARATUS.—FINAL TREATMENT OF THE TEA.—TABLES AND MEMORANDA.

"The subject of tea machinery is now one of the first interest to a large class of people whom we strongly commend the volume,"—Chamber of Commerce Fournal.

"Contains a very full account of the machinery necessary for the proper outit of a factory, and also a description of the processes best carried out by this machinery,"—Fournal Society of Arts.

FLOUR MANUFACTURE.

COTTON MANUFACTURE.

A Manual of Practical Instruction of the Processes of Opening, Carding, Combing, Drawing, Doubling and Spinning of Cotton, the Methods of Dyeing, &c. For the Use of Operatives, Overlookers, and Manufacturers.

MODERN CYCLES.

MOTOR CARS OR POWER CARRIAGES FOR COMMON ROADS

PRACTICAL TANNING.

A Handbook of Modern Procesess, Receipts, and Suggestions for the Treatment of Hides, Skins, and Pelts of every Description. By L. A. Flemming, American Tanner. 472 pages. 8vo, cloth. [Just Published. Net 25/0]

THE ART OF LEATHER MANUFACTURE.

Being a Practical Handbook, in which the Operations of Tanning, Currying, and Leather Dressing are fully Described, and the Principles of Tanning Explained, and many Recent Processes Introduced; as also Methods for the Stimation of Tannin, and a Description of the Arts of Glue Boiling, Gut Dressing, &c. By Alexander Watt. Fourth Edition. Crown 8vo. cloth.

"A sound, comprehensive treatise on tanning and its accessories. The book is an eminently aluable production, which redounds to the credit of both author and publishers."—Chemical

THE ART OF SOAP-MAKING.

A Practical Handbook of the Manufacture of Hard and Soft Soaps, Toilet Soaps, &c. Including many New Processes, and a Chapter on the Recovery of Glycerine from Waste Leys. By ALEXANDER WATT. Sixth Edition, including an Appendix on Modern Candlemaking. Crown 8vo, cloth. 7/6 "A thoroughly practical treatise. We congratulate the author on the success of his endeavour to fill a void in English technical literature."—Nature.

"The work will prove very useful, not merely to the technological student, but to the practical soup boiler who wishes to understand the theory of his art."—Chemical News.

PRACTICAL PAPER-MAKING.

"The author caters for the requirements of responsible mill hands, apprentices, &c., whilst manual will be found of great service to students of technology, as well as to vectoral parameters and mill owners. The illustrations form an excellent feature."—The World's Pager Frade

THE ART OF PAPER-MAKING.

A Practical Handbook of the Manufacture of Paper from Rags, Esparto, Straw, and other Fibrous Materials. Including the Manufacture of Pulp from Wood Fibre, with a Description of the Machinery and Appliances used. To which are added Details of Processes for Recovering Sods from Waste Liquors. By Alexander Watt. With Illustrations. Crown 8vo, cloth

"It may be regarded as the standard work on the subject. The book is full of valuable information. The 'Art of Paper-Making' is in every respect a model of a text-book, either for a technical class, or for the private student." "Paper and Privating Tradas Journal."

A TREATISE ON PAPER.

For Printers and Stationers. With an Outline of Paper Manufacture; Complete Tables of Sizes, and Specimens of Different Kinds of Paper. By RICHARD PARKINSON, late of the Manchester Technical School. Demy 8vo, cloth 3/6

CEMENTS, PASTES, GLUES, AND GUMS.

A Practical Guide to the Manufacture and Application of the various Agglutinants required in the Building, Metal-Working, Wood-Working, and Leather-Working Trades, and for Workshop and Office Use. With upwards of 900 Recipes. By H. C. STANDAGE. Third Edition. Crown 8vo, cloth 2/0

"We have pleasure in speaking favourably of this volume. So far as we have had experience, which is not inconsiderable, this manual is trustworthy."—Athenaum.

THE CABINET-MAKER'S GUIDE TO THE ENTIRE CONSTRUCTION OF CABINET WORK.

FRENCH POLISHING AND ENAMELLING.

A Practical Work of Instruction. Including Numerous Recipes for making Polishes, Varnishes, Glaze-Lacquers, Revivers, &c. By RICHARD BITMEAD, Author of "The Cabinet-Maker's Guide." Small crown 8vo, cloth . 1/6

WATCH REPAIRING. CLEANING. AND ADJUSTING.

A Practical Handbook dealing with the Materials and Tools Used, and the Methods of Repairing, Cleaning, Altering, and Adjusting all kinds of English and Foreign Watches, Repeaters, Chronographs, and Marine Chronometers. By F. J. GARRARD, Springer and Adjuster of Marine Chronometers and Deck Watches for the Admiralty. With over 200 Illustrations. Crown 8vo, cloth.

[Just Published. Net 4/6]

MODERN HOROLOGY, IN THEORY AND PRACTICE.

THE WATCH ADJUSTER'S MANUAL.

A Practical Guide for the Watch and Chronometer Adjuster in Making, Springing, Timing and Adjusting for Isochronism, Positions and Temperatures By C. E. FRITTS. 370 pp., with Illustrations, 8vo, cloth 16/C

THE WATCHMAKER'S HANDBOOK.

Intended as a Workshop Companion for those engaged in Watchmaking and the Allied Mechanical Arts. Translated from the French of CLAUDIUS SAUNIER, and enlarged by JULIEN TRIPLIN, F.R.A.S., and EDWARD RIGG, M.A., Assayer in the Royal Mint. Third Edition. Cr. 8vo, cloth. 9/0 "Each part is truly a treatise in itself. The arrangement is good and the language is clear and concise. It is an admirable guide for the young watchmaker."—Engineering.

HISTORY OF WATCHES & OTHER TIMEKEEPERS.

By JAMES F. KENDAL, M.B.H. Inst. 1/6 boards; or cloth, gilt . 2/6 "The best which has yet appeared on this subject in the English language."—Industries.
"Open the book where you may, there is interesting matter in it concerning the ingenious devices of the ancient or modern horologer."—Saturday Review.

ELECTRO-PLATING & ELECTRO-REFINING OF METALS.

Being a new edition of ALEXANDER WATT'S "ELECTRO-DEPOSITION." Revised and Largely Rewritten by ARNOLD PHILIP, B.Sc., A.I.E.E., Principal Assistant to the Admiralty Chemist. Large Crown 8vo, cloth. . Net 12/8

"Altogether the work can be highly recommended to every electro-plater, and is of undoubted interest to every electro-metallurgist."—Electrical Review.
"Eminently a book for the practical worker in electro-deposition. It contains practical descriptions of methods, processes and materials, as actually pursued and used in the workshop."—
Employer.

ELECTRO-METALLURGY.

Practically Treated.' By ALEXANDER WATT. Tenth Edition, including the most recent Processes. 12mo, cloth "From this book both amateur and artisan may learn everything necessary for the successful prosecution of electroplating."—Iron.

JEWELLER'S ASSISTANT IN WORKING IN GOLD.

A Practical Treatise for Masters and Workmen, Compiled from the Experience of Thirty Years' Workshop Practice. By GEORGE E. GEE. Crown 8vo. 7/6 "This manual of technical education is apparently destined to be a valuable surflary to a handicraft which is certainly capable of great improvement."—The Times.

ELECTROPLATING.

A Practical Handbook on the Deposition of Copper, Silver, Nickel, Gold, Aluminium, Brass, Platinum, &c., &c. By J. W. URQUHART, C.E. Fourth Edition, Revised. Crown 8vo, cloth: 5/0

"An excellent practical manual."—Engineering.
"An excellent work, giving the newest information."—Horological Yournal.

ELECTROTYPING.

The Reproduction and Multiplication of Printing Surfaces and Works of Art by the Electro-Deposition of Metals. By J. W. URQUHART, C.E. Crown 8vo. cloth

"The book is thoroughly practical; the reader is, therefore, conducted through the leading laws of electricity, then through the metals used by electrotypers, the apparatus, and the depositing processes, up to the final preparation of the work."—dry Journal.

GOLDSMITH'S HANDBOOK.

By George E. Gre, Jeweller, &c. Fifth Edition. 12mo, cloth . . . 3/0 "A good, sound educator,"-Herelegical Journal,

SILVERSMITH'S HANDBOOK.

By GEORGE E. GRE, Jeweller, &c. Third Edition, with numerous Illustrations. 12mo, cloth
"The chief merit of the work is its practical character. . . . The workers in the trade will speedily discover its merits when they sit down to study it."—English Machanic.

*** The above two works together, strongly half-bound, price 7s.

SHEET METAL WORKER'S INSTRUCTOR.

Comprising a Selection of Geometrical Problems and Practical Rules for Describing the Various Patterns Required by Zinc, Sheet-Iron, Copper, and Tin-Plate Workers. By RRUBEN HENRY WARN, Practical Tin-Plate Worker. New Edition, Revised and greatly Enlarged by JOSEPH G. HONNER, A.M.I.M.E. Crown 8vo, 254 pp., with 430 Illustrations, cloth

SAVOURIES AND SWEETS:

Suitable for Luncheons and Dinners. By Mss M. L. Allen (Mrs. A. MACAIRE), Author of "Breakfast Dishes," &c. Twenty-ninth Edition. F'cap . . .

BREAKFAST DISHES

BREAD & BISCUIT BAKER'S & SUGAR-BOILER'S ASSISTANT.

Including a large variety of Modern Recipes. With Remarks on the Art of Bread-making. By ROBERT WELLS. Third Edition. Crown 8vo, cloth. 1/0 "A large number of wrinkles for the ordinary cook, as well as the baker,"-Saturday Review.

PASTRYCOOK & CONFECTIONER'S GUIDE.

For Hotels, Restaurants, and the Trade in general, adapted also for Family Use. By R. Wells, Author of "The Bread and Biscuit Baker". . . 1/O "We cannot speak too highly of this really excellent work. In these days of keen competition was readers cannot do better than purchase this book."—Baker's Times.

ORNAMENTAL CONFECTIONERY.

"A valuable work, practical, and should be in the hands of every baker and confectioner.

The Einstrative designs are worth treble the amount charged for the work."—Baker's Times.

MODERN FLOUR CONFECTIONER.

Containing a large Collection of Recipes for Cheap Cakes, Biscuits, &c. With remarks on the Ingredients Used in their Manufacture. By R. Wells. 1.0 "The work is of a decidedly practical character, and in every recipe regard is had to economical weeking."—North British Daily Mail.

RUBBER HAND STAMPS

HANDYBOOKS FOR HANDICRAFTS.

BY PAUL N. HASLUCK.

Editor of "Work" (New Series), Author of "Lathe Work," "Milling Machines." &c. Crown 8vo, 144 pp., price 1s. each.

EST These Handybooks have been written to supply information for Workmen, Students, and Amateurs in the several Handicrafts, on the actual Practice of STUDENTS, and AMATEUES in the several transcrapts, on the actual FRACTICE with Workshop, and are intended to convey in plain language Technical Know-lende of the several Crafts. In describing the processes employed, and the manipulation of material, workshop terms are used; workshop practice is fully explained; and the text is freely illustrated with drawings of modern tools, appliances, and brocesses.

METAL TURNER'S HANDYBOOK.

A Practical Manual for Workers at the Foot-Lathe. With 100 Illustrations.

"The book will be of service alike to the amateur and the artisan turner. It displays therough knowledge of the subject."—Scotsman.

WOOD TURNER'S HANDYBOOK.

A Practical Manual for Workers at the Lathe. With over 100 Illustrations.

"We recommend the book to young turners and amateurs. A multitude of workmen have bithesto sought in vain for a manual of this special industry."—Mechanical World.

WATCH JOBBER'S HANDYBOOK.

A Practical Manual on Cleaning, Repairing, and Adjusting. With upwards of Too Illustrations 1/0

"We strongly advise all young persons connected with the watch trade to acquire and study this inexpensive work."—Clerkenwell Chronicle.

PATTERN MAKER'S HANDYBOOK.

A Practical Manual on the Construction of Patterns for Founders. With upwards of 100 Illustrations 1/0
"A most valuable, if not indispensable, manual for the pattern maker,"—Knowledge.

MECHANIC'S WORKSHOP HANDYBOOK.

A Practical Manual on Mechanical Manipulation, embracing Information on various Handicraft Processes. With Useful Notes and Miscellaneous Memoranda. Comprising about 200 Subjects . 1/0
"A very clever and useful book, which should be found in every workshop; and it should certainly find a place in all technical schools."—Saturday Review.

MODEL ENGINEER'S HANDYBOOK.

A Practical Manual on the Construction of Model Steam Engines. With upwards of 100 Illustrations.
"Mr. Hasluck has produced a very good little book."—Builder.

CLOCK JOBBER'S HANDYBOOK.

A Practical Manual on Cleaning, Repairing, and Adjusting. With upwards of

CABINET WORKER'S HANDYBOOK.

A Practical Manual on the Tools, Materials, Appliances, and Processes employed in Cabinet Work. With upwards of 100 Illustrations . 1/O "Mr. Hasluck's thorough-going little Handybook is amongst the most practical guides we have seen for beginners in cabinet-work." "Saturday Review."

WOODWORKER'S HANDYBOOK.

Embracing Information on the Tools, Materials, Appliances and Processes
Employed in Woodworking. With 104 Illustrations.

"Written by a man who knows, not only how work ought to be done, but how to do it, and
how to convey his knowledge to others."—*Engineering*.

"It is aluck writes admirably, and gives complete instructions."—*Engineer*.

"He is the converted of the processes of a practical teacher with the manipulative skill and
scientific knowledge of processes or special to a practical teacher with the manipulative skill and
can be produced at a popular price."—School mechanician, and the manuals are marvels of what
"Helpful to workmen of all ages and degrees of experience."—Delly Chronicle.
"Concise, clear, and practical."—Schoolay Review.

COMMERCE, COUNTING-HOUSE WORK, TABLES. ETC.

LESSONS IN COMMERCE.

By Professor R. Gambaro, of the Royal High Commercial School at Genoa. Edited and Revised by JAMES GAULT, Professor of Commerce and Commercial Law in King's College, London. Fourth Edition. Crown 8vo, cloth . 3/6

Law in King's College, London. Fourth Edition. Crown 8vo, cloth . 3/6
"The publishers of this work have rendered considerable service to the cause of commercial education by the opportune production of this volume. . . The work is peculiarly acceptable to singlish readers and an admirable addition to existing class books. In a phrase, we think the work attains its object in furnishing a brief account of those laws and customs of British trade with which the commercial man interested therein should be familiar."—Chamber of Commerce Journal.

In fact, in ravaluable guide in the hands of those who are preparing for a commercial career, and, the fact, the information it contains on matters of business should be impressed on every one."—Comming House.

THE FOREIGN COMMERCIAL CORRESPONDENT.

"Whoever wishes to correspond in all the languages mentioned by Mr. Bater cannot do better than study this work, the materials of which are excellent and conveniently arranged. They consist not of entire specimen letters, but—what are far more useful—short passages, sentences, or phrases expressing the same general idea in various forms."—Athenanm.

"A careful examination has convinced us that it is unusually complete, well arranged and cellable. The book is a thoroughly good one."—Scheelmaster.

FACTORY ACCOUNTS: their PRINCIPLES & PRACTICE. A Handbook for Accountants and Manufacturers, with Appendices on the Nomenclature of Machine Details; the Income Tax Acts; the Rating of Factories; Fire and Boiler Insurance; the Factory and Workshop Acts, &c., including also a Glossary of Terms and a large number of Specimen Rulings. By EMILE GARCKE and J. M. Fells. Fifth Edition, Revised and Enlarged. Demy 8vo, cloth

of as A very interesting description of the requirements of Factory Accounts. . . The principle of as the very interesting description of the requirements of Factory Accounts to the general commercial books is one which we thoroughly agree with. "Accountants Journal" There are few owners of factories who would not derive great benefit from the perusal of this most admirable work."—Local Government Chronicle.

MODERN METROLOGY.

"We recommend the work to all interested in the practical reform of our weights and

A SERIES OF METRIC TABLES.

In which the British Standard Measures and Weights are compared with those of the Metric System at present in Use on the Continent. By C. H. Dowling, C.E. 8vo, cloth

"Mr. Dowling's Tables are well put together as a ready reckoner for the conversion of one evitem into the other."—Athenesis.

4RON AND METAL TRADES' COMPANION.

For Expeditiously Ascertaining the Value of any Goods bought or sold by Weight, from 18. per cwt. to 1128. per cwt., and from one farthing per pound to one shilling per pound. By Thomas Downie. Strongly bound in leather,

"A most useful set of tables, nothing like them before existed."—Building News.
"Although specially adapted to the from and metal trades, the tables will be found useful in every other business in which merchandise is bought and sold by weight."—Retiwey News.

NUMBER, WEIGHT, AND FRACTIONAL CALCULATOR.

Containing upwards of 250,000 Separate Calculations, showing at a Glance the Value at 422 Different Rates, ranging from 171th of a Penny to 200. each, or per cwt., and 200 per ton, of any number of articles consecutively, from 1 to 470. Any number of cwts, qrts, and lbs, from r cwt. to 470 cwts. Any number of tons, cwts, qrts, and lbs, from r to r,coo tons. By William Chanwick, Public Accountant. Fourth Edition, Revised and Improved. 8vo, strongly bound

"It is as easy of reference for any answer or any number of answers as a dictionary. For making up accounts or estimates the book must prove invaluable to all who have any considerable quantity of calculations involving price and measure in any combination to do,"—*Hugimeer*.

"The most perfect work of the kind yet prepared,"—*Clasgem Herald*.

THE WEIGHT CALCULATOR.

Being a Series of Tables upon a New and Comprehensive Plan, exhibiting as one Reference the exact Value of any Weight from 1 lb. to 15 tons, at 300 One Reserence the exact Value of any Weight from 1 lb. to 15 tons, at 300 Progressive Rates, from 1d. to 168s, per cwt., and containing 186,000 Direct Answers, which, with their Combinations, consisting of a single addition (mostly to be performed at sight), will afford an aggregate of 10,266,000 Answers; the whole being calculated and designed to ensure correctness and promote despatch. By Henry Harren, Accountant. Sixth Edition, carefully Corrected. Royal 8vo, strongly half-bound. Uset Published. 21 5s.

"A practical and useful work of reference for men of business generally."—Ironmonger.
"Of priceless value to business men. It is a necessary book in all mercantile offices,"—
Shafteld Independent.

THE DISCOUNT GUIDE.

Comprising several Series of Tables for the Use of Merchants, Manufacturers, Comprising several Series of Tables for the Use of Merchants, Manufacturers, Ironmongers, and Others, by which may be ascertained the Exact Profit arising from any mode of using Discounts, either in the Purchase or Sale of Goods, and the method of either Altering a Rate of Discount, or Advancing a Price, so as to produce, by one operation, a sum that will realise any required Profit after allowing one or more Discounts: to which are added Tables of Profit or Advance from 12 to 95 per cent., Tables of Discount from 12 to 95 per cent. Tables of Discount from 12 to 95 per cent., Tables of Discounts. By Herney Harrey, Accountant. New Edition, Corrected. Demy 8vo, half-bound. 215 a.

"A book such as this can only be appreciated by business men, to whom the saving of time-means saving of money. The work must prove of great value to merchants, manufacturers, and general traders,"—British Trade Journal,

TABLES OF WAGES.

At 54, 52, 50 and 48 Hours per Week. Showing the Amounts of Wages from One quarter of an hour to Sixty-four hours, in each case at Rates of Wages advancing by One Shilling from 45. to 555. per week. By Thos. GABUTT, Accountant. Square crown 8vo, half-bound

IRON-PLATE WEIGHT TABLES.

For Iron Shipbuilders, Engineers, and Iron Merchants. Containing the Calculated Weights of upwards of 150,000 different sizes of Iron Plates from 1 foot by 6 in. by ½ in. to 10 feet by 5 feet by 1 in. Worked out on the Basis of 40 lbs. to the square foot of Iron of 1 inch in thickness. By H. Burlinson and W. H. SIMPSON. 4to, half-bound

ORIENTAL MANUALS AND TEXT-BOOKS.

Notice, Messrs. Crosby Lockwood & Son will forward on application a New and Revised List of Text-books and Manuals for Students in Oriental Languages, many of which are used as Text-books for the Examinations for the Indian Civil Service and the Indian Staff Corps; also as Class Books in Colleges and Schools in India.

AGRICULTURE, FARMING, GARDENING, ETC.

THE COMPLETE GRAZIER AND FARMER'S AND CATTLE BREEDER'S ASSISTANT

A Compendium of Husbandry. Originally Written by WILLIAM YOUATT. Fourteenth Edition, entirely Re-written, considerably Enlarged, and brought Pourteenth Edition, entirely Re-written, considerably Enlarged, and proughs up to Present Requirements, by WILLIAM FREAM, LL.D., Assistant Commissioner, Royal Commission on Agriculture, Author of "The Elements of Agriculture," &c. Royal 8vo, 1,100 pp., 450 Illustrations, handsomely bound.

BOOK L ON THE VARIETIES, BREEDING, REARING, FATTENING AND MANAGEMENT OF CATTLE.

BOOK II. ON THE ECONOMY AND MANAGEMENT OF THE DAIRY.

BOOK III. ON THE BEEDING, REARING, AND MANAGEMENT OF HORSES.

BOOK IV. ON THE BREEDING, REARING, AND FATTENING OF SHEEP.

BOOK V. ON THE BREEDING, REARING, AND FATTENING OF SWINE.

BOOK VI. ON THE DISEASES OF LIVE STOCK.

BOOK VII. ON THE BRHEDING, REARING, AND MANAGEMENT OF POULTRY. BOOK VIII. ON FARM OFFICES AND IMPLEMENTS OF HUSBANDRY. BOOK IN. ON THE CULTURE AND MANAGEMENT OF GRASS LANDS. BOOK X. ON THE CULTURATION AND APPLICATION OF GRASSES, PULSE AND ROOTS. ON MANUERS AND THEIR BOOK X. ON MANUERS AND THEIR BOOK XI. ON MANURES AND THEIR APPLICATION TO GRASS LAND AND CROPS.
BOOK XII. MONTHY FARMWORK

"Dv. Fream is to be congratulated on the successful attempt he has made to give us a work which will at once become the standard classic of the farm practice of the country. We believe that it will be found that it has no compeer among the many works at present in existence.

The illustrations are admirable, while the frontispiece, which represents the well-known bull, New Year's Gift, bred by the Queen, is a work of art. "The Times.

"The book must be recognised as occupying the proud position of the most exhaustive work of selecence in the English language on the subject with which it deals."—Alkeneum.

"The most comprehensive guide to modern farm practice that exists in the English language to-day."—In most comprehensive guide to modern farm practice that exists in the English language to-day.

"In point of exhaustiveness and accuracy the work will certainly hold a pre-eminent and unique position among books dealing with scientific agricultural practice. It is, in fact, an agricultural library of itself."—North British Agriculturist.

FARM LIVE STOCK OF GREAT BRITAIN.

By ROBERT WALLACE, F.L.S., F.R.S.E., &c., Professor of Agriculture and Rural Economy in the University of Edinburgh. Third Edition, thoroughly Revised and considerably Enlarged. With over 120 Phototypes of Prize Stock. Demy 8vo, 384 pp., with 79 Plates and Maps, cloth.

"A really complete work on the history, breeds, and management of the farm stock of Great Bettala, and one which is likely to find its way to the shelves of every country gentleman's library."

The Tibers. "The Farm Live Stock of Great Britain' is a production to be proud of, and its issue not the least of the services which its author has rendered to agricultural science."—Scottish Farmer.

NOTE-BOOK OF AGRICULTURAL FACTS & FIGURES FOR FARMERS AND FARM STUDENTS

By PRIMROSE McConnell, B.Sc., Fellow of the Highland and Agricultural Society, Author of "Elements of Farming." Sixth Edition, Re-written, Revised, and greatly Enlarged. Fcap. 8vo, 480 pp., leather, gilt edges .

CONTENTS: SURVEYING AND LEVELLING.—WRIGHTS AND MASURES.—MACHINERY AND BUILDINGS.—LABOUR.—OPERATIONS.—DRAINING.—EMBANKING.—GROLOGICAL MEMORANDA.—SOILS.—MANURES.—CROPPING.—CROPS.—ROTATIONS.—WEEDS.—FEEDING.—DAIRYING.—LIVE STOCK.—HOSSES.—CATTLE.—SHEEP.—PIGS.—POULTRY.— FORESTRY.-HORTICULTURE.-MISCELLANEOUS.

"No farmer, and certainly no agricultural student, ought to be without this multum-in-parve samual of all subjects connected with the farm."—North Brisish Agriculturist.
"This little pocket-book contains a large amount of useful information upon all kinds of agricultural subjects. Something of the kind has long been wanted."—Mark Lane Express.
"The amount of information it contains is most surprising; the arrangement of the matter is so methodical—although so compressed—as to be intelligible to everyone who takes a glance through its pages. They teem with information."—Farm and Home.

THE ELEMENTS OF AGRICULTURAL GEOLOGY.

A Scientific Aid to Practical Farming. By PRIMROSE McCONNELL. Author of "Note-Book of Agricultural Facts and Figures," &c. Royal 8vo, cloth.

"On every page the work bears the impress of a masterly knowledge of the subject dealt with, and we have nothing but unstituted praise to offer."—Field.

BRITISH DAIRYING.

A Handy Volume on the Work of the Dairy-Farm. For the Use of Technical Farmer. By Prof. J. P. Sheldon. With Illustrations. Second Edition, Revised. Crown 8vo, cloth

Revised. Crown 8vo, cloth

"Confidently recommended as a useful text-book on dairy farming."—Agricultural Gasette.

"Probably the best half-crown manual on dairy work that has yet been produced."—North

British Agriculturist.

"It is the soundest little work we have yet seen on the subject."—The Times.

MILK, CHEESE, AND BUTTER.

A Practical Handbook on their Properties and the Processes of their Production. Including a Chapter on Cream and the Methods of its Separation from Milk. By JOHN OLIVER, late Principal of the Western Dairy Institute, Berkeley. With Coloured Plates and soo Illustrations. Crown 8vo, cloth.

"An exhaustive and masterly production. It may be cordially recommended to all students and practitioners of dairy science."—North British Agriculturist.

"We recommend this very comprehensive and carefully-written book to dairy-farmers and students of dairying. It is a distinct acquisition to the library of the agriculturist."—Agricultural

SYSTEMATIC SMALL FARMING.

Or, The Lessons of My Farm. Being an Introduction to Modern Farm Practice for Small Farmers. By R. Scott Burn, Author of "Outlines of Modern Farming," &c. Crown 8vo, cloth. "This is the completest book of its class we have seen, and one which every amateur farmer will read with pleasure, and accept as a guide."—Field.

OUTLINES OF MODERN FARMING.

By R. Scott Burn. Soils, Manures, and Crops—Farming and Farming Economy—Cattle, Sheep, and Horses—Management of Dairy, Pigs, and Poultry—Utilisation of Town-Sewage, Irrigation, &c. Sixth Edition. In On Vol., 2,250 pp., half-bound, profusely Illustrated. 12/0

FARM ENGINEERING, The COMPLETE TEXT-BOOK of.

Comprising Draining and Embanking; Irrigation and Water Supply; Farm Roads, Fences and Gates; Farm Buildings; Barn Implements and Machines; Field Implements and Machines; Agricultural Surveying, &c. By Professor John Scott. In One Vol., 1,150 pp., half-bound, with over 60 Illustrations.

"Written with great care, as well as with knowledge and ability. The author has done his work well; we have found him a very trustworthy guide wherever we have tested his statements. The volume will be of great value to agricultural students." March Lane Edgress.

THE FIELDS OF GREAT BRITAIN.

A Text-Book of Agriculture. Adapted to the Syllabus of the Science and Art Department. For Elementary and Advanced Students. By HUGH CLEMENTS (Board of Trade). Second Edition, Revised, with Additions. . 2/6

"It is a long time since we have seen a book which has pleased us more, or which contains such a vast and useful fund of knowledge,"—Educational Times.

TABLES and MEMORANDA for FARMERS, GRAZIERS, AGRICULTURAL STUDENTS, SURVEYORS, LAND AGENTS, AUCTIONEERS, &c.

With a New System of Farm Book-keeping. By SIDNEY FRANCIS. Fifth Edition. 272 pp., waistcoat-pocket size, limp leather 1/8 "Welghing less than 1 oz., and occupying no more space than a match-box, it contains a mass of facts and calculations which has never before, in such handy form, been obtainable. Every operation on the farm is dealt with. The work may be taken as thoroughly accurate, the whole of the tables having been revised by Dr. Fream. We cordially recommend it."—Bell's Weekly

ROTHAMSTED EXPERIMENTS AND THEIR PRACTICAL LESSONS FOR FARMERS.

Part I. STOCK. Part II. CROPS. By C. J. R. TIPPER. Crown 8vo, cloth

"We have no doubt that the book will be welcomed by a large class of farmers and others uterested in agriculture."—Standard.

AGRICULTURE, FLORES SEED ST.

EXTLIBITS AND THE FIFE	·—
The Inverse at Tax American State of the Inverse	3.
TO DESCRIPTION OF THE PROPERTY	*
	1/6 2/- 3/6
医阴茎连连 4、一种	2/6
THE TE	6 - 1 6 5 -
BOIX-	1/- 6/-
	-
	, 2/6
FIDDMANT TALL TA	5/-
The same	3/- 2/-
12 1 22 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2	2/6
	2/6 1/6
THE FORTIS . WHEN	1,170
france	
A STATE A STATE OF THE STATE OF	2/-
A PLATE CLERK IN ME	4/6 3/-
- P. Cardi () Man (新元) () (Min ()) (Min ()) (An ()) (3/-
1. 4	7/- 3/-
A POLY	2/6
Military .	2/6 2/6
1. Letter 1. ages.	2/-
Reference of the second	MEAD . 1/6
When there are a second or a s	н . 1/6
THE LADIES P	2/-
	3/-
PURITY THE	2 -
	AL Court E.C.
Marke a	



AUCTIONEERING, VALUING, LAND SURVEYING, ESTATE AGENCY, ETC.

INWOOD'S TABLES FOR PURCHASING ESTATES AND FOR THE VALUATION OF PROPERTIES.

Including Advowsons, Assurance Policies, Copyholds, Deferred Annuities, Freeholds, Ground Rents, Immediate Annuities, Leaseholds, Life Interests, Mortgages, Perpetuities, Renewals of Leases, Reversions, Sinking Funds, &c., &c. 27th Edition, Revised and Extended by WILLIAM SCHOOLING, F.R.A.S., with Logarithms of Natural Numbers and Thoman's Logarithmic Interest and Annuity Tables. 360 pp., Demy 8vo, cloth.

[Just Published. Net 810

"Those interested in the purchase and sale of estates, and in the adjustment of compensation cases, as well as in transactions in annuities, life insurances, &c., will find the present edition of eminent service."—Bugintering.

"This valuable book has been considerably enlarged and improved by the labours of Mr. Schooling, and is now very complete indeed."—Economics.

"Altogether this edition will prove of extreme value to many classes of professional men in saving them many long and tedious calculations."—Investors' Review.

BROKER, HOUSE THE APPRAISER, AUCTIONEER, BROKER, HOUSE AND ESTATE AGENT AND VALUER'S POCKET ASSISTANT.

For the Valuation for Purchase, Sale, or Renewal of Leases, Annuities, and Reversions, and of Property generally; with Prices for Inventories, &c. By JOHN WHEELER, Valuer, &c. Sixth Edition, Re-written and greatly Extended by C. NORRIS. Royal 32mo, cloth

"A near and concise book of reference, containing an admirable and clearly-arranged list of prices for inventories, and a very practical guide to determine the value of furniture, &c."—Stenders, "Contains a large quantity of varied and useful information as to the valuation for purchase, sale, or renewal of leases, anultites and reversions, and of property generally, "the prices fuventories, and a guide to determine the value of interior fittings and other effects." "Beliefer."

AUCTIONEERS: THEIR DUTIES AND LIABILITIES.

A Manual of Instruction and Counsel for the Young Auctioneer. By ROBERT SQUIBBS, Auctioneer. Second Edition, Revised. Demy 8vo, cloth . 12/6 "The work is one of general excellent character, and gives much information in a compendious and satisfactory form."—Builder.
"May be recommended as giving a great deal of information on the law relating to auctioneers, in a very readable form."—Law Yournal.

THE AGRICULTURAL VALUER'S ASSISTANT.

A Practical Handbook on the Valuation of Landed Estates; including Example of a Detailed Report on Management and Realisation; Forms of Valuations of Tenant Right; Lists of Local Agricultural Customs; Scales of Compensation under the Agricultural Holdings Act, and a Brief Treatise on Compensation under the Lands Clauses Acts, &c. By Tom Bright, Agricultural Valuer. Author of "The Agricultural Surveyor and Estate Agent's Handbook." Fourth Edition, Revised, with Appendix containing a Digest of the Agricultural Holdings Acts, 1883—1900. Crown 8vo, cloth . Net 6/0

"Full of tables and examples in connection with the valuation of tenant-right, estates, labour, contents and weights of timber, and farm produce of all kinds."—A gricultural Gasette.

"An eminently practical handbook, full of practical tables and data of undoubted interest and value to surveyors and auctioneers in preparing valuations of all kinds."—Parmer.

POLE PLANTATIONS AND UNDERWOODS.

A Practical Handbook on Estimating the Cost of Forming, Renovating, Improving, and Grubbing Plantations and Underwoods, their Valuation for Purposes of Transfer, Rental, Sale or Assessment. By Tom Bright. Crown 8vo, cloth 3/6 . .

"To valuers, foresters and agents it will be a welcome sid."—North British Agriculturisi.
"Well calculated to assist the valuer in the discharge of his duties, and of undoubted intregated and use both to surveyors and suctioneers in preparing valuations of all kinds,"—Keet Hereld.

AGRICULTURAL SURVEYOR AND ESTATE AGENT'S HANDBOOK.

Of Practical Rules, Formulæ, Tables, and Data. A Comprehensive Manual or the Use of Surveyors, Agents, Landowners, and others interested in the Equipment, the Management, or the Valuation of Landed Estates. By Tom Braght, Agricultural Surveyor and Valuer, Author of "The Agricultural Valuer's Assistant," &c. With Illustrations. Fcap. 8vo, Leather. Net 7/8

"An exceedingly useful book, the contents of which are admirably chosen. The classes for whom the work is intended will find it convenient to have this comprehensive handbook accessible for reference."—Live Sack Fournac.

"It is a singularly compact and well informed compendium of the facts and figures likely to be required in estate work, and is certain to prove of much service to those to whom it is addressed."—Satirman.

THE LAND VALUER'S BEST ASSISTANT.

Being Tables on a very much Improved Plan, for Calculating the Value of Estates. With Tables for reducing Scotch, Irish, and Provincial Customary Acres to Statute Measure, &c. By R. Hudson, C.E. New Edition Royal 32mo, leather, elastic band

"Of incalculable value to the country gentleman and professional man."-Farmers' Journal.

THE LAND IMPROVER'S POCKET-BOOK.

Comprising Formulæ, Tables, and Memoranda required in any Computation relating to the Permanent Improvement of Landed Property. By JOHN EWART, Surveyor. Second Edition, Revised. Royal 32mo, oblong, leather . 4/0 "A compendious and handy littl volume."-Speciator.

THE LAND VALUER'S COMPLETE POCKET-BOOK.

Being the above Two Works bound together. Leather . . 7/6

HANDBOOK OF HOUSE PROPERTY.

A Popular and Practical Guide to the Purchase, Tenancy, and Compulsory Sale of Houses and Land, including Dilapidations and Fixtures: with Examples of all kinds of Valuations, Information on Building and on the right use of Decorative Art. By E. L. TARBUCK, Architect and Surveyor. Seventh Edition. 12mo, cloth [Just Published, BIO

"The advice is thoroughly practical."—Law Yournal.

"For all who have destings with house property, this is an indispensable guide."—Decoration.

"Carefully brought up to date, and much improved by the addition of a division on Fine Art.

A well-written and thoughtful work."—Land Agents' Record.

LAW AND MISCELLANEOUS.

MODERN JOURNALISM.

A Handbook of Instruction and Counsel for the Young Journalist. By JOHN B. MACKIE, Fellow of the Institute of Journalists. Crown 8vo, cloth . 2/0 "This invaluable guide to journalism is a work which all aspirants to a journalistic career will read with advantage."— Fournalist.

HANDBOOK FOR SOLICITORS AND ENGINEERS

Engaged in Promoting Private Acts of Parliament and Provisional Orders for the Authorisation of Railways, Tramways, Gas and Water Works, &c. By L. L. MACASSEY, of the Middle Temple, Barrister-at-Law, M.I.C.E.

PATENTS for INVENTIONS, HOW to PROCURE THEM.

Compiled for the Use of Inventors, Patentees and others. By G. G. M. HARDINGHAM, Assoc. Mem. Inst. C.E., &c. Demy 8vo, cloth . . . 1/8

CONCILIATION & ARBITRATION In LABOUR DISPUTES.

A Historical Sketch and Brief Statement of the Present Position of the A Historical Sketch and Brief Statement of the Albert Svo, 200 pp., Question at Home and Abroad. By J. S. JEANS. Crown 8vo, 200 pp., 2/6

EVERY MAN'S OWN LAWYER.

A Handy-Book of the Principles of Law and Equity. With a CONCISE DICTIONARY OF LEGAL TERMS. BY A BARRISTER. Forty-second Eddition, carefully Revised, and comprising New Acts of Parliament, including the Prevention of Cruelty to Children Act, 1904; Weights and Measures Act, 1904; Lucensing Act, 1904; Shop Hours Act, 1904; as well as the Motor Car Act, 1903; Employment of Children Act, 1903; Poor Prisoners' Defence Act, 1903; &c. Judicial Decisions pronounced during the year have also been duly noted. Crown 8vo, 800 pp., strongly bound in cloth. [Just Published. 6/8]

*. This Standard Work of Reference forms a Complete Epitome of the Laws of England, comprising (amongst other matter);

THE RIGHTS AND WRONGS OF INDIVIDUALS

LANDLORD AND TEMANT
VENDORS AND PURCHASERS
LEASES AND MORTGAGES
JOINT-STOCK MOPARIES
LEASES SERVANDAMIES
CONTRACT ANNA GREETISHIP
PRIVE EARLY, SHIPPING LAW
SALE AND PURCHASE PGOODS
CHEQUES BILLS AND NOTES
BILLS PER SALE BANKRUPTCY
LIFE, FIRE, AND MARINE INSURANCE
LIBEL AND SLANDER

CRIMINAL LAW
PARLIAMENTARY ELECTIONS
COUNTY COUNCILS
DISTRICT AND FARISH COUNCILS
BOROUGH CORPORATIONS
TRUSTERS AND EXECUTORS
CLERGY AND CHURCHWARDENS
COPYRIGHT, PATENTS, TRADE MARKSHUSBAND AND WIPE, DIVORCE
INFANCY, CUSTODY OF CHILDREN
PUBLIC HEALTH AND NUISANCES
GAME LAWS, GAMING, INNEREPERS
TAKES AND DEATH DUTIES

FORMS OF WILLS, AGREEMENTS, NOTICES, &C.

The object of this work is to enable those who consult it to help themselves to the law; and thereby to dispense, as far as possible, with professional assistance and advice. There are many wrongs and grievances which persons submit to from time to time through not humaing how or where to apply for redress; and many persons have as great a fewal of lawyer's office as of a time som. With this book at hand it is believed that many a SIX. AND-SIGHTENESS may be seved; many a wrong redressed; many a right reclaimed; many a law said avoided; and many on eoil about. The work has established titelf as the standard legs in the standard legs

. Opinions of the Press.

- "The amount of information given in the volume is simply wonderful. The continued popularity of the work shows that it fulfils a useful purpose."—Law Yournal.
 - "As a book of reference this volume is without a rival."-Pail Mall Gazette.
 - "No Englishman ought to be without this book."-Engineer.
 - "Ought to be in every business establishment and in all libraries."—Sheffield Post.
 - "The 'Concise Dictionary' adds considerably to its value."-Westminster Gazette,
- "It is a complete code of English Law written in plain language, which all can understand.

 Should be in the hands of every business man, and all who wish to abolish lawyers' bills,"—

 Weakly Times.
 - "A useful and concise epitome of the law, compiled with considerable care."-Law Magazine.
 - "A complete digest of the most useful facts which constitute English law."-Globe.
 - "Admirably done, admirably arranged, and admirably cheap."-Leeds Mercury
- "A concise, cheap, and complete epitome of the English law. So plainly written that he who runs may read, and he who reads may understand."—Figure.
 - "A dictionary of legal facts well put together. The book is a very useful one."—Speciator.

LABOUR CONTRACTS.

A Popular Handbook on the Law of Contracts for Works and Services. By DAVID GIBBONS. Fourth Edition, with Appendix of Statutes by T. F. UTTLEY, Solicitor. Fcap. 8vo, cloth

WEALE'S SERIES

OF

SCIENTIFIC AND TECHNICAL WORKS.

"It is not too much to say that no books have ever proved more popular with or more useful to young engineers and others than the excellent treatises comprised in WEALE'S SERIES."—Engineer.

A Rew Classified List.

PAGE CIVIL ENGINEERING AND SURVEYING 2	ARCHITECTURE AND BUILDING 6
MINING AND METALLURGY 8	
MECHANICAL ENGINEERING 4	AGRICULTURE, GARDENING, ETO 10
NAVIGATION, SHIPBUILDING, ETO. 5	MATHEMATIOS, ARITHMETIO, ETO. 12
BOOKS OF REFERENCE AND MIS	CELLANEOUS VOLUMES 14



CROSBY LOCKWOOD AND SON, 7, STATIONERS' HALL COURT, LONDON, E.C.

1904.

CIVIL ENGINEERING & SURVEYING.
Civil Engineering.
By Henry Law, M.Inst.C.E. Including a Treatise on Hydraulic Engineering by G. R. Burnell, M.I.C.E. Seventh Edition, revised, with Large Additions by D. K. Clark, M.I.C.E 6/8
Pioneer Engineering:
A Treatise on the Engineering Operations connected with the Settlement of Waste Lands in New Countries. By EDWARD DOBSON, M.INST.C.E. With numerous Plates. Second Edition
Iron Bridges of Moderate Span: Their Construction and Erection. By Hamilton W. Penderd. With 40 Illustrations
Iron and Steel Bridges and Viaduots. A Practical Treatise upon their Construction for the use of Engineers, Draughtsmen, and Students. By Francis Campin, C.E. With Illus. 3/8
Constructional Iron and Steel Work,
As applied to Public, Private, and Domestic Buildings. By Francis Campin, C.E
Tubular and other Iron Girder Bridges. Describing the Britannia and Conway Tubular Bridges. DEMPSEY, C.E. Fourth Edition
Materials and Construction;
A Theoretical and Practical Treatise on the Strains, Designing, and Erection of Works of Construction. By Francis Campin, C.E 3/0
Banitary Work in the Smaller Towns and in Villages. By Charles Slagg, Assoc. M.Inst.C.E. Third Edition 3/0
Construction of Roads and Streets. By H. Law, C.E., and D. K. Clark, C.E. Sixth Edition, revised, with Additional Chapters by A. J. Wallis-Tayler, A.M. Inst. C.E. 6/0
Their Construction and Arrangement and the Manufacture and Distribution of Coal Gas. Originally written by S. Hughes, C.E. Ninth Edition. Revised, with Notices of Recent Improvements, by Henry O'Conner, A.M. Inst. C.E., Author of "The Gas Engineers' Pocket Book." [Just Published. 6/0]
Water Works
For the Supply of Cities and Towns. With a Description of the Principal Geological Formations of England as influencing Supplies of Water. By SAMUEL HUGHES, F.G.S., C.E. Enlarged Edition
The Power of Water,
As applied to drive Flour Mills, and to give motion to Turbines and other Hydrostatic Engines. By Joseph Glynn, F.R.S. New Edition 2/0
Wells and Well-Sinking. By John Gro. Swindell, A.R.I.B.A., and G. R. Burnell, C.E. Revised Edition. With a New Appendix on the Qualities of Water. Illustrated 2/0
The Drainage of Lands, Towns, and Buildings. By G. D. Dempsey, C.E. Revised, with large Additions on Recent Practice, by D. K. CLARK, M.I.C.E. Third Edition
The Blasting and Quarrying of Stone, For Building and other Purposes. With Remarks on the Blowing up of Bridges. By Gen. Sir J. BURGOYNE, K.C.B
Foundations and Concrete Works.
With Practical Remarks on Footings, Planking, Sand, Concrete Béton, File-driving, Caissons, and Cofferdams. By E. Dosson. Ninth Ed. 1/6

Pneu	matics.	
	Including Acoustics and the Phenomena of Wind Currents, for the Us	e of
	Including Acoustics and the Phenomena of Wind Currents, for the Us Beginners. By CHARLES TOMLINSON, F.R.S. Fourth Edition	/6
Land	l and Engineering Surveying.	
	For Students and Practical Use. By T. BAKER, C.E. Nineteenth Edit	ion,
	Revised and Extended by F. E. DIXON, A.M. Inst. C.E., Professional A ciate of the Institution of Surveyors. With numerous Illustrations and	880-
	ciate of the Institution of Surveyors. With numerous Illustrations and	twe
		2/0
men	uration and Measuring.	_
	For Students and Practical Use. With the Mensuration and Levellin	g or
	Land for the purposes of Modern Engineering. By T. Baker, C.E. I Edition by E. NUGENT, C.E.	ì/S
	TRACTION BY D. 1100BR1; O.B	• •
	MINING AND METALLINON	
	MINING AND METALLURGY.	
Mini	ng Calculations,	
	For the use of Students Preparing for the Examinations for Col Managers' Certificates, comprising numerous Rules and Example Arithmetic, Algebra, and Mensuration. By T. A. O'DONAHUE, M First-Class Certificated Colliery Manager.	liery
	Managers' Certificates, comprising numerous Rules and Example	عنيه
	Arithmetic, Algebra, and Mensuration. By T. A. O'DONAHUE, M.	.E.,
Wine	First-Class Certificated Colliery Manager	3/6
wine	Palogy,	4
	Rudiments of. By A. RAMSAY, F.G.S. Fourth Edition, revised enlarged. Woodcuts and Plates.	3/6
Coal	and Coal Mining,	<i>5</i> ,
COMI	A Rudimentary Treatise on. By the late Sir Warington W. Smy	-TH
	F.R.S. Eighth Edition, revised by T. Forster Brown	3/6
Meta	dlurgy of Iron.	J, U
	Containing Methods of Assay, Analyses of Iron Ores, Processes of M	enu.
	facture of Iron and Steel, &c. By H. BAUERMAN, F.G.S. With nume	LOM
	Containing Methods of Assay, Analyses of Iron Ores, Processes of M facture of Iron and Steel, &c. By H. BAUERMAN, F.G.S. With nume Illustrations. Sixth Edition, revised and enlarged	5/0
The	Mineral Surveyor and Yaluer's Complete Gui	de.
	By W. LINTERN. Fourth Edition, with an Appendix on Magnetic	
	Angular Surveying	3/6
Blate	and Slate Quarrying:	
	Scientific, Practical, and Commercial. By D. C. DAVIES, F.G.S. numerous Illustrations and Folding Plates. Fourth Edition	Vith
	numerous Illustrations and Folding Plates. Fourth Edition	3/0
AF	Irst Book of Mining and Quarrying, With the Sciences connected therewith, for Primary Schools and Sel struction. By J. H. COLLINS, F.G.S. Second Edition	
	With the Sciences connected therewith, for Primary Schools and Sel	f-In-
	struction. By J. H. COLLINS, F.G.S. Second Edition	1/5
Bubt	erraneous Surveying,	
	With and without the Magnetic Needle. By T. FENWICK and T. BA	KER,
W::	C.E. Illustrated	2/6
2 1111	Manual of. By WILLIAM MORGANS, Lecturer on Practical Mining at	
	Bristol School of Mines	2/8
Mini	ng Tools, Atlas	-/-
	Of Engravings to Illustrate the above, containing 235 Illustrations of Mi	nine
	Tools, drawn to Scale. 4to	4/6
Phys	sical Geology,	
	Partly based on Major-General PORTLOCK'S "Rudiments of Geolo By RALPH TATE, A.L.S., &c. Woodcuts.	gy."
	By RALPH TATE, A.L.S., &c. Woodcuts	2/0
Hist	orical Geology.	
	Partly based on Major-General PORTLOCK'S "Rudiments." By R. TATE, A.L.S. &c. Woodcuts	J.PH
	TATE, A.L.S., &c. Woodcuts	2/8
Geol	ogy, Physical and Historical.	
	Consisting of "Physical Geology," which sets forth the Leading Princ of the Science; and "Historical Geology," which treats of the Mi	iples
	of the Science; and "Historical Geology," which treats of the Mis	-
	and Organic Conditions of the Earth at each successive epoca. By KA	4/0
	TATE, P.G.S.	~~

	MECHANICAL ENGINEERING.
The	Workman's Manual of Engineering Drawing. By John Maxton, Instructor in Engineering Drawing, Royal Nava? College, Greenwich, Eighth Edition. 300 Plates and Diagrams . 3/6
E freti	Their Analysis and Valuation. For the Use of Chemists and Engineers. By H. J. Phillips, F.C.S., formerly Analytical and Consulting Chemist to the Great Eastern Railway. Fourth Edition. 2/0
Fuel,	Its Combustion and Economy. Consisting of an Abridgment of "A Treatise on the Combustion of Coal and the Prevention of Smoke." By C. W. WILLIAMS, A.I.C.E. With Extensive Additions by D. K. CLARK, M. Inst.C.E. Fourth Edition 3/6
The	HOLLETMAKEY'S ASSISTANT In Drawing, Templating, and Calculating Boiler Work, &c. By J. Court- NEY, Practical Boilermaker. Edited by D. K. CLARK, C.E 2/0
The	Boiler-Maker's Ready Reckoner, With Examples of Practical Geometry and Templating for the Use of Platers, Smiths, and Riveters. By JOHN COURTNEY. Edited by D. K. CLARK M. L.C.E. Eith Edition
	The last two Works in One Volume, half-bound, entitled "The Boiler- maker's Ready-Reckoner and Assistant." By J. Courtney and D. K. Clark. Price 7(0.
Btea	m Boilers: Their Construction and Management. By R. ARMSTRONG, C.E. Illustrated 1/8
	m and Machinery Management. A Guide to the Arrangement and Economical Management of Machinery. By M. Powis Balls, M. Inst. M. E
Stea	m and the Steam Engine, Stationary and Portable. Being an Extension of the Treatise on the Steam Engine of Mr. J. SEWELL. By D. K. CLARK, C.E. Fourth Edition 3/8
The	Steam Engine, A Treatise on the Mathematical Theory of, with Rules and Examples for Practical Men. By T. BAKER, C.E
_	Steam Engine. By Dr. Lardner. Illustrated
	motive Engines. By G. D. Dempsey, C.E. With large Additions treating of the Modern Locomotive, by D. K. CLARK, M. Inst. C.E
	motive Engine-Driving. A Practical Manual for Engineers in charge of Locomotive Engines. By MICHAEL REVNOLDS. Eleventh Edition. 3s. 6d.; cloth boards . 4/6
	lonary Engine-Driving. A Practical Manual for Engineers in charge of Stationary Engines. By MICHAEL REVNOLDS. Seventh Edition. 3s. 6d.; cloth boards . 4/6
	Smithy and Forge. Including the Farrier's Art and Coach Smithing. By W. J. E. CRANK. Fourth Edition
	As applied to Marine, Land, and Locomotive Engines, Floating Docks, Dredging Machines, Bridges, Ship-building, &c. By J. G. WINTON. Fourth Edition, Illustrated. 3/6
	comprising Metallurgy, Moulding, Casting, Forging, Tools, Workshop Machinery, Mechanical Manipulation, Manufacture of the Steam Engine, &c. By Francis Campin, C.E. Third Edition
Deta	ils of Machinery. Comprising Instructions for the Execution of various Works in Iron in the Fitting-Shop, Foundry, and Boiler-Yard. By Francis Campin, C.E. 3/0

Elementary Engineering:
A Manual for Young Marine Engineers and Apprentices. In the Form of Questions and Answers on Metals, Alloys, Strength of Materials, &c.
By J. S. Brewer. Fifth Edition
Horse-power Motion, Toothed-Wheel Gearing, Long and Short Driving Bands, Angular Forces, &c. By JAMES ARMOUR, C.E. Third Edition 2/0
Iron and Heat, Exhibiting the Principles concerned in the Construction of Iron Beams,
Pillars, and Girders. By J. Armour, C.E
Machinery, by J. NASMYTH, C.E
Mechanics: Being a concise Exposition of the General Principles of Mechanical Science, and their Applications. By CHARLES TOMLINSON, F.R.S. 1/6
Cranes (The Construction of),
And other Machinery for Raising Heavy Bodies for the Erection of Buildings, &c. By JOSEPH GLYNN, F.R.S 1/6
NAVIGATION, SHIPBUILDING, ETC.
The Sailor's Sea Book:
A Rudimentary Treatise on Navigation. By JAMES GREENWOOD, B.A. With numerous Woodcuts and Coloured Plates. New and enlarged
Edition. By W. H. Rosser
Consisting of The Sailor's Sea-Book, by James Greenwood and W. H. Rosser; together with Mathematical and Nautical Tables for the Working of the Problems, by Henry Law, C.E., and Prof. J. R. Young . 7/0
Navigation and Nautical Astronomy, In Theory and Practice. By Prof. J. R. Young. New Edition. 2/6
Mathematical Tables,
For Trigonometrical, Astronomical, and Nautical Calculations; to which is prefixed a Treatise on Logarithms. By H. Law, C.E. Together with a Series of Tables for Navigation and Nautical Astronomy. By Professor J. R. Young. New Edition
Masting, Mast-Making, and Rigging of Ships.
Masting, Mast-Making, and Rigging of Ships. Also Tables of Spars, Rigging, Blocks; Chain, Wire, and Hemp Ropes, &c., relative to every class of vessels. By ROBERT-KIPPING, N.A 2/0 Sails and Sail-Making.
With Draughting, and the Centre of Effort of the Sails. By ROBERT KIPPING, N.A
Marine Engines and Steam Yessels. By R. Murray, C.E. Eighth Edition, thoroughly revised, with Additions by the Author and by George Carlisle, C.E 4/6
Naval Architecture: An Exposition of Elementary Principles. By James Peake 3/6
Ships for Ocean and River Service, Principles of the Construction of. By Hakon A. Sommerfeldt . 1/6
Atlas of Engravings
The Forms of Ships and Boats.
By W. BLAND. Tenth Edition, with numerous Illustrations and Models 1/6

ARCHITECTURE AND THE BUILDING ARTS. Constructional Iron and Steel Work. As applied to Public, Private, and Domestic Buildings. By Francis Campin, C.E. 3/8 . 3/6 Building Estates: The Science of Building: The Art of Building: General Principles of Construction, Strength, and Use of Materials, Working Drawings, Specifications, &c. By Edward Dosson, M.R.I.B.A. 2/0 A Book on Building, Civil and Ecclesiastical. By Sir EDMUND BECKETT, Q.C. (Lord Grim-THORPE). Second Edition Dwelling-Houses (The Erection of), Illustrated by a Perspective View, Plans, and Sections of a Pair of Villas, with Specification, Quantities, and Estimates. By S. H. Brooks, Architect 2/6 Cottage Building. Acoustics in Relation to Architecture and Building: The Laws of Sound as applied to the Arrangement of Buildings. By Professor T. ROGRR SMITH, F.R.I.B.A. New Edition, Revised . . . 1/6 The Rudiments of Practical Bricklaying. General Principles of Bricklaying; Arch Drawing, Cutting, and Setting; Pointing; Paving, Tiling, &c. By ADAM HAMMOND. With 68 Woodcuts Brickwork: Bricks and Tiles, The Practical Brick and Tile Book. Comprising: BRICK AND TILE MAKING, by E. Dosson, M.INST.C.E.; Practical BRICKLAYING, by A. HAMMOND; BRICK-COTTING AND SETTING, by A. HAMMOND. 550 pp. with 270 Illustrations, half-bound . . 6/0 Carpentry and Joinery-THE ELEMENTARY PRINCIPLES OF CARPENTEY. Chiefly composed from the Standard Work of Thomas Tredgold, C.E. With Additions, and Treatise on Joinery, by E. W. Tarn, M.A. Eighth Edition 3/6 Carpentry and Joinery—Atlas Of 35 Plates to accompany and Illustrate the foregoing book. Descriptive Letterpress. 4to 6/0

A P	ractical Treatise on Handrailing; Showing New and Simple Methods. By GEO. COLLINGS. Third Edition, including a Treatise on StairBuilding. With Plates
Circu	nlar Work in Carpentry and Joinery. A Practical Treatise on Circular Work of Single and Double Curvature. By George Collings. Fourth Edition
Roof	Carpentry: Practical Lessons in the Framing of Wood Roofs. For the Use of Working Carpenters. By GEO. COLLINGS
The	Construction of Roofs of Wood and Iron; Deduced chiefly from the Works of Robison, Tredgold, and Humber. E. WYNDHAM TARN, M.A., Architect. Fourth Edition 1/6
The	Joints Made and Used by Builders. By WYVILL J. CHRISTY, Architect. With 160 Woodcuts 3/0
Shor	ing And its Application: A Handbook for the Use of Students. By George H. Blagrove. With 31 Illustrations
The	Timber Importer's, Timber Merchant's, and Builder's Standard Guide. By R. E. Grandy
Plun	nbing: A Text-Book to the Practice of the Art or Craft of the Plumber. With Chapters upon House Drainage and Ventilation. By Wm. PATON BUCHAM. Ninth Edition, with 512 Illustrations 3/6
Vent	illation: A Text Book to the Practice of the Art of Ventilating Buildings. By W. P. BUCHAN, R.P., Author of "Plumbing," &c. With 170 Illustrations 3/6
The	Practical Plasterer: A Compendium of Plain and Ornamental Plaster Work. By W. KEMP 2/0
Hou	se Painting, Graining, Marbling, & Sign Writing. With a Course of Elementary Drawing, and a Collection of Useful Receipts. By ELLIS A. DAVIDSON. Eighth Edition. Coloured Plates
A G	rammar of Colouring, Applied to Decorative Painting and the Arts. By George Field. New Edition, enlarged, by Ellis A. Davidson. With Coloured Plates 3/0
Elen	nentary Decoration As applied to Dwelling Houses, &c. By James W. Facey. Illustrated 2/0
Prac	tical House Decoration. A Guide to the Art of Ornamental Painting, the Arrangement of Colours in Apartments, and the Principles of Decorative Design. By JAMES W. FACEY 2/28
, :	The last two Works in One handsome Vol., half-bound, entitled "House Decoration, Elementary and Practical," price 5/0.
Port	land Cement for Users. By Henry Faija, A.M.Inst.C.E. Third Edition, Corrected 2/0
Lim	es, Cements, Mortars, Concretes, Mastics, Plas- tering, &c. By G. R. Burnell, C.E. Fifteenth Edition
	By G. R. Burnell, C.E. Fifteenth Edition 1/6

Maso	onry and Stone-Cutting. The Principles of Masonic Projection and their application to Construct By Edward Dosson, M.R.I.B.A.	ion 2/8
Arch	es, Piers, Buttresses, &c.: Experimental Essays on the Principles of Construction. By W. Bla	ND.
Quan	atities and Measurements, In Bricklayers', Masons', Plasterers', Plumbers', Painters', Paperhang' Gilders', Smiths', Carpenters' and Joiners' Work. By A. C. Braton.	/8 /8
The	Complete Measurem: Setting forth the Measurement of Boards, Glass, Timber and Stone. By HORTON. Sixth Edition.	R
Guide	e to Superficial Measurement: Tables calculated from z to 200 inches in length, by z to ro8 inche breadth. For the use of Architects, Surveyors, Engineers, Timber breahts, Builders, &c. By James Hawkings. Fifth Edition 3	
Light	An Introduction to the Science of Optics. For the Use of Students of Artecture, Engineering, and other Applied Sciences. By E. W. Ta	chi RN,
	By GRORGE WIGHTWICK, Architect. Sixth Edition, revised and enlar by G. Huskisson Guillaume, Architect	ged 3/6
	iteoture—Orders: The Orders and their Æsthetic Principles. By W. H. LEEDS. Illustra	
	itecture—Styles: The History and Description of the Styles of Architecture of Vari	/6 ous !/0
ı	itecture—Design: The Principles of Design in Architecture, as deducible from Nature exemplified in the Works of the Greek and Gothic Architects. By El LACY GARBETT, Architect. Illustrated	2/6
	Adapted to Young Students and Amateurs in Architecture, Painting, By George Pyne	&c. 2/0
Krchi	itectural Modelling in Paper. By T. A. RICHARDSON. With Illustrations, engraved by O. Jewitt 1	/6
1	Staining, and the Art of Painting on Glass From the German of Dr. Gessert and Emanuel Otto Fromberg. W an Appendix on The Art of Enamelling	
1	wius—The Architecture of. In Ten Books. Translated from the Latin by Joseph Gwilt, F.S. F.R.A.S. With 23 Plates	A., /O
N.B.	.—This is the only Edition of VITRUVIUS procurable at a moderate price	f.
i	an Architecture, An Inquiry into the Principles of Beauty in. With an Historical View of a Rise and Progress of the Art in Greece. By the EARL OF ABERDERN.	the /O
. :	The two preceding Works in One handsome Vol., half-bound, entitled "Ancient Architecture," price 6/0.	

	,
INDUSTRIAL AND US	EFUL ARTS.
Cements, Pastes, Glues, and Gum	s.
A Guide to the Manufacture and Applicatio	n of Agglutinants. With 900
Recipes and Formulæ. By H. C. STANDAGE	
Clocks, Watches, and Bells for Pu	iblic Purposes.
A Rudimentary Treatise. By EDMUND BE LL.D., K.C., F.R.A.S. Eighth Edition, wit	h new List of Great Bells and
an Appendix on Weathercocks.	[Just published. 4/6
. The above, handsomely bound, clot.	i boards, 5/6.
Electro-Metallurgy,	Total Philips
Practically Treated. By ALEXANDER WATT. The Goldsmith's Handbook.	Tenth Edition . 3/6
Containing full Instructions in the Art of A	lloving, Melting, Reducing,
Containing full Instructions in the Art of A Colouring, Collecting and Refining, Recovery &c., &c. By George E. Gee. Sixth Editio	of Waste, Solders, Enamels,
The Silversmith's Handbook,	n 3/0
On the same plan as the GOLDSMITH'S HAND	воок. Ву G. E. Gee. 3/0
*** The last two Works, in One hanasome l	Tol., half-bound, 7/0.
The Hall-Marking of Jewellery.	
Comprising an account of all the different Kingdom; with the Stamps and Laws relati	Assay Towns of the United
Marks at the various Assay Offices. By Grou	
French Polishing and Enamellin	g.
Numerous Recipes for making Polishes, Varn	
Practical Organ Building.	1/6
By W. E. DICKSON, M.A. Second Edition, I	Revised, with Additions 2/6
Coach-Building:	-
A Practical Treatise. By JAMES W. BURGESS.	With 57 Illustrations 2/6
The Cabinet-Maker's Guide To the Entire Construction of Cabinet-Work.	Day D. Damanan O.O.
The Brass Founder's Manual:	By R. BITMEAD . 2/6
Instructions for Modelling, Pattern Making, &	c. By W. Graham . 2/0
The Sheet-Metal Worker's Guide.	
For Tinsmiths, Coppersmiths, Zincworkers, &c	. By W. J. E. CRANE. 1/6
Sewing Machinery:	C.P. 0/0
Its Construction, History, &c. By J. W. UR Gas Fitting:	QUHART, C.E , 2/0
A Practical Handbook. By JOHN BLACK. N	ew Edition 2/6
Construction of Door Locks.	
From the Papers of A. C. Hobbs. Edited by C	
The Model Locomotive Engineer	r, Fireman, and
Engine-Boy. By Michael Reynolds	2/8
The Art of Letter Painting made	· · · · · 3/6
By J. G. BADENOCH. With 12 full-page Engl	
The Art of Boot and Shoemaking	
Measurement, Last-fitting, Cutting-out, Closing	g, &c. By J. B. Leno. 2/0
Mechanical Dentistry:	
By Charles Hunter, Fourth Edition . Wood Engraving:	3/0
A Practical and Easy Introduction to the Art.	By W. N. Brown . 1/6
Laundry Management.	, , 170
A Handbook for Use in Private and Public La	undries 2/0

AGRICULTURE, GARDENING, ETC.
Draining and Embanking; A Practical Treatise. By Prof. JOHN SCOTT. With 68 Illustrations 1/6
Irrigation and Water Supply: A Practical Treatise on Water Meadows, Sewage Irrigation, Warping, &c. on the Construction of Wells, Ponds, Reservoirs, &c. By Prof. John Scott. With 34 Illustrations
Farm Roads, Fences, and Gates: A Practical Treatise on the Roads, Tramways, and Waterways of the Farm; the Principles of Enclosures; and the different kinds of Fences, Gates, and Stiles. By Prof. JOHN SCOTT. With 75 Illustrations 1/6
Farm Buildings: A Practical Treatise on the Buildings necessary for various kinds of Farms, their Arrangement and Construction, with Plans and Estimates. By Prof. JOHN SCOTT, With 105 Illustrations
Treating of the Application of Power and Machines used in the Threehingbarn, Stockyard, Dairy, &c. By Prof. J. Scott. With 123 Illustrations 2/0
Field Implements and Machines: With Principles and Details of Construction and Points of Excellence, their Management, &c. By Prof. John Scott. With 138 Illustrations. 2/0
A Treatise on Land Surveying; Levelling, and Setting-out; with Directions for Valuing Estates. By Prof. J. Scott. With 62 Illustrations . 1/6
By Professor JOHN SCOTT. Comprising the above Seven Volumes in One, 1,150 pages, and over 600 Illustrations. Half-bound 12/0
Outlines of Farm Management. Treating of the General Work of the Farm; Stock; Contract Work; Labour, &c. By R. Scott Burn
Outlines of Landed Estates Management. Treating of the Varieties of Lands, Methods of Farming, Setting-out of Farms, Roads, Fences, Gates, Drainage, &c. By R. Scott Burn. 2/6
Soils, Manures, and Crops. (Vol. I. Outlines of Modern Farming.) By R. Scott Burn . 2/0
Farming and Farming Economy. (Vol. II. Outlines of Modern Farming.) By R. Scott Burn 3/0
Stock: Cattle, Sheep, and Horses. (Vol. III. Outlines of Modern Farming.) By R. Scott Burn 2/6
Dairy, Pigs, and Poultry. (Vol. IV. Outlines of Modern Farming.) By R. Scott Burn 2/0
Utilization of Sewage, Irrigation, and Reclamation of Waste Land. (Vol. V. Outlines of Modern Farming.) By R. Scott Burn. 2/6
Outlines of Modern Farming. By R. Scott Burn. Consisting of the above Five Volumes in One, 1,850 pp., profusely Illustrated, half-bound 12/0

Book-keeping for Farmers and Estate Owners. A Practical Treatise, presenting, in Three Plans, a system adapted for all classes of Farms. By J. M. WOODMAN. Fourth Edition
Ready Reckoner for the Admeasurement of Land. By A. Arman. Revised and extended by C. Norris. Fifth Edition 2/0
Miller's, Corn Merchant's, and Farmer's Ready Reckoner. Second Edition, revised, with a Price List of Modern Flour Mill Machinery, by W. S. Hutton, C.E
The Hay and Straw Measurer. New Tables for the Use of Auctioneers, Valuers, Farmers, Hay and Straw Dealers, &c. By JOHN STEELE
Meat Production. A Manual for Producers, Distributors, and Consumers of Butchers' Meat. By John Ewart 26
Sheep: The History, Structure, Economy, and Diseases of. By W. C. SPOONER, M.R.V.S. Fifth Edition, with fine Engravings
Market and Kitchen Gardening. By C. W. Shaw, late Editor of "Gardening Illustrated" 3/8
Kitchen Gardening Made Easy. Showing the best means of Cultivating every known Vegetable and Herk &c., with directions for management all the year round. By George M. F. Glenny. Illustrated
Cottage Gardening: Or Flowers, Fruits, and Vegetables for Small Gardens. By E. Hospay, 1/6
Garden Receipts. Edited by CHARLES W. QUIN
Fruit Trees, The Scientific and Profitable Culture of, From the French of M. Du Breull. Fifth Edition, carefully Revised by Grorge Glenny. With 187 Woodcuts
The Tree Planter and Plant Propagator: With numerous Illustrations of Grafting, Layering, Budding, Implementa, Houses, Pits, &c. By Samuel Wood
The Tree Pruner: A Practical Manual on the Pruning of Fruit Trees, Shrubs, Climbers, and Flowering Plants. With numerous Illustrations. By Samuel Wood 1/8 **O The above Two Vols. in One, handsomely half-bound, price 3/6.
The Art of Grafting and Budding. By Charles Balter. With Illustrations

MA	ATHEMATICS, ARI	THME	ETIC,	ET	C.
Danes	ulutina Casustuu				
Desci	riptive Geometry, An Elementary Treatise on; with a The extracted from the French of G. Mongs of the Principles and Practice of Isometri M.A. With 14 Plates	cory of Shad To which	ows and of a is added a an. By J. E	Perspe Descr HEA	ctive, iption THER, 2/0
Proof	tical Plane Geometry:	•			
÷ 1.000	Giving the Simplest Modes of Construct and Geometrical Construction of the Gr With 215 Woodcuts	ing Figures round. By	contained J. F. HEA	in one	Plane M.A. 2/0
Knal	ytical Geometry and Coni	c Section	na.		
	A Rudimentary Treatise on. By JA written and enlarged by Professor J. R.	MES HANN. Young	A New	Editio •	n, re- 2/0
Eucli	id (The Elements of).		•		
	With many Additional Propositions an prefixed an Introductory Essay on Logic *** Sold also separate	. By Hen	ry Notes; RY LAW, (to wh	ich is 2/6
Τέn	clid. The First Three Books. By HE	NRY LAW.	C. R		1/6
	clid. Books 4, 5, 6, 11, 12. By HE				
		NEI LAW,	. Е.	• •	1/6
Plane	Trigonometry,				
	The Elements of. By JAMES HANN.				1/6
Sphe	rical Trigonometry,				
	The Elements of. By JAMES HANN.	Revised	by CHARL	ES H.	Dow-
	LING, C.E				1/0
. Or	with " The Elements of Plane Trigono	metry." in (ne Volum	e. 2/6	
-				-, -	
	rential Calculus, Elements of the. By W. S. B. Woolho	USE, F.R.A	.S., &c.	. °.	1/6
Integ	ral Calculus.				
#1L	By Homersham Cox, B.A		• •	• •	1/6
Alget	ora,	3.7.4. 37.00			
	The Elements of. By James Haddon, Miscellaneous Investigations, and a Coll	ection of Pro	h Appendi: oblems	k, conta	ining 2/0
A Ke	y and Companion to the	Aboye.			
_	An extensive Repository of Solved Ex By J. R. Young	amples and	Problems	in Alg	1/6
Comr	nercial Book-keeping.				
	With Commercial Phrases and Forms German. By JAMES HADDON, M.A.	in English	, French,	Italian •	, and 1/6
Arith	imetic,				
	A Rudimentary Treatise on. With fu	ll_Explanat	ions of its	Theor	etical
	Principles, and numerous Examples for	Practice.	For the Us	e of So	chools
	and for Self-Instruction. By J. R. You in Belfast College. Thirteenth Edition	ung, late Pi	olessor of	Mather	natics
			• •	• •	1/6
A We	y to the Above.				
	By J. R. Young				1/6
Equa	tional Arithmetic,				
-	Applied to Questions of Interest, Annu	uiti es, L ife <i>I</i>	Assurance,	and G	eneral
	Commerce; with various Tables by whi	ch all Calcı	lations ma	y be g	reatly
	facilitated. By W. HIPSLEY				1/6
	ımetic,			•	
	Rudimentary, for the Use of Schools HADDON, M.A. Revised by ABRAHAM	and Self-I	nstruction.	Ву Ј	1/6
A Ke	y to the Above.				410

Mathematical Instruments:
Their Construction, Adjustment, Testing, and Use concisely Explained By J. F. HEATHER, M.A., of the Royal Military Academy, Woolwich Fifteenth Edition, Revised, with Additions, by A. T. WALMISLEY M.I.C.E. Original Edition, in x vol., Illustrated
"." In ordering the above, be careful to say "Original Edition," or give the number in the Series (32), to distinguish it from the Enlarged Edition in 3 vols. (as follows)—
Drawing and Measuring Instruments.
Including—I. Instruments employed in Geometrical and Mechanical Drawing, and in the Construction, Copying, and Measurement of Maps and Plans. II. Instruments used for the purposes of Accurate Measurement and for Arithmetical Computations. By J. F. HEATHER, M.A 1/6
Optical Instruments.
Including (more especially) Telescopes, Microscopes, and Apparatus for producing copies of Maps and Plans by Photography. By J. F. HEATHER M.A. Illustrated
Surveying and Astronomical Instruments.
Including—I. Instruments used for Determining the Geometrical Feature of a portion of Ground. II. Instruments employed in Astronomical Observations. By J. F. Heathers, M.A. Illustrated 1/6
"." The above three volumes form an enlargement of the Author's original work, "Mathematical Instruments," price 2/0. (Described at top of page.)
Mathematical Instruments:
Their Construction, Adjustment, Testing and Use. Comprising Drawing, Measuring, Optical, Surveying, and Astronomical Instruments. By J. F. Heather, M.A. Enlarged Edition, for the most part entirely re-written. The Three Parts as above, in One thick Volume.
The Slide Rule, and How to Use It.
Containing full, easy, and simple Instructions to perform all Business Calculations with unexampled rapidity and accuracy. By Charles Hoare, C.E. With a Slide Rule, in tuck of cover. Eighth Edition
Logarithms.
With Mathematical Tables for Trigonometrical, Astronomical, and Nautical Calculations. By HENRY LAW, C.E. Revised Edition . 3/0
Compound Interest and Annuities (Theory of).
With Tables of Logarithms for the more Difficult Computations of Interest, Discount, Annuities, &c., in all their Applications and Uses for Mercantile and State Purposes. By FEDOR THOMAN, Paris. Fourth Edition . 4/0
Mathematical Tables,
For Trigonometrical, Astronomical, and Nautical Calculations; to which is prefixed a Treatise on Logarithms. By H. Law, C.E. Together with a Series of Tables for Navigation and Nautical Astronomy. By Professor J. R. Young. New Edition
Mathematics.
As applied to the Constructive Arts. By Francis Campin, C.E., &c. Third Edition
Astronomy.
By the late Rev. ROBERT MAIN, F.R.S. Third Edition, revised and corrected to the Present Time. By W. T. LYNN, F.R.A.S
Statics and Dynamics,
The Principles and Practice of. Embracing also a clear development of Hydrostatics, Hydrodynamics, and Central Forces. By T. Baker, C.E. Fourth Edition 1/6

300KS OF REFERENCE AND MISCELLANEOUS VOLUMES.

A D	ictionary of Painters, and Handbook for Pic Amateurs.	ture
	Being a Guide for Visitors to Public and Private Picture Galleries, a Art-Students, including Glossary of Terms, Sketch of Principal Sch Painting, &c. By PHILIPPE DARVL, B.A.	nd for ools of 2/6
Pain	Ating Popularly Explained. By T. J. GULLICK, Painter, and JOHN TIMBS, F.S.A. Including I Oil, Mosaic, Water Colour, Water-Glass, Tempera Encaustic, Min Painting on Ivory, Vellum, Pottery, Enamel, Glass, &c. Sixth Edition	resco, iature, 5/0
A D	ictionary of Terms used in Architecture, Buing, Engineering, Mining, Metallurgy, Architecture, Edine Arts, &c. By John Weale. Sixth Edition. Edited by R. Hunt, F.R.S	hæ-
W	1	
Musi	A Rudimentary and Practical Treatise. With numerous Example. CHARLES CHILD SPENCER.	s. By 2/6
Pian	oforte,	
	The Art of Playing the. With numerous Exercises and Lessons CHARLES CHILD SPENCER.	1/6
The	House Manager. A Guide to Housekeeping, Cookery, Pickling and Preserving, Hou Work, Dairy Management, Cellarage of Wines, Home-brewing and making, Gardening, &c. By An Old Housekeeper	sehold Wine- 3/6
Man	By R. Gooding, M.D. Intended as a Family Guide in all caracteristics. Accident and Emergency. Third Edition, carefully revised	ses of 2/0
Man	agement of Health. A Manual of Home and Personal Hygiene. By Rev. James Baird	1/0
W- 4-	Dhilasanha	
Matt	Iral Philosophy, For the Use of Beginners. By Charles Tomlinson, F.R.S	1/6
The	Elementary Principles of Electric Lighting.	
	By ALAN A. CAMPBELL SWINTON, M.INST.C.E., M.I.E.E.	Fifth
	Edition	1/6
The	Electric Telegraph,	
	Its History and Progress. By R. SABINE, C.E., F.S.A., &c	3/0
Hen	dbook of Field Fortification.	
	By Major W. W. KNOLLYS, F.R.G.S. With 163 Woodcuts	3/0
Logi	C, Pure and Applied. By S. H EMMENS	1/6
Lock	ce on the Human Understanding, Selections from. With Notes by S. H. EMMENS	1/6
m.	Commondiana Calenlaton	
The	Compendious Calculator (Intuitive Calculations). Or Easy and Concise Methods of Performing various Arithmetical Operations required in Commercial and Buttansactions; together with Useful Tables, &c. By Daniel O'Got Tamestre sinch Edition carefully project by C. Novalence.	ısiness

Measures, Weights, and Moneys of all Nations. With an Analysis of the Christian, Hebrew, and Mahometan Calendars. By W. S. B. WOOLHOUSE, F.R.A.S., F.S.S. Seventh Edition
Grammar of the English Tongue, Spoken and Written. With an Introduction to the Study of Comparative Philology. By HYDE CLARKE, D.C.L. Fifth Edition
Dictionary of the English Language. As Spoken and Written. Containing above 100,000 Words. By Hyder Clarke, D.C.L
Gomposition and Punctuation, Familiarly Explained for those who have neglected the Study of Grammar. By Justin Brenan. Nineteenth Edition
French Grammar. With Complete and Concise Rules on the Genders of French Nouns. By G. L. Strauss, Ph.D
English-French Dictionary. Comprising a large number of Terms used in Engineering, Mining, &c. By Alfred Elwes
French Dictionary. In two Parts—I. French-English. II. English-French, complete in One Vol
French and English Phrase Book. Containing Introductory Lessons, with Translations, Vocabularies of Words, Collection of Phrases, and Easy Familiar Dialogues 1/8
German Grammar. Adapted for English Students, from Heyse's Theoretical and Practical Grammar, by Dr. G. L. Strauss 1/8
German Triglot Dictionary. By N. E. S. A. Hamilton. Part I. German-French-English. Part II. English-German-French. Part III. French-German-English 3/0
German Triglot Dictionary. (As above). Together with German Grammar, in One Volume . 5/0
Italian Grammar. Arranged in Twenty Lessons, with Exercises. By ALFRED ELWES. 1/8
Italian Triglot Dictionary, Wherein the Genders of all the Italian and French Nouns are carefully noted down. By Alpred Elwes. Vol. I. Italian-English-French. 2/6
Italian Triglot Dictionary. By Alpred Elwes. Vol. II. English-French-Italian 2/6
Italian Triglot Dictionary. By Alpred Elwes. Vol. III. French-Italian-English 2/6
Italian Triglot Dictionary. (As above). In One Vol
Spanish Grammar. In a Simple and Practical Form. With Exercises. By ALFRED ELWES 1/6
Spanish-English and English-Spanish Dictionary. Including a large number of Technical Terms used in Mining, Engineering, &c., with the proper Accents and the Gender of every Noun. By ALFRED ELWES 4/0

Port	tuguese Grammar, In a Simple and Practical Form. With Exercises. By Alfred Elwes.	1/6
Port	tuguese-English and English-Portuguese tionary.	
	Including a large number of Technical Terms used in Mining, Engine &c., with the proper Accents and the Gender of every Noun. By A. ELWES. Fourth Edition, revised	LFREE
Anir	mal Physics, Handbook of. By Dionveius Lardner, D.C.L. With 520 Illustra In One Vol. (732 pages), cloth boards	
	. Sold also in Two Parts, as follows:—	1,0
	Animal Physics. By Dr. Lardner. Part I., Chapters I.—VII. Animal Physics. By Dr. Lardner. Part II., Chapters VIII.—X.	

WEALE'S SCIENTIFIC & TECHNICAL SERIES.

MATHEMATICS, ARITHMETIC, &c.	
Geometry, Descriptive. J. F. HEATHER	2/-
Practical Plane Geometry. J. F. HEATHER	2/-
Analytical Geometry. J. HANN & J. R. Young	2/-
Geometry. Part I. (Euclid, Bks. I.—III.) H. LAW	1/6
Part II. (Euclid, Books IV., V., VI., XI.,	
XII.). H. LAW	1/6
Geometry, in I vol. (Euclid's Elements)	2/6
Plane Trigonometry. J. HANN	1/6
Spherical Trigonometry. J. HANN	1/-
The above 2 vols., bound together	2/6
Differential Calculus. W. S. B. Woolhouse	1/6
Integral Calculus. H. Cox	1/-
Algebra. J. Haddon	2/-
Key to ditto	1/6
Book-keeping. J. HADDON	1/6
Book-keeping. J. Haddon	1/6
Key to ditto	1/6
Key to ditto. Equational Arithmetic. W. Hipsley Arithmetic. J. Haddon	1/6
	1/6
Key to ditto	1/6
Key to ditto	2/-
Drawing & Measuring Instruments. J. F. HEATHER	1/6
Optical Instruments. J. F. HEATHER	1/6
Surveying & Astronomical Instruments. J. F.	•
Heather	1/6
The above 3 vols., bound together	4/6
Mensuration and Measuring. T. BAKER	1/6
Slide Rule, & How to Use it. C. HOARE	2/6
Slide Rule, & How to Use it. C. HOARE Measures, Weights, & Moneys. W. S. B. WOOLHOUSE	2/6
Logarithms, Treatise on, with Tables. H. Law.	3/-
Compound Interest and Annuities. F. THOMAN .	4/-
Compendious Calculator. D. O'GORMAN	2/6
Mathematics. F. CAMPIN	3/-
Astronomy. R. Main & W. T. Lynn	2/-
Statics and Dynamics. T. BAKER	1/6
Superficial Measurement. J. HAWKINGS	3/6
CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court,	E.C.



B89083901256A

may be kept

& TECHNICAL SERIES.

ARCHITECTURE. Building Estates. F. MAITLAND 2/-Science of Building. E. W. TARN . 3/6 Building, Art of. E. Dobson and J. P. Allen 2/-Book on Building. Sir E. Beckett . . . 4/6 Dwelling Houses, Erection of. S. H. Brooks 2/6 Cottage Building. C. B. ALLEN . . . 2/-Acoustics of Public Buildings. Prof. T. R. SMITH. 1/6 Practical Bricklaying. A. HAMMOND 1/6 Practical Brick Cutting & Setting. A. HAMMOND. 1/6 Brickwork, F. WALKER 1/6 Brick and Tile Making, E. Dobson. 3/-Practical Brick & Tile Book. Dobson & Hammond 6/-Oarpentry and Joinery. T. TREDGOLD & E. W. TARN 3/6 Atlas of 35 plates to the above . 6/-Handrailing, and Staircasing. G. Collings . 2/6 Oircular Work in Carpentry. G. Collings 2/6 Roof Carpentry. G. Collings . . 2/-Construction of Roofs. E. W. TARN . Joints used by Builders. J. W. CHRISTY 3/-Shoring. G. H. BLAGROVE Timber Importer's & Builder's Guide. R. E. GRANDY 2/-Plumbing. W. P. BUCHAN 3/6 Ventilation of Buildings. W. P. BUCHAN 3/6 Practical Plasterer. W. KEMP . 2/-House-Painting. E. A. DAVIDSON 5/-Elementary Decoration. J. W. FACEY. 2/-Practical House Decoration. J. W. FACEY 2/6 Gas-Fitting. J. BLACK . Portland Cement for Users. H. FAIJA & D. B. BUTLER 3/-Limes, Cements, & Mortars. G. R. BURNELL . . Masonry and Stone Cutting. E. Dobson . . . 1/6 2/6 Arches, Piers, and Buttresses. W. BLAND 1/6 Quantities and Measurements. A. C. BRATON 1/6 Complete Measurer. R. Horton Superficial Measurement. J. HAWKINGS 3/6 Light, for use of Architects. E. W. TARN 1/6 Hints to Young Architects. WIGHTWICK & GUILLAUME Dictionary of Architectural Terms. J. WEALE

CROSBY LOCKWOOD & SON, 7, Stationers' Hall Court, E.C.

ENGINEERING LIBRARY

1/6 2/-3/6 2/6 6/-1/6 5/-1/-6/-

2/6 5/-3/-2/-2/6 2/6 1/6

ENGINEERING LIBRARY	2/- 4/6
LIBRARY	3/-
	, 3/-
	7/-
	3/-
·	2/6
Flatered with manager	2/6
Coach Building. J. W. BURGESS	2/6
Brass Founder's Manual. W. Graham	2/-
French Polishing and Enamelling. B. BITMEAD.	1/6
House Decoration. J. W. FACEY	5/-
Letter-Painting Made Easy. J. G. BADENOCH	1/6
Boot and Shoemaking. J. B. LENO	2/-
Mechanical Dentistry, C. HUNTER	3/-
Wood Engraving To a Brown	1/6
Laundry Managemen	2 -

CROSBY LOCKWOOD

89083901256

b89083901256a